NEMA Standards Publication

NEMA TS 4-2016

Hardware Standards for Dynamic Message Signs (DMS) with NTCIP Requirements

National Electrical Manufacturers Association

NEMA Standards Publication TS 4-2016

Hardware Standards for Dynamic Message Signs (DMS)
with NTCIP Requirements

Published by:

National Electrical Manufacturers Association
1300 North 17th Street, Suite 900
Rosslyn, Virginia 22209

www.nema.org

© 2016 National Electrical Manufacturers Association. All rights including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American Copyright Conventions.

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

The National Electrical Manufacturers Association (NEMA) standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process and establishes rules to promote fairness in the development of consensus, it does not write the document and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, express or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health or safety–related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

© 2016 National Electrical Manufacturers Association

CONTENTS

Section 1 General **1**

1.1 Scope and Introduction **1**

1.2 References **1**
1.2.1 Normative References 1
1.2.2 Contacts 2

1.3 General Statements **4**

1.4 Types of DMS **4**
1.4.1 Dynamic Message Signs (DMS) 4
1.4.2 Changeable Message Signs 4
1.4.3 Blankout Signs (BOS) 4

1.5 Types of Technologies **5**

1.6 Definitions, Terms, and Acronyms **5**

Section 2 Environmental Requirements **16**

2.1 Environmental and Operating Standards **16**
2.1.1 Definitions of Major Units of the DMS Equipment 16
2.1.2 Compliance of Major Units 16
2.1.3 Electrical 17
2.1.4 Transients 18
2.1.5 Temperature and Humidity 19
2.1.6 Vibration 19
2.1.7 Shock 20
2.1.8 Time and Timing 20

2.2 DMS Equipment Tests **20**
2.2.1 Test Facilities (Except Vibration and Shock) 20
2.2.2 Test Unit 21
2.2.3 Test Functions 21
2.2.4 Test G: Vibration Test 25
2.2.5 Test H: Shock (Impact) Test 26
2.2.6 Test J: Power Interrupt Tests 27
2.2.7 Test K: Timing Accuracy Tests 28

Section 3 DMS Mechanical Construction **30**

3.1 General **30**
3.1.1 Weather-Tight Enclosure 30
3.1.2 Temperature Control 30
3.1.3 DMS Face 31
3.1.4 Galvanic Protection 31
3.1.5 Light Leaks 31
3.1.6 Contrast Border 31

3.2 Fixed-Location DMS **32**
3.2.1 Design Life of Fixed DMS 32
3.2.2 Structural integrity 32
3.2.3 Aluminum Housings 32
3.2.4 Housings Made of Other Materials 33
3.2.5 Front and Rear Access 33
3.2.6 Front Access DMS 33
3.2.7 Rear Access DMS 33
3.2.8 Walk-In Access DMS 34

© 2016 National Electrical Manufacturers Association

3.2.9 Convenience Outlets, Walk-In Access 35

3.3 Portable DMS 35
3.3.1 Transport Safety 35
3.3.2 Structural Integrity 35
3.3.3 Major Subsystems 36
3.3.4 Corrosion Protection and Finishes 37
3.3.5 Power Sources 37

Section 4 Controller to DMS Interface 38

4.1 Interface with DMS Housing 38

4.2 Wiring 38

4.3 Wire Entrances 38

4.4 Pixel Control Wiring 38
4.4.1 Power Supply Locations 38
4.4.2 DMS Controller and Driver Module Locations 39

Section 5 Display Properties 40

5.1 General 40
5.1.1 Development Sources 40
5.1.2 Legibility versus Visibility 40
5.1.3 Photometric and Colorimetric Requirements 40

5.2 Contrast Ratio 40

5.3 Cone of Vision Type Classification 41
5.3.1 Light Emitting Technology 43

5.4 Luminance Intensity Requirements 43
5.4.1 Luminous Intensity Uniformity 45

5.5 Chromaticity Classifications and Limits 46
5.5.1 Chromaticity Limits 46
5.5.2 Chromaticity Uniformity 46

5.6 Display Characters 46
5.6.1 Fonts and Font Alphabets 46
5.6.2 Required Fonts by DMS Type 48

5.7 Display Change Time 52

5.8 Moving arrows 52

5.9 Test Methods 53
5.9.1 General Test Parameters 53
5.9.2 Test Area 54
5.9.3 Considerations for Precision and Bias of Test Methods and Accuracy of Test Results 55

Section 6 Optical Components 56

6.1 General 56
6.1.1 Pixel Spacing 56
6.1.2 Character Module Spacing 56
6.1.3 Interchangeability of LED Modules 57
6.1.4 Character Replacement 57

6.2 LED Light System 57
6.2.1 General 57
6.2.2 LED Selection 57
6.2.3 LED Use 57

© 2016 National Electrical Manufacturers Association

Section 7 DMS Controller Cabinet 58

7.1 General 58

7.2 DMS Controller Cabinet Design 58
7.2.1 Layout 58
7.2.2 Protection 58

Section 8 Electronics and Electrical 59

8.1 General 59

8.2 Components 59
8.2.1 General 59
8.2.2 Wiring, Cabling, and Harnesses 59
8.2.3 Circuit Loading, Surge Protection and Disconnects 59
8.2.4 Printed Circuit Boards 59

8.3 DMS Controller 59
8.3.1 General 59
8.3.2 Communication Interfaces 59
8.3.3 Communications 60
8.3.4 Internal Clock 60
8.3.5 Watchdog Timer 60
8.3.6 Loss of Power 60
8.3.7 Communications Link Monitor 60
8.3.8 Manual Test Interface 60
8.3.9 Controller Reset 60

8.4 Controller Functions 61
8.4.1 General 61
8.4.2 Control Architectures 61
8.4.3 Common Functionality 61
8.4.4 Centralized Messaging Architecture 62
8.4.5 Local Messaging Architecture 62
8.4.6 Display Writing 62
8.4.7 NTCIP Protocol and Command Sets 62
8.4.8 Other Protocols and Command Sets 62

8.5 Local Control 63

Section 9 Performance Monitoring 64

9.1 Display Diagnostics and Monitoring 64
9.1.1 LED Pixel Tests 64
9.1.2 LED Temperature Monitor 64
9.1.3 Brightness Controls 64

9.2 Controller Diagnostics and Monitoring 65
9.2.1 Watchdog Timer 65
9.2.2 Results of Controller Failures 65
9.2.3 Power Line Failures 65
9.2.4 Communication Link Failures 65
9.2.5 Subsystem Component Communications 66

9.3 Error and Failure Log 66

9.4 Message Verification 66

9.5 Defective Character Module 66

Section 10 Power Requirements 67

10.1 AC or DC Electrical Service 67

© 2016 National Electrical Manufacturers Association

10.2 Power Panels for AC Only 67
10.2.1 Minimum Requirements 67
10.2.2 Service Drop Advisory 67
10.3 Distribution Panels for DC 67
10.4 Ground to Neutral Isolation 67
10.5 Surge Protection Device 67
10.6 Convenience Outlets AC Only 67
10.6.1 Calculated Electrical Load 68
10.7 Reserve Power Source 68
10.8 DMS Operation 68
10.8.1 Content/Message 68
10.8.2 Message Brightness 68
10.8.3 Definition of Critical vs. Non-Critical Loads 68
10.9 Reserve Power Source Sizing Considerations 68
10.9.1 UPS/Battery 68
Section 11 Conformance 70
11.1 General 70
11.1.1 Involved Parties 70
11.1.2 Other 70
11.2 Conformance Document Types 70
11.2.1 Certificates 70
11.2.2 Conformance Testing 70
11.2.3 Statement 70
11.2.4 Inspections 71
11.2.5 Evaluation 71
11.3 Requirements 71
11.3.1 Mandatory 71
11.3.2 Optional 71
11.4 Conformance Documentation Requirements 71
11.5 Conformance Table 72
Section 12 Documentation 78
12.1 Drawing Documentation 78
12.1.1 System Diagrams 78
12.1.2 Wiring Diagrams 78
12.1.3 Mechanical Drawings 78
12.2 Site Specific Documentation 78
12.2.1 Conformance Table Checklist 78
12.2.2 NTCIP MIB File 78
12.2.3 As-Built Documentation 79
12.2.4 Configuration Information 79
12.2.5 Revision Numbers 79
12.2.6 Test Results 79
12.2.7 Product Burn-In 79
12.3 Manuals 79
12.3.1 Electronic Copy 79
12.3.2 Hardcopy 79
12.3.3 Service 79

© 2016 National Electrical Manufacturers Association

12.3.4 Troubleshooting 80
12.3.5 Operator's Manual 80

12.4 Warranty Documentation 80

FIGURES

Figure 2-1 Test Profile 22

Figure 5-1 Example Comparison—15 versus 30 Degree Cone of Vision (Vertical Plane) (top figure) 42

Figure 5-2 Example Overall Cone of Vision Comparison— 15 versus 30 Degree Angle (Horizontal Plane) (bottom figure) 42

Figure 5-3 Graphical Representation of Character Height, Character Width, and Stroke Width 47

Figure 5-4 Example—Standard Font Containing 5 x 7 Pixels 47

Figure 5-5 Example—Standard Font Containing 5 × 7 Pixels 48

Figure 5-6 Geometric Configuration of Test Equipment for Determination of Luminance and Contrast for All Technologies and Chromaticity of Light Emitting Technologies 53

Figure 5-7 Layout Examples for a Test Module and the Positioning of the Measuring Area (Circle) 54

TABLES

Table 2-1 Compliance of Major Units 17

Table 2-2 Operating Voltages 17

Table 2-3 Wet-Bulb, Dry-Bulb Relative Humidity at Barometric Pressure of 29.92 In. of Mercury 19

Table 2-4 Test Functions 21

Table 2-5 Effect of Power Interruption 27

Table 5-1 Minimum Contrast Ratio Requirements, Yellow 41

Table 5-2 Minimum Contrast Ratio Requirements, White 41

Table 5-3 Minimum Contrast Ratio Requirements, Green 41

Table 5-4 Minimum Contrast Ratio Requirements, Red 41

Table 5-5 Minimum Contrast Ratio Requirements, Blue 41

Table 5-6 Luminance Intensity Limits in CD/M^2 for On-Axis (0° Horizontal, 0° Vertical) Test Angles—for Yellow 44

Table 5-7 Luminance Intensity Limits in CD/M^2 for On-Axis (0° Horizontal, 0° Vertical) Test Angles—for White 44

Table 5-8 Luminance Intensity Limits in CD/M^2 for On-Axis (0° Horizontal, 0° Vertical) Test Angles—for White/Yellow 44

Table 5-9 Luminance Intensity Limits in CD/M^2 for On-Axis (0° Horizontal, 0° Vertical) Test Angles—for Green 44

Table 5-10 Luminance Intensity Limits in CD/M^2 for On-Axis (0° Horizontal, 0° Vertical) Test Angles—for Red 45

Table 5-11 Luminance Intensity Limits in CD/M^2 for On-Axis (0° Horizontal, 0° Vertical) Test Angles—for Orange 45

© 2016 National Electrical Manufacturers Association

Table 5-12 Luminance Intensity Limits in CD/M^2 for On-Axis (0° Horizontal, 0° Vertical) Test Angles—for Blue 45

Table 5-13 Chromaticity Limits for Light-Emitting DMS Technology 46

Table 5-14 NEMA TS 4 Font Ratios—Width/Stroke/Spacing 50

Table 5-15 MUTCD Font Ratios—Width/Stroke/Spacing 51

© 2016 National Electrical Manufacturers Association

FOREWORD

This NEMA Standards Publication, TS 4-2016, *Hardware Standards for Dynamic Message Signs (DMS), with NTCIP Requirements*, was developed to standardize minimum performance requirements and specifications for design and implementation of dynamic traffic messaging equipment that can be safely installed and provided to the end user with operational features based on current technology. Within NEMA TS 4-2016, any reference to a specific manufacturer is strictly for the purpose of defining interchangeability where there exists no nationally recognized standard covering all the requirements. The manufacturer references do not constitute a preference. NEMA TS 4-2016 is intended to reduce hazards to persons and property when traffic-messaging equipment is properly selected and installed in conformance with the requirements herein.

A future version of NEMA TS 4-2016 may address alternative non-grid power sources.

The user's attention is called to the possibility that compliance with NEMA TS 4-2016 may require use of an invention covered by patent rights. By publication of NEMA TS 4-2016, no position is taken with respect to the validity of any claims or of any patent rights in connection therewith.

In the preparation of NEMA TS 4-2016, input of users and other interested parties has been sought and evaluated. Inquiries, comments, and proposed or recommended revisions should be submitted to the concerned NEMA product subdivision by contacting the:

Senior Technical Director, Operations
National Electrical Manufacturers Association
1300 North 17th Street, Suite 900
Rosslyn, Virginia 22209

The Dynamic Message Sign Technical Committee developed NEMA TS 4-2016 under the auspices of the NEMA Transportation Management Systems and Associated Control Devices Section (3TS), of which it is a part.

At the time that NEMA TS 4-2016 was prepared, the following NEMA members and their representatives were active voting members of the NEMA 3TS Dynamic Message Sign Technical Committee (3TS DMS TC):

- Adaptive Micro Systems, Inc. www.adaptivedisplays.com
- Daktronics, Inc. www.daktronics.com (Co-Chairs)
- Parsons delcantechnologies.com
- SES America sesamerica.com
- Skyline Products, Inc. www.skylineproducts.com
- Ver-Mac, Inc. www.ver-mac.com

3TS section approval of NEMA TS 4-2016 does not necessarily imply that all Section members voted for its approval or participated in its development. When NEMA TS 4-2016 was approved, the Transportation Management Systems and Associated Control Devices Section was composed of the following members:

- Adaptive Micro Systems, Inc. www.adaptivedisplays.com
- Applied Information, Inc. appinfoinc.com
- Daktronics, Inc. www.daktronics.com
- Eberle Design, Inc. www.editraffic.com
- Horizon Signal Technologies, Inc. www.horizonsignal.com
- Intelight Inc. www.intelight-its.com
- John Thomas, Inc. www.jtitraffic.com
- OMJC Signal, Inc. www.omjcsignal.com

© 2016 National Electrical Manufacturers Association

- Parsons delcantechnologies.com
- Peek Traffic Corporation www.peektraffic.com
- SES America sesamerica.com
- Siemens Industry, Inc. www.industry.usa.siemens.com
- Skyline Products, Inc. www.skylineproducts.com
- TransCore, ITS, LLC www.transcore.com
- Ver-Mac, Inc. www.ver-mac.com

© 2016 National Electrical Manufacturers Association

History

As the implementation of dynamic message signage and general light emitting technology increased in the United States during the late 1980s and early 1990s, various transportation departments tried a number of diverse technologies to meet their signing needs. This eventually led to a wide variety of agency specifications developed across the country, a number of opposing philosophies for implementation by the users, and some unsubstantiated claims by manufacturers. It also led to conflicting definitions and references from one agency to the next for what constituted a dynamic message sign (DMS) or its use.

In 1995, based on industry need, NEMA created the NEMA 3TS Transportation Section.

In August 1997, the DMS manufacturers formed a new committee of the NEMA Transportation Section and met for the first time to outline a plan for developing this hardware standard. Between 1997 and 2005, the NEMA 3TS section developed NEMA TS 4-2005. In 2005 NEMA TS 4-2005 was published and used by the transportation industry.

In 2012, the NEMA 3TS Section authorized a project to revise existing NEMA TS 4-2005. That project resulted in NEMA TS 4-2016, which removes older DMS technology and incorporates the new full color technology available. The 3TS Section, particularly its Dynamic Message Sign Technical Committee also worked to harmonize NEMA TS 4-2016 with EN 12966-1 for Environmental, Display, and testing requirements. The major sections overhauled during this project are Section 2 Environmental Requirements, Section 5 Display Properties, Section 8 Electronics and Electrical. Minor revisions occurred in other portions of NEMA TS 4-2016 to reflect the removal of older display technologies. NEMA TS 4-2016 incorporates all of the current best practices of the industry for specifying a DMS.

© 2016 National Electrical Manufacturers Association

Section 1
General

1.1 Scope and Introduction

The goal of NEMA TS 4-2016 is to provide the user with safe, dependable, functional, and easily maintained Dynamic Message Sign (DMS) equipment.

NEMA TS 4-2016 defines the minimum hardware and functional characteristics of electronically controlled DMS used for displaying messages to travelers.

NEMA TS 4-2016 predominantly addresses DMS.

Conformance to NEMA TS 4-2016 is defined in Section 11.

Portions of NEMA TS 4-2016 may be referenced as part of agency (procurement) specifications.

NEMA TS 4-2016 is not intended to be, or is meant to take the place of any application guides for DMS.

Items such as sign siting practices, selection of character heights, siting of cabinets and relations between legibility and travel speed, etc. were all considered to be outside the scope of NEMA TS 4-2016.

1.2 References

The following standards (normative references) contain provisions which, through reference in this text, constitute provisions of NEMA TS 4-2016. Additional documents and standards (other references) are referenced that might provide a more complete understanding. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this standard should apply the most recent editions of the standards indicated.

1.2.1 Normative References

AASHTO LTS-6	*Standard Specifications for Structural Supports for Highway Signs, Luminaires, and Traffic Signals, 6th Edition*
ANSI/AWS D8.8M:2014	*Specification for Automotive Weld Quality Arc-Welding of Steel*
ASTM E810-03(2013)	*Standard Test Method for Coefficient of Retroreflection of Retroreflective Sheeting Utilizing the Coplanar Geometry*
CIE 1931	*Color Specification—The CIE 1931 Standard Colorimetric System and the CIE 1964 Supplementary Standard Colorimetric System*
EN 55022	*Limits and Methods of Measurement of Radio Disturbance Characteristics of Information Technology Equipment*
EN 12966:2014	*Road vertical signs—Variable message traffic signs*
IEC/EN 61000-6-1	*Electromagnetic compatibility (EMC)—Part 6-1: Generic Standards—Immunity standard for residential, commercial and light-industrial environments*
FMVSS, Part 571	National Highway Traffic Safety Administration, 49 CFR Part 571, *Federal Motor Vehicle Safety Standards (FMVSS)*

© 2016 National Electrical Manufacturers Association