

IES Method for Evaluating Light Source Color Rendition

**IES Method for
Evaluating Light Source Color Rendition**

Publication of this Technical Memorandum
has been approved by IES.
Suggestions for revisions should be
directed to the IES.

Copyright 2018 by the Illuminating Engineering Society.

Approved by the IES Standards Committee, June 25, 2018, as a Transaction of the Illuminating Engineering Society.

Approved as an American National Standard July 27, 2018.

All rights reserved. No part of this publication may be reproduced in any form, in any electronic retrieval system or otherwise, without prior written permission of the IES.

Published by the Illuminating Engineering Society, 120 Wall Street, New York, New York 10005.

IES Standards and Guides are developed through committee consensus and produced by the IES Office in New York. Careful attention is given to style and accuracy. If any errors are noted in this document, please forward them to the Director of Standards and Research, standards@ies.org or the above address, for verification and correction. The IES welcomes and urges feedback and comments.

Printed in the United States of America.

ISBN# 978-0-87995-379-9

DISCLAIMER

IES publications are developed through the consensus standards development process approved by the American National Standards Institute. This process brings together volunteers representing varied viewpoints and interests to achieve consensus on lighting recommendations. While the IES administers the process and establishes policies and procedures to promote fairness in the development of consensus, it makes no guaranty or warranty as to the accuracy or completeness of any information published herein.

The IES disclaims liability for any injury to persons or property or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on this document

In issuing and making this document available, the IES is not undertaking to render professional or other services for or on behalf of any person or entity. Nor is the IES undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

The IES has no power, nor does it undertake, to police or enforce compliance with the contents of this document. Nor does the IES list, certify, test or inspect products, designs, or installations for compliance with this document. Any certification or statement of compliance with the requirements of this document shall not be attributable to the IES and is solely the responsibility of the certifier or maker of the statement.

Prepared by the IES Color Committee:

Wendy Luedtke, *Chair*

Jason Livingston, *Co-Chair*

E. Bretschneider*

A. David

W. Davis

T. Esposito

A. Feldman*

P. Fini

F. Florentine*

M. Royer

M. Wei

J. Fuller*

J. Gaines*

T. Hensley

K. Houser

S. Lavoie*

N. Miller*

H. Ratafia

L. Whitehead

M. Wood

M. Raz*

*Advisory

AMERICAN NATIONAL STANDARD

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether that person has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation to any American National Standard. Moreover, no person shall have the right or authority to issue and interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised at any time. The procedures of the American National Standards Institute require that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of approval. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Contents

1.0	INTRODUCTION	1
1.1	Calculation Components	1
1.2	Calculated Measures	2
1.3	Changes from IES TM-30-15	2
2.0	SCOPE	2
3.0	CORE CALCULATIONS	2
3.1	Colorimetric Observer	2
3.2	Test Source	2
3.3	Reference Illuminant	3
3.4	Color Evaluation Samples (CES)	4
3.5	Range and Interpolation of Data	4
3.6	Calculation of Tristimulus Values	4
3.7	Color Space and Chromatic Adaptation Transformation	5
3.7.1	Calculation of Color Coordinates	5
3.8	Color Difference Formula	6
4.0	CALCULATED MEASURES	7
4.1	Fidelity Index (R_f)	7
4.2	Sample Color Fidelity ($R_{f,CESi}$)	8
4.3	Hue-Angle Bins	8
4.4	Gamut Index (R_g)	8
4.5	Color Vector Graphic (CVG)	11
4.6	Local Chroma Shift ($R_{cs,hj}$)	12
4.7	Local Hue Shift ($R_{hs,hj}$)	13
4.8	Local Color Fidelity ($R_{f,hj}$)	15
5.0	COMMENTARY	16
5.1	Average Values	16
5.2	Color Rendition Preference and Other Perceptions	16
5.3	Preferred Chromaticity	17
5.4	Comparison Across CCTs	17
5.5	Energy Efficiency	17
5.6	Color Samples	17
5.7	Fluorescence and Whiteness	17
	ANNEX A – COLOR EVALUATION SAMPLES	18
	ANNEX B – COLOR SPECIFICATION FOR HUE-ANGLE BIN GRAPHICS	20
	ANNEX C – BACKGROUND FOR COLOR VECTOR GRAPHIC	21
	REFERENCES	22

1.0 INTRODUCTION

Accurately quantifying the color rendition characteristics of a light source is a complex problem. Color rendition affects many subjective perceptual attributes of a space, including naturalness, vividness, preference, normalness, and visual clarity. Traditionally, there have been distinct approaches for characterizing color rendition, focusing on concepts such as color fidelity, color discrimination, or color preference, and often relying on a single-number characterization. These approaches vary in their relationship to any given subjective impression. Regardless of approach, there is no one metric or measure that can accurately quantify all subjective perceptions of color rendition or identify the most desirable light source for every application.^{1,2} A precise and robust method for comprehensively characterizing color rendition is critical to specifying appropriate light sources and optimizing spectral characteristics of light sources.

This Technical Memorandum describes a method for evaluating light source color rendition that takes an objective and statistical approach, quantifying both overall average properties (color fidelity, gamut area) and hue-specific properties (fidelity, chroma shift, hue shift) of a light source using numerical and graphical techniques. It is important to note that it does not attempt to directly characterize human perceptions, such as color preference, or to provide a single number that captures the combined color rendition qualities of a light source. Using various combinations of the included measures, a user is expected to be able to rely on experience and/or design guidelines to determine what is most appropriate for a specific application. This document focuses only on describing the objective characterization techniques; it does not relate values to a subjective evaluation.

This Technical Memorandum consolidates and synthesizes numerous research efforts that have been ongoing for several years, and was developed by representatives of the manufacturing, specification, and research segments of the lighting industry.

1.1 Calculation Components

This document is a tool comprising a set of measures that are all based on a standardized calculation procedure. The method is based on theoretically comparing the appearance of a set of color samples as rendered by a test light source and a reference illuminant, quantified with a model of human

vision. Thus, the method includes three primary components: a system for defining the reference illuminant, specification of the color samples, and implementation of a model of human vision. An overview of each component is provided here.

The method described in this document compares color samples as rendered by a given test source and a reference illuminant at the same correlated color temperature (CCT), with the reference illuminant being Planckian radiation up to and including 4000 K, a proportional blend of Planckian radiation and a CIE daylight (D) series illuminant between 4001 K and 4999 K, or a CIE D series illuminant at or above 5000 K. This familiar reference-based approach is compatible with a typical lighting design process, where color temperature is decided before color rendition is considered. The implications of choosing this system for defining the reference illuminant—based on the 2015 version of this document, IES TM-30-15—have been documented in “What is the Reference? An Examination of Alternatives to the Reference Sources Used in IES TM-30-15.”³ It is important to note that all measures specified in this document rely on the same reference scheme, allowing for a cohesive system.

This method utilizes 99 color evaluation samples (CES)—each represented by a spectral reflectance function—to quantify the difference in color rendition between the test source and reference illuminant. The samples were statistically down-selected from an initial collection of more than 100,000 measured objects, in order to be representative of the world of possible colors.⁴⁻⁶ A majority of the more than 100,000 spectral reflectance functions considered came from the University of Leeds database,⁷ which is itself a meta-base containing objects of various origins: textiles, plastics, skin tones, color systems. The Leeds database also includes the Standard Object Colour Spectra (SOCS) database,⁸ which contains printed materials, skin tones, natural objects, paints, and textiles. Additional data included natural objects,^{9,10} flowers,¹¹ skin tones,¹² and paints.^{9,13}

Finally, embedded within this method is the most current uniform color space, CAM02-UCS,¹⁴⁻¹⁶ which is based on CIECAM02¹⁷⁻¹⁹ and its native chromatic adaptation transformation. This color space was chosen because of its greater uniformity than CIELAB, and is important for ensuring the uniformity of the CES across color space and at a wide range of CCTs.^{5,14,20} The CIE 1964 10° standard colorimetric observer²¹ is used for all calculations except in determining CCT, where the definition calls for use of the CIE 1931 2° standard colorimetric

observer.²² This model of human vision helps ensure that color differences are appropriately scaled.

It is possible (and expected) that scientific advances related to any calculation component included in this Technical Memorandum will subsequently lead to updates to the method.

1.2 Calculated Measures

Using a unified calculation system, this Technical Memorandum (TM) provides equations and direction for calculating 50 primary numerical measures and one graphic (color vector graphic). The 50 numerical measures include 1 average color fidelity measure (fidelity index, R_f), 1 gamut area measure (gamut index, R_g), 16 hue-specific fidelity measures (local color fidelity, $R_{f,h}$), 16 hue-specific measures of chroma shift (local chroma shift, $R_{cs,h}$), and 16 hue-specific measures of hue shift (local hue shift, $R_{hs,h}$). Whereas R_f and R_g are global averages, the hue-specific local chroma shift and local hue shift values are important for characterizing *gamut shape*, which is the pattern of hue and chroma shift for different hues. Equations to calculate a sample-specific color fidelity value for each of the 99 CES (sample fidelity, $R_{f,CES}$) are also provided. This document is accompanied by software to aid in calculation and display of the results.

The measures included within this TM are intended to be used in various combinations—or in isolation—depending on the needs of a given application and design intent. This document does not establish performance thresholds, nor does it provide direction on how to do so, for any of the measures. Some experiments have been completed that relate the measures of this TM to subjective evaluations and propose performance thresholds.²³⁻²⁶

1.3 Changes from IES TM-30-15

This document replaces IES TM-30-15. The following technical changes have been made:

- For color samples with no native data outside the range of 400 to 700 nm, the extrapolation method was changed from a logarithm-based extrapolation to a flat extrapolation.
- The range encompassing the blended reference was changed from 4501 – 5499 K to 4001 – 4999 K.
- The scaling factor used in color fidelity calculations was changed from 7.54 to 6.73.

These changes have no material effect on the rank order of light sources for any of the included

measures. They make IES R_f (ANSI/IES TM-30-18) and CIE R_f (CIE 224:2017²⁷) equivalent measures. CIE 224:2017 is limited only to color fidelity, and its scope does not include measures for color rendition considerations beyond color fidelity.

This revision also provides greater clarity on the derivation of the color vector graphic, and specifies the equations used to calculate local chroma shift and local hue shift.

2.0 SCOPE

This evaluation method is applicable to light sources and lighting systems intended for general illumination of indoor spaces and some outdoor settings, at light levels where photopic vision is dominant. It is best suited to characterize nominally white light sources (i.e., those that fall on or near the Planckian locus). If a light source's chromaticity falls outside of the chromaticity bins defined in ANSI C77.388-2017,²⁸ then calculations based on this TM should be interpreted with caution.

3.0 CORE CALCULATIONS

3.1 Colorimetric Observer

Tristimulus values for the color evaluation samples shall be determined using the CIE 1964 10° standard colorimetric observer, with color matching functions (CMFs) $\bar{x}_{10}(\lambda)$, $\bar{y}_{10}(\lambda)$, $\bar{z}_{10}(\lambda)$.¹⁰ The 1 nm-increment table is available in CIE 15:2004, *Colorimetry – Part 1: CIE Standard Colorimetric Observers*.²¹ The exception is in determining the CCT of the test source, which by definition requires the use of the CIE 1931 2° standard colorimetric observer.^{17,21,22} It should also be noted that, for light source specifications, the CIE 1931 standard colorimetric observer [$\bar{x}(\lambda)$, $\bar{y}(\lambda)$, $\bar{z}(\lambda)$] is used to calculate chromaticity coordinates (x , y) and (u' , v'). The 1964 10° CMFs are used for light sources in this document only for the purpose of calculating color rendition measures.

3.2 Test Source

The relative spectral power distribution (SPD) of the light source in question (*test source*) is denoted $S_i(\lambda)$. The necessary wavelength range is described in **Section 3.5**. The tristimulus values of the test source shall be calculated as follows: