



ATIS-0500032.v002

ATIS Standard on -

**ATIS STANDARD FOR IMPLEMENTATION OF AN IMS-BASED NG9-1-1
SERVICE ARCHITECTURE**



As a leading technology and solutions development organization, the Alliance for Telecommunications Industry Solutions (ATIS) brings together the top global ICT companies to advance the industry's most pressing business priorities. ATIS' nearly 200 member companies are currently working to address the All-IP transition, 5G, network functions virtualization, big data analytics, cloud services, device solutions, emergency services, M2M, cyber security, network evolution, quality of service, billing support, operations, and much more. These priorities follow a fast-track development lifecycle — from design and innovation through standards, specifications, requirements, business use cases, software toolkits, open source solutions, and interoperability testing.

ATIS is accredited by the American National Standards Institute (ANSI). The organization is the North American Organizational Partner for the 3rd Generation Partnership Project (3GPP), a founding Partner of the oneM2M global initiative, a member of and major U.S. contributor to the International Telecommunication Union (ITU), as well as a member of the Inter-American Telecommunication Commission (CITEL). For more information, visit www.atis.org.

Notice of Disclaimer & Limitation of Liability

The information provided in this document is directed solely to professionals who have the appropriate degree of experience to understand and interpret its contents in accordance with generally accepted engineering or other professional standards and applicable regulations. No recommendation as to products or vendors is made or should be implied.

NO REPRESENTATION OR WARRANTY IS MADE THAT THE INFORMATION IS TECHNICALLY ACCURATE OR SUFFICIENT OR CONFORMS TO ANY STATUTE, GOVERNMENTAL RULE OR REGULATION, AND FURTHER, NO REPRESENTATION OR WARRANTY IS MADE OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS. ATIS SHALL NOT BE LIABLE, BEYOND THE AMOUNT OF ANY SUM RECEIVED IN PAYMENT BY ATIS FOR THIS DOCUMENT, AND IN NO EVENT SHALL ATIS BE LIABLE FOR LOST PROFITS OR OTHER INCIDENTAL OR CONSEQUENTIAL DAMAGES. ATIS EXPRESSLY ADVISES THAT ANY AND ALL USE OF OR RELIANCE UPON THE INFORMATION PROVIDED IN THIS DOCUMENT IS AT THE RISK OF THE USER.

NOTE - The user's attention is called to the possibility that compliance with this standard may require use of an invention covered by patent rights. By publication of this standard, no position is taken with respect to whether use of an invention covered by patent rights will be required, and if any such use is required no position is taken regarding the validity of this claim or any patent rights in connection therewith. Please refer to <https://www.atis.org/policy/patent-assurances/> to determine if any statement has been filed by a patent holder indicating a willingness to grant a license either without compensation or on reasonable and non-discriminatory terms and conditions to applicants desiring to obtain a license.

Published by

**Alliance for Telecommunications Industry Solutions
1200 G Street, NW, Suite 500
Washington, DC 20005**

Copyright © 2022 by Alliance for Telecommunications Industry Solutions
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher. For information contact ATIS at 202.628.6380. ATIS is online at < <http://www.atis.org> >.

ATIS Standard for Implementation of an IMS-based NG9-1-1 Service Architecture

Alliance for Telecommunications Industry Solutions

Approved April 5, 2022

Abstract

This Standard defines the Stage 2 (architecture) and Stage 3 (protocol) specifications for an IMS-based NG9-1-1 Service Architecture. This Standard includes the architecture, functional elements, call flows, protocols, and interfaces which were derived from the Stage 1 requirements in ATIS-0500023, "Applying Common IMS to NG9-1-1 Networks".

Foreword

The Alliance for Telecommunication Industry Solutions (ATIS) serves the public through improved understanding between carriers, customers, and manufacturers.

The ESIF IP Multimedia Subsystem for 9-1-1 (IMS911) subgroup led this joint work effort that addresses the application of common IMS (Stage 1, 2, and 3) for the processing, transport, and/or delivery of Emergency Service calls within the NG9-1-1 network to the appropriate Public Safety Answering Point (PSAP). This is a joint effort with the Emergency Services Interconnection Forum Next Generation Emergency Service (ESIF NGES) Subcommittee, Packet Technologies and Systems Committee (PTSC) and the Wireless Technologies and Systems Committee Systems and Network Subcommittee (WTSC SN).

The Emergency Services Interconnection Forum (ESIF) provides a forum to facilitate the identification and resolution of technical and/or operational issues related to the interconnection of wireline, wireless, cable, satellites, Internet and emergency services networks.

The ESIF Next Generation Emergency Services (NGES) Subcommittee coordinates emergency services needs and issues with and among SDOs and industry forums/committees, within and outside ATIS, and develops emergency services (such as E9-1-1) standards, and other documentation related to advanced (i.e., Next Generation) emergency services architectures, functions, and interfaces for communications networks.

The Packet Technologies and Systems Committees (PTSC) develops and recommends standards and technical reports related to services, architectures, and signaling, in addition to related subjects under consideration in other North American and international standards bodies. PTSC coordinates and develops standards and technical reports relevant to telecommunications networks in the U.S., reviews and prepares contributions on such matters for submission to U.S. ITU-T and U.S. ITU-R Study Groups or other standards organizations, and reviews for acceptability or per contra the positions of other countries in related standards developments and takes or recommends appropriate actions.

The Wireless Technologies and Systems Committee (WTSC) develops and recommends standards and technical reports related to wireless and/or mobile services and systems, including service descriptions and wireless technologies. WTSC develops and recommends positions on related subjects under consideration in other North American, regional, and international standards bodies.

The WTSC Systems and Networks Subcommittee (WTSC SN) develops, maintains, amends and enhances American National Standards and ATIS deliverables related to system aspects, networks, and terminals within the GSM family (GSM/EGPRS/UMTS) such as circuit-switched, packet-switched and IP Multimedia services including future developments.

Suggestions for improvement of this document are welcome. They should be sent to the Alliance for Telecommunications Industry Solutions, ESIF, 1200 G Street NW, Suite 500, Washington, DC 20005.

At the time of consensus on this document, the committees responsible for its development, had the following leadership:

D. Morkunas, ESIF Chair (Intrado)

J. Torres, ESIF First Vice-Chair (Verizon Wireless)

B. Abley, ESIF Second Vice-Chair (NENA)

T. Reese, ESIF IMS911 Co-Chair, ESIF NGES Co-Chair (Ericsson)

M. Dolly, PTSC Chair (AT&T)

V. Shaikh, PTSC Vice-Chair (Peraton Labs)

M. Younge, WTSC Chair (T-Mobile)

D. Zelmer, WTSC Vice-Chair (AT&T)

T. Brooks, WTSC SN Chair (T-Mobile)

P. Musgrove, WTSC SN Vice-Chair (AT&T)

Table of Contents

Preface	1
1 Scope, Purpose, & Application	2
1.1 Scope.....	2
1.2 Purpose	2
1.3 Application	2
2 Normative References	2
3 Informative References.....	5
4 Definitions, Acronyms, & Abbreviations	5
4.1 Definitions	5
4.2 Acronyms & Abbreviations.....	7
5 Introduction.....	10
6 Assumptions & Requirements	10
6.1 Basic Assumptions	10
6.2 Requirements	11
7 Architecture	11
7.1 Overview.....	11
7.2 IMS-Based NG9-1-1 Service Architecture Functional Elements	13
7.2.1 <i>Emergency Call Session Control Function (E-CSCF)</i>	13
7.2.2 <i>Interrogating Call Session Control Function (I-CSCF)</i>	13
7.2.3 <i>Location Retrieval Function (LRF)</i>	14
7.2.4 <i>Routing Determination Function (RDF)</i>	14
7.2.5 <i>Location Server (LS)</i>	14
7.2.6 <i>Interconnection Border Control Function (IBCF)</i>	14
7.2.7 <i>Legacy Network Gateway (LNG)</i>	15
7.2.8 <i>Emergency Call Routing Function (ECRF)</i>	15
7.2.9 <i>Legacy PSAP Gateway (LPG)</i>	15
7.2.10 <i>Application Server (AS)</i>	16
7.2.11 <i>Multimedia Resource Function Controller (MRFC)</i>	16
7.2.12 <i>Multimedia Resource Function Processor (MRFP)</i>	16
7.2.13 <i>Transit Function (TRF)</i>	16
7.3 Support for Secure Telephone Identity (STI) Services	17
7.3.1 <i>STI Verification of 9-1-1 Originations</i>	17
7.3.2 <i>STI Authentication of PSAP-Originated/Callback Calls</i>	19
7.4 Resource-Priority Header Signing and SIP Priority Header Signing.....	21
7.5 Reference Protocols	24
8 Stage 2 Call Flows.....	26
8.1 Legacy Wireline Origination to i3 and Legacy PSAPs	26
8.1.1 <i>Delivery of Legacy Wireline Emergency Call Origination to i3 PSAP</i>	26
8.1.2 <i>Delivery of Legacy Wireline Emergency Call Origination to Legacy PSAP</i>	29
8.2 Legacy CMRS Origination to i3 and Legacy PSAPs	31
8.2.1 <i>Delivery of Legacy Wireless Emergency Call Origination to i3 PSAP Using WCM</i>	31
8.2.2 <i>Delivery of Legacy Wireless Emergency Call Origination to Legacy PSAP Using WCM</i>	35
8.2.3 <i>Delivery of Legacy Wireless Emergency Call Origination to i3 PSAP using NCAS</i>	39
8.2.4 <i>Delivery of Legacy Wireless Emergency Call Origination to Legacy PSAP using NCAS</i>	43
8.3 IMS Originating Network to i3 and Legacy PSAPs – LbyV	48
8.3.1 <i>Delivery of Emergency Call Origination from IMS Origination Network to i3 PSAP with LbyV</i>	48

8.3.2	<i>Delivery of Emergency Call Origination from IMS Origination Network to Legacy PSAP with LbyV</i>	50
8.4	IMS Originating Network to i3 and Legacy PSAPs – LbyR.....	55
8.4.1	<i>Delivery of Emergency Call Origination from IMS Origination Network to i3 PSAP with LbyR.....</i>	55
8.4.2	<i>Delivery of Emergency Call Origination from IMS Origination Network to Legacy PSAP with LbyR</i>	58
8.5	Non-IMS Originating Network to i3 and Legacy PSAPs – LbyV	62
8.5.1	<i>Delivery of Emergency Call Origination from Non-IMS VoIP Origination Network to i3 PSAP with LbyV</i>	62
8.5.2	<i>Delivery of Emergency Call Origination from Non-IMS VoIP Origination Network to Legacy PSAP with LbyV.....</i>	66
8.6	Non-IMS VoIP Originating Network to i3 and Legacy PSAPs – LbyR	70
8.6.1	<i>Delivery of Emergency Call Origination from Non-IMS Origination Network to i3 PSAP with LbyR.</i>	70
8.6.2	<i>Delivery of Emergency Call Origination from Non-IMS Origination Network to Legacy PSAP with LbyR</i>	73
8.7	TTY Interworking on Emergency Calls to Legacy/i3 PSAPs	78
8.7.1	<i>RTT Calls from IMS Originating Network to Legacy PSAP via NG9-1-1.....</i>	78
8.7.2	<i>TTY Calls from Legacy Originating Network to an i3 PSAP via NG9-1-1</i>	80
8.7.3	<i>TTY Calls from Legacy Originating Network to a Legacy PSAP via NG9-1-1.....</i>	85
8.8	Call Transfer/Bridging.....	89
8.8.1	<i>Support for Attended Emergency Call Transfer Requests from i3 PSAPs to Transfer-to PSAPs/Destinations</i>	90
8.8.2	<i>Support for Attended Emergency Call Transfer Requests from Legacy PSAPs to Transfer-to PSAPs/Destinations</i>	124
8.8.3	<i>Support for Blind Transfer Requests from i3 PSAPs to Transfer-to PSAPs/Destinations.....</i>	136
8.9	Policy Routing Scenarios.....	142
8.10	Failure Scenarios.....	145
8.10.1	<i>Error Conditions.....</i>	145
8.11	PSAP Callback Flows.....	146
8.12	Caller Identity and Resource-Priority Header Authentication/Signing and Verification	147
8.12.1	<i>9-1-1 Origination from an IMS Originating Network.....</i>	148
8.12.2	<i>9-1-1 Origination from a Non-IMS VoIP Originating Network.....</i>	150
8.12.3	<i>Callback to IMS Home Network - Transit Function Interacts with STI-AS.....</i>	152
8.12.4	<i>Callback to IMS Home Network - Exit IBCF Interacts with STI-AS</i>	154
8.12.5	<i>Callback to Non-IMS VoIP Home Network – Transit Function Interacts with STI-AS.....</i>	156
8.12.6	<i>Callback to Non-IMS VoIP Home Network – Exit IBCF Interacts with STI-AS.....</i>	158
9	Stage 3	160
9.1	Procedures & Header Usage for the Emergency CSCF (E-CSCF).....	160
9.1.1	<i>Header Usage.....</i>	161
9.2	Procedures & Header Usage for the Location Retrieval Function (LRF).....	162
9.2.1	<i>Processing of Origination from i3-Compliant Originating Network or LNG.....</i>	162
9.2.2	<i>Using Incoming Signaling Information to Facilitate Error Handling</i>	162
9.2.3	<i>Header Usage.....</i>	163
9.2.4	<i>Procedures at Policy Routing Function (PRF).....</i>	163
9.3	Procedures at the RDF	165
9.3.1	<i>Procedures for Provisioning the RDF.....</i>	165
9.4	Procedures at the LNG	165
9.4.1	<i>SS7 Wireline to SIP Header Mapping Example</i>	166
9.4.2	<i>CAMA Wireline to SIP Header Mapping Example.....</i>	167
9.4.3	<i>FG D Wireline to SIP Header Mapping Example.....</i>	167
9.4.4	<i>SS7 Wireline Compatibility Mode to SIP Header Mapping Example.....</i>	167
9.4.5	<i>CAMA MF WCM to SIP Header Mapping Example.....</i>	168
9.4.6	<i>FG D MF WCM to SIP Header Mapping Example</i>	168
9.4.7	<i>SS7 NCAS to SIP Header Mapping Example.....</i>	169
9.4.8	<i>CAMA MF NCAS to SIP Header Mapping Example.....</i>	169
9.4.9	<i>FG D MF NCAS to SIP Header Mapping Example</i>	169
9.5	Procedures at the LPG	170
9.6	Procedures at the IBCF	171

9.6.1	Entry Point IBCF	171
9.6.2	Exit Point IBCF.....	172
9.7	Procedures at the I-CSCF	173
9.8	Procedures at the Conferencing Application Server (AS).....	173
9.9	Procedures at the Multimedia Resource Function Controller (MRFC)	174
9.10	Procedures at the Multimedia Resource Function Processor (MRFP).....	174
9.11	Procedures at the Transit Function	174
9.12	Procedures at the STI-AS.....	174
9.13	Procedures at the STI-VS.....	175
10	Location Validation	175
11	Test Calls.....	176
12	Logging.....	176
13	Discrepancy Reporting	177
14	Security Considerations.....	178
15	Network Monitoring Thresholds	179
A	SIP INVITE Profile for Emergency Calls.....	181
B	Message Examples	184
B.1	Legacy Fixed Line UE to Traditional Legacy PSAP (Wireline) Example	184
B.2	Legacy Mobile UE to Traditional Legacy PSAP (Wireless) Example	185
B.3	Fixed Line IP OSP UE to Traditional Legacy PSAP Example	185
B.4	Mobile IP OSP UE to Traditional Legacy PSAP Example	186
C	Analysis of Network Monitoring Thresholds in IMS-based NG9-1-1 Emergency Services Network	187

Table of Figures

Figure 7.1:	IMS origination network emergency call architecture from 3GPP TS 23.167	12
Figure 7.2:	IMS-Based NG9-1-1 Service Architecture	13
Figure 8.1:	Delivery of Legacy Wireline Emergency Call Origination to i3 PSAP	27
Figure 8.2:	Delivery of Legacy Wireline Emergency Call Origination to Legacy PSAP	29
Figure 8.3:	Delivery of Legacy Wireless Emergency Call Origination to i3 PSAP Using WCM	32
Figure 8.4:	Delivery of Legacy Wireless Emergency Call Origination to Legacy PSAP Using WCM.....	36
Figure 8.5:	Delivery of Legacy Wireless Emergency Call Origination to i3 PSAP Using NCAS40	36
Figure 8.6:	Delivery of Legacy Wireless Emergency Call Origination to Legacy PSAP Using NCAS.....	44
Figure 8.7:	Delivery of IMS Emergency Call Origination to i3 PSAP with LbyV	49
Figure 8.8:	Delivery of IMS Emergency Call Origination to Legacy PSAP with LbyV	51
Figure 8.9:	Delivery of IMS Emergency Call Origination to i3 PSAP with LbyR.....	56
Figure 8.10:	Delivery of IMS Emergency Call Origination to Legacy PSAP with LbyR	59
Figure 8.11:	Delivery of Non-IMS Emergency Call Origination to i3 PSAP with LbyV	64
Figure 8.12:	Delivery of Non-IMS Emergency Call Origination to Legacy PSAP with LbyV	67
Figure 8.13:	Delivery of Non-IMS Emergency Call Origination to i3 PSAP with LbyR	71
Figure 8.14:	Delivery of Non-IMS Emergency Call Origination to Legacy PSAP with LbyR	74
Figure 8.15:	RTT Calls from IMS Originating Network to Legacy PSAP via NG9-1-1	79

Figure 8.16: TTY Calls from Legacy Originating Network to an i3 PSAP via NG9-1-1 – Part I 82

Figure 8.17: TTY Calls from Legacy Originating Network to an i3 PSAP via NG9-1-1 – Part II 84

Figure 8.18: TTY Calls from Legacy Originating Network to a Legacy PSAP via NG9-1-1 – Part I 86

Figure 8.19: TTY Calls from Legacy Originating Network to a Legacy PSAP via NG9-1-1 – Part II..... 88

Figure 8.20: Conferencing Functional Architecture..... 90

Figure 8.21: i3 PSAP Establishes Conference with Conferencing AS/MRFC..... 92

Figure 8.22: i3 PSAP Requests that IBCF/B2BUA be Invited to the Conference 94

Figure 8.23: i3 PSAP Requests that a Transfer-to i3 PSAP be Invited to the Conference 96

Figure 8.24: i3 PSAP Requests that a Transfer-to Legacy PSAP be Invited to the Conference 99

Figure 8.25: Transfer-from i3 PSAP Disconnects from the Conference – Transfer-to PSAP is an I3 PSAP 101

Figure 8.26: Transfer-from i3 PSAP Disconnects from the Conference – Transfer-to PSAP is a Legacy PSAP 102

Figure 8.27: Transfer-to i3 PSAP Completes the Transfer and Terminates the Call 104

Figure 8.28: Transfer-to Legacy PSAP/LPG Completes the Transfer and Terminates the Call 106

Figure 8.29: Transfer-from i3 PSAP Invokes the Conference..... 109

Figure 8.30: Application Server (AS) Bridges Call #1 and Call #2 via IBCF#2 111

Figure 8.31: Application Server (AS) Invites Transfer-to i3 PSAP to Conference..... 113

Figure 8.32: Application Server (AS) Invites Transfer-to Legacy PSAP to Conference 116

Figure 8.33: Transfer-from i3 PSAP Drops out of Conference with Transfer-to i3 PSAP 119

Figure 8.34: Transfer-from i3 PSAP Drops out of Conference with Transfer-to Legacy PSAP 120

Figure 8.35: Conference AS/MRFC Released by Transfer-to i3 PSAP 122

Figure 8.36: Conference AS/MRFC Released by Transfer-to Legacy PSAP..... 123

Figure 8.37: Legacy PSAP Requests Transfer; LPG Establishes Conference with Conferencing AS/MRFC 125

Figure 8.38: Transfer-from Legacy PSAP Disconnects from the Conference – Transfer-to PSAP is an I3 PSAP 128

Figure 8.39: Transfer-from Legacy PSAP Disconnects from the Conference – Transfer-to PSAP is a Legacy PSAP 129

Figure 8.40: Legacy PSAP Establishes Conference with Conferencing AS/MRFC 131

Figure 8.41: Transfer-from Legacy PSAP Drops out of Conference with Transfer-to i3 PSAP 134

Figure 8.42: Transfer-from Legacy PSAP Drops out of Conference with Transfer-to Legacy PSAP 135

Figure 8.43: Blind Transfer: Transfer-from i3 PSAP to Transfer-to i3 PSAP..... 137

Figure 8.44: IMS Based Call to i3 PSAP – PRF Example..... 144

Figure C.1: Call Setup, Call Routing and Dereferencing Transactions 187

Figure C.2: Other Transactions 188

Table of Tables

Table 9-1: Mapping at LNG 166

Table 9-2: SS7 Wireline to SIP Header Mapping Example..... 166

Table 9-3: CAMA MF Wireline to SIP Header Mapping Example	167
Table 9-4: FG D MF Wireline to SIP Header Mapping Example	167
Table 9-5: SS7 WCM to SIP Header Mapping Example	167
Table 9-6: CAMA MF WCM to SIP Header Mapping Example	168
Table 9-7: FG D MF WCM to SIP Header Mapping Example	168
Table 9-8: SS7 NCAS to SIP Header Mapping Example	169
Table 9-9: CAMA MF NCAS to SIP Header Mapping Example	169
Table 9-10: FG D MF NCAS to SIP Header Mapping Example	170
Table A-1: SIP INVITE Header Profile Legend	181
Table A-2: SIP INVITE Header Profile	182

ATIS Standard on –

Implementation of an IMS-based NG9-1-1 Service Architecture

Preface

ATIS has developed a Next Generation 9-1-1 network and emergency call processing architecture based on contributions received since 2011 and based on requirements by a number of wireless carriers to have an IP Multimedia Subsystem (IMS)-compatible NG9-1-1 design¹. Additionally, the NENA i3 Architecture Working Group² deferred the IMS-based Emergency Services IP Network (ESInet) development to ATIS. ATIS' goal in developing this standard has been transparent interoperability between the two network designs.

ATIS' intent in this development work was to produce a standard method for IMS-based carriers to offer NG9-1-1 services wholly within their IMS platforms, while maintaining consistency and interoperability with the NENA i3 ESInet/NGCS (Next Generation Core Services) design goals. This kind of standards approach allows IMS-based carriers to take advantage of complete IMS interoperability and features found in their existing IMS ecosystems, while still remaining interoperable with downstream i3 PSAPs that implement NENA i3 standards and interfaces.

It is also ATIS' goal to assure that terminating NG9-1-1 entities, such as i3 PSAPs, find the upstream networks that are built on the ATIS IMS-based NG9-1-1 Service Architecture to be as completely interoperable with their systems and networks as that of a NENA i3 NG9-1-1 standard SIP-based architecture. This goal of transparency, both upstream and downstream between architectures, ensures that an i3 PSAP should find no difference whether the i3 PSAP interconnects to a NENA i3 ESInet with NGCS, or interconnects to an ATIS IMS-based NG9-1-1 Service Architecture. This consistent interoperability principle has guided all of ATIS' development work since the beginning, as documented within the original Issue Statement underlying this work.

The ATIS IMS-based NG9-1-1 Service Architecture provides compatibility for IMS-based carriers acting as an NG9-1-1 System Service Provider (911SSP) to seamlessly interoperate with NENA i3 ESInet architectures.

For entities early in the process of selecting ESInet solutions, the expectation within this ATIS development work was that the ATIS IMS-based NG9-1-1 Service Architecture would offer a choice for carriers that already had an IMS ecosystem, but not be considered a viable architecture choice for 9-1-1 service entities that had no plans for an IMS infrastructure.

Public Safety entities should naturally understand the applicability of an IMS-based NG9-1-1 Service Architecture network approach to processing emergency calls, yet in this case, they can remain confidently focused on NENA i3-based NG9-1-1 architectures, (this is because IMS may be of interest to carriers, not to jurisdictions), which means that Public Safety's progress and momentum to adopt NG9-1-1 will not be impeded by the introduction of this ATIS NG9-1-1 Service Architecture standard.

¹ IMS is a set of standards based on the IETF RFC 3261 [Ref 18] family of standards that also introduces additional requirements, specific for carrier operators not differentiated in the more general SIP RFCs.

² The NENA i3 Architecture Working Group developed NENA-STA-010.3 [Ref 27].

1 Scope, Purpose, & Application

1.1 Scope

This ATIS Standard applies IP Multimedia Subsystem (IMS) architecture concepts to Next Generation 9-1-1 (NG9-1-1) networks to encompass:

- Definition of an IMS-based NG9-1-1 Emergency Services Network architecture and set of additional gateway functional elements that are integrated into this IMS-based NG9-1-1 Service Architecture, adopted from the existing NENA i3 architecture, to support the delivery of emergency calls to legacy and NG9-1-1/i3 Public Safety Answering Points (PSAPs).
- NG9-1-1 network deployment scenarios showing an IMS-based NG9-1-1 Service Architecture interconnecting with a variety of originating network and PSAP types, and associated Stage 2/3 call flows.

1.2 Purpose

IMS standards for Emergency Services have been under development and enhancement in 3GPP since 3GPP Release 9. However, from a Next Generation Emergency Services (NG9-1-1) network perspective, the IMS architecture only defined Emergency Service call processing for the originating network and has not defined call processing, transport, or delivery of Emergency Service calls by an IMS-based NG9-1-1 Emergency Services Network.

The purpose of this Standard is to define the Stage 2 (architecture) and Stage 3 (protocols) to enable North American deployment of NG9-1-1 emergency services networks that are based upon the 3GPP IMS specifications. This IMS-based NG9-1-1 emergency services network is called IMS-based NG9-1-1 Service Architecture.

This Standard includes the architecture, functional elements, call flows, protocols, and interfaces which were derived from the Stage 1 requirements in ATIS-0500023, "Applying Common IMS to NG9-1-1 Networks" [Ref 26].

1.3 Application

The standard applies to requests for emergency services originating from legacy, IMS-based, and generic Voice over Internet Protocol (VoIP) originating networks by routing those emergency service requests to the appropriate PSAP. This standard applies to routing voice, text, and multimedia requests.

2 Normative References

The following standards contain provisions which, through reference in this text, constitute provisions of this ATIS Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this ATIS Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

[Ref 1] 3GPP TS 23.167, *Technical Specification Group Services and System Aspects; IP Multimedia Subsystem (IMS) emergency sessions*.³

[Ref 2] 3GPP TS 24.229, *Technical Specification Group Services and System Aspects; IP multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3*.³

[Ref 3] 3GPP TS 22.101, *Technical Specification Group Services and System Aspects; Service aspects; Service principles*.³

[Ref 4] 3GPP TS 23.002, *Technical Specification Group Services and System Aspects; Network architecture*.³

³ This document is available from the Third Generation Partnership Project (3GPP) at: < <http://www.3gpp.org/specs/specs.htm> >