



ATIS-0700015.v005

ATIS Standard on -

**ATIS Standard for Implementation of 3GPP Common IMS
Emergency Procedures for IMS Origination and ESInet/Legacy
Selective Router Termination**



As a leading technology and solutions development organization, the Alliance for Telecommunications Industry Solutions (ATIS) brings together the top global ICT companies to advance the industry's most pressing business priorities. ATIS' nearly 200 member companies are currently working to address the All-IP transition, 5G, network functions virtualization, big data analytics, cloud services, device solutions, emergency services, M2M, cyber security, network evolution, quality of service, billing support, operations, and much more. These priorities follow a fast-track development lifecycle — from design and innovation through standards, specifications, requirements, business use cases, software toolkits, open source solutions, and interoperability testing.

ATIS is accredited by the American National Standards Institute (ANSI). The organization is the North American Organizational Partner for the 3rd Generation Partnership Project (3GPP), a founding Partner of the oneM2M global initiative, a member of the International Telecommunication Union (ITU), as well as a member of the Inter-American Telecommunication Commission (CITEL). For more information, visit www.atis.org.

Notice of Disclaimer & Limitation of Liability

The information provided in this document is directed solely to professionals who have the appropriate degree of experience to understand and interpret its contents in accordance with generally accepted engineering or other professional standards and applicable regulations. No recommendation as to products or vendors is made or should be implied.

NO REPRESENTATION OR WARRANTY IS MADE THAT THE INFORMATION IS TECHNICALLY ACCURATE OR SUFFICIENT OR CONFORMS TO ANY STATUTE, GOVERNMENTAL RULE OR REGULATION, AND FURTHER, NO REPRESENTATION OR WARRANTY IS MADE OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS. ATIS SHALL NOT BE LIABLE, BEYOND THE AMOUNT OF ANY SUM RECEIVED IN PAYMENT BY ATIS FOR THIS DOCUMENT, AND IN NO EVENT SHALL ATIS BE LIABLE FOR LOST PROFITS OR OTHER INCIDENTAL OR CONSEQUENTIAL DAMAGES. ATIS EXPRESSLY ADVISES THAT ANY AND ALL USE OF OR RELIANCE UPON THE INFORMATION PROVIDED IN THIS DOCUMENT IS AT THE RISK OF THE USER.

NOTE - The user's attention is called to the possibility that compliance with this standard may require use of an invention covered by patent rights. By publication of this standard, no position is taken with respect to whether use of an invention covered by patent rights will be required, and if any such use is required no position is taken regarding the validity of this claim or any patent rights in connection therewith. Please refer to <https://www.atis.org/policy/patent-assurances/> to determine if any statement has been filed by a patent holder indicating a willingness to grant a license either without compensation or on reasonable and non-discriminatory terms and conditions to applicants desiring to obtain a license.

Published by

Alliance for Telecommunications Industry Solutions
1200 G Street, NW, Suite 500
Washington, DC 20005

Copyright © 2021 by Alliance for Telecommunications Industry Solutions
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher. For information contact ATIS at 202.628.6380. ATIS is online at < <http://www.atis.org> >.

ATIS Standard on

ATIS Standard for Implementation of 3GPP Common IMS Emergency Procedures for IMS Origination and ESInet/Legacy Selective Router Termination

Alliance for Telecommunications Industry Solutions

Approved June 2021

Abstract

This document identifies and adapts as necessary 3GPP common IMS emergency procedures for applicability in North America to support emergency communications originating from an IMS subscriber (wireline or wireless; fixed, mobile or nomadic) and terminating at an ESInet, or, for appropriate media, legacy emergency services network to support Multimedia Emergency Services (MMES).

It is the intent of this standard to support a full multimedia experience; therefore, simultaneous text, voice, pictures, and video are supported in this standard.

ATIS Standard on –

ATIS Standard for Implementation of 3GPP Common IMS Emergency Procedures for IMS Origination and ESInet/Legacy Selective Router Termination

Foreword

As a leading technology and solutions development organization, the Alliance for Telecommunications Industry Solutions (ATIS) brings together the top global information and communications technology (ICT) companies to advance the industry's most-pressing business priorities. ATIS serves the public through improved understanding between carriers, customers, and manufacturers.

This standard was developed jointly between ESIF, PTSC, and WTSC.

The Emergency Services Interconnection Forum (ESIF) provides a forum to facilitate the identification and resolution of technical and/or operational issues related to the interconnection of wireline, wireless, cable, satellites, Internet and emergency services networks.

The Packet Technologies and Systems Committee (PTSC) develops and recommends standards and technical reports related to services, architectures, and signaling, in addition to related subjects under consideration in other North American and international standards bodies. PTSC coordinates and develops standards and technical reports relevant to telecommunications networks in the U.S., reviews and prepares contributions on such matters for submission to U.S. ITU-T and U.S. ITU-R Study Groups or other standards organizations, and reviews for acceptability or per contra the positions of other countries in related standards development and takes or recommends appropriate actions.

The Wireless Technologies and Systems Committee (WTSC) develops and recommends standards and technical reports related to wireless and/or mobile services and systems, including service descriptions and wireless technologies. WTSC develops and recommends positions on related subjects under consideration in other North American, regional, and international standards bodies.

Suggestions for improvement of this document are welcome. They should be sent to the Alliance for Telecommunications Industry Solutions, WTSC, 1200 G Street NW, Suite 500, Washington, DC 20005.

At the time of initiation or issuance of the letter ballot for this document, the committees responsible for its development had the following leadership:

R. Muscat, ESIF Chair (Bexar Metro 911)
D. Morkunas, ESIF First Vice Chair (Intrado)
J. Torres, ESIF Second Vice Chair (Verizon Wireless)

M. Dolly, PTSC Chair (AT&T)
V. Shaikh, PTSC Vice-Chair (Peraton Labs)

M. Younge, WTSC Chair (T-Mobile)
D. Zelmer, WTSC Vice Chair (AT&T)

F. Khatibi, Technical Editor (Qualcomm)

The **IMSESINET** Subcommittee was responsible for the development of this document.

Table of Contents

1	Scope, Purpose, & Application	7
1.1	Scope.....	7
1.2	Purpose	7
1.3	Application	7
2	Normative References	7
3	Informative References.....	9
4	Definitions, Acronyms, & Abbreviations	10
4.1	Definitions	10
4.2	Acronyms & Abbreviations.....	11
5	Introduction.....	13
6	Assumptions & Requirements	15
6.1	Basic Assumptions	15
6.2	Assumptions Associated with Caller Identity, RPH and SIP Priority Header Signing/Verification 15	
6.3	Requirements	16
6.4	Requirements Associated with Caller Identity, RPH and SIP Priority Header Signing/Verification 20	
7	Architecture	22
7.1	Overview.....	22
7.2	IMS Functional Elements.....	25
7.2.1	User Equipment (UE).....	25
7.2.2	Proxy Call Session Control Function (P-CSCF)	25
7.2.3	Emergency Call Session Control Function (E-CSCF)	25
7.2.4	Serving Call Session Control Function (S-CSCF)	25
7.2.5	Location Retrieval Function (LRF)	25
7.2.6	Routing Determination Function (RDF)	25
7.2.7	Media Gateway Control Function (MGCF)	26
7.2.8	Emergency Access Transfer Function (EATF)	26
7.2.9	Interrogating Call Session Control Function (I-CSCF).....	26
7.2.10	Location Server (LS).....	26
7.2.11	Breakout Gateway Control Function (BGCF)	26
7.2.12	Interconnection Border Control Function (IBCF)	26
7.2.13	Home Subscriber Server (HSS).....	26
7.3	Emergency Services Network Functional Elements	26
7.3.1	Automatic Location Identification (ALI)	26
7.3.2	Border Control Function (BCF).....	26
7.3.3	Emergency Service Routing Proxy (ESRP).....	26
7.3.4	Emergency Call Routing Function (ECRF).....	27
7.3.5	Public Safety Answering Point (PSAP).....	27
7.3.6	Selective Router (SR)	27
7.4	Functional Elements Supporting Caller Identity Authentication/Verification and RPH Signing/Verification.....	27
7.4.1	P-CSCF.....	27
7.4.2	IBCF	27
7.4.3	Secure Telephone Identity Authentication Service (STI-AS).....	28
7.4.4	Secure Telephone Identity Verification Service (STI-VS).....	28
7.4.5	Call Validation Treatment (CVT).....	28
7.4.6	Secure Key Store (SKS)	28

7.4.7	Certificate Provisioning Service	28
7.4.8	Secure Telephone Identity Certificate Repository (STI-CR).....	28
7.4.9	ESRP	28
7.5	High Level Signaling Flow Diagram	29
7.6	Adding or Dropping Media to an Existing Voice Call	30
7.7	Procedures Related to Establishment of IMS Emergency Session	31
7.7.1	SOS Service URNs.....	31
7.8	MMES (audio and video) Call to Legacy PSAP via Legacy SR.....	31
7.9	MMES Upgrade Attempt of an Emergency Call with Legacy PSAP	32
7.10	MMES (without an offer of audio or text media) Call to Legacy PSAP via Legacy SR.....	33
8	Stage 3	36
8.1	Reference Protocols	36
8.1.1	Location Retrieval & Routing Functions.....	36
8.1.2	Caller Identity and Resource Priority Header/Priority Header Signing and Verification	38
8.2	Call Flows	39
8.2.1	Call Delivery to a NENA i3 ESInet.....	39
8.2.2	Call Delivery to a Legacy Selective Router.....	47
8.2.3	Emergency Access Network Flows	50
8.2.4	IMS Emergency Registration Flows.....	50
8.2.5	IMS Emergency Session Origination Flows.....	53
8.3	PSAP Callback Flows	55
8.3.1	Emergency Callback with Verification Performed by Entry IBCF	56
8.3.2	Emergency Callback with Verification Performed by CSCF	58
8.4	Location Acquisition & Conveyance Flows	59
8.5	Stage 3 Description	59
8.5.1	Procedures & Header Usage for the Emergency CSCF	59
8.5.2	Procedures & Header Usage for the Location Retrieval Function.....	64
8.5.3	Procedures at the RDF	67
8.5.4	Procedures at the BGCF.....	67
8.5.5	Procedures at the MGCF	67
8.5.6	Procedures at the IBCF	69
8.5.7	Procedures at the P-CSCF	69
8.5.8	Procedures at the S-CSCF	69
8.5.9	Procedures at the EATF	69
8.5.10	Procedures at the UE.....	69
8.5.11	Procedures for the Location Server	70
8.6	Media Considerations for Delivering Multimedia Calls	70
8.6.1	Considerations for Delivering Voice Media.....	70
8.6.2	Considerations for Delivering Real Time Video Media	70
8.6.3	Considerations for Delivering GTT Media.....	70
8.6.4	Considerations for Delivering Text Media.....	71
8.7	Stage 3 Call Flows	71
8.7.1	Routing Fixed UE to a Legacy Network Based upon Network Acquired Location (Dual Hosted Location Information Scenario)	71
8.7.2	Routing Fixed UE to a Legacy Network Based upon Network Acquired Location (Single Location Information Scenario)	72
8.7.3	Routing Fixed UE to an ESInet based upon Network Acquired Location.....	74
8.7.4	Routing a UE Provided Location to the Legacy Emergency Services Network	74
8.7.5	Routing a UE Provided Location to the ESInet.....	75
8.7.6	Initial Location Request.....	76
8.7.7	Update Location Request	77
8.7.8	Emergency Location Report	78
9	Access Network Requirements.....	79
9.1	LTE Access.....	79
9.2	HSPA Access	79

A	SIP INVITE Profile for Emergency Calls.....	81
B	Using MLP Between the LRF & LS for L0	85
	B.1 Request/Response Queries between LRF & LS over L0	85
	B.2 Asynchronous Data Push from LS to LRF over L0	87
C	Location Acquisition & Conveyance	91
	C.1 Control Plane Location Solution.....	91
	C.1.1 Control Plane Location for IMS Call Origination for LTE Access	91
	C.1.2 Control Plane Location Subsequent to IMS Call Origination for LTE Access	92
	C.1.3 Control Plane Location for IMS Call Origination for HSPA Access	93
	C.1.4 Control Plane Location Subsequent to IMS Call Origination for HSPA Access	94
	C.1.5 Location Continuity following handover of an IMS Emergency Call	95
	C.2 User Plane Location Solution.....	97
	C.2.1 User Plane Location for IMS Call Origination	97
	C.2.2 User Plane Location Subsequent to IMS Call Origination	99
D	Routing Methodology	100
	D.1 Flow Charts for Routing Methodology.....	101
E	Message Examples	106
	E.1 SIP INVITE Sent from P-CSCF to E-CSCF for Fixed-line UE.....	106
	E.2 SIP INVITE Sent from E-CSCF to LRF for Fixed-line UE	106
	E.3 SIP INVITE Sent from E-CSCF towards the Legacy PSAP for Fixed-line UE	107
	E.4 Response from the LRF to the E-CSCF for a Call that is to be Routed to a Legacy Emergency Services Network.....	107
	E.5 Response from the LRF to the E-CSCF for a Call that is to be Routed to an ESInet	108
	E.5.1 Response from LRF Containing Location-by-Reference.....	108
	E.5.2 Response from LRF Containing Location-by-Value	108
	E.6 Query & Response Examples between the LRF & RDF	109
	E.6.1 Query from the LRF to the RDF	109
	E.6.2 Response to the LRF from RDF	109
	E.7 SIP INVITE Sent from BGCF towards the Legacy Emergency Services Network Fixed-line UE.....	110
	E.8 SIP INVITE Sent from IBCF towards the ESInet for Mobile UE	110
F	Access Network Types	111
	F.1 LTE Access	111
	F.1.1 Summary & References	111
	F.1.2 Support of IMS Emergency Calls	111
	F.1.3 Handover of IMS Emergency Calls	111
	F.1.4 Location Support for IMS Emergency Calls	111
	F.2 HSPA Access	111
	F.2.1 Summary & References	111
	F.2.2 Support of IMS Emergency Calls	112
	F.2.3 Handover of IMS Emergency Calls	112
	F.2.4 Location Support for IMS Emergency Calls	112
G	Use Case	113
	G.1 IMS Emergency Call with Location Value Routed to a Legacy PSAP via a Legacy Emergency Services Network.....	113
	G.2 IMS Emergency Call with Location Value Routed to an ESInet	114
	G.3 IMS Emergency Call with a “Telephone Number” Routed to a Legacy PSAP via a Legacy Emergency Services Network	114
	G.4 IMS Emergency Call with a “Telephone Number” Routed to an ESInet	115

G.5 IMS Emergency Call with MDN/MSISDN & Cell Site/Sector Information Routed to a Legacy PSAP via a Legacy Emergency Services Network.....	116
G.6 IMS Emergency Call with MDN/MSISDN & Cell Site/Sector Information Routed to an ESInet..	117
G.7 IMS Emergency Call with Location Reference URI Routed to a Legacy PSAP via a Legacy Emergency Services Network Short Description	119
G.8 IMS Emergency Call with Location Reference URI Routed to an ESInet Short Description	120
G.9 IMS Emergency Call with Network Acquired Mobile Location Routed to a Legacy PSAP via a Legacy Emergency Services Network.....	121
G.10 IMS Emergency Call with Network Acquired Mobile Location Routed to an ESInet by Reference	122
G.11 IMS Call Received from a Mobile UE with Location Information but without a Valid Callback Number, & Routed to a Legacy PSAP via a Legacy Emergency Services Network	122
G.12 IMS Call Received from a Mobile UE with Location Information but without a Valid Callback Number & Routed to an ESInet.....	124
G.13 Adding Multimedia to an Existing Emergency Call	126
H Location-by-Reference.....	128

Table of Figures

Figure 7.1 – IMS origination network emergency call architecture from 3GPP TS 23.167	22
Figure 7.2 - Expanded Architecture	23
Figure 7.3 - Emergency Call - Caller Identity Authentication and RPH Signing Architecture ...	24
Figure 7.4 – A High Level Signaling Flow Diagram	29
Figure 7.5 – Adding Media to an Existing Voice Call	30
Figure 7.6 – MMES (audio and video) Call to Legacy PSAP via Legacy SR.....	31
Figure 7.7 – MMES Upgrade Attempt of an Emergency Call with Legacy PSAP	33
Figure 7.8 - MMES (w/o audio or text) Call to Legacy PSAP via Legacy SR (flow 2 of 2)	35
Figure 8.1 – LRF Decomposition Architecture	37
Figure 8.2 – UE Location-Routed Call Delivery to NENA i3 ESInet – Location-by-Reference.	40
Figure 8.3 – Cell-Routed Call Delivery to NENA i3 ESInet – Location-by-Reference	42
Figure 8.4 – Call Delivery to NENA i3 ESInet – Location-by-Value Delivered to ESInet	44
Figure 8.5 - Call Delivery to NENA i3 ESInet - Caller Identity and RPH Signing/Verification...	46
Figure 8.6 – Mobile Call Origination and Delivery to a Legacy Emergency Services Network using Associated Location	48
Figure 8.7 – IMS Emergency Registration	51
Figure 8.8 – Emergency Session Establishment	53
Figure 8.9 - Fixed UE Routed to Legacy using Network Provided Location Passing TN.....	72
Figure 8.10 – Fixed UE Routed to Legacy using Network Provided Location Passing Reference ID	73
Figure 8.11 – Fixed UE Routed to ESInet using Network Provided Location	74
Figure 8.12 - UE Provided Location to Legacy	75
Figure 8.13 - UE Provided Location to ESInet.....	75
Figure 8.14 – Initial Location Request from Legacy Emergency Services Network.....	76
Figure 8.15 – Initial Query from ESInet	77
Figure 8.16 – Update Location Request from Legacy Emergency Services Network shown as MLP interaction.....	77
Figure 8.17 – Update Location Request from ESInet shown as MLP interaction	78
Figure 8.18 – Emergency Location Report	79

Figure C.1 – Control Plane Location for IMS Emergency Call Origination for LTE Access.....	91
Figure C.2 – Control Plane Location following IMS Emergency Call Origination for LTE Access	92
Figure C.3 – Control Plane Location for IMS Emergency Call Origination for HSPA Access ..	93
Figure C.4 – Control Location following IMS Emergency Call Origination for HSPA Access...	94
Figure C.5 – Location Continuity following handover of an IMS Emergency Call	96
Figure C.6 – User Plane Location for IMS Emergency Call Origination for LTE, HSPA, and HRPD Access	98
Figure C.7 – User Plane Location following IMS Emergency Call Origination for LTE, HSPA, and HRPD Access	99
Figure D.1 – Emergency Call is Detected by IMS Origination Network and Routing Location is Acquired/Derived	101
Figure D.2 – Route URI is Determined	102
Figure D.3 – Emergency Call is Routed to NENA i3 ESInet – Additional Data “By-Value”	103
Figure D.4 – Emergency Call is Routed to NENA i3 ESInet – Additional Data “By-Reference”	104
Figure D.5 – LRF Determines that Emergency Call is to be Routed to Legacy Emergency Services Network.....	104
Figure D.7 – Emergency Call is Routed via Default or LRO Route URI	105
Figure D.8 – Emergency Call is Delivered to Legacy SR with 10 or 20 Digits of Information	105
Figure H.1 – UE Location-Routed Call Delivery to NENA i3 ESInet – Location-by-Reference provided by UE	128

Table of Tables

Table 8.1 – SIP to SS7 Interworking.....	68
Table 8.2 – SIP to CAMA/Feature Group D MF Interworking	69
Table A.1 – Profile Legend	81
Table A.2 – SIP INVITE Header Profile	82
Table B.1 – ELIR (eme_lir element)	85
Table B.2 – ELIR (eme_lir element)	85
Table B.3 – msid attribute values	85
Table B.4 – target_serving_node element.....	86
Table B.5 – ELIA (eme_lia element).....	86
Table B.6 – eme_pos element values for ELIA.....	86
Table B.7 – ELR (emerep element).....	88
Table B.8 – eme_event values	88
Table B.9 – eme_trigger values.....	88
Table B.10 – eme_pos element values for ELR	88
Table B.11 – target_serving_node element.....	89
Table B.12 – serving_cell element.....	89

1 Scope, Purpose, & Application

1.1 Scope

The scope of this standard is to identify and adapt as necessary 3GPP common IP Multimedia Subsystem (IMS) emergency procedures for applicability in North America to support emergency communications originating from an IMS subscriber (fixed, nomadic¹, or mobile) and delivered to a National Emergency Number Association (NENA) i3 Emergency Services IP network (i3 ESInet) and associated NG9-1-1 Core Services (NGCS), or to a legacy Selective Router. ATIS-0700015.v002 specified procedures limited to voice and Global Text Telephony (GTT) [Ref 3] communication. ATIS-0700015.v003 expanded the procedures to incorporate additional multimedia including text, pictures, and video. ATIS-0700015.v004 addressed issues associated with specific transfer models in an i3 ESInet/NGCS. This version, ATIS-0700015.v005, addresses caller authentication in the context of emergency (9-1-1) and callback calls.

While the main focus of this standard is IMS emergency service origination and in particular the associated impacts to an originating device and originating IMS network, the standard also covers related support from the access network and for location acquisition, subscriber home networks in the case of roaming, and considers support for service origination (e.g., callback) from a Public Safety Answering Point (PSAP).

This standard describes the IMS to ESInet interface, as well as the IMS to Selective Router interface. It identifies the types of media that can be delivered to each type of emergency services network.

With respect to 3GPP specifications, the scope of this standard is based upon capabilities defined in Release 16, except where explicitly noted otherwise. With respect to the NENA i3 standard [Ref 100], if there are any discrepancies between this standard and the NENA i3 standard concerning the definition of i3 architecture functional elements, interfaces, or procedures, the NENA i3 standard takes precedence.

1.2 Purpose

The purpose of this standard is to enable deployment in North America of support for Multimedia Emergency Services (MMES) calls² in the IP domain from originating networks that conform to 3GPP IMS specifications. The standard is intended to complement the NENA i3 standard [Ref 100] and to define any changes and limitations to the 3GPP IMS solution that are needed for operation in North America.

1.3 Application

The standard applies to support for MMES calls made using IMS in North America. More specifically, it only applies for those MMES services that establish a single SIP session and are able to properly function with only the service logic defined for the P-CSCF and E-CSCF as specified in 3GPP TS 23.167 [Ref 1] and in this standard. Any MMES-based service that requires additional service logic beyond what is defined in this standard, such as may be present in other service platforms like S-CSCFs or AS's as specified in 3GPP TS 23.228 [Ref 34] are for future study.

2 Normative References

The following standards contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this American National Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

[Ref 1] 3GPP TS 23.167, *IP Multimedia Subsystem (IMS) emergency sessions*.³

¹ Additional detailed support for nomadic use cases is for further study.

² In this standard, the term “calls” is used to mean requests, including voice, texts, etc.

³ This document is available from the Third Generation Partnership Project (3GPP) at < <http://www.3gpp.org/specs/specs.htm> >.