



ATIS-0600012.01

ATIS Standard on -

**Electrical Primary Protection Considerations for
Broadband xDSL Systems**



As a leading technology and solutions development organization, the Alliance for Telecommunications Industry Solutions (ATIS) brings together the top global ICT companies to advance the industry's most pressing business priorities. ATIS' nearly 200 member companies are currently working to address the All-IP transition, 5G, network functions virtualization, big data analytics, cloud services, device solutions, emergency services, M2M, cyber security, network evolution, quality of service, billing support, operations, and much more. These priorities follow a fast-track development lifecycle — from design and innovation through standards, specifications, requirements, business use cases, software toolkits, open source solutions, and interoperability testing.

ATIS is accredited by the American National Standards Institute (ANSI). The organization is the North American Organizational Partner for the 3rd Generation Partnership Project (3GPP), a founding Partner of the oneM2M global initiative, a member of the International Telecommunication Union (ITU), as well as a member of the Inter-American Telecommunication Commission (CITEL). For more information, visit www.atis.org.

Notice of Disclaimer & Limitation of Liability

The information provided in this document is directed solely to professionals who have the appropriate degree of experience to understand and interpret its contents in accordance with generally accepted engineering or other professional standards and applicable regulations. No recommendation as to products or vendors is made or should be implied.

NO REPRESENTATION OR WARRANTY IS MADE THAT THE INFORMATION IS TECHNICALLY ACCURATE OR SUFFICIENT OR CONFORMS TO ANY STATUTE, GOVERNMENTAL RULE OR REGULATION, AND FURTHER, NO REPRESENTATION OR WARRANTY IS MADE OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS. ATIS SHALL NOT BE LIABLE, BEYOND THE AMOUNT OF ANY SUM RECEIVED IN PAYMENT BY ATIS FOR THIS DOCUMENT, AND IN NO EVENT SHALL ATIS BE LIABLE FOR LOST PROFITS OR OTHER INCIDENTAL OR CONSEQUENTIAL DAMAGES. ATIS EXPRESSLY ADVISES THAT ANY AND ALL USE OF OR RELIANCE UPON THE INFORMATION PROVIDED IN THIS DOCUMENT IS AT THE RISK OF THE USER.

NOTE - The user's attention is called to the possibility that compliance with this standard may require use of an invention covered by patent rights. By publication of this standard, no position is taken with respect to whether use of an invention covered by patent rights will be required, and if any such use is required no position is taken regarding the validity of this claim or any patent rights in connection therewith. Please refer to [<http://www.atis.org/legal/patentinfo.asp>] to determine if any statement has been filed by a patent holder indicating a willingness to grant a license either without compensation or on reasonable and non-discriminatory terms and conditions to applicants desiring to obtain a license.

Published by

**Alliance for Telecommunications Industry Solutions
1200 G Street, NW, Suite 500
Washington, DC 20005**

Copyright © 2017 by Alliance for Telecommunications Industry Solutions
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher. For information contact ATIS at 202.628.6380. ATIS is online at < <http://www.atis.org> >.

ATIS-0600012.01

ATIS Standard on

Electrical Primary Protection Considerations for Broadband xDSL Systems

Alliance for Telecommunications Industry Solutions

Approved December 8, 2017

Abstract:

xDSL Broadband equipment is susceptible to disturbances that require the use of electrical primary protection devices. These primary protectors could have a negative impact on the signal of interest during steady-state conditions as well as during protector switching or clamping operation. The characteristics of these electrical primary protectors and their impact on xDSL broadband signals are considered herein. This is the first communication service platform specific document in a suite of ATIS Standards intended to provide requirements and guidance for the use of electrical primary protectors in various technology architectures. This particular ATIS Standard will address xDSL.

Foreword

The Alliance for Telecommunication Industry Solutions (ATIS) serves the public through improved understanding between providers, customers, and manufacturers. The Sustainability in Telecom: Energy and Protection (STEP) Committee – formerly the Network Interface, Power, and Protection Committee (NIPP) – engages industry expertise to develop standards and technical reports for telecommunications equipment and environments in the areas of energy efficiency, environmental impacts, power and protection. The work products of STEP enable vendors, operators and their customers to deploy and operate reliable, environmentally sustainable, energy efficient communications technologies. STEP is committed to proactive engagement with national, regional and international standards development organizations and forums that share its scope of work.

The mandatory requirements are designated by the word *shall* and recommendations by the word *should*. Where both a mandatory requirement and a recommendation are specified for the same criterion, the recommendation represents a goal currently identifiable as having distinct compatibility or performance advantages. The word *may* denotes a optional capability that could augment the standard. The standard is fully functional without the incorporation of this optional capability.

Suggestions for improvement of this document are welcome. They should be sent to the Alliance for Telecommunications Industry Solutions, STEP, 1200 G Street NW, Suite 500, Washington, DC 20005.

At the time of consensus on this document, STEP, which was responsible for its development, had the following leadership:

- E. Gallo, STEP Chair and STEP NEP Vice Chair (Ericsson)
- J. Fuller, STEP Vice Chair and STEP NEP Chair (AT&T)

The Network Electrical Protection (NEP) Subcommittee was responsible for the development of this document.

Table of Contents

1	Scope, Purpose, & Application.....	1
1.1	Scope.....	1
1.1.1	<i>Electrical Protection</i>	1
1.1.2	<i>Equipment Covered</i>	1
2	References	1
2.1	Normative References.....	2
2.2	Informative References.....	3
3	Definitions, Acronyms, & Abbreviations	3
3.1	Definitions.....	3
3.2	Acronyms & Abbreviations.....	5
4	Description of DSL	6
4.1	Pair Bonding (Non-Physical Layer Bonding).....	8
4.2	Performance Comparisons of Different xDSL Technologies.....	8
5	Available Primary Protection Technologies.....	10
5.1	Carbon Air Gap Protectors.....	11
5.2	Gas Tube Protectors.....	12
5.2.1	<i>GDT Oscillation</i>	13
5.3	Solid State Protectors.....	14
5.3.1	<i>Metal Oxide Varistors & Avalanche Breakdown Diodes or Silicon Avalanche Diodes</i>	14
5.3.2	<i>Thyristors</i>	14
5.4	Gas Tube + MOV: Backup or Hybrid Configuration.....	14
5.4.1	<i>Gas Tube + MOV: Backup</i>	14
5.4.2	<i>Gas Tube + MOV: Hybrid</i>	15
6	Primary Protector Considerations on xDSL Performance.....	15
6.1	Primary Protector Operation Effects on xDSL.....	15
6.2	Steady State Effects of Primary Protectors on xDSL.....	16
6.2.1	<i>Insertion Loss</i>	16
6.2.2	<i>Return Loss</i>	17
6.2.3	<i>Longitudinal Balance</i>	18
6.2.4	<i>Capacitance vs. Voltage</i>	19
6.3	Effects on Loop Length.....	20
6.4	Crosstalk.....	20
6.5	Vectoring.....	20
7	Summary Guidelines for Selection of Primary Protectors.....	21
8	Characterizing Primary Surge Protection on a Specific xDSL System.....	24
8.1	Test Purpose.....	24
8.2	Test Conditions.....	24
8.3	Test Procedure.....	25
9	Susceptibility of DSL Services to Asymmetrical Primary Protector Operation	27
10	Service to Cell Towers	29
A	Expected Surge Voltages at the Network Interface.....	30

Table of Figures

Figure 4.1 - Rate and Reach Performance - ADSL2plus 9

Figure 4.2 - Rate and Reach Performance - VDSL2 profile 8d 9

Figure 4.3 - Rate and Reach Performance - VDSL2 profile 17a 10

Figure 5.1 - Breakdown Voltage Comparisons 11

Figure 5.2 - Impulse Breakdown, Gas Tube, Hybrid, Solid State 11

Figure 5.3 - Gas Tube Operating Regions 12

Figure 5.4 - GDT Oscillation Traces 13

Figure 5.5 - Gas Tube + MOV “Backup” 15

Figure 5.6 - Gas Tube + MOV “Hybrid” 15

Figure 6.1 - Insertion Loss – ADSL Frequencies 16

Figure 6.2 - Insertion Loss – VDSL Frequencies 17

Figure 6.3 - Return Loss – ADSL Frequencies 17

Figure 6.4 - Return Loss – VDSL Frequencies 18

Figure 6.5 - Longitudinal Balance – ADSL Frequencies 18

Figure 6.6 - Longitudinal Balance – VDSL Frequencies 19

Figure 7.1 - Primary Protector vs. xDSL Selection Flow Chart 23

Figure 7.2 - Primary Protector Types 23

Figure 8.1 - Signal Impairments Test with Various Primary Protectors using a Television 26

Figure 8.2 - Signal Impairments Test with Various Primary Protectors using a Digital Storage Oscilloscope (DSO) 27

Figure 9.1 - Longitudinal Voltage Surge on Primary Protection 28

Table of Tables

Table 4.1 - DSL Systems 7

Table 6.1 - xDSL Power and Voltage Levels 19

Table 7.1 - Primary Protector Comparisons 22

Table 8.1 - Surge Voltage and Current Test Values 24

Table 8.2 - Additional Surge Voltage and Current Test Values 25

ATIS Standard on –

Electrical Primary Protection Considerations for Broadband xDSL Systems

1 Scope, Purpose, & Application

1.1 Scope

1.1.1 Electrical Protection

The purpose of this ATIS Standard is to assist the service provider in choosing appropriate primary protection methods for xDSL communications circuits. For the purposes of this specification, the definition of a primary protector is a device typically installed by the service provider to mitigate large lightning- and/or AC power-related transients. Additional information on lightning-related transients can be found in Annex A. The primary protector in some instances may be integrated within equipment as a convenience to the service provider. Primary protectors are typically required on outside plant telecommunications circuits per the National Electrical Code® (NEC®) NFPA 70 [10]. This ATIS Standard describes protector characteristics that may impact broadband xDSL systems for outside plant, and inter-building applications and the services running over these links. These protectors are categorized by technology type and configurations. This document describes protectors in their non-operating state and their effect on these services, and also considers the effects of protector response to a surge event and how that operation may affect these services. This is a subtending document and is intended to be used with the Broadband umbrella document and is in support of the Broadband Document, ATIS-0600012[1]. These protectors are designed and installed to protect against both induced lightning and ac power fault events.

It is not the intent of this specification to describe secondary and tertiary protectors and their usage.

1.1.2 Equipment Covered

This ATIS Standard applies to the electrical protection at all xDSL network equipment locations. Examples include: xDSL equipment at Central Office (CO) Type facilities, remote sites, and at the customer location (including the entrance or interface point, and equipment at the customer location). This equipment may interface with various types of cable media, such as coaxial cable or twisted pair that provides the xDSL signal and possible power.

Although a variety of existing and proposed xDSL equipment types are considered, the merits of the different technologies, and/or architecture types, are not covered.

The following are examples of equipment/items included in this ATIS standard:

- Primary protectors.
- CO equipment.
- Remote equipment.
- Cell Site equipment.
- NIDs, iNIDs, NIUs, ONTs, BETs, and other points of demarcation.
- CPE such as Set-Top Boxes (STBs), xDSL splitters, telephones, etc.

2 References

The following standards contain provisions which, through reference in this text, constitute provisions of this ATIS Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this ATIS Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.