



**ATIS-1000628.a.2001(S2020)**

**ECS –  
Connection and Ring Back Addendum**



As a leading technology and solutions development organization, the Alliance for Telecommunications Industry Solutions (ATIS) brings together the top global ICT companies to advance the industry's most pressing business priorities. ATIS' nearly 200 member companies are currently working to address the All-IP transition, 5G, network functions virtualization, big data analytics, cloud services, device solutions, emergency services, M2M, cyber security, network evolution, quality of service, billing support, operations, and much more. These priorities follow a fast-track development lifecycle — from design and innovation through standards, specifications, requirements, business use cases, software toolkits, open source solutions, and interoperability testing.

ATIS is accredited by the American National Standards Institute (ANSI). The organization is the North American Organizational Partner for the 3rd Generation Partnership Project (3GPP), a founding Partner of the oneM2M global initiative, a member of the International Telecommunication Union (ITU), as well as a member of the Inter-American Telecommunication Commission (CITEI). For more information, visit [www.atis.org](http://www.atis.org).

---

## AMERICAN NATIONAL STANDARD

Approval of an American National Standard requires review by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made towards their resolution. The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

**CAUTION NOTICE:** This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

---

## Notice of Disclaimer & Limitation of Liability

The information provided in this document is directed solely to professionals who have the appropriate degree of experience to understand and interpret its contents in accordance with generally accepted engineering or other professional standards and applicable regulations. No recommendation as to products or vendors is made or should be implied.

NO REPRESENTATION OR WARRANTY IS MADE THAT THE INFORMATION IS TECHNICALLY ACCURATE OR SUFFICIENT OR CONFORMS TO ANY STATUTE, GOVERNMENTAL RULE OR REGULATION, AND FURTHER, NO REPRESENTATION OR WARRANTY IS MADE OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE OR AGAINST INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS. ATIS SHALL NOT BE LIABLE, BEYOND THE AMOUNT OF ANY SUM RECEIVED IN PAYMENT BY ATIS FOR THIS DOCUMENT, AND IN NO EVENT SHALL ATIS BE LIABLE FOR LOST PROFITS OR OTHER INCIDENTAL OR CONSEQUENTIAL DAMAGES. ATIS EXPRESSLY ADVISES THAT ANY AND ALL USE OF OR RELIANCE UPON THE INFORMATION PROVIDED IN THIS DOCUMENT IS AT THE RISK OF THE USER.

<p>NOTE - The user's attention is called to the possibility that compliance with this standard may require use of an invention covered by patent rights. By publication of this standard, no position is taken with respect to whether use of an invention covered by patent rights will be required, and if any such use is required no position is taken regarding the validity of this claim or any patent rights in connection therewith. Please refer to [<a href="http://www.atis.org/legal/patentinfo.asp">http://www.atis.org/legal/patentinfo.asp</a>] to determine if any statement has been filed by a patent holder indicating a willingness to grant a license either without compensation or on reasonable and non-discriminatory terms and conditions to applicants desiring to obtain a license.</p>
--

---

## ATIS-1000628.a.2001 (S2020), ECS – Connection and Ring Back Addendum

Is an American National Standard developed by the **Signaling, Architecture, and Control (SAC)** Subcommittee under the **ATIS Packet Technologies and Systems Committee (PTSC)**.

*Published by*

**Alliance for Telecommunications Industry Solutions**  
**1200 G Street, NW, Suite 500**  
**Washington, DC 20005**

Copyright © 2020 by Alliance for Telecommunications Industry Solutions  
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher. For information contact ATIS at 202.628.6380. ATIS is online at < <http://www.atis.org> >.

## **ATIS-1000628.a.2001(S2020)**

(Formerly T1.628a-2001; Supplement to T1.628-2000)

American National Standard for Telecommunications

# **ECS -- Connection and Ring Back Addendum**

Secretariat

**Alliance for Telecommunications Industry Solutions**

Approved August 21, 2001

**American National Standards Institute, Inc.**

### **Abstract**

This addendum to T1.628-2000 specifies the use of the Connection Hold network capability by the Emergency Calling Service (ECS) to support ECS call hold and ring back. This addendum also specifies the TCAP messages exchanged between a switching node routing ECS calls and a Selective Routing Database (SRDB) that contains information determining the PSAP that should receive the emergency calls originating from a given caller or calling location.

## Foreword

The information contained in this Foreword is not part of this American National Standard (ANS) and has not been processed in accordance with ANSI's requirements for an ANS. As such, this Foreword may contain material that has not been subjected to public review or a consensus process. In addition, it does not contain requirements necessary for conformance to the standard.

Accredited Standards Committee T1, Telecommunications serves the public through improved understanding between carriers, customers, and manufacturers. Technical Subcommittee T1S1 of Committee T1 develops telecommunications standards and technical reports related to services, architectures, and signaling, in addition to related subjects under consideration in other North American and international standards bodies.

ANSI guidelines specify two categories of requirements: mandatory and recommendation. The mandatory requirements are designated by the word *shall* and recommendations by the word *should*. Where both a mandatory requirement and a recommendation are specified for the same criterion, the recommendation represents a goal currently identifiable as having distinct compatibility or performance advantages.

Suggestions for improvement of this standard are welcome. They should be sent to the Alliance for Telecommunications Industry Solutions, T1 Secretariat, 1200 G Street NW, Suite 500, Washington, DC 20005.

This standard was processed and approved for submittal to ANSI by Accredited Standards Committee on Telecommunications, T1. Committee approval of the standard does not necessarily imply that all members voted for its approval.

Working Group T1S1.7 on Services, Architecture, and Control of Technical Subcommittee T1S1 on Services, Architectures, and Signaling, was responsible for the development of this standard.

**Table of Contents**

**1 SCOPE, PURPOSE, AND APPLICATION ..... 1**

**2 NORMATIVE REFERENCES ..... 1**

**3 CHANGES TO T1.628-2000 §1, SCOPE, PURPOSE, AND APPLICATION ..... 2**

**4 CHANGES TO T1.628-2000 §2, NORMATIVE REFERENCES ..... 2**

**5 CHANGES TO T1.628-2000 §4, DESCRIPTION OF EMERGENCY CALLING SERVICE ..... 2**

**6 CHANGES TO T1.628-2000 §5, FUNCTIONAL CAPABILITIES AND INFORMATION FLOWS ..... 2**

**7 CHANGES TO T1.628-2000, §6 SWITCHING AND SIGNALLING SPECIFICATION FOR ECS AT THE USER-NETWORK INTERFACE ..... 3**

**8 CHANGES TO T1.628-2000 §7, SWITCHING AND SIGNALING SPECIFICATION FOR ECS AT INTEREXCHANGE INTERFACES ..... 7**

**Table of Tables**

Table 1/T1.628A ECS analyzedInformation message .....10

Table 2/T1.628A ECS analyzeRoute .....13

Table 3/T1.628A ECS terminationAttempt message.....15

Table 4/T1.628 ECS collectedInformation message .....18

Table 5/T1.628A ECS forwardCall message.....21

American National Standard  
for Telecommunications –

## ECS -- Connection and Ring Back Addendum

### 1 Scope, Purpose, and Application

This addendum to T1.628-2000 specifies the use of the Connection Hold network capability by the Emergency Calling Service (ECS) to support ECS call hold and ring back. This addendum also specifies the TCAP messages exchanged between a switching node routing ECS calls and a Selective Routing Database (SRDB) that contains information determining the PSAP that should receive the emergency calls originating from a given caller or calling location.

The Connection Hold Network Capability disables a calling user's capability to initiate release of a call. Connection hold also provides a mechanism to indicate that the calling user has requested disconnect (or reconnect) without initiating release procedures.

The procedures described in this addendum supplement the procedures in T1.628–2000, *American National Standard for Telecommunications—Emergency Calling Service*. In particular the procedures described here take precedence over normal call release procedures when ECS Call Hold is invoked.

The use of connection hold is restricted when the caller has an ISDN user–network interface. Due to existing provisions of the DSS1 protocol it is not possible to prevent an ISDN caller from disconnecting an active call. When call hold is applied to ECS calls originating from an ISDN user–network interface and the caller disconnects, the network will attempt to reconnect to the user's terminal in cases when the network has information that permits it to identify the end user's terminal.

A PSAP using an ISDN access can invoke the network to apply ring back to the caller's terminal using the protocol defined in this addendum.

Following the references clause, the remainder of this addendum specifies changes to the existing text of T1.628-2000 using ~~strikeout~~ to indicate deletions and underlining to indicate insertions.

### 2 Normative References

The following listed standards contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this American National Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below.

T1.628-2000, *Emergency Calling Service*.<sup>1</sup>

T1.666-1999, *Signalling System Number 7 (SS7)—Operator Services Network Capabilities*.<sup>1</sup>

---

<sup>1</sup> This document is available from the Alliance for Telecommunications Industry Solutions, 1200 G Street N.W., Suite 500, Washington, DC 20005. <<http://www.atis.org>>