

RTCA, Inc.
1150 18th Street, NW, Suite 910
Washington, DC 20036
USA

Minimum Operational Performance Standards (MOPS) for Detect and Avoid (DAA) Systems

RTCA DO-365C
September 15, 2022

Prepared by: SC-228
©2022, RTCA, Inc.

Copies of this document may be obtained from:

RTCA, Inc.
1150 18th Street, NW, Suite 910
Washington, DC 20036-4001, USA
Telephone: 202-833-9339
Facsimile: 202-833-9434
Internet: rtca.org

Please visit the RTCA online store for document pricing and ordering information.

FOREWORD

This document was prepared by Special Committee 228 (SC-228) and approved by the RTCA Program Management Committee (PMC) on September 15, 2022.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Standards Development Organization and develops consensus based recommendations on contemporary aviation issues. RTCA's objectives include, but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity, and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organization's recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

DISCLAIMER

This publication is based on material submitted by various participants during the SC approval process. Neither the SC nor RTCA has made any determination whether these materials could be subject to valid claims of patent, copyright or other proprietary rights by third parties, and no representation or warranty, expressed or implied is made in this regard. Any use of or reliance on this document constitutes an acceptance thereof "as is" and is subject to this disclaimer.

REVISION (REV) HISTORY

Rev Level	Description	Date	Effective Sections
-	Initial Publication	05/31/2017	All
A	Added Terminal Area DWC, Transit through Class B, Support for GBSS	03/26/2020	All
B	Added Class 3 – ACAS Xu, Non-cooperative DWC applicable to all classes, updated ATAR classes for different performance levels	03/18/2021	All
C	Added an EO/IR sensor class option as an alternative to ATAR	09/15/2022	All

EXECUTIVE SUMMARY

RTCA has been developing the Minimum Operational Performance Standards (MOPS) for equipment needed to support the safe operations of Unmanned Aircraft (UA) flights within the National Airspace System (NAS) and beyond the operational limits placed on small Unmanned Aircraft Systems (UAS) (see Section [107](#) of Title 14 (Aeronautics and Space) of the United States Code of Federal Regulations (14 U.S. CFR)). In 2013, RTCA initiated Special Committee 228 (SC-228) with a narrower scope; namely, to develop MOPS needed for (a) a Detect and Avoid (DAA) system (the focus of Working Group 1 (WG-1) and (b) a Control and Non-Payload Communications (CNPC) link system (the focus of WG-2).

The DAA system was specified to assist the remote pilot with operating an aircraft safely in the NAS. All aircraft flying in the NAS must comply with the operating rules of 14 CFR, specifically, §§ [91.3](#), [91.111](#), [91.113](#), [91.123](#) and [91.181\(b\)](#), which address see and avoid, collision avoidance, right-of-way rules, and remaining well clear. The DAA equipment may also be used to comply with the duties in International Civil Aviation Organization (ICAO) Annex 2 to the Convention on International Civil Aviation, specifically Chapter 2, Paragraph 2.3.1. These operating regulations assumed that a pilot would be onboard the aircraft and would be able to fully comply with these rules.

This document contains MOPS for DAA systems used in aircraft transiting and performing extended operations in Class D, E, and G airspace along with transiting Class B and C airspace. It includes equipment to enable UAS operations near Terminal Areas during approach and departure in Class C, D, E, and G airspace, and off-airport locations, but not operating in the visual traffic pattern or on the surface. It does not apply to small UAS (under 55 pounds (lbs)) operating in low-level environments (below 400') or other segmented areas.

This page intentionally left blank.

TABLE OF CONTENTS

1	PURPOSE AND SCOPE	1
1.1	Introduction.....	1
1.2	Document Hierarchy	2
1.3	System Overview	4
1.3.1	DAA Equipment Description – Unmanned Aircraft.....	8
1.3.2	DAA Equipment Description – Control Station	10
1.3.3	DAA Equipment Description – Ground Based Surveillance	11
1.3.4	DAA Equipment Description – Airborne Collision Avoidance System for Unmanned Aircraft.....	12
1.3.5	System Limitations	12
1.4	Operational Application(s).....	13
1.5	Intended Function	14
1.6	Operational Goals	14
1.6.1	General.....	14
1.6.2	Unmanned Aircraft (UA).....	15
1.6.3	UA DAA Surveillance Equipment.....	16
1.6.4	GBSS Equipment	16
1.6.5	DAA Alerting, Guidance Processing and DAA Traffic Display	16
1.6.6	Control Station.....	16
1.6.7	Compatibility with Other Systems	16
1.7	Assumptions.....	16
1.7.1	Equipage and Airworthiness Assumptions	17
1.7.2	Remote Pilot Assumptions.....	17
1.7.3	Operational Assumptions.....	18
1.7.4	Modeling and Simulation Assumptions.....	18
1.7.5	Control Station (CS) Assumptions.....	19
1.7.6	Performance Assumptions for UA and Intruder Avionics	19
1.7.6.1	Performance Assumptions for UA Avionics.....	19
1.7.6.2	Performance Assumptions for Cooperative Intruder Avionics	20
1.8	Test Procedures	21
1.8.1	Environmental Tests	21
1.8.2	Bench Tests	22
1.8.3	Installed Equipment Considerations	22
1.8.4	Operational Tests	22
1.9	Definitions of Terms	22
1.10	Aircraft Equipment Information Vulnerabilities.....	22
2	DAA EQUIPMENT PERFORMANCE REQUIREMENTS AND TEST PROCEDURES	25
2.1	General Requirements.....	25
2.1.1	Airworthiness	25
2.1.2	Intended Function	25
2.1.3	Federal Communications Commission Rules	25
2.1.4	Fire Protection.....	25
2.1.5	Operation of CS Controls.....	25
2.1.6	Accessibility of Controls.....	25
2.1.7	Effects of Test	25

2.1.8	DAA Equipment Interfaces.....	25
2.1.9	Design Assurance.....	25
2.1.10	DAA Equipment Classes and Articles	26
2.1.10.1	DAA Equipment Classes	28
2.1.10.2	DAA Equipment Articles.....	29
2.2	DAA Equipment Performance Requirements – Standard Conditions	33
2.2.1	General DAA Equipment Characteristics	33
2.2.1.1	Latency.....	33
2.2.1.2	DAA Surveillance Equipment.....	34
2.2.1.3	ATAR.....	35
2.2.1.4	Airborne Active Surveillance.....	35
2.2.1.5	ADS-B In System.....	35
2.2.1.6	TCAS II System (Class 2).....	36
2.2.1.7	ACAS Xu System (Class 3)	36
2.2.1.8	GBSS (Class 6, Class 7, Class 8).....	36
2.2.1.9	EO/IR Sensor System.....	37
2.2.2	DAA Input/Output (I/O) Requirements	37
2.2.2.1	UA DAA Processor Input Data.....	39
2.2.2.1.1	Ownship State Data.....	39
2.2.2.1.1.1	Flight Intent and Active Runway Center Point Data (Optional).....	42
2.2.2.1.2	ATAR Intruder Data	43
2.2.2.1.3	Active Surveillance Intruder Data.....	44
2.2.2.1.4	ADS-B In Intruder Data	46
2.2.2.1.4.1	Intruder ADS-B Traffic State Vector Report Data.....	47
2.2.2.1.4.2	ADS-B Intruder Mode Status Data	48
2.2.2.1.4.3	TIS-B/ADS-R Service Status Data – Optional	49
2.2.2.1.4.4	CAS RA REPORT DATA	49
2.2.2.1.4.5	Operational Coordination Message Data	50
2.2.2.1.5	TCAS II RA and Coordination Data.....	51
2.2.2.1.6	Surveillance Equipment Operating Status and Health Data.....	52
2.2.2.1.7	Reserved.....	53
2.2.2.1.8	C2 Link Data.....	53
2.2.2.1.9	GBSS Data –DAA Equipment Class 6	53
2.2.2.1.9.1	GBSS Status Data	53
2.2.2.1.9.2	GBSS Prioritized Track Data.....	53
2.2.2.1.10	EO/IR intruder Data	55
2.2.2.2	UA DAA Processor Output Data	56
2.2.2.2.1	Prioritized Track Data.....	56
2.2.2.2.1.1	Unique Track ID (Track Number)	57
2.2.2.2.1.2	Flight ID.....	57
2.2.2.2.1.3	Time of Applicability (TOA).....	57
2.2.2.2.1.4	Intruder Alert/Priority	58
2.2.2.2.1.5	Source Data Type.....	58
2.2.2.2.1.6	Validated ADS-B	58
2.2.2.2.1.7	Air/Ground Status	58
2.2.2.2.1.8	Relative Horizontal Position	58
2.2.2.2.1.9	Relative Horizontal Position Accuracy.....	59
2.2.2.2.1.10	Bearing Invalid.....	59
2.2.2.2.1.11	Relative Horizontal Velocity.....	59
2.2.2.2.1.12	Relative Horizontal Velocity Accuracy.....	59
2.2.2.2.1.13	Relative Altitude.....	59

2.2.2.2.1.14	Relative Altitude Accuracy	60
2.2.2.2.1.15	Altitude Invalid.....	60
2.2.2.2.1.16	Relative Vertical Rate.....	60
2.2.2.2.1.17	Relative Vertical Rate Accuracy	60
2.2.2.2.1.18	DAA Alerting Data	60
2.2.2.2.1.19	Traffic Track Angle.....	60
2.2.2.2.2	DAA System Modes of Operation and Health Status	61
2.2.2.2.3	TCAS II TA/RA – DAA Equipment Class 2	61
2.2.2.2.4	Onboard Data Recording Capability	61
2.2.2.2.5	Input/Output Required to Enable Visual-Like Clearances.....	62
2.2.2.3	CS DAA Processor Input Data.....	62
2.2.2.4	CS DAA Processor Output Data	62
2.2.2.4.1	CS DAA Processor Health Status Data.....	63
2.2.2.4.2	CS DAA Processor GBSS Prioritized Track Data –DAA Equipment Class 6	63
2.2.2.5	DAA Control Panel Input	63
2.2.2.6	DAA Control Panel Output.....	63
2.2.2.7	CS DAA Traffic Display Input Data.....	64
2.2.2.7.1	Ownship Pressure Altitude.....	65
2.2.2.7.2	Ownship Length and Width Code.....	65
2.2.3	Active Surveillance, Equipment Class 2 RA Function, and Tracker Performance Requirements	65
2.2.3.1	DAA Active Surveillance and DAA Equipment Class 2 RA Function	65
2.2.3.1.1	DAA Active Surveillance	66
2.2.3.1.2	DAA with TCAS II RA Functionality (DAA Equipment Class 2).....	67
2.2.3.2	DAA Track Processing – Surveillance Data Processing and Tracking.....	68
2.2.3.2.1	Track Management	69
2.2.3.2.1.1	Track Initiation.....	69
2.2.3.2.1.2	Track Capacity and Output Prioritization	69
2.2.3.2.1.3	ADS-B Report Processing and Track Maintenance	70
2.2.3.2.1.4	Track Termination.....	78
2.2.3.2.2	Data Association	78
2.2.3.2.3	Intruder State Estimation	80
2.2.3.2.3.1	Individual Time of Track Extrapolation and Traffic State File Generation.....	83
2.2.4	DAA Alerting and Guidance Processing Requirements	83
2.2.4.1	DAA Alerting and Guidance Suppression	83
2.2.4.1.1	Intruder-Specific Alerting and Guidance Suppression.....	85
2.2.4.2	Ownship Intent Information	85
2.2.4.3	DAA Alerting.....	85
2.2.4.3.1	DAA Well Clear (DWC) Definition	85
2.2.4.3.2	Hazard Alert Zone (HAZ) Definition	86
2.2.4.3.3	Non-Hazard Zone (NHZ) Definition	89
2.2.4.3.4	Slant Range Equation.....	89
2.2.4.3.5	Alert Types and Prioritization.....	90
2.2.4.3.5.1	Preventive Alert	90
2.2.4.3.5.2	Corrective Alert.....	91
2.2.4.3.5.3	Warning Alert	91
2.2.4.3.5.4	Prioritization of Alert Types	92
2.2.4.3.6	Alert Parameters by DWC	93
2.2.4.3.6.1	En Route DWC Alerts.....	93
2.2.4.3.6.2	Terminal DWC Alerts	98
2.2.4.3.6.3	Non-Cooperative DWC Alerts.....	101

2.2.4.3.7	Alerting Special Cases	104
2.2.4.3.7.1	Special Cases – ATAR or EO/IR Only	104
2.2.4.3.7.2	Special Cases – No Bearing	105
2.2.4.3.7.3	Special Cases – No Altitude.....	106
2.2.4.3.7.4	Special Cases – Unvalidated ADS-B	107
2.2.4.4	Guidance Processing	108
2.2.4.4.1	Guidance Processing – En Route and Non-Cooperative.....	112
2.2.4.4.1.1	DAA Maneuver Guidance to Maintain DWC – En Route and Non-Cooperative	113
2.2.4.4.1.2	DAA Maneuver Guidance to Regain DWC – En Route and Non-Cooperative	120
2.2.4.4.2	Guidance Processing in the Terminal Area.....	124
2.2.4.4.2.1	DAA Maneuver Guidance to Maintain DWC – DTA.....	124
2.2.4.4.2.2	DAA Maneuver Guidance to Regain DWC – DTA.....	127
2.2.4.4.3	Guidance Processing Special Cases	130
2.2.4.4.3.1	Special Cases – Maintain DAA Well Clear	130
2.2.4.4.3.2	Special Cases – Regain DAA Well Clear	133
2.2.4.5	Collision Avoidance Interoperability with Guidance.....	135
2.2.4.5.1	Class 2 RA Guidance	136
2.2.4.5.1.1	Guidance Processing for an MTE with Directive RA and DAA Warning Alert	138
2.2.4.5.2	Vertical DAA Guidance.....	139
2.2.4.5.2.1	Determining Intruders' Vertical RA Capability	140
2.2.4.5.2.2	Determining Intruders' Vertical RA Complement (VRC) Information.....	141
2.2.4.5.2.3	Vertical DAA Guidance Modification	144
2.2.4.5.3	Horizontal DAA Guidance.....	147
2.2.4.6	Class 3 RA Alerting and Guidance	148
2.2.5	DAA Traffic Display Subsystem Requirements	149
2.2.5.1	General DAA Traffic Display	149
2.2.5.2	Traffic Display Criteria (TDC).....	150
2.2.5.2.1	Default Traffic Display Criteria	150
2.2.5.3	DAA Traffic Display Information	150
2.2.5.4	Interfaces	151
2.2.5.4.1	DAA Traffic Display Latency.....	151
2.2.5.4.2	Time of Applicability of Traffic State Vector Data	151
2.2.5.5	Display Design – General.....	152
2.2.5.5.1	Display Characteristics.....	152
2.2.5.5.2	Dynamics	152
2.2.5.5.3	Labels.....	152
2.2.5.5.4	Symbols.....	152
2.2.5.6	Display Elements.....	152
2.2.5.6.1	Ownship Symbol	152
2.2.5.6.2	Traffic Information Formats	153
2.2.5.6.2.1	Data Tags	153
2.2.5.6.2.2	Data Blocks	154
2.2.5.6.2.3	Traffic Symbols	155
2.2.5.6.3	Number of Traffic Elements.....	161
2.2.5.6.4	Information Elements.....	161
2.2.5.6.4.1	Traffic Monitored by TCAS II.....	161
2.2.5.6.4.2	Traffic Application Capability.....	161
2.2.5.6.4.3	Traffic Altitude.....	161
2.2.5.6.4.4	Traffic Vertical Direction	163
2.2.5.6.4.5	Traffic Identification	164
2.2.5.6.4.6	Traffic Ground Speed.....	164

2.2.5.6.4.7 (Reserved)	164
2.2.5.6.4.8 Traffic Emergency Priority Status	164
2.2.5.6.4.9 Traffic Horizontal Velocity Vector	165
2.2.5.6.4.10 Traffic Range	165
2.2.5.6.5 Operational Elements	165
2.2.5.7 Guidance Display	166
2.2.5.7.1 DAA Guidance to Maintain DWC	166
2.2.5.7.2 DAA Guidance to Regain DWC	171
2.2.5.7.3 RA Guidance for Class 2 DAA Systems	173
2.2.5.7.4 RA Guidance for Class 3 DAA Systems	175
2.2.5.7.4.1 Horizontal RA Guidance	176
2.2.5.7.4.2 Vertical RA Guidance	179
2.2.5.7.4.3 Visual RA Alerts	183
2.2.5.8 DAA Traffic Display Characteristics	185
2.2.5.8.1 Display Range	185
2.2.5.8.2 Range Rings	185
2.2.5.8.3 Altitude Tape	186
2.2.5.8.4 Display Orientation	186
2.2.5.8.5 Traffic Coasting Indicator	186
2.2.5.9 Display Design – Other	186
2.2.5.9.1 Traffic Display Symbol Prioritization for Overlay	186
2.2.5.9.2 DAA System Health Display Monitoring Function	187
2.2.5.9.3 Display of Status Indication	187
2.2.5.10 Input and Control – General	188
2.2.5.10.1 Display Range	188
2.2.5.10.2 Altitude Bands	188
2.2.5.10.3 Traffic Altitude Selection	188
2.2.5.10.4 Traffic Selection	188
2.2.5.10.5 Decluttering	188
2.2.5.10.6 Brightness Control	189
2.2.5.11 CS Integration	189
2.2.5.11.1 Multi-function Display	189
2.2.5.12 DAA Aural Alerts	190
2.2.5.12.1 DAA Aural Alerts – En Route and Non-Cooperative	191
2.2.5.12.2 DAA Aural Alerts – DTA	191
2.2.5.12.2.1 Class 2 RA Aural Alerts	191
2.2.5.12.2.2 Class 3 RA Aural Alerts	192
2.2.5.13 DAA Display Features to Enable Visual-Like Clearances	196
2.2.6 Pilot Entry Subsystem	197
2.2.7 DAA Pilot-Selected Modes	197
2.2.8 High-level DAA Operational Monitoring Function	199
2.2.8.1 High-level DAA Operational Monitoring Display	200
2.2.8.2 High-level DAA Operational Monitoring Master Caution Warning Light/System	200
2.2.9 DAA Subsystem Operational Status	200
2.2.9.1 DAA Subsystem Operational Status Reporting	202
2.2.9.2 DAA Subsystem Initiation Test	202
2.2.9.3 DAA Subsystem Initiation Operational Status Test Report	203
2.2.9.4 DAA Subsystem Operational Status Display	203
2.2.9.5 DAA Subsystem Lack of Operating Mode Report	203
2.2.10 Restart after Power Interruption while in Flight	203
2.3 DAA Equipment Environmental Testing – Overview	203

2.3.1	Use of Special Purpose Software	203
2.3.2	DAA Airborne Equipment Required Performance – Environmental Test Conditions	204
2.3.3	DAA Ground Based Equipment Required Performance – Environmental Test Conditions	208
2.4	DAA Equipment Performance Requirements – Standard Conditions Test Procedures.....	214
2.4.1	General DAA Equipment Characteristics (§2.2.1)	215
2.4.1.1	Latency (§2.2.1.1)	215
2.4.1.2	DAA Surveillance Equipment (§2.2.1.2)	215
2.4.1.3	ATAR (§2.2.1.3)	215
2.4.1.4	Airborne Active Surveillance (§2.2.1.4)	216
2.4.1.5	ADS-B In System (§2.2.1.5)	216
2.4.1.6	TCAS II System (Class 2) (§2.2.1.6)	216
2.4.1.7	ACAS Xu System (Class 3) (§2.2.1.7)	216
2.4.1.8	GBSS (Class 6, Class 7, Class 8) (§2.2.1.7)	216
2.4.1.9	EO/IR Sensor System (§2.2.1.9)	216
2.4.2	DAA Input/Output (I/O) Requirements (§2.2.2).....	216
2.4.2.1	UA DAA Processor Input Data (§2.2.2.1)	217
2.4.2.1.1	Ownship State Data (§2.2.2.1.1)	217
2.4.2.1.1.1	Flight Intent and Active Runway Center Point Data (Optional) (§2.2.2.1.1.1)	218
2.4.2.1.1.2	ATAR Intruder Data (§2.2.2.1.2).....	218
2.4.2.1.1.3	Active Surveillance Intruder Data (§2.2.2.1.3).....	219
2.4.2.1.1.4	ADS-B In Intruder Data (§2.2.2.1.4)	219
2.4.2.1.1.4.1	Intruder ADS-B Traffic State Vector Report Data (§2.2.2.1.4.1).....	219
2.4.2.1.1.4.2	ADS-B Intruder Mode Status Data (§2.2.2.1.4.2).....	220
2.4.2.1.1.4.3	TIS-B/ADS-R Service Status Data – Optional (§2.2.2.1.4.3).....	220
2.4.2.1.1.4.4	TCAS II RA Report Data (§2.2.2.1.4.4)	220
2.4.2.1.1.4.5	Operational Coordination Message Data (§2.2.2.1.4.5).....	220
2.4.2.1.1.5	TCAS II RA and Coordination Data (§2.2.2.1.5)	220
2.4.2.1.1.6	Surveillance Equipment Operating Status and Health Data (§2.2.2.1.6).....	221
2.4.2.1.1.7	Flight Control System (FCS) (§2.2.2.1.7).....	221
2.4.2.1.1.8	C2 Link (§2.2.2.1.7).....	221
2.4.2.1.1.9	GBSS Data – DAA Equipment Class 6 (§2.2.2.1.9).....	221
2.4.2.1.1.9.1	GBSS Status Data (§2.2.2.1.9.1).....	221
2.4.2.1.1.9.2	GBSS Prioritized Track Data (§2.2.2.1.9.2)	221
2.4.2.1.1.10	EO/IR Sensor System Intruder Data (§2.2.2.1.10).....	221
2.4.2.2	UA DAA Processor Output Data (§2.2.2.2)	221
2.4.2.2.1	Prioritized Track Data (§2.2.2.2.1)	221
2.4.2.2.1.1	Unique Track ID (Track Number) (§2.2.2.2.1.1).....	222
2.4.2.2.1.2	Flight ID (§2.2.2.2.1.2)	222
2.4.2.2.1.3	Time of Applicability (TOA) (§2.2.2.2.1.3)	222
2.4.2.2.1.4	Intruder Alert/Priority (§2.2.2.2.1.4).....	222
2.4.2.2.1.5	Source Data Type (§2.2.2.2.1.5)	222
2.4.2.2.1.6	Validated ADS-B (§2.2.2.2.1.6).....	222
2.4.2.2.1.7	Air/Ground Status (§2.2.2.2.1.7).....	222
2.4.2.2.1.8	Relative Horizontal Position (§2.2.2.2.1.8).....	222
2.4.2.2.1.9	Relative Horizontal Position Accuracy (§2.2.2.2.1.9)	223
2.4.2.2.1.10	Bearing Invalid (§2.2.2.2.1.10)	223
2.4.2.2.1.11	Relative Horizontal Velocity (§2.2.2.2.1.11)	223
2.4.2.2.1.12	Relative Horizontal Velocity Accuracy (§2.2.2.2.1.12).....	223
2.4.2.2.1.13	Relative Altitude (§2.2.2.2.1.13).....	223
2.4.2.2.1.14	Relative Altitude Accuracy (§2.2.2.2.1.14).....	223
2.4.2.2.1.15	Altitude Invalid (§2.2.2.2.1.15)	223

2.4.2.2.1.16	Relative Vertical Rate (§2.2.2.2.1.16)	223
2.4.2.2.1.17	Relative Vertical Rate Accuracy (§2.2.2.2.1.17)	224
2.4.2.2.1.18	DAA Alerting Data (§2.2.2.2.1.18)	224
2.4.2.2.1.19	Traffic Track Angle (§2.2.2.2.1.19)	224
2.4.2.2.2	DAA System Modes of Operation and Health Status (§2.2.2.2.2)	224
2.4.2.2.3	TCAS II TA/RA – DAA Equipment Class 2 (§2.2.2.2.3)	224
2.4.2.2.4	Onboard Data Recording Capability (§2.2.2.2.4)	224
2.4.2.2.5	Input/Output Required to Enable Visual-Like Clearances (§2.2.2.2.5)	225
2.4.2.3	CS DAA Processor Input Data (§2.2.2.3)	225
2.4.2.4	CS DAA Processor Output Data (§2.2.2.4)	225
2.4.2.4.1	CS DAA Processor Health Status Data (§2.2.2.4.1)	225
2.4.2.4.2	CS DAA Processor GBSS Prioritized Track Data –DAA Equipment Class 6 (2.2.2.4.2)	225
2.4.2.5	DAA Control Panel Input (§2.2.2.5)	225
2.4.2.6	DAA Control Panel Output (§2.2.2.6)	225
2.4.2.7	CS DAA Traffic Display Input Data (§2.2.2.7)	226
2.4.2.7.1	Ownship Pressure Altitude (§2.2.2.7.1)	226
2.4.2.7.2	Ownship Length and Width Code (§2.2.2.7.2)	226
2.4.3	Active Surveillance, Equipment Class 2 RA Function, and Tracker Performance Requirements	226
2.4.3.1	DAA Active Surveillance and DAA Equipment Class 2 RA Function (§2.2.3.1)	226
2.4.3.1.1	DAA Active Surveillance (§2.2.3.1.1)	226
2.4.3.1.2	DAA with TCAS II RA Functionality (DAA Equipment Class 2) (§2.2.3.1.2)	235
2.4.3.2	DAA Track Processing – Surveillance Data Processing and Tracking (§2.2.3.2)	235
2.4.3.2.1	Track Management (§2.2.3.2.1)	236
2.4.3.2.1.1	Track Initiation (§2.2.3.2.1.1)	236
2.4.3.2.1.2	Track Capacity and Output Prioritization (§2.2.3.2.1.2)	236
2.4.3.2.1.3	ADS-B Report Processing and Track Maintenance (§2.2.3.2.1.3)	237
2.4.3.2.1.4	Track Termination (§2.2.3.2.1.4)	239
2.4.3.2.2	Data Association (§2.2.3.2.2)	239
2.4.3.2.3	Intruder State Estimation (§2.2.3.2.3)	241
2.4.3.2.3.1	Individual Time of Track Extrapolation and Traffic State File Generation (§2.2.3.2.3.1)	241
2.4.4	DAA Alerting and Guidance Processing Requirements (§2.2.4)	242
2.4.4.1	DAA Alerting and Guidance Suppression (§2.2.4.1)	242
2.4.4.1.1	Intruder-Specific Alerting and Guidance Suppression (§2.2.4.1.1)	242
2.4.4.2	Ownship Intent Information (§2.2.4.2)	243
2.4.4.3	DAA Alerting (§2.2.4.3)	243
2.4.4.3.1	DAA Well Clear (DWC) Definition (§2.2.4.3.1)	244
2.4.4.3.2	Hazard Alert Zone (HAZ) Definition (§2.2.4.3.2)	244
2.4.4.3.3	Non-Hazard Zone (NHZ) Definition (§2.2.4.3.3)	244
2.4.4.3.4	Slant Range Equation (§2.2.4.3.4)	244
2.4.4.3.5	Alert Types and Prioritization (§2.2.4.3.5)	244
2.4.4.3.5.1	Preventive Alert (§2.2.4.3.5.1)	244
2.4.4.3.5.2	Corrective Alert (§2.2.4.3.5.2)	244
2.4.4.3.5.3	Warning Alert (§2.2.4.3.5.3)	244
2.4.4.3.5.4	Prioritization of Alert Types (§2.2.4.3.5.4)	245
2.4.4.3.6	Alert Parameters by DWC (§2.2.4.3.6)	245
2.4.4.3.6.1	En Route DWC Alerts (§2.2.4.3.6.1)	245
2.4.4.3.6.2	Terminal DWC Alerts (§2.2.4.3.6.2)	248
2.4.4.3.6.3	Non-Cooperative DWC Alerts (§2.2.4.3.6.3)	250
2.4.4.3.7	Alerting Special Cases (§2.2.4.3.7)	252
2.4.4.3.7.1	Special Cases – ATAR or EO/IR Only (§2.2.4.3.7.1)	252

2.4.4.3.7.2	Special Cases – No Bearing (§2.2.4.3.7.2)	253
2.4.4.3.7.3	Special Cases – No Altitude (§2.2.4.3.7.3)	254
2.4.4.3.7.4	Special Cases – Unvalidated ADS-B (§2.2.4.3.7.4)	255
2.4.4.4	Guidance Processing (§2.2.4.4)	255
2.4.4.4.1	Guidance Processing – En Route and Non-Cooperative (§2.2.4.4.1)	256
2.4.4.4.1.1	DAA Maneuver Guidance to Maintain DWC – En Route and Non-Cooperative (§2.2.4.4.1.1)	256
2.4.4.4.1.2	DAA Maneuver Guidance to Regain DWC – En Route and Non-Cooperative (§2.2.4.4.1.2)	263
2.4.4.4.2	Guidance Processing in the Terminal Area (§2.2.4.4.2)	264
2.4.4.4.2.1	DAA Maneuver Guidance to Maintain DWC – DTA (§2.2.4.4.2.1)	264
2.4.4.4.2.2	DAA Maneuver Guidance to Regain DWC – DTA (§2.2.4.4.2.2)	269
2.4.4.4.3	Guidance Processing Special Cases (§2.2.4.4.3)	270
2.4.4.4.3.1	Special Cases – Maintain DAA Well Clear (§2.2.4.4.3.1)	270
2.4.4.4.3.2	Special Cases – Regain DAA Well Clear (§2.2.4.4.3.2)	273
2.4.4.5	Collision Avoidance Interoperability with Guidance (§2.2.4.5)	274
2.4.4.5.1	Class 2 RA Guidance (§2.2.4.5.1)	274
2.4.4.5.1.1	Guidance Processing for an MTE with Directive RA and DAA Warning Alert (§2.2.4.5.1.1)	274
2.4.4.5.2	Vertical DAA Guidance (§2.2.4.5.2)	275
2.4.4.5.2.1	Determining Intruders' Vertical RA Capability (§2.2.4.5.2.1)	275
2.4.4.5.2.2	Determining Intruders' Vertical RA Complement (VRC) Information (§2.2.4.5.2.2)	276
2.4.4.5.2.3	Vertical DAA Guidance Modification (§2.2.4.5.2.3)	278
2.4.4.5.3	Horizontal DAA Guidance (§2.2.4.5.3)	279
2.4.4.6	Class 3 RA Alerting and Guidance (§2.2.4.6)	281
2.4.5	DAA Traffic Display Subsystem Requirements (§2.2.5)	281
2.4.5.1	General DAA Traffic Display (§2.2.5.1)	281
2.4.5.2	Traffic Display Criteria (TDC) (§2.2.5.2)	281
2.4.5.2.1	Default Traffic Display Criteria (§2.2.5.2.1)	283
2.4.5.3	DAA Traffic Display Information (§2.2.5.3)	283
2.4.5.4	Interfaces (§2.2.5.4)	284
2.4.5.4.1	DAA Traffic Display Latency (§2.2.5.4.1)	284
2.4.5.4.2	Time of Applicability of Traffic State Vector Data (§2.2.5.4.2)	284
2.4.5.5	Display Design – General (§2.2.5.5)	285
2.4.5.5.1	Display Characteristics (§2.2.5.5.1)	285
2.4.5.5.2	Dynamics (§2.2.5.5.2)	285
2.4.5.5.3	Labels (§2.2.5.5.3)	285
2.4.5.5.4	Symbols (§2.2.5.5.4)	285
2.4.5.6	Display Elements (§2.2.5.6)	286
2.4.5.6.1	Ownship Symbol (§2.2.5.6.1)	286
2.4.5.6.2	Traffic Information Formats (§2.2.5.6.2)	286
2.4.5.6.2.1	Data Tags (§2.2.5.6.2.1)	286
2.4.5.6.2.2	Data Blocks (§2.2.5.6.2.2)	287
2.4.5.6.2.3	Traffic Symbols (§2.2.5.6.2.3)	288
2.4.5.6.3	Number of Traffic Elements (§2.2.5.6.3)	294
2.4.5.6.4	Information Elements (§2.2.5.6.4)	295
2.4.5.6.4.1	Traffic Monitored by TCAS II (§2.2.5.6.4.1)	295
2.4.5.6.4.2	Traffic Application Capability (§2.2.5.6.4.2)	295
2.4.5.6.4.3	Traffic Altitude (§2.2.5.6.4.3)	295
2.4.5.6.4.4	Traffic Vertical Direction (§2.2.5.6.4.4)	298
2.4.5.6.4.5	Traffic Identification (§2.2.5.6.4.5)	299

2.4.5.6.4.6	Traffic Ground Speed (§2.2.5.6.4.6)	299
2.4.5.6.4.7	(Reserved)	299
2.4.5.6.4.8	Traffic Emergency Priority Status (§2.2.5.6.4.8)	299
2.4.5.6.4.9	Traffic Horizontal Velocity Vector (§2.2.5.6.4.9)	300
2.4.5.6.4.10	Traffic Range (§2.2.5.6.4.10)	300
2.4.5.6.5	Operational Elements (§2.2.5.6.5)	301
2.4.5.7	Guidance Display (§2.2.5.7)	301
2.4.5.7.1	DAA Guidance to Maintain DWC (§2.2.5.7.1)	301
2.4.5.7.2	DAA Guidance to Regain DWC (§2.2.5.7.2)	303
2.4.5.7.3	TCAS II RA Guidance for TCAS II/DAA Integrated Systems (§2.2.5.7.3)	303
2.4.5.7.4	RA Guidance for Class 3 DAA Systems (§2.2.5.7.4)	304
2.4.5.7.4.1	Horizontal RA Guidance (§2.2.5.7.4.1)	304
2.4.5.7.4.2	Vertical RA Guidance (§2.2.5.7.4.2)	305
2.4.5.7.4.3	Visual RA Alerts	307
2.4.5.8	DAA Traffic Display Characteristics (§2.2.5.8)	307
2.4.5.8.1	Display Range (§2.2.5.8.1)	307
2.4.5.8.2	Range Rings (§2.2.5.8.2)	308
2.4.5.8.3	Altitude Tape (§2.2.5.8.3)	308
2.4.5.8.4	Display Orientation (§2.2.5.8.4)	308
2.4.5.8.5	Traffic Coasting Indicator (§2.2.5.8.5)	309
2.4.5.9	Display Design – Other (§2.2.5.9)	309
2.4.5.9.1	Traffic Display Symbol Prioritization for Overlay (§2.2.5.9.1)	309
2.4.5.9.2	DAA System Health Display Monitoring Function (§2.2.5.9.2)	309
2.4.5.9.3	Display of Status Indication (§2.2.5.9.3)	310
2.4.5.10	Input and Control – General (§2.2.5.10)	311
2.4.5.10.1	Display Range (§2.2.5.10.1)	311
2.4.5.10.2	Altitude Bands (§2.2.5.10.2)	312
2.4.5.10.3	Traffic Altitude Selection (§2.2.5.10.3)	312
2.4.5.10.4	Traffic Selection (§2.2.5.10.4)	312
2.4.5.10.5	Decluttering (§2.2.5.10.5)	313
2.4.5.10.6	Brightness Control (§2.2.5.10.6)	313
2.4.5.11	CS Integration (§2.2.5.11)	314
2.4.5.11.1	Multi-function Display (§2.2.5.11.1)	314
2.4.5.12	DAA Aural Alerts (§2.2.5.12)	314
2.4.5.12.1	DAA Aural Alerts – En Route and Non-Cooperative (§2.2.5.12.1)	316
2.4.5.12.2	DAA Aural Alerts - DTA (§2.2.5.12.2)	316
2.4.5.12.2.1	Class 2 RA Aural Alerts (§2.2.5.12.2.1)	317
2.4.5.12.2.2	Class 3 RA Aural Alerts (§2.2.5.12.2.2)	317
2.4.5.13	DAA Display Features to Enable Visual-Like Clearances (§2.2.5.13)	318
2.4.6	Pilot Entry Subsystem (§2.2.6)	319
2.4.7	DAA Pilot-Selected Modes (§2.2.7)	319
2.4.8	High-level DAA Operational Monitoring Function (§2.2.8)	330
2.4.8.1	High-level DAA Operational Monitoring Display (§2.2.8.1)	331
2.4.8.2	High-level DAA Operational Monitoring Master Caution Warning Light/System (§2.2.8.2)	331
2.4.9	DAA Subsystem Operational Status (§2.2.9)	331
2.4.9.1	DAA Subsystem Operational Status Reporting (§2.2.9.1)	332
2.4.9.2	DAA Subsystem Initiation Test (§2.2.9.2)	332
2.4.9.3	DAA Subsystem Initiation Operational Status Test Report (§2.2.9.3)	333
2.4.9.4	DAA Subsystem Operational Status Display (§2.2.9.4)	334
2.4.9.5	DAA Subsystem Lack of Operating Mode Report (§2.2.9.5)	335

2.4.10	Restart after Power Interruption while in Flight (§2.2.10).....	336
2.5	Environmental Qualification for UA DAA Processor Test Procedure – Airborne	336
2.5.1	Verification of Ownship Input Data.....	336
2.5.2	Verification of ATAR Input Data	337
2.5.3	Verification of E0/IR Input Data.....	337
2.5.4	Verification of Active Surveillance Input Data.....	337
2.5.5	Verification of ADS-B/ADS-R Input Data	337
2.5.6	Verification of TCAS II Input Data (Class 2).....	337
2.5.7	Verification of All Surveillance Sources	338
2.5.8	Verification of Alerting Prioritization.....	338
2.5.9	Verification of Guidance Processing	338
2.6	Environmental Qualification for CS DAA Processor Test Procedure (§2.3.3 Ground Testing)	338
2.6.1	Verification of Guidance Processing	339
2.6.2	Environmental Qualification for CS DAA Control Panel Test Procedure – Ground.....	339
2.6.3	Environmental Qualification for DAA Traffic Display Test Procedure – Ground.....	339
2.7	Requirement-to-Test Procedure Application Coverage	339
3	MANUFACTURER CONSIDERATIONS FOR INSTALLED EQUIPMENT.....	357
3.1	Equipment Installation	357
3.1.1	Accessibility	357
3.1.2	Aircraft/Control Station Environment.....	357
3.1.3	Display Visibility	357
3.1.4	Dynamic Range.....	357
3.1.5	Failure Protection.....	357
3.1.6	Interference Effects	358
3.1.7	Inadvertent Turnoff.....	358
3.1.8	UA and CS Power Sources	358
3.2	Installed Equipment Performance Considerations	358
3.3	Installed Equipment Tests	359
3.3.1	Ground Tests.....	359
3.3.1.1	Equipment Function.....	359
3.3.1.2	Interference Effects	359
3.3.2	Flight Evaluation Test Procedures	359
4	AIRCRAFT OPERATIONAL PERFORMANCE CHARACTERISTICS.....	361
5	MEMBERSHIP	363
APPENDIX A RESERVED		A-1
APPENDIX B ACRONYMS, ABBREVIATIONS AND DEFINITIONS		B-1
B.1	Acronyms and Abbreviations.....	B-1
B.2	Definitions.....	B-18
APPENDIX C DEVELOPMENT OF DETECT AND AVOID WELL CLEAR.....		C-1
C.1	Background	C-1
C.2	Development of DAA Well Clear for En Route	C-1

C.2.1	SaRP Well Clear Efforts	C-1
C.2.2	FAA White Paper on DAA Well Clear	C-3
C.2.3	Implications of the En Route DWC Definition	C-4
C.2.4	En Route DWC	C-4
C.3	Terminal DWC Development	C-5
C.3.1	Fast-Time Simulation of Terminal DWC Variations	C-5
C.3.2	TOPS 1a and 1b results	C-6
C.3.3	TOPS2 Results	C-8
C.3.4	DTA Definition	C-12
C.4	Non-Cooperative DWC	C-12
C.4.1	Metrics	C-13
C.4.2	Encounter Sets	C-13
C.4.3	Selection of Four Candidate DWCs	C-14
C.4.4	Evaluation with Open-loop and Closed-Loop Fast-Time Simulations	C-15
C.4.5	Human-in-the-Loop Simulation Results	C-18
C.4.6	Selection of the En Route Non-Cooperative DWC	C-19
C.5	Mathematical DWC Definitions	C-20
C.6	Conclusion	C-21
C.7	References	C-22

APPENDIX D UAS MANEUVER PERFORMANCE REQUIREMENTS D-1

D.1	Introduction	D-1
D.2	Domain/Assumptions	D-1
D.2.1	DAA Turn Maneuvers	D-1
D.2.2	DAA Vertical Maneuvers	D-2
D.2.3	Derivation of Maneuver Initiation Requirements for DAA Vertical Maneuvers	D-3
D.3	En Route DAA Well Clear	D-7
D.3.1	Assumptions	D-7
D.3.2	Application	D-8
D.4	Non-Cooperative DAA Well Clear	D-14
D.4.1	Assumptions	D-14
D.4.2	Application	D-15
D.5	Terminal DAA Well Clear	D-21
D.5.1	Assumptions	D-21
D.5.2	Application	D-22
D.6	References	D-27

APPENDIX E LATENCY ANALYSIS..... E-1

E.1	Definitions and Terminology	E-1
E.2	Data Flow for Latency Calculation	E-3
E.2.1	Latency Example for Class 6 DAA System	E-3
E.2.2	Latency Example for Class 7 DAA System	E-5
E.2.3	Latency Example for Class 8 DAA System	E-6
E.3	Specific Latency Allocations	E-7
E.3.1	Surveillance Sources	E-7
E.3.2	Tracker Latency	E-9
E.3.3	GNSS Latency	E-9
E.3.4	Alerting Latency	E-9
E.3.5	C2 Link System Latency	E-10

E.3.6	Guidance and Display Latency	E-10
E.3.7	Additional Total Latency Between Tracker and Display	E-10
E.3.8	C2 Link System Uplink Latency (Formerly Command-to-Execute Latency)	E-10
E.4	Interoperability Considerations of Class 2 and Class 3 Systems	E-10
E.4.1	Class 2 TCAS II Interoperability Considerations	E-10
E.4.2	Class 3 ACAS Xu Interoperability Considerations.....	E-11

APPENDIX F EXAMPLE FUNCTIONAL DESCRIPTION FOR AIRBORNE SURVEILLANCE DATA PROCESSOR (ASDP) SUBSYSTEM..... F-1

F.1	Introduction.....	F-1
F.2	Assumptions.....	F-1
F.3	Airborne Track Processing Subsystem	F-3
F.4	ATAR Tracker	F-4
F.4.1	Track Initiation.....	F-5
F.4.2	Track Establishment.....	F-12
F.4.3	Extended Kalman Filter	F-13
F.5	AST Tracker.....	F-21
F.5.1	Track Measurement/Association.....	F-22
F.5.2	Track Initiation.....	F-22
F.5.3	Track Establishment.....	F-24
F.5.4	Polar Filter Update	F-26
F.5.5	Extended Kalman Filter Update.....	F-29
F.6	Tracker for Sensor Messages with Full State information.....	F-45
F.7	Inter-Sensor Linking	F-45
F.7.1	Finding Central Track for ADS-B or AST Sensor Track.....	F-47
F.7.2	Finding Central Track for ATAR or GBSS Sensor Track	F-47
F.7.3	Finding Central Track for EO/IR Sensor Track.....	F-48
F.7.4	Linking Sensor Track to a Central Track	F-48
F.8	Best Sensor Selection.....	F-52
F.9	Track Management	F-56
F.9.1	Common Time Track Extrapolation	F-56
F.10	Adding Bias Effects to Error Covariance.....	F-57
F.10.1	ATAR Bias Inclusion.....	F-58
F.10.2	AST Bias Inclusion – Horizontal	F-60
F.10.3	Altitude Bias Inclusion	F-60

APPENDIX G DAA ALERTING LOGIC AND MANEUVER GUIDANCE FOR UAS REFERENCE IMPLEMENTATION.....G-1

G.1	Conceptual Overview of the DAIDALUS Reference Implementation.....	G-1
G.2	High-Level Functional Block Diagram of the DAIDALUS Reference Implementation.....	G-1
G.2.1	Hazard Tables and Alerters	G-3
G.2.2	Detection Logic.....	G-3
G.2.3	Guidance-Processing Logic	G-4
G.2.4	Alerting Logic.....	G-8
G.3	Data Requirements for DAIDALUS Reference Implementation.....	G-8
G.4	Mathematical Description of the DAIDALUS Reference Implementation	G-12
G.4.1	Nomenclature.....	G-12
G.4.2	Geometric Assumptions.....	G-13
G.4.3	DWC Logic.....	G-14

G.4.4	Detection Logic.....	G-14
G.4.5	Guidance Processing Logic.....	G-16
G.4.6	Alerting Logic.....	G-21
G.5	Verification and Validation.....	G-22
G.6	Sensor Uncertainty Mitigation.....	G-23
G.7	References.....	G-24

APPENDIX H RIGHT OF WAYH-1

H.1	Introduction.....	H-1
H.2	References.....	H-1
H.2.1	ROW References.....	H-2
H.2.2	References for Modeling & Simulation Analysis.....	H-2
H.3	Quantified Right of Way.....	H-3
H.3.1	Vertically Converging Encounters.....	H-3
H.3.2	Horizontally Unambiguous Encounters.....	H-4
H.3.3	Horizontally Ambiguous Encounters.....	H-4
H.3.4	QROW Summary for Ambiguous Encounters.....	H-12
H.4	ROW Modeling and Simulation and Analysis Results.....	H-13
H.4.1	M&S Components.....	H-15
H.4.2	Results.....	H-29
H.5	Check Cases.....	H-41
H.5.1	Check Case: Head-On.....	H-41
H.5.2	Check Case: Overtaken.....	H-42
H.5.3	Check Case: Overtaking.....	H-42
H.5.4	Check Case: Left Oblique Overtaking.....	H-42
H.5.5	Check Case: Right Oblique Overtaking.....	H-43
H.5.6	Check Case: Converging from Left.....	H-43
H.5.7	Check Case: Converging from Right.....	H-43

APPENDIX I TCAS II GUIDANCE MATERIAL I-1

I.1	Introduction.....	I-1
I.2	Antenna Installation Guidance.....	I-1
I.3	Antenna Installed Performance.....	I-1
I.4	Interference Limiting.....	I-2

APPENDIX J CLASS 3 RESOLUTION ADVISORY (RA) TYPES AND OUTPUTSJ-1

J.1	Mapping Vertical RAs to Control Station Outputs and Displays.....	J-2
J.2	Mapping Horizontal RAs to Control Station Outputs and Displays.....	J-14

APPENDIX K CLASS 3 DAA SYSTEM-SPECIFIC REQUIREMENT EXPLANATIONS AND EXEMPTIONS K-1

K.1	Class 3 DAA Equipment (ACAS Xu) Overview.....	K-6
K.2	Ownship State Data (§2.2.2.1.1).....	K-7
K.3	ATAR Intruder Data (§2.2.2.1.2).....	K-7
K.4	Active Surveillance Intruder Data (§2.2.2.1.3).....	K-7
K.5	ADS-B In Intruder Data (§2.2.2.1.4).....	K-7
K.6	Surveillance Equipment Operating Status and Health Data (§2.2.2.1.6).....	K-8

K.7	Prioritized Track Data (§2.2.2.2.1)	K-8
K.8	Relative Horizontal Position (§2.2.2.2.1.8).....	K-8
K.9	Relative Horizontal Velocity (§2.2.2.2.1.11).....	K-8
K.10	Relative Altitude (§2.2.2.2.1.13).....	K-8
K.11	Relative Vertical Rate (§2.2.2.2.1.16).....	K-9
K.12	DAA System Modes of Operation and Health Status (§2.2.2.2.2)	K-9
K.13	Active Surveillance, Equipment Class 2 RA Function, and Tracker Performance Requirements (§2.2.3).....	K-9
K.13.1	Track Initiation (§2.2.3.2.1.1).....	K-9
K.13.2	ADS-B Report Processing and Track Maintenance (§2.2.3.2.1.3)	K-9
K.13.3	Track Termination (§2.2.3.2.1.4).....	K-11
K.13.4	Intruder State Estimation (§2.2.3.2.3).....	K-11
K.14	Warning – En Route DWC (§2.2.4.3.6.1.3).....	K-11
K.15	Guidance Processing	K-13
K.16	Corrective Maneuver Guidance – En Route – Class 3 (§2.2.4.4.1.1.3)	K-14
K.17	DAA Maneuver Guidance to Regain DWC – En Route and Non-Cooperative (§2.2.4.4.1.2)	K-15
K.18	Special Cases – Corrective Maneuver Guidance – ATAR Only (§2.2.4.4.3.1.1.1).....	K-15
K.19	Special Cases – Regain DAA Well Clear (§2.2.4.4.3.2).....	K-15
K.20	Collision Avoidance Interoperability with Guidance (§2.2.4.5).....	K-15
K.20.1	Class 2 RA Guidance (§2.2.4.5.1).....	K-16
K.20.2	Vertical and Horizontal DAA Guidance (§2.2.4.5.2 and §2.2.4.5.3).....	K-16
K.21	Resolution Advisory Symbols for Class 2 and Class 3 Systems (§2.2.5.6.2.3.2.8).....	K-16
K.22	DAA Guidance to Maintain DWC (§2.2.5.7.2)	K-17
K.23	RA Guidance for Class 3 DAA Systems (§2.2.5.7.4).....	K-19
K.24	Class 3 RA Aural Alerts (§2.2.5.12.2.2)	K-19
K.25	En Route DWC Alerts (§2.2.4.3.6.1).....	K-19
K.25.1	Exemption Agreement	K-25
K.25.2	Agreed Upon Justification Categories	K-31
K.26	Corrective Maneuver Guidance – En Route and Non-Cooperative (§2.2.4.4.1.1.1)	K-55
K.27	Special Cases – Unvalidated ADS-B Only (§2.2.4.4.3.1.4).....	K-56
K.28	References.....	K-57

APPENDIX L OPEN- AND CLOSED-LOOP DAA METRICS..... L-1

L.1	Purpose and Background	L-1
L.1.1	Open-Loop Metrics	L-1
L.1.2	Closed-Loop Metrics.....	L-1
L.2	Hazard Definition and Encounter Characterization for Open-Loop Metrics	L-2
L.2.1	Mathematical Definition of the HAZ.....	L-3
L.2.2	Mathematical Definition of the NHZ.....	L-5
L.2.3	Definition of Hazard and NHZ Parameters.....	L-5
L.3	Definition of Open-Loop Technical Performance Metrics	L-10
L.3.1	Performance Metrics Analyzing Tracks with HAZ Violation (Alert Required).....	L-12
L.3.2	Performance Metrics Analyzing Tracks with MAZ Violation (Alerts Permissible).....	L-16
L.3.3	Performance Metrics Analyzing Tracks in the NHZ (Alerts Undesirable).....	L-18
L.3.4	Additional Open-Loop Considerations	L-20
L.4	Generating an Encounter Timeline for Closed-Loop Metrics.....	L-23
L.5	Closed-Loop Safety Metrics	L-24
L.5.1	Maintain DWC Safety Metrics.....	L-24
L.5.2	Collision Avoidance Safety Metrics	L-28

L.5.3	Operational Suitability Metrics	L-31
L.6	Severity of LoWC (SLoWC) Details	L-34
L.6.1	Fernandez-Guasti's Squirrel Mapping	L-35
L.6.2	En Route SLoWC Examples	L-36
L.6.3	SLoWC Metric Distribution Against Unmitigated Uncorrelated Encounters.....	L-44
L.6.4	Potential for Over-Assessing Penetration	L-45
L.6.5	Examples of Terminal Area SLoWC	L-47
L.7	References	L-49

APPENDIX M INTEROPERABILITY OF DAA AND ACAS..... M-1

M.1	Purpose and Scope	M-1
M.2	Minimum Aviation SYSTEM Performance Standards for the Interoperability of Airborne Collision Avoidance Systems	M-1
M.3	Collision Avoidance Region	M-1
M.4	Previous Studies Related to TCAS on UAs	M-4

APPENDIX N ADS-B POSITION VALIDATION CRITERIA USING TCAS II, RADAR, OR EO/IR FOR DAA N-1

N.1	Background	N-1
N.2	Experience with ADS-B Position Validation Using Active Surveillance Position.....	N-1
N.3	Slant Range within which ADS-B Position Validation is Required	N-1
N.4	Range, Bearing and Altitude Criteria for ADS-B Position Validation Using TCAS II.....	N-5
N.4.1	TCAS II Range Validation Threshold.....	N-5
N.4.2	TCAS II Altitude Validation Threshold.....	N-6
N.4.3	TCAS II Bearing Validation Threshold	N-6
N.5	Range, Bearing and Altitude Criteria for ADS-B Position Validation Using Radar	N-7
N.5.1	Radar Range Validation Threshold	N-8
N.5.2	Altitude Validation Threshold.....	N-8
N.5.3	Bearing Validation Threshold.....	N-9
N.6	Bearing and Elevation Criteria for ADS-B Position Validation Using EO/IR	N-10
N.6.1	Bearing Validation Threshold.....	N-10
N.6.2	Elevation Validation Threshold	N-11
N.7	Position Validation Interval	N-12

APPENDIX O EQUIPMENT CLASS TO REQUIREMENT CROSS –REFERENCES.....O-1

APPENDIX P TEST VECTORS..... P-1

P.1	Summary and Assumptions.....	P-1
P.1.1	Sources Used for Test Vector Derivation	P-1
P.1.2	Intruder and Ownship Assumptions.....	P-2
P.1.3	Verification of Achievability	P-2
P.2	Description of Individual Test Vector Sets	P-2
P.2.1	Head-on.....	P-2
P.2.2	Convergence at Fix	P-3
P.2.3	Convergence with Fast-Moving Jet	P-3
P.2.4	Overtake	P-3
P.2.5	Maneuver	P-4
P.2.6	Designer	P-4

P.2.7	Dynamic	P-4
P.2.8	Peripheral Guidance	P-4
P.2.9	Dynamic Terminal	P-4
P.2.10	Terminal Area	P-5
P.3	Track File Description	P-5
P.3.1	Test Vector Information File Format and Contents	P-6
P.3.2	Truth Track Format and Contents	P-8
P.3.3	Format and Contents of Degraded Ownship Track.....	P-8
P.3.4	Format and Contents of Degraded Intruder Track – ADS-B	P-9
P.3.5	Format of Degraded Intruder Track – Mode C and Mode S Active Surveillance	P-10
P.3.6	Format of Degraded Intruder Track – Air-to-Air Radar Surveillance	P-10
P.3.7	Format of Degraded Intruder Track – EO/IR Surveillance.....	P-11
P.3.8	Format of Tracker Output	P-12
P.3.9	Encounter Characterization and Required Performance Files	P-13
P.4	Test Vector Model Parameters.....	P-15
P.4.1	Ownship Error Model	P-15
P.4.2	ADS-B Error Model.....	P-16
P.4.3	Air-to-Air Radar Model	P-17
P.4.4	Ground Based Surveillance System Model.....	P-19
P.4.5	Active Surveillance Model.....	P-19
P.4.6	EO/IR Model.....	P-20
P.5	References.....	P-21

APPENDIX Q SENSOR, TRACKING, AND ALERTING ASSESSMENT.....Q-1

Q.1	Introduction.....	Q-1
Q.2	Analysis Approach Overview	Q-1
Q.3	Encounter Trajectories	Q-3
Q.4	Sensor Model Descriptions	Q-4
Q.4.1	ADS-B.....	Q-4
Q.4.2	ATAR.....	Q-5
Q.4.3	Ground Based Surveillance Derivation.....	Q-6
Q.4.4	Active Surveillance	Q-7
Q.4.5	EO/IR	Q-7
Q.4.6	Ownship Navigation (NAV) Model.....	Q-8
Q.5	Tracking Assessment	Q-9
Q.6	DAIDALUS and SUM Algorithm Implementations	Q-14
Q.6.1	Overview.....	Q-14
Q.6.2	DAIDALUS	Q-14
Q.6.3	SUM.....	Q-16
Q.7	Alerting and Guidance “Wrappers”	Q-17
Q.8	Alerting Assessment	Q-18

APPENDIX R AUTOMATION REQUIREMENTS.....R-1

R.1	Introduction.....	R-1
R.2	Assumptions and Limitations.....	R-2
R.3	Automated RA Processing and Execution Requirements	R-3
R.4	Automated RTC Processing and Execution Requirements.....	R-5
R.5	Automation Control Requirements for RA and RTC.....	R-6
R.6	Automation Display Requirements	R-7

TABLE OF FIGURES

Figure 1-1: Top-Level DAA System 7

Figure 1-2: Class 1 and 2 DAA Equipment Onboard the Aircraft..... 8

Figure 1-3: Class 3 DAA Equipment Onboard the Aircraft 10

Figure 1-4: DAA Equipment in the Control Station 11

Figure 2-1: Class 1 with Class 5, 6, and 7 Options 30

Figure 2-2: Class 2 with Class 5, 6, and 7 Options 31

Figure 2-3: Class 3 DAA System Overview with Article Information..... 32

Figure 2-4: Class 8 with Class 5 Option 33

Figure 2-5: DAA Input/Output Data Diagram 37

Figure 2-6: DAA Track Processing Objectives 68

Figure 2-7: ADS-B Track Validation State Transition Diagram 75

Figure 2-8: Illustration of Safe Non-Contiguous Guidance 111

Figure 2-9: Illustration of Corrective Guidance Information..... 115

Figure 2-10: Illustration of Peripheral Corrective Guidance Information 116

Figure 2-11: Illustration of Class 3 Peripheral Corrective Guidance Information..... 117

Figure 2-12: Illustration of Warning Guidance Information..... 120

Figure 2-13: Illustration of (a) Horizontal and (b) Vertical Guidance to Regain DWC 123

Figure 2-14: Illustration of Guidance to Maintain and Regain DWC for Class 5 Equipment
During Approach/Landing when a Climb is Predicted to Increase Vertical
Separation at CPA..... 128

Figure 2-15: Illustration of Guidance to Maintain and Regain DWC for Class 5 Equipment
During Approach/Landing when a Climb is Predicted to Decrease Vertical
Separation at CPA..... 130

Figure 2-16: Illustration of Guidance during a Directive RA and Warning Alert 139

Figure 2-17: Example Means of Determining Intruder VRC Information 144

Figure 2-18: Basic Directional Traffic Symbol (Example) 156

Figure 2-19: Basic Non-directional Traffic Symbol (Example) 156

Figure 2-20: Directional and Non-directional Designated Traffic Symbols..... 156

Figure 2-21: Directional and Non-directional Maneuver Guidance Traffic Symbols 157

Figure 2-22: Directional and Non-Directional Preventive Alert Symbols..... 158

Figure 2-23: Directional and Non-Directional Corrective Alert Symbols..... 158

Figure 2-24: Directional and Non-Directional Warning Alert Symbols..... 158

Figure 2-25: Unvalidated ADS-B Only Corrective Alert..... 160

Figure 2-26 : Directional and Non-Directional RA Symbol for Class 2 and Class 3 Systems..... 160

Figure 2-27: Using Transparent Bands for Positive Maintain-DWC Guidance 170

Figure 2-28: Using Green Bands for Positive Maintain-DWC Guidance..... 170

Figure 2-29: Using Transparent Bands for Unassessed Trajectories 171

Figure 2-30: Using Dashed Grey Bands for Unassessed Trajectories 171

Figure 2-31: Vertical and Horizontal Maneuver Guidance to Regain DWC 173

Figure 2-32: RA Vertical Guidance: Altitude Tape with Transparent Bands for Positive Guidance 174

Figure 2-33: RA Vertical Guidance: Altitude Tape with Green Bands for Positive Guidance 174

Figure 2-34: Example Depiction of a Horizontal RA - Target Heading = 300 deg and Left Turn
issued by CAS Logic. Vertical DAA Guidance depicted within an Altitude Tape 177

Figure 2-35: Example Methods for depicting Non-assessed Trajectories for Class 3 systems using Grey Dashed Bandings (a), or Compass Rose Markings (b)	178
Figure 2-36: Example Methods for depicting Non-assessed Trajectories during a Class 3 Horizontal RA. The Markings have been modified to indicate that the Avoidance Band extends to -180 deg rather than -97.5deg	179
Figure 2-37: Example Methods for depicting Non-assessed Trajectories during a Class 3 Horizontal RA with a Secondary Intruder generating Horizontal Corrective Guidance	179
Figure 2-38: Example Depiction of a Single-Intruder Vertical RA, with a Target Vertical Rate of +1000 FPM	182
Figure 2-39: Example Depiction of a Blended RA, with a Target Heading of 300 deg and a Target Vertical Rate of +1000 FPM	183
Figure C-1: DWC Recommendation from SaRP to SC-228 (not to scale or shape)	C-3
Figure C-2: DWC Proposal from the FAA White Paper (not to scale or shape)	C-4
Figure C-3: Traffic Pattern Legs (FAA Airplane Flying Handbook)	C-6
Figure C-4: TOPS2 Simulated Terminal Area Traffic	C-9
Figure C-5: UAS and VFR Speed and Altitude	C-14
Figure C-6: DWC Average Warning Alert	C-16
Figure C-7: C20+C21 Metric with Various Surveillance Volumes	C-16
Figure C-8: LRs Binned by UA Speed	C-17
Figure C-9: RRs Binned by UA Speed	C-18
Figure C-10: Minimum, Median, Maximum Alert Look-ahead Time by DWC Definition (HITL)	C-19
Figure D-1: Vertical Maneuver Profile	D-3
Figure D-2: Maneuver Initiation Range for Level-Turn Maneuvers, Altitude < 10000'	D-8
Figure D-3: Maneuver Initiation Time to LoWC for Level-Turn Maneuvers, Altitude < 10000'	D-9
Figure D-4: Maneuver Initiation Range for Level-Turn Maneuvers, 10000' ≤ Altitude < 18000'	D-9
Figure D-5: Maneuver Initiation Range for Vertical Maneuvers against Non-Cooperative intruders, Altitude < 10000'	D-10
Figure D-6: Maneuver Initiation Range for Vertical Maneuvers against Cooperative Intruders, Altitude < 10000'	D-11
Figure D-7: Maneuver Initiation Range for Vertical Maneuvers against Cooperative Intruders, 10000' ≤ Altitude < 18000'	D-11
Figure D-8: Maneuver Initiation Range for Horizontal & Vertical Maneuvers against Transit DWC, Non-Cooperative Intruders, Altitude < 10000'	D-12
Figure D-9: Maneuver Initiation Range for Horizontal & Vertical Maneuvers against Transit DWC, Cooperative Intruders, Altitude < 10000'	D-13
Figure D-10: Maneuver Initiation Range for Horizontal & Vertical Maneuvers against Transit DWC, Cooperative Intruders, 10000' ≤ Altitude < 18000'	D-13
Figure D-11: Class A1 Maneuver Initiation Range for Level-Turn Maneuvers, Altitude < 10000'	D-16
Figure D-12: Class A1 Maneuver Initiation Time to LoWC for Level-Turn Maneuvers, Altitude < 10000'	D-17
Figure D-13: Class A2 Maneuver Initiation Range for Level-Turn Maneuvers, Altitude < 10000'	D-17
Figure D-14: Class A2 Maneuver Initiation Time to LoWC for Level-Turn Maneuvers, Altitude < 10000'	D-18
Figure D-15: Class A3 and EO/IR Sensor Maneuver Initiation Range for Level-Turn Maneuvers, Altitude < 10000'	D-18
Figure D-16: Class A3 and EO/IR Sensor Maneuver Initiation Time to LoWC for Level-Turn Maneuvers, Altitude < 10000'	D-19
Figure D-17: Maneuver Initiation Range for Vertical Maneuvers against Non-Cooperative Intruders, Altitude < 10000'	D-19

Figure D-18: Maneuver Initiation Range for Vertical Maneuvers against Cooperative Intruders, Altitude < 10000'	D-20
Figure D-19: Maneuver Initiation Range for Vertical Maneuvers against Cooperative Intruders, 10000' ≤ Altitude < 18000'	D-20
Figure D-20: Maneuver Initiation Range for Level-Turn Maneuvers against 90-kt DTA Intruder.....	D-23
Figure D-21: Maneuver Initiation Time to LoWC for Level-Turn Maneuvers against 90-kt DTA Intruder.....	D-23
Figure D-22: Maneuver Initiation Range for Level-Turn Maneuvers against 140-kt DTA Intruder.....	D-24
Figure D-23: Maneuver Initiation Time to LoWC for Level-Turn Maneuvers against 140-kt DTA Intruder.....	D-24
Figure D-24: Maneuver Initiation Range for Vertical Maneuvers against 90-kt DTA Intruder.....	D-25
Figure D-25: Maneuver Initiation Time to LoWC for Vertical Maneuvers against 90-kt DTA Intruder.....	D-26
Figure D-26: Maneuver Initiation Range for Vertical Maneuvers against 140-kt DTA Intruder.....	D-26
Figure D-27: Maneuver Initiation Time to LoWC for Vertical Maneuvers against 140-kt DTA Intruder.....	D-27
Figure E-1: Notional Representation of Latency Terminology	E-3
Figure E-2: Notional Class 6 DAA System with Simplified Data Flow.....	E-4
Figure E-3: Notional Class 7 DAA System with Simplified Data Flow.....	E-5
Figure E-4: Notional Class 8 DAA System with Simplified Data Flow.....	E-7
Figure F-1: Track Processing Subsystem.....	F-3
Figure F-2: ATAR Tracker	F-5
Figure F-3: Geometry of Ownship/Target in an ECEF Coordinate System	F-7
Figure F-4: AST Tracker	F-21
Figure F-5: Linking Parameters	F-46
Figure F-6 : Algorithm to find a central track to link with an ADS-B or AST sensor track.....	F-49
Figure F-7: Sensor track/central track linking logic	F-50
Figure F-8 : Algorithm to find a central track to link with an ATAR or GBSS sensor track	F-51
Figure F-9: Algorithm to find a central track to link with an EO/IR sensor track	F-52
Figure F-10: Best Sensor Selection Algorithm Flowchart.....	F-55
Figure G-1: Notional Functional Block Diagram of DAIDALUS.....	G-2
Figure G-2: Constant Velocity Aircraft Projection.....	G-4
Figure G-3: Concept of DAIDALUS Horizontal Maneuver Guidance to Maintain DWC.....	G-5
Figure G-4: Notional Illustration of Maneuver Guidance Evolution for an Example Encounter	G-7
Figure H-1: Vertically Converging Encounter with the UA Climbing.....	H-4
Figure H-2: Vertically Converging Encounter with the UA Descending	H-4
Figure H-3: Horizontally Unambiguous Encounter with a Sufficiently Large HMD.....	H-4
Figure H-4: Head-On Geometry with Bearing and Relative Heading Criteria.....	H-6
Figure H-5: Overtaken Geometry with Bearing Criteria	H-7
Figure H-6: Overtaking Geometry with Bearing and Relative Heading Criteria	H-8
Figure H-7: Left Oblique Overtaking Geometry with Bearing Criteria.....	H-9
Figure H-8: Right Oblique Overtaking Geometry with Bearing Criteria	H-10
Figure H-9: Converging from Left.....	H-11
Figure H-10: Converging from Right	H-12
Figure H-11: M&S to Support Validating QROW	H-14
Figure H-12: Encounter Model to Generate Aircraft Trajectories for the M&S Framework	H-15
Figure H-13: Aircraft Initial Speed and Altitude Histograms.....	H-16
Figure H-14: Human Visual Acquisition Model in the M&S Framework	H-17
Figure H-15: P(Visual Detection of Small and Large Aircraft in Overtaking Scenarios)	H-18
Figure H-16: Observation Flight Test Ranges	H-19
Figure H-17: LL Observation Ranges, Converging from Left/Right	H-19

Figure H-18: LL Observation Ranges, Head-On, Overtaking and Overtaken.....	H-20
Figure H-19: Manned Aircraft Pilot Response Model after Visual Acquisition of the UA.....	H-20
Figure H-20: Bearing Partition Zones.....	H-21
Figure H-21: Example of Human Partition Zones	H-22
Figure H-22: Performance Metrics to Demonstrate Efficacy of QROW.....	H-23
Figure H-23: Benign Momentary Nick at the LoWC Boundary vs. Prolonged, Severe LoWC	H-25
Figure H-24: Well Clear Penetration Integral Formulation	H-25
Figure H-25: Well Clear Penetration Integral: Head-On	H-26
Figure H-26: Well Clear Penetration Integral: Converging from Right	H-27
Figure H-27: Well Clear Penetration Integral: Overtaking.....	H-27
Figure H-28: Description of Simulation Environment.....	H-28
Figure H-29: LoWC Maneuver Logic	H-28
Figure H-30: DAA Performance Metrics with and without QROW: Head-On.....	H-31
Figure H-31: DAA Performance Metrics with QROW: Overtaken.....	H-32
Figure H-32: DAA Performance Metrics with QROW: Overtaking	H-33
Figure H-33: DAA Performance Metrics with QROW: Left Oblique Overtaking	H-34
Figure H-34: DAA Performance Metrics with QROW: Right Oblique Overtaking.....	H-34
Figure H-35: DAA Performance Metrics with QROW: Converging from Left.....	H-35
Figure H-36: Number of Viable DAA Maneuvers for Converging from Left.....	H-36
Figure H-37: DAA Performance Metrics with QROW: Converging from Right.....	H-37
Figure H-38: Number of Viable DAA Maneuvers for Converging from Right	H-38
Figure H-39: Stressing Geometry – Converging from Right.....	H-39
Figure H-40: PI for Right Turn Maneuver vs. Intruder Location	H-40
Figure H-41: HMD and Maneuver Likelihood at 15 seconds before LoWC.....	H-41
Figure I-1: Interrogation Range Reduction as a Function of Attenuation.....	I-2
Figure K-1: Elements of ACAS Xu RAs	K-12
Figure K-2: Timing of the ACAS Xu RA compared to other DAA Alerting and Guidance Events	K-13
Figure K-3: Visualization of Surveillance Noise Impacts on Non-Maneuvering Encounters, with Respect to Altitude Separation (ADS-B Surveillance).....	K-34
Figure K-4: Visualization of Surveillance Noise Impacts on Non-Maneuvering Encounters, with Respect to Horizontal Offset (ADS-B Surveillance)	K-35
Figure K-5: Visualization of Surveillance Noise Impacts on Non-Maneuvering Encounters, with Respect to Horizontal Offset (Active Surveillance)	K-36
Figure K-6: Encounter Visualization Example: Projected CPA versus Range along the Relative Velocity Vector.....	K-37
Figure K-7: Encounter Example in Ground-Fixed Frame	K-38
Figure K-8: Encounter Example	K-39
Figure K-9: Encounter Visualization Example of Head-On Encounters	K-40
Figure K-10: Justification Category B Example: Late Alert Failure DAA Test Vector LL132 (ADS-B Surveillance).....	K-41
Figure K-11: Justification Category B Example: Late Alert Failure DAA Test Vector P8 (Mode S).....	K-42
Figure K-12: Justification Category B Example: Early Alert Failure DAA Test Vector LL145 (Mode S Surveillance)	K-43
Figure K-13: Justification Category B Example: Early Alert Failure DAA Test Vector LL168 (Mode S Surveillance)	K-44
Figure K-14: Justification Category B Example: Must Not Alert Failure DAA Test Vector H28 (ADS-B Surveillance).....	K-45
Figure K-15: Justification Category B Example: Must Not Alert Failure DAA Test Vector LL174 (Mode S Surveillance)	K-46

Figure K-16: Justification Category B Example: Must Alert Failure DAA Test Vector LL121 (ADS-B Surveillance).....	K-47
Figure K-17: Justification Category B Example: Must Alert Failure DAA Test Vector LL171 (ADS-B Surveillance).....	K-48
Figure L-1: Summary of Closed-Loop TPMs.....	L-2
Figure L-2: Zones Used in Alert Evaluation.....	L-3
Figure L-3: Horizontal Expansion of Hazard and NHZ for a Head-on Encounter.....	L-7
Figure L-4: Alert Scoring Process.....	L-12
Figure L-5: Sample Horizontal Plot of Prolonged Proximity Encounter.....	L-21
Figure L-6: Notional Performance Visualization (Not Real Data).....	L-22
Figure L-7: Deviation Diagram.....	L-32
Figure L-8: Horizontal and Vertical Course Deviations.....	L-33
Figure L-9: Fernandez-Guasti's Squirrel Mapping.....	L-36
Figure L-10: SLoWC Propagation for Co-altitude Head-on Intruders with different HMDs.....	L-37
Figure L-11: SLoWC Propagation for Head-on Intruders with 100 ft Vertical Offset with different HMDs.....	L-38
Figure L-12: SLoWC Propagation for Vertically Converging and Altitude-crossing Head-on Intruders with different HMDs.....	L-39
Figure L-13: SLoWC Propagation for Vertically Converging Head-on Intruders with Altitude-crossing after CPA.....	L-40
Figure L-14: SLoWC Propagation for Turning Away against Head-on Intruders with different HMDs.....	L-41
Figure L-15: SLoWC Propagation for Co-altitude Crossing Intruders.....	L-42
Figure L-16: SLoWC Propagation for Co-altitude Overtaking Geometries.....	L-43
Figure L-17: SLoWC Distribution for 15,000 Unmitigated Encounters with LoWC.....	L-44
Figure L-18: Comparison of Unmitigated and Mitigated SLoWC Distribution.....	L-45
Figure L-19: SLoWC Assessed Against Turning Geometry with Momentary LoWC.....	L-46
Figure L-20: SLoWC vs. Horizontal CPA for 100K Unmitigated MALE Correlated Encounters.....	L-47
Figure L-21: TA_SLoWC for a Co-altitude Arrival.....	L-48
Figure L-22: TA_SLoWC for Overlapping Arrival and Departure.....	L-48
Figure L-23: TA_SLoWC for Turning Convergence.....	L-49
Figure Q-1: Analysis Process Flow Chart.....	Q-2
Figure Q-2: Horizontal Position Tracking Error as a Function of Horizontal Range.....	Q-10
Figure Q-3: Relative Altitude Tracking Error as a Function of Horizontal Range.....	Q-10
Figure Q-4: Relative Velocity Tracking Error as a Function of Horizontal Range.....	Q-11
Figure Q-5: Vertical Rate Tracking Error as a Function of Horizontal Range.....	Q-11
Figure Q-6: EO/IR Position Tracking Error as a Funtion of Horizontal range.....	Q-12
Figure Q-7: EO/IR Velocity Tracking Error as a Funtion of Horizontal range.....	Q-12
Figure Q-8: EO/IR Altitude Tracking Error as a Funtion of Horizontal range.....	Q-13
Figure Q-9: EO/IR Altitude Rate Tracking Error as a Funtion of Horizontal range.....	Q-13
Figure Q-10: Alerting Metrics Definitions.....	Q-18

TABLE OF TABLES

Table 1-1: DAA Data Flows, Interfaces and Associated Requirement Locations.....	5
Table 2-1: DAA Class Table and DAA Article Labels.....	26
Table 2-2: Radar Classes.....	28
Table 2-3: Allowable Latency Contributions for DAA Subsystems.....	34

Table 2-4: DAA Ownship State Data Input	40
Table 2-5: ATAR Intruder Data Input	43
Table 2-6: Traffic Data Input from Onboard Active Surveillance.....	45
Table 2-7: DAA Traffic State Data Input from ADS-B.....	47
Table 2-8: DAA Intruder Mode Status Data Input from ADS-B.....	49
Table 2-9: RA Report Data Input from ADS-B.....	50
Table 2-10: Operational Coordination Message Data Content	51
Table 2-11: TCAS Coordination Data if RA is Issued against Ownship.....	52
Table 2-12: Surveillance Equipment Health Data	52
Table 2-13: GBSS Prioritized Track Data	54
Table 2-14: EO/IR Intruder Data Input.....	55
Table 2-15: UA DAA Prioritized Track Report Data	57
Table 2-16: Acceptable Minimum Combinations of Velocity Uncertainty and Ground Speed to Support Traffic Directionality.....	61
Table 2-17: Data Received by the CS DAA Processor.....	62
Table 2-18: CS DAA Processor Output Data	62
Table 2-19: DAA Traffic Display Input	64
Table 2-20: RTCA DO-185B Requirements to Support DAA Active Surveillance.....	66
Table 2-21: Summary of Acceptable Means for Velocity Qualification	71
Table 2-22: UA DAA Prioritized Track State Output Data.....	81
Table 2-23: Single-Source Integrated Track Performance.....	82
Table 2-24: DWC Applicability.....	86
Table 2-25: Parameters for En Route DWC Alerting Requirements	94
Table 2-26: Parameters for Terminal DWC Alerting Requirements	100
Table 2-27: Parameters for Non-Cooperative DWC Alerting Requirements	102
Table 2-28: Types of Corrective TCAS II RAs	136
Table 2-29: Types of Preventive TCAS II RAs.....	137
Table 2-30: DAA Vertical Interoperability and Coordination Summary	140
Table 2-31: Written Message per RA Type.....	184
Table 2-32: Aural Annunciations per RA Type.....	192
Table 2-33: Aural Annunciations per Vertical RA Type.....	194
Table 2-34: Aural Annunciations per Horizontal RA Type.....	195
Table 2-35: Aural Annunciations per Blended RA Type.....	195
Table 2-36: Minimum DAA Operational Modes – Equipment Class 1/8.....	197
Table 2-37: Minimum DAA Operational Modes – Equipment Class 2.....	197
Table 2-38: DAA Subsystems and Operating Statuses.....	201
Table 2-39: DAA Airborne Equipment Environmental Test Requirements.....	205
Table 2-40: CS Equipment Environmental Test Conditions and Performance Matrix.....	210
Table 2-41: Cross-Reference of DAA Surveillance Reqs to RTCA DO-185B Test Procedures.....	227
Table 2-42: Cross-Reference of DAA Surveillance Reqs to RTCA DO-300A Test Procedures	232
Table 2-43: List of Sensor Combinations	240
Table 2-44: Requirement-to-Test Matrix.....	340
Table C-1: TOPS 1b Metrics by DWC Candidate	C-8
Table C-2: Metrics Considered for the En Route Non-cooperative DWC	C-13
Table C-3: Four Candidate DWC Definitions and En Route Cooperative Definition.....	C-15
Table C-4: UA Speed Bins	C-17
Table C-5: Proportion of LoWC by DWC Definition (HITL).....	C-19
Table D-1: Aircraft Speed Bounds per Altitude and Turn Capability	D-7
Table D-2: UAS Performance per NonCooperative Sensor Class.....	D-15
Table D-3: Intruder RCS/Airspeed Bins	D-15
Table D-4: Aircraft Speed Bounds per Turn Capability	D-22

Table E-1: Allowable Latency Contributions for DAA Subsystems	E-2
Table E-2: Sample GBSS Latency Calculations for a Class 6 DAA System	E-4
Table E-3: Sample GBSS Latency Calculations for Class 7 DAA System	E-6
Table E-4: Sample GBSS Latency Calculations for a Class 8 DAA System	E-7
Table E-5: Latency Requirements from MOPS of Sensors Used in DAA	E-8
Table G-1: Ownship Input State	G-8
Table G-2: Traffic Input State.....	G-9
Table G-3: Ownship Performance Limits	G-9
Table G-4: Output Data Types.....	G-10
Table G-5: Output Requirements	G-11
Table G-6: Hazard Table Parameters	G-11
Table G-7: Default Hazard Tables in DAIDALUS.....	G-12
Table G-8: Configuration Parameters	G-12
Table G-9: Nomenclature Unique to This Appendix.....	G-13
Table G-10: Aircraft Uncertainty Information Data Requirements	G-23
Table G-11: Sensor Uncertainty Mitigation Scaling Factors.....	G-24
Table H-1: Summary of QROW for Ambiguous Geometries	H-12
Table H-2: Human Visual Acquisition Model Parameters Used for ROW M&S	H-17
Table H-3: Comprehensive Maneuver Directions Based on Partition Zone Pairs.....	H-21
Table H-4: Intruder Pilot Response Assumptions.....	H-23
Table H-5: Check Case: Head-on	H-41
Table H-6: Check Case: Overtaken	H-42
Table H-7: Check Case: Overtaking	H-42
Table H-8: Check Case: Left Oblique Overtaking.....	H-42
Table H-9: Check Case: Right Oblique Overtaking	H-43
Table H-10: Check Case: Converging from Left.....	H-43
Table H-11: Check Case: Converging from Right.....	H-43
Table I-1: 90% Detection Range as a Function of Interference Limiting.....	I-3
Table I-2: Adjusted 90% Detection Range as a Function of Interference Limiting	I-4
Table I-3: Supported Alert Times at Maximum IL	I-5
Table I-4: Supported Alert Times in High IL Conditions.....	I-5
Table J-1: Mapping Vertical RAs to Control Station Outputs and Displays	J-2
Table J-2: Combined Control Label 270 Bit Mapping	J-9
Table J-3: Vertical Control Label 270 Bit Mapping	J-9
Table J-4: Up Advisory Label 270 Bit Mapping	J-9
Table J-5: Down Advisory Label 270 Bit Mapping.....	J-10
Table J-6: Mapping Horizontal RAs to Control Station Outputs and Displays	J-14
Table J-7: Combined Control Label 271 Bit Mapping	J-16
Table J-8: AHRA Subfield Target Track Angle Bit Mapping.....	J-18
Table J-9: RA Message Format Bit Mapping	J-19
Table K-1: Mapping of DO-365 Requirements to Appendix K – Explanations.....	K-1
Table K-2: Mapping of DO-365 Requirements to Appendix K – Exemptions	K-5
Table K-3: Converting Class 3 Vertical Rate Output to Altitude	K-18
Table K-4: ACAS Xu En Route DWC Alerting Report Card – Preventive	K-20
Table K-5: ACAS Xu En Route DWC Alerting Report Card – Corrective.....	K-21
Table K-6: ACAS Xu Special Case Alerting Report Card – Radar-Only	K-22
Table K-7: ACAS Xu Special Case Alerting Report Card – No Bearing.....	K-22
Table K-8: ACAS Xu Special Case Alerting Report Card – No Altitude	K-23
Table K-9: ACAS Xu Special Case Alerting Report Card – Unvalidated ADS-B.....	K-24
Table K-10: Late Alert Exemptions.....	K-26
Table K-11: Early Alert Exemptions	K-27

Table K-12: Must Not Alert Exemptions.....	K-28
Table K-13: Must Alert Exemptions.....	K-29
Table K-14: Radar Only Special Case Alerting Exemptions.....	K-29
Table K-15: No Bearing Special Case Alerting Exemptions.....	K-30
Table K-16: No Altitude Special Case Alerting Exemptions	K-31
Table K-17: ADS-B Noise Parameters	K-50
Table K-18: Mode S Noise Parameters.....	K-50
Table K-19: Active Mode C Noise Parameters	K-50
Table K-20: Air-to-Air Radar Noise Parameters	K-51
Table K-21: Passing Cases in Report Card, but >10% Surveillance Failures – Converging.....	K-51
Table K-22: Passing Cases in Report Card, but >10% Surveillance Failures – Head-on.....	K-52
Table K-23: Passing Cases in Report Card, but >10% Surveillance Failures – Maneuvering	K-52
Table K-24: Passing Cases in Report Card, but >10% Surveillance Failures – Overtake	K-53
Table K-25: Passing Cases in Report Card, but >10% Surveillance Failures – Peripheral	K-53
Table K-26: Passing Cases in Report Card, but >10% Surveillance Failures – Dynamic	K-54
Table K-27: ACAS Xu En Route Corrective Maneuver Report Card.....	K-56
Table L-1: Parameters for Calculating the Size of HAZ and NHZ – En Route.....	L-5
Table L-2: Parameters for Calculating the Size of HAZ and NHZ – DAA Terminal Area.....	L-8
Table L-3: Parameters for Calculating the Size of HAZ and NHZ – Non-Cooperative	L-9
Table L-4: Possible Reference Intruders.....	L-23
Table N-1: Position Validation Range	N-3
Table N-2: Surveillance Range for Different Levels of Interference Limiting(NM).....	N-4
Table N-3: Range Validation Error Budget for ADS-B Position Using TCAS II or Radar	N-6
Table N-4: Bearing Error for a 0.1 NM 95% Position Error for Ownship and Traffic.....	N-7
Table N-5: Altitude Validation Error Budget for ADS-B Position Using Radar.....	N-9
Table N-6: Bearing Validation Error Budget for ADS-B Position Using Radar	N-10
Table N-7: Bearing Validation Error Budget for ADS-B Position Using EO/IR	N-10
Table N-8: Elevation Validation Error Budget for ADS-B Position Using EO/IR	N-11
Table N-9: Distance Closed During Interval between Revalidations	N-12
Table N-10: Hybrid Surveillance Validation Interval.....	N-13
Table O-1: Article Matrix for Partial Standard Compliance.....	O-2
Table P-1: Categories and Numbers of DAA Test Vectors	P-1
Table P-2: Contents of Test Vector Information File	P-6
Table P-3: Data Fields in Test Vector Truth Tracks	P-8
Table P-4: Data Fields in Ownship Test Vector Tracks	P-9
Table P-5: Data Fields in ADS-B Test Vector Tracks.....	P-9
Table P-6: Data Fields in Mode C and Mode S Test Vector Tracks.....	P-10
Table P-7: Data Fields in Radar Test Vector Tracks	P-10
Table P-8: Data Fields in EO/IR Test Vector Tracks	P-11
Table P-9: Data Fields in Tracker Output Test Vector Tracks	P-12
Table P-10: Notional Contents of an Encounter Characterization File.....	P-13
Table P-11: Key for Interpreting the HAZ and the NHZ Columns in Table P-9.....	P-15
Table P-12: Ownship Error Model Parameters.....	P-15
Table P-13: Altitude Layer B Values.....	P-16
Table P-14: ADS-B Model Parameters.....	P-16
Table P-15: ATAR Model Parameters.....	P-17
Table P-16: ATAR FOR Model Parameters	P-18
Table P-17: GBSS Model	P-19
Table P-18: Active Surveillance Model Parameters	P-20
Table Q-1: ADS-B Model Parameters Pt 1.....	Q-4
Table Q-2 : ADS-B Model Parameters Pt 2.....	Q-5

Table Q-3: ATAR Model Parameters Pt 1	Q-5
Table Q-4: ATAR Model Parameters Pt 2	Q-6
Table Q-5 : Active Surveillance Model Parameters Pt 1	Q-7
Table Q-6: Active Surveillance Model Parameters Pt 2	Q-7
Table Q-7: EO/IR Model Parameters.....	Q-8
Table Q-8: Ownship Navigation (NAV) Model Parameters.....	Q-8
Table Q-9: Sensor Uncertainty Mitigation Scaling Factors.....	Q-17
Table Q-10: Alerting Metric Results Given Representative DAA Open-Loop System	Q-19
Table Q-11: Alerting Jitter Results Given Representative DAA Open-Loop System.....	Q-19

This Page Intentionally Left Blank

1 PURPOSE AND SCOPE

1.1 Introduction

This document contains Minimum Operational Performance Standards (MOPS) for Detect and Avoid (DAA) systems used in Unmanned Aircraft Systems (UAS) transiting through Class B, C, D, E, and G airspace and performing extended operations higher than 400' Above Ground Level (AGL) in Class D, E (up to Flight Level (FL) 180), and G airspace. It includes equipment to enable UAS operations in Terminal Areas during approach and departure in Class C, D, E and G airspace and off-airport locations. It does not apply to small UAS (sUAS) operating in low-level environments (below 400') or other segmented areas. Likewise, it does not apply to operations in the Visual Flight Rules (VFR) traffic pattern of an airport or to surface operations. For a complete description of operations and environments, refer to RTCA DO-398 Operational Services and Environment Description for Detect and Avoid Systems. These standards specify DAA system characteristics that should be useful for designers, manufacturers, installers and users of the equipment.

These MOPS focus on Unmanned Aircraft (UA) to enable safe flight in airspace normally frequented by commercial transport and general aviation aircraft. Aircraft operations in all classes of airspace vary, from operation under Instrument Flight Rules (IFR) in Reduced Vertical Separation Minimum (RVSM) airspace to VFR operations with minimal onboard equipment. The UA may need to carry relatively large and high-power sensor systems, depending on the class of sensors required for the speed of the UA. Alternatively, these MOPS also allow a class of equipment where all sensors are on the ground, which enables operations of UAS with reduced payload capabilities (see Subparagraph 2.1.10.1 for descriptions of all equipment classes). This version of the document adds a class of non-cooperative sensor that does allow some weight and power savings. Future revisions of this document may address other operational scenarios and sensors better suited to smaller UAS needs, pending further negotiation with airspace regulators.

During the original development of this document, members of the committee expressed concern about equipment without an explicit collision avoidance function providing an appropriate level of safety for the in-scope operations. Concerns were expressed regarding the safety of the system when compared to manned see-and-avoid capability, the usability of the well clear definition developed herein, and the impacts of replacing "collision avoidance" with a "regain well clear" concept. Concerns were also expressed that a formal safety analysis was not available to guide MOPS development, and that a top-level performance requirement was not established to provide a means for requirement traceability to lower-level requirements. To this end, the Federal Aviation Administration (FAA) commissioned an internal Safety Risk Management Panel during development of RTCA Document 365 (DO-365) to analyze and identify the conditions under which Equipment Class 1 or Equipment Class 2 is sufficient for the intended operations in the National Airspace System (NAS) (see Subparagraph 2.1.10.1 for a description of equipment classes). The FAA is using this safety analysis to determine required equipment and any necessary operational mitigations. Going forward, the committee expects the FAA to update the safety analysis based on changes to DAA systems or the NAS.

Compliance with these standards is recommended as one means of assuring that the equipment will perform its intended function(s) satisfactorily under the conditions specified herein. Any regulatory application of this document is the sole responsibility of appropriate governmental agencies.