

RTCA, Inc.
1150 18th Street NW, Suite 910
Washington, DC 20036
USA

**Minimum Operational Performance Standards (MOPS) for
Universal Access Transceiver (UAT)
Automatic Dependent Surveillance - Broadcast (ADS-B)**

Copies of this document may be obtained from
RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

FOREWORD

This document was prepared by Special Committee 186 (SC-186) and approved by the RTCA Program Management Committee (PMC) on June 23, 2022.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Standards Development Organization and develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organization's recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders and advisory circulars.

Since RTCA is not an agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

DISCLAIMER

This publication is based on material submitted by various participants during the SC approval process. Neither the SC nor RTCA has made any determination whether these materials could be subject to valid claims of patent, copyright or other proprietary rights by third parties, and no representation or warranty, expressed or implied is made in this regard. Any use of or reliance on this document shall constitute an acceptance thereof "as is" and be subject to this disclaimer.

This Page Intentionally Left Blank

TABLE OF CONTENTS

1	PURPOSE AND SCOPE	1
1.1	Introduction	1
1.2	ADS-B Transmitting Subsystem Overview	4
1.3	UAT System Overview	5
1.3.1	UAT Medium Access for ADS-B and Ground Uplink Segments	5
1.3.2	Ground Uplink Message Transmissions	6
1.3.3	ADS-B Message Transmissions	7
1.3.4	Traffic Information Service - Broadcast (TIS-B) Transmission	8
1.3.5	Message Structure	8
1.4	Operational Applications	10
1.4.1	General Support for Surveillance	10
1.4.2	'ADS-B Out' Applications	10
1.4.2.1	ATC Surveillance Service	10
1.4.2.2	Airport Surface Surveillance	10
1.4.3	'ADS-B In' Applications	11
1.4.3.1	Situational Awareness	11
1.4.4	Collision Avoidance Systems	12
1.4.5	ADS-B Weather Applications	12
1.4.6	UAS RPAS Operations	12
1.4.7	ADS-B Configuration Identification	12
1.5	Assumptions and Rationale	13
1.6	Test Procedures	13
1.7	Aircraft Equipment Information Vulnerabilities	14
2	Equipment Performance Requirements and Test Procedures	17
2.1	General Requirements	17
2.1.1	Airworthiness	17
2.1.2	Intended Function	17
2.1.3	Communication Regulations	17
2.1.4	Fire Protection	17
2.1.5	Operation of Controls	17
2.1.6	Accessibility of Controls	17
2.1.7	Equipment Interfaces	17
2.1.8	Effects of Test	18
2.1.9	Integration with Other Avionics Equipment	18
2.1.10	Design Assurance	18
2.1.11	Equipage Classes	18
2.1.12	Transmitting Subsystem	20
2.1.13	Receiving Subsystem	21
2.1.14	Antenna Subsystem	21
2.2	Equipment Performance – Standard Conditions	21
2.2.1	Definitions of Standard Conditions	21
2.2.1.1	Signal Levels	21
2.2.1.2	Desired Signals	21
2.2.1.3	Data Quantization	21
2.2.1.4	Definition of Reserved	22
2.2.2	ADS-B Transmitter Characteristics	22
2.2.2.1	Transmission Frequency	22

2.2.2.2	Modulation Rate	22
2.2.2.3	Modulation Type	22
2.2.2.4	Modulation Distortion	23
2.2.2.5	Transmitter Power Output	23
2.2.2.6	In Band Transmission Spectrum	25
2.2.2.7	Out-of-Band Emissions	26
2.2.3	Broadcast Message Characteristics	26
2.2.3.1	ADS B Message Format	26
2.2.3.1.1	Synchronization	27
2.2.3.1.2	Payload	27
2.2.3.1.3	FEC Parity	27
2.2.3.1.3.1	Code Type	27
2.2.3.1.3.2	Generation and Transmission Order of FEC Parity	27
2.2.3.2	Ground Uplink Message Format	28
2.2.3.2.1	Synchronization	28
2.2.3.2.2	Payload (Before Interleaving and After De-interleaving)	28
2.2.3.2.2.1	UAT-Specific Header	29
2.2.3.2.2.1.1	“GROUND STATION LATITUDE” Field Encoding	29
2.2.3.2.2.1.2	“GROUND STATION LONGITUDE” Field Encoding	29
2.2.3.2.2.1.3	“POSITION VALID” Flag Encoding	30
2.2.3.2.2.1.4	“UTC COUPLED” Field Encoding	30
2.2.3.2.2.1.5	“Reserved” Subfield	30
2.2.3.2.2.1.6	“APPLICATION DATA VALID” Flag Encoding	30
2.2.3.2.2.1.7	“SLOT ID” Field Encoding	30
2.2.3.2.2.1.8	“TIS-B SITE ID” Field Encoding	31
2.2.3.2.2.1.9	“Reserved” Subfield	31
2.2.3.2.2.2	Ground Uplink Application Data	31
2.2.3.2.2.2.1	“Length” Field Encoding	32
2.2.3.2.2.2.2	“Reserved” Subfield	32
2.2.3.2.2.2.3	“Frame Type” Subfield Encoding	32
2.2.3.2.2.2.4	Frame Data Content	32
2.2.3.2.2.2.4.1	FIS-B APDU	33
2.2.3.2.2.2.4.2	FIS-B Current Report List (CRL)	33
2.2.3.2.2.2.4.3	Traffic Uplink Management Message	33
2.2.3.2.2.2.4.3.1	“Service Status Bits” Field	33
2.2.3.2.2.2.4.3.2	“Service Status” Flag	34
2.2.3.2.2.2.4.3.3	“Address Qualifier” Field	34
2.2.3.2.2.2.4.3.4	“Aircraft Address” Field	34
2.2.3.2.2.2.4.4	Other Potential Future Frame Data Content	34
2.2.3.2.3	FEC Parity (Before Interleaving and After De-interleaving)	35
2.2.3.2.3.1	Code Type	35
2.2.3.2.3.2	Generation and Transmission Order of FEC Parity	35
2.2.3.2.4	Interleaved Payload and FEC Parity	35
2.2.4	The ADS-B Message Payload	36
2.2.4.1	Payload Type	36
2.2.4.2	Payload Elements	36
2.2.4.2.1	Payload Element Subtypes (PES)	37
2.2.4.2.1.1	“Payload Element Subtype Number” Field in Payload Element Subtypes	37
2.2.4.3	ADS-B Payload Composition by Payload Type Code	37
2.2.4.4	Payload Transmission Order	39
2.2.4.5	Payload Contents	39

2.2.4.5.1	HEADER (HDR) Element.....	39
2.2.4.5.1.1	“PAYLOAD TYPE CODE” Field Encoding.....	39
2.2.4.5.1.2	“ADDRESS QUALIFIER” Field Encoding.....	39
2.2.4.5.1.3	“ADDRESS” Field Encoding.....	40
2.2.4.5.1.3.1	ICAO Aircraft Address of Transmitting Aircraft.....	41
2.2.4.5.1.3.2	Self-Assigned Temporary Aircraft Address of Transmitting Aircraft.....	41
2.2.4.5.1.3.3	ICAO Aircraft Address of TIS-B or ADS-R/ADS-SLR Aircraft/Vehicle.....	42
2.2.4.5.1.3.4	TIS-B Track File Identifier.....	42
2.2.4.5.1.3.5	Surface Vehicle Address.....	42
2.2.4.5.1.3.6	Fixed ADS-B Beacon Address.....	42
2.2.4.5.1.3.7	ADS-R/ADS-SLR Target with Non-ICAO Aircraft Address.....	42
2.2.4.5.2	STATE VECTOR Element.....	42
2.2.4.5.2.1	“LATITUDE” and “LONGITUDE” Field Encoding.....	43
2.2.4.5.2.2	“ALTITUDE TYPE” (ALT TYPE) Flag Encoding.....	45
2.2.4.5.2.3	“ALTITUDE” Field Encoding.....	46
2.2.4.5.2.4	“Navigation Integrity Category” (NIC) Field Encoding.....	47
2.2.4.5.2.4.1	“Navigation Integrity Category” (NIC) Encoding During no Fault Detection and Exclusion Condition.....	47
2.2.4.5.2.4.2	“Navigation Integrity Category” and “Position Integrity Category” Field Encoding During Fault Detection and Exclusion Condition.....	48
2.2.4.5.2.5	“Air/Ground Velocity State” (A/GV STATE) Field Encoding.....	49
2.2.4.5.2.5.1	Determination of Vertical Status.....	50
2.2.4.5.2.5.2	Validation of Vertical Status.....	51
2.2.4.5.2.5.3	Vertical Status Determination Algorithm.....	51
2.2.4.5.2.5.3.1	Vertical Status Determination Algorithm Definitions.....	52
2.2.4.5.2.5.3.2	VSDA Applicability.....	52
2.2.4.5.2.5.3.2.1	Fixed-Wing VSDA Definitions.....	52
2.2.4.5.2.5.3.2.2	Fixed-Wing Requirements.....	52
2.2.4.5.2.5.3.2.3	VSDA Start-up and Validity Requirements.....	53
2.2.4.5.2.5.3.2.4	Fixed-Wing Performance Requirements.....	53
2.2.4.5.2.6	“HORIZONTAL VELOCITY” Field Encoding.....	54
2.2.4.5.2.6.1	Encoding as North Velocity Form.....	54
2.2.4.5.2.6.2	Encoding as Ground Speed Form.....	55
2.2.4.5.2.6.3	Encoding as East Velocity Form.....	56
2.2.4.5.2.6.4	Encoding as Track Angle/Heading Form.....	58
2.2.4.5.2.7	“VERTICAL VELOCITY or AIRCRAFT/VEHICLE SIZE” Field.....	59
2.2.4.5.2.7.1	Encoding as Vertical Velocity Form.....	59
2.2.4.5.2.7.1.1	“Vertical Velocity Source” Flag Encoding.....	60
2.2.4.5.2.7.1.2	“Vertical Velocity Sign” (VV Sign) Flag Encoding.....	60
2.2.4.5.2.7.1.3	“Vertical Rate” Subfield Encoding.....	60
2.2.4.5.2.7.2	Encoding as Aircraft/Vehicle Size Form.....	61
2.2.4.5.2.8	“UTC” Flag Encoding.....	64
2.2.4.5.2.9	“Uplink Feedback” Field Encoding.....	64
2.2.4.5.2.10	Reserved Byte 18 of Payload Type Zero.....	66
2.2.4.5.3	STATE VECTOR Element (For TIS-B or ADS-R/ADS-SLR).....	66
2.2.4.5.3.1	“TIS-B SITE ID” Field Encoding.....	66
2.2.4.5.3.2	Encoding for All Other Fields.....	67
2.2.4.5.4	MODE STATUS Element.....	67
2.2.4.5.4.1	“EMITTER CATEGORY” Field Encoding.....	67
2.2.4.5.4.2	“CALL SIGN/FLIGHT PLAN ID” Field Encoding.....	68

2.2.4.5.4.3	Compressed Format Encoding for “EMITTER CATEGORY” and “CALL SIGN /FLIGHT PLAN ID” Fields Encoding	70
2.2.4.5.4.3.1	Bytes 18 and 19	70
2.2.4.5.4.3.2	Bytes 20 and 21	71
2.2.4.5.4.3.3	Bytes 22 and 23	71
2.2.4.5.4.4	“Emergency/Priority Status” Field Encoding	71
2.2.4.5.4.5	“UAT MOPS VERSION” Field Encoding	73
2.2.4.5.4.6	“Source Integrity Level” (SIL) Field Encoding	74
2.2.4.5.4.7	“TRANSMIT MSO” Field Encoding	75
2.2.4.5.4.8	“System Design Assurance” (SDA) Field Encoding	75
2.2.4.5.4.9	“Navigation Accuracy Category for Position” (NAC _P) Field Encoding	76
2.2.4.5.4.10	“Navigation Accuracy Category for Velocity” (NAC _V) Field Encoding	77
2.2.4.5.4.11	“Reserved” Subfield	78
2.2.4.5.4.12	“CAPABILITY CODES” Field Encoding	78
2.2.4.5.4.12.1	“UAT IN Capability” Subfield Encoding	79
2.2.4.5.4.12.2	“1090ES IN Capability” Subfield Encoding	79
2.2.4.5.4.12.3	“Collision Avoidance (CA) Operational” Subfield Encoding	80
2.2.4.5.4.13	“OPERATIONAL MODES” Field Encoding	80
2.2.4.5.4.13.1	“CA Resolution Advisory Active” Flag Encoding	81
2.2.4.5.4.13.2	“IDENT Switch Active” Flag Encoding	81
2.2.4.5.4.13.3	“Reserved” Subfield	81
2.2.4.5.4.14	“Call Sign Identification” (CSID) Flag Encoding	81
2.2.4.5.4.15	Reserved	82
2.2.4.5.4.16	“Source Integrity Level Supplement” (SIL _{SUPP}) Flag Encoding	82
2.2.4.5.4.17	“Geometric Vertical Accuracy” (GVA) Field Encoding	82
2.2.4.5.4.18	“Single Antenna” Flag Encoding	83
2.2.4.5.4.19	“Navigational Integrity Category Supplement” (NIC _{SUPP}) Field Encoding	83
2.2.4.5.4.20	”Manned/Unmanned Operation” (M/U) Field Encoding	83
2.2.4.5.4.21	“Reserved” Subfield	84
2.2.4.5.5	AUXILIARY STATE VECTOR Element	84
2.2.4.5.5.1	“SECONDARY ALTITUDE” Field Encoding	84
2.2.4.5.5.2	“Reserved” Field	85
2.2.4.5.6	TARGET STATE Element (Payload Type Codes “3” and “4”)	85
2.2.4.5.6.1	“Selected Altitude Type” (SAT) Flag Encoding	85
2.2.4.5.6.2	“Selected Altitude” Field Encoding	86
2.2.4.5.6.3	“Barometric Pressure Setting” (Minus 800 millibars) Field Encoding	86
2.2.4.5.6.4	“Selected Heading” Field Encoding	87
2.2.4.5.6.5	“Status of MCP/FCU Mode Bits” (ST) Flag Encoding	88
2.2.4.5.6.6	“Mode Indicators: Autopilot Engaged” (AP) Flag Encoding	88
2.2.4.5.6.7	“Mode Indicators: VNAV Mode Engaged” (VNAV) Flag Encoding	88
2.2.4.5.6.8	“Mode Indicators: Altitude Hold Mode” (ALT) Flag Encoding	89
2.2.4.5.6.9	“Mode Indicators: Approach Mode” (APP) Flag Encoding	89
2.2.4.5.6.10	“Mode Indicators: LNAV Mode Engaged” (LNAV) Flag Encoding	89
2.2.4.5.6.11	“Reserved” Subfield	89
2.2.4.5.7	TARGET STATE Element (Payload Type Code “6”)	89
2.2.4.5.8	Reserved	90
2.2.4.5.9	EPISODIC Element (Payload Type Code 11) (Optional)	90
2.2.4.5.9.1	Payload Frames	91
2.2.4.5.9.1.1	“Payload Frame Type Code” Field Encoding	91
2.2.4.5.9.1.2	“Payload Frame Type Length Code” (PFTLC) Field Encoding	91
2.2.4.5.9.1.3	“Payload Frame Data”	92

2.2.4.5.9.1.4	UAS/RPAS Contingency P-Frame (PFTC=0) (Optional).....	92
2.2.4.5.9.1.4.1	“Contingency Plan” Subfield.....	93
2.2.4.5.9.1.4.2	“UAS/RPAS TCP Altitude” Subfields.....	94
2.2.4.5.9.1.4.3	“UAS/RPAS TCP Latitude” Subfields.....	94
2.2.4.5.9.1.4.4	“UAS/RPAS TCP Longitude” Subfields.....	94
2.2.4.5.9.1.5	PIREP P-Frame (PFTC=1) (Optional).....	95
2.2.4.5.9.1.5.1	“PIREP Time” Field in PIREP P-Frame.....	96
2.2.4.5.9.1.5.2	“Flight Visibility” Field in PIREP P-Frame.....	97
2.2.4.5.9.1.5.3	“Flight Weather 1” Field in PIREP P-Frame.....	97
2.2.4.5.9.1.5.4	“Flight Weather 2” Field in PIREP P-Frame.....	100
2.2.4.5.9.1.5.5	“Flight Weather 3” Field in PIREP P-Frame.....	100
2.2.4.5.9.1.5.6	“Layer ‘A’ Height” Field in PIREP P-Frame.....	100
2.2.4.5.9.1.5.7	“Layer ‘A’ Thickness” Field in PIREP P-Frame.....	101
2.2.4.5.9.1.5.8	“Layer ‘A’ Height Type” Field in PIREP P-Frame.....	102
2.2.4.5.9.1.5.9	“Layer ‘A’ Coverage” Field in PIREP P-Frame.....	103
2.2.4.5.9.1.5.10	“PIREP Air Temperature” Field in PIREP P-Frame.....	103
2.2.4.5.9.1.5.11	“PIREP Air Temperature Type” Field in PIREP P-Frame.....	104
2.2.4.5.9.1.5.12	“PIREP Wind Direction” Field in PIREP P-Frame.....	104
2.2.4.5.9.1.5.13	“PIREP Wind Speed” Field in PIREP P-Frame.....	105
2.2.4.5.9.1.5.14	“Turbulence Duration” Field in PIREP P-Frame.....	105
2.2.4.5.9.1.5.15	“Turbulence Intensity” Field in PIREP P-Frame.....	106
2.2.4.5.9.1.5.16	“Turbulence Location” Field in PIREP P-Frame.....	106
2.2.4.5.9.1.5.17	“Layer ‘B’ Height” Field in PIREP P-Frame.....	106
2.2.4.5.9.1.5.18	“Layer ‘B’ Thickness” Field in PIREP P-Frame.....	107
2.2.4.5.9.1.5.19	“Layer ‘B’ Height Type” Field in PIREP P-Frame.....	107
2.2.4.5.9.1.5.20	“Layer ‘B’ Coverage” Field in PIREP P-Frame.....	107
2.2.4.5.9.1.5.21	“PIREP Icing” Field in PIREP P-Frame.....	107
2.2.4.5.9.1.5.22	“Airspeed Change” Field in PIREP P-Frame.....	108
2.2.4.5.9.1.5.23	“Wind Shear Height” Field in PIREP P-Frame.....	109
2.2.4.5.9.1.5.24	“Braking Action” Field in PIREP P-Frame.....	110
2.2.4.5.9.1.5.25	“Runway Number” Field in PIREP P-Frame.....	110
2.2.4.5.9.1.5.26	“Runway Position” Field in PIREP P-Frame.....	111
2.2.4.5.9.1.5.27	“Layer ‘C’ Height” Field in PIREP P-Frame.....	111
2.2.4.5.9.1.5.28	“Layer ‘C’ Thickness” Field in PIREP P-Frame.....	112
2.2.4.5.9.1.5.29	“Layer ‘C’ Height Type” Field in PIREP P-Frame.....	112
2.2.4.5.9.1.5.30	“Layer ‘C’ Coverage” Field in PIREP P-Frame.....	112
2.2.4.5.9.1.5.31	“Flight Weather 1 Vicinity Direction” Field in PIREP P-Frame.....	112
2.2.4.5.9.1.5.32	“Flight Weather 2 Vicinity Direction” Field in PIREP P-Frame.....	113
2.2.4.5.9.1.5.33	“Turbulence Type” Field in PIREP P-Frame.....	113
2.2.4.5.9.2	EPISODIC Element Assembly.....	114
2.2.4.5.9.2.1	UAS/RPAS Contingency Message Scheduling.....	115
2.2.4.5.9.2.2	ADS-B Wx PIREP Message Scheduling.....	115
2.2.4.5.9.3	Payload Type Code “11” Message Assembly and Transmission Scheduling.....	115
2.2.4.5.10	Payload Element Subtype Definitions.....	115
2.2.4.5.10.1	ADS-B Wx AIREP: Payload Element Subtypes “1” through “3” (Optional).....	116
2.2.4.5.10.1.1	AIREP Wind and Turbulence (Payload Element Subtype Number = 1).....	117
2.2.4.5.10.1.1.1	“Subtype Number” Field in AIREP Payload Element Subtype Number = 1.....	117
2.2.4.5.10.1.1.2	“Wind Quality Indicator” Field in AIREP Payload Element Subtype Number = 1.....	117
2.2.4.5.10.1.1.3	“Wind Speed” Field in Payload Element Subtype Number = 1.....	118
2.2.4.5.10.1.1.4	“Wind Direction” Field in Payload Element Subtype Number = 1.....	119
2.2.4.5.10.1.1.5	“Mean EDR” Field in Payload Element Subtype Number = 1.....	120

2.2.4.5.10.1.1.6	“Peak EDR” Field in Payload Element Subtype Number = 1	120
2.2.4.5.10.1.1.7	“Peak EDR Offset” Field in Payload Element Subtype Number = 1	121
2.2.4.5.10.1.1.8	“Roll Angle” Field in Payload Element Subtype Number = 1	122
2.2.4.5.10.1.1.9	“Reserved” Subfield in Payload Element Subtype Number = 1	122
2.2.4.5.10.1.2	AIREP Water, Temperature, and ARV (Payload Element Subtype Number = 2)	122
2.2.4.5.10.1.2.1	“Subtype Number” Field in Payload Element Subtype Number = 2	123
2.2.4.5.10.1.2.2	“Icing Status” Field in Payload Element Subtype Number = 2	123
2.2.4.5.10.1.2.3	“Air Temperature Type” Field in Payload Element Subtype Number = 2	125
2.2.4.5.10.1.2.4	“Air Temperature” Field in Payload Element Subtype Number = 2	125
2.2.4.5.10.1.2.5	“Airspeed Type” Field in Payload Element Subtype Number = 2	126
2.2.4.5.10.1.2.6	“Airspeed” Field in Payload Element Subtype Number = 2	126
2.2.4.5.10.1.2.7	“Water Vapor” Field in Payload Element Subtype Number = 2	127
2.2.4.5.10.1.2.8	“Heading Type” Field in Payload Element Subtype Number = 2	128
2.2.4.5.10.1.2.9	“Heading” Field in Payload Element Subtype Number = 2	128
2.2.4.5.10.1.3	AIREP Aircraft State (Payload Element Subtype Number = 3)	129
2.2.4.5.10.1.3.1	“Subtype Number” Field in Payload Element Subtype Number = 3	129
2.2.4.5.10.1.3.2	“Aircraft Configuration” Field in Payload Element Subtype Number = 3	129
2.2.4.5.10.1.3.3	“Aircraft Type” Field in Payload Element Subtype Number = 3	130
2.2.4.5.10.1.3.4	“Gross Weight” Field in Payload Element Subtype Number = 3	131
2.2.4.5.10.1.3.5	“Wingspan” Field in Payload Element Subtype Number = 3	131
2.2.4.5.10.1.3.6	“Reserved” Subfield in Payload Element Subtype Number = 3	132
2.2.4.5.11	High Velocity and/or Altitude (HVA) STATE VECTOR Element (Optional)	133
2.2.4.5.11.1	“LATITUDE” and “LONGITUDE” Field Encoding	134
2.2.4.5.11.2	“HVA GEOMETRIC ALTITUDE (HAE)” Field Encoding	134
2.2.4.5.11.3	“Position Integrity Category” (PIC) Field Encoding	136
2.2.4.5.11.4	“HVA HORIZONTAL VELOCITY” Field	137
2.2.4.5.11.4.1	HVA North Velocity Form Encoding	137
2.2.4.5.11.4.2	HVA East Velocity Form Encoding	138
2.2.4.5.11.5	“HVA VERTICAL VELOCITY” Field Encoding	139
2.2.4.5.11.6	“HVA Rate” Subfield Encoding	140
2.2.5	Procedures for Processing of Time Data	141
2.2.5.1	UTC Coupled Condition	142
2.2.5.2	Non-UTC Coupled Condition	143
2.2.6	Procedures for ADS-B Message Transmission	144
2.2.6.1	Scheduling of ADS-B Message Types	144
2.2.6.1.1	Payload Selection Cycle	144
2.2.6.1.2	ADS-B Payload Type Allocation	145
2.2.6.1.2.1	Event-Driven ADS-B Payload Allocation	145
2.2.6.1.2.2	Selection of SV and HVA SV	147
2.2.6.1.3	Message Transmission Cycle	148
2.2.6.1.3.1	Payload Element Subtype Transmission Cycle for AIREP Capable Equipment	149
2.2.6.2	ADS-B Message Transmit Timing	150
2.2.6.2.1	The Message Start Opportunity (MSO) for Normal Rate Transmissions	150
2.2.6.2.1.1	MSO Selection for High Rate Transmissions	151
2.2.6.2.2	Relationship of the MSO to the Modulated Data	151
2.2.6.3	Report Assembly on Transmission of Ownship ADS-B Message	151
2.2.7	UAT Transmitter Message Data Characteristics	152
2.2.7.1	UAT Transmitter Input Requirements	152
2.2.7.2	Time Registration and Latency	154
2.2.7.2.1	Requirements When in Non-Precision Condition and UTC Coupled	155
2.2.7.2.2	Requirements When in Precision Condition and UTC Coupled	155

2.2.7.2.3	Requirements When Non-UTC Coupled	156
2.2.7.2.4	Total Latency of Position Measurements	156
2.2.7.2.5	Data Timeout	156
2.2.7.2.6	Requirements When Transmitting at a High Rate	157
2.2.8	Receiver Characteristics	157
2.2.8.1	Receiving Diversity	157
2.2.8.2	Receiver Performance	159
2.2.8.2.1	Receiver Sensitivity	159
2.2.8.2.1.1	Long ADS-B Message As Desired Signal	159
2.2.8.2.1.2	Basic ADS-B Message As Desired Signal.....	159
2.2.8.2.1.3	Ground Uplink Message As Desired Signal	159
2.2.8.2.2	Receiver Desired Signal Dynamic Range.....	160
2.2.8.2.3	Receiver Selectivity	160
2.2.8.2.4	Receiver Tolerance to Pulsed Interference	161
2.2.8.2.5	Receiver Tolerance to Overlapping ADS-B Messages (Self Interference)	162
2.2.8.2.6	Rate of False “Trigger”	162
2.2.8.2.7	Trigger Processing Rate.....	162
2.2.8.3	Receiver Message Processing.....	163
2.2.8.3.1	Criteria for Successful Message Reception	163
2.2.8.3.1.1	ADS-B Messages	163
2.2.8.3.1.2	Ground Uplink Messages.....	163
2.2.8.3.2	Receiver Discrimination Between ADS-B and Ground Uplink Message Types.....	164
2.2.8.3.3	Receiver Processing of ADS-B Synchronization “Trigger”	164
2.2.8.3.4	Receiver Processing of Ground Uplink Synchronization “Trigger”	165
2.2.8.3.5	Receiver Time of Message Receipt	165
2.2.9	Report Assembly Requirements.....	166
2.2.9.1	Report Assembly on Receipt of ADS-B Message.....	166
2.2.9.2	Report Assembly on Receipt of Ground Uplink Message.....	167
2.2.10	Receiver Subsystem Capacity and Throughput Requirements.....	167
2.2.10.1	Fundamental Principals of Report Assembly	167
2.2.10.2	Capacity for Successful Message Reception	168
2.2.10.3	Applicable Messages	168
2.2.10.4	Message Reception-to-Report Completion Time	169
2.2.11	Special Requirements for Transceiver Implementations.....	169
2.2.11.1	Transmit-Receive Turnaround Time	169
2.2.11.2	Receive-Transmit Turnaround Time	170
2.2.12	Mutual Suppression Pulses.....	170
2.2.13	Self Test and Monitors	170
2.2.13.1	Self Test.....	170
2.2.13.2	Broadcast Monitoring.....	171
2.2.13.3	Address Verification.....	171
2.2.13.4	Receiver Self-Test Capability.....	171
2.2.13.5	Failure Annunciation.....	171
2.2.13.5.1	ADS-B Device Failure and ADS-B Function Failure Annunciations	171
2.2.13.5.2	Reserved.....	171
2.2.13.5.3	Co-Located Transmitting and Receiving Device Failure Annunciation.....	172
2.2.14	Antenna System.....	172
2.2.14.1	Polarization.....	172
2.2.14.2	Antenna Voltage Standing Wave Ratio (VSWR).....	172
2.2.14.3	Requirements for Optional Passive Diplexer	172
2.2.14.3.1	Diplexer RF Requirements	173

2.2.14.3.1.1	The UAT Channel	173
2.2.14.3.1.2	The Transponder Channel	173
2.2.14.3.1.3	Channel to Channel Isolation	173
2.2.15	Interfaces	174
2.2.15.1	ADS-B Transmitting Subsystem Interfaces	174
2.2.15.1.1	ADS-B Transmitting Subsystem Input Interfaces	174
2.2.15.1.1.1	Discrete Input Interfaces.....	174
2.2.15.1.1.2	Digital Communication Input Interfaces	174
2.2.15.1.1.3	Processing Efficiency	174
2.2.15.1.1.4	SSR Reply Reception Interface	174
2.2.15.1.2	ADS-B Transmitting Subsystem Output Interfaces.....	175
2.2.15.1.2.1	Discrete Output Interfaces.....	175
2.2.15.1.2.2	Digital Communication Output Interfaces	175
2.2.15.2	UAT Receiving Subsystem Interfaces.....	175
2.2.15.2.1	UAT Receiving Subsystem Input Interfaces.....	175
2.2.15.2.1.1	Discrete Input Interfaces.....	175
2.2.15.2.1.2	Digital Communication Input Interfaces	175
2.2.15.2.1.3	Processing Efficiency	175
2.2.15.2.2	UAT Receiving Subsystem Output Interfaces.....	175
2.2.15.2.2.1	Discrete Output Interfaces.....	175
2.2.15.2.2.2	Digital Communication Output Interfaces	176
2.2.16	Power Interruption.....	176
2.2.17	Compatibility with Other Systems	176
2.2.17.1	EMI Compatibility.....	176
2.2.17.2	Compatibility with GNSS Receivers.....	176
2.2.17.3	Compatibility with Other Navigation Receivers and ATC Transponders.....	176
2.3	Equipment Performance – Environmental Conditions	176
2.3.1	Environmental Test Conditions	177
2.3.2	Detailed Environmental Test Procedures	183
2.3.2.1	Transmission Frequency (§2.2.2.1).....	183
2.3.2.2	Modulation Type (§2.2.2.3).....	183
2.3.2.3	Modulation Rate and Distortion (§2.2.2.2 and §2.2.2.4).....	183
2.3.2.4	Transmitter Power Output (§2.2.2.5).....	183
2.3.2.5	In-Band Transmission Spectrum (§2.2.2.6).....	183
2.3.2.6	Message Transmission Cycle (Transmitter Diversity) (§2.2.6.1.3).....	183
2.3.2.7	Message Start Opportunity (MSO) (§2.2.6.2.1)	183
2.3.2.8	Relationship of the MSO to the Modulated Data (§2.2.6.2.2).....	183
2.3.2.9	Report Assembly on Transmission of Ownship ADS-B Message (§2.2.6.3 and §2.2.7.1).....	183
2.3.2.10	Receiving Diversity (§2.2.8.1)	185
2.3.2.10.1	Full Diversity (§2.2.8.1.a and §2.2.8.1.b).....	185
2.3.2.10.2	Antenna Switching (§2.2.8.1.c)	185
2.3.2.11	Long ADS-B Message As Desired Signal (§2.2.8.2.1.1)	185
2.3.2.12	Basic ADS-B Message As Desired Signal (§2.2.8.2.1.2).....	185
2.3.2.13	Ground Uplink Message As Desired Signal (§2.2.8.2.1.3)	186
2.3.2.14	Receiver Desired Signal Dynamic Range (§2.2.8.2.2).....	186
2.3.2.15	Receiver Selectivity (§2.2.8.2.3)	186
2.3.2.16	Report Assembly on Receipt of ADS-B Message (§2.2.9.1)	186
2.3.2.17	Report Assembly on Receipt of Ground Uplink Message (§2.2.9.2).....	186
2.3.2.18	Address Verification (§2.2.13.3).....	186
2.3.2.19	Receiver Self Test Capability (§2.2.13.4)	186
2.3.2.20	Transmission Device Failure Annunciation (§2.2.13.5.1).....	186

2.3.2.21	Requirements for Optional Passive Diplexer (§2.2.14.3).....	186
2.3.2.22	Power Interruption (§2.2.16)	186
2.3.2.22.1	Power Interruption for ADS-B Transmitting Subsystems (§2.2.16).....	186
2.3.2.22.2	Power Interruption for ADS-B Receiving Subsystems (§2.2.16).....	186
2.4	Equipment Test Procedures.....	187
2.4.1	Definition of Standard Conditions of Test	187
2.4.1.1	Verification of Signal Levels (§2.2.1.1).....	188
2.4.1.2	Verification of Desired Signals (§2.2.1.2).....	188
2.4.1.3	Verification of Data Quantization (§2.2.1.3).....	189
2.4.1.4	Verification of Definition of Reserved (§2.2.1.4)	189
2.4.2	Verification of ADS-B Transmitter Characteristics (§2.2.2).....	189
2.4.2.1	Verification of Transmission Frequency (§2.2.2.1)	189
2.4.2.2	Verification of Modulation Rate (§2.2.2.2).....	192
2.4.2.3	Verification of Modulation Type (§2.2.2.3).....	192
2.4.2.4	Verification of Modulation Distortion (§2.2.2.4).....	193
2.4.2.5	Verification of Transmitter Power Output (§2.2.2.5).....	195
2.4.2.6	Verification of In Band Transmission Spectrum (§2.2.2.6)	198
2.4.2.7	Verification of Out-of-Band Emissions (§2.2.2.7).....	198
2.4.3	Verification of Broadcast Message Characteristics (§2.2.3)	199
2.4.3.1	Verification of ADS-B Message Format (§2.2.3.1)	199
2.4.3.1.1	Verification of Synchronization (§2.2.3.1.1).....	199
2.4.3.1.2	Verification of Payload (§2.2.3.1.2)	199
2.4.3.1.3	Verification of FEC Parity (§2.2.3.1.3)	199
2.4.3.1.3.1	Verification of Code Type (§2.2.3.1.3.1).....	199
2.4.3.1.3.2	Verification of Generation and Transmission Order of FEC Parity (§2.2.3.1.3.2).....	205
2.4.3.2	Verification of Ground Uplink Message Format (§2.2.3.2).....	205
2.4.3.2.1	Verification of Synchronization (§2.2.3.2.1).....	205
2.4.3.2.2	Verification of Payload (Before Interleaving and After De-interleaving) (§2.2.3.2.2)	205
2.4.3.2.2.1	Verification of UAT-Specific Header (§2.2.3.2.2.1)	205
2.4.3.2.2.1.1	Verification of “GROUND STATION LATITUDE” Field Encoding (§2.2.3.2.2.1.1)	205
2.4.3.2.2.1.2	Verification of “GROUND STATION LONGITUDE” Field Encoding (§2.2.3.2.2.1.2)	205
2.4.3.2.2.1.3	Verification of “POSITION VALID” Field Encoding (§2.2.3.2.2.1.3)	205
2.4.3.2.2.1.4	Verification of “UTC Coupled” Field Encoding (§2.2.3.2.2.1.4)	205
2.4.3.2.2.1.5	Verification of “Reserved” Subfield Encoding (§2.2.3.2.2.1.5).....	205
2.4.3.2.2.1.6	Verification of “APPLICATION DATA VALID” Field Encoding (§2.2.3.2.2.1.6) ...	205
2.4.3.2.2.1.7	Verification of “SLOT ID” Field Encoding (§2.2.3.2.2.1.7).....	206
2.4.3.2.2.1.8	Verification of “TIS-B SITE ID” Field Encoding (§2.2.3.2.2.1.8)	206
2.4.3.2.2.1.9	Verification of “Reserved” Subfield Encoding (§2.2.3.2.2.1.9).....	206
2.4.3.2.2.2	Verification of Ground Uplink Application Data (§2.2.3.2.2.2).....	206
2.4.3.2.2.2.1	Verification of “Length” Subfield Encoding (§2.2.3.2.2.2.1)	206
2.4.3.2.2.2.2	Verification of “Reserved” Subfield Encoding (§2.2.3.2.2.2.2).....	206
2.4.3.2.2.2.3	Verification of “Frame Type” Subfield Encoding (§2.2.3.2.2.2.3)	206
2.4.3.2.2.2.4	Verification of Frame Data Content (§2.2.3.2.2.2.4).....	206
2.4.3.2.2.2.4.1	Verification of FIS-B APDU (§2.2.3.2.2.2.4.1).....	206
2.4.3.2.2.2.4.2	Verification of FIS-B CRL (§2.2.3.2.2.2.4.2).....	206
2.4.3.2.2.2.4.3	Verification of Traffic Uplink Management Message (§2.2.3.2.2.2.4.3).....	206
2.4.3.2.3	Verification of FEC Parity (Before Interleaving and After De-interleaving) (§2.2.3.2.3).....	206
2.4.3.2.3.1	Verification of Code Type (§2.2.3.2.3.1).....	206
2.4.3.2.3.2	Verification of Generation and Transmission Order of FEC Parity (§2.2.3.2.3.2).....	207

2.4.3.2.4	Verification of Interleaved Payload and FEC Parity (§2.2.3.2.4)	207
2.4.4	Verification of The ADS-B Message Payload (§2.2.4)	207
2.4.4.1	Verification of Payload Type (§2.2.4.1)	207
2.4.4.2	Verification of Payload Elements (§2.2.4.2)	207
2.4.4.2.1	Verification of Payload Element Subtypes (§2.2.4.2.1)	207
2.4.4.2.1.1	Verification of “Payload Element Subtype Number” Field in Payload Element Subtypes (§2.2.4.2.1.1)	207
2.4.4.3	Verification of ADS-B Payload Composition by Payload Type Code (§2.2.4.3)	207
2.4.4.4	Verification of Payload Transmission Order (§2.2.4.4)	207
2.4.4.5	Verification of Payload Contents (§2.2.4.5)	207
2.4.4.5.1	Verification of HEADER Element (§2.2.4.5.1)	207
2.4.4.5.1.1	Verification of “PAYLOAD TYPE CODE” Field Encoding (§2.2.4.5.1.1)	207
2.4.4.5.1.2	Verification of “ADDRESS QUALIFIER” Field Encoding (§2.2.4.5.1.2)	208
2.4.4.5.1.3	Verification of “ADDRESS” Field Encoding (§2.2.4.5.1.3)	209
2.4.4.5.1.3.1	Verification of ICAO Aircraft Address of Transmitting Aircraft (§2.2.4.5.1.3.1)	209
2.4.4.5.1.3.2	Verification of Self-Assigned Temporary Aircraft Address of Transmitting Aircraft (§2.2.4.5.1.3.2)	210
2.4.4.5.1.3.3	Verification of ICAO Aircraft Address of TIS-B or ADS-R/ADS-SLR Target Aircraft (§2.2.4.5.1.3.3)	212
2.4.4.5.1.3.4	Verification of TIS-B Track File Identifier (§2.2.4.5.1.3.4)	212
2.4.4.5.1.3.5	Verification of Surface Vehicle Address (§2.2.4.5.1.3.5)	212
2.4.4.5.1.3.6	Verification of Fixed ADS-D Beacon Address (§2.2.4.5.1.3.6)	212
2.4.4.5.1.3.7	Verification of ADS-R/ADS-SLR Target with Non-ICAO Aircraft Address (§2.2.4.5.1.3.7)	212
2.4.4.5.2	Verification of STATE VECTOR Element (§2.2.4.5.2)	212
2.4.4.5.2.1	Verification of “LATITUDE” and “LONGITUDE” Field Encoding (§2.2.4.5.2.1)	213
2.4.4.5.2.1.1	Verification of Latitude and Longitude for $NAC_P < 10$ (§2.2.4.5.2.1 and §2.2.7.2.1)	214
2.4.4.5.2.1.2	Verification of Latitude and Longitude for $NAC_P \geq 10$ (§2.2.4.5.2.1 and §2.2.7.2.2)	219
2.4.4.5.2.2	Verification of “ALTITUDE TYPE” Flag Encoding (§2.2.4.5.2.2)	219
2.4.4.5.2.3	Verification of “ALTITUDE” Field Encoding (§2.2.4.5.2.3)	220
2.4.4.5.2.4	Verification of “Navigation Integrity Category” (NIC) Field Encoding (§2.2.4.5.2.4)	223
2.4.4.5.2.4.1	Verification of “Navigation Integrity Category” (NIC) Field Encoding During no Fault Detection and Exclusion Condition (§2.2.4.5.2.4.1)	223
2.4.4.5.2.4.2	Verification of “Navigation Integrity Category” and “Position Integrity Category” Field Encoding During Fault Detection and Exclusion Condition (§2.2.4.5.2.4.2)	224
2.4.4.5.2.5	Verification of “Air/Ground Velocity State” Field Encoding (§2.2.4.5.2.5)	226
2.4.4.5.2.5.1	Verification of Determination of Vertical Status (§2.2.4.5.2.5.1)	227
2.4.4.5.2.5.2	Verification of the Validation of Vertical Status (§2.2.4.5.2.5.2)	228
2.4.4.5.2.5.3	Verification of Vertical Status Determination Algorithm (§2.2.4.5.2.5.3)	231
2.4.4.5.2.5.3.1	Verification of Vertical Status Determination Algorithm Definitions (§2.2.4.5.2.5.3.1)	232
2.4.4.5.2.5.3.2	Verification of Vertical Status Determination Algorithm Applicability (§2.2.4.5.2.5.3.2)	232
2.4.4.5.2.5.3.2.1	Verification of Fixed-Wing VSDA Definitions (§2.2.4.5.2.5.3.2.1)	232
2.4.4.5.2.5.3.2.2	Verification of Fixed-Wing VSDA Requirements Structure (§2.2.4.5.2.5.3.2.2)	232
2.4.4.5.2.5.3.2.3	Verification of Fixed-Wing VSDA Start-up and Validity Requirements (§2.2.4.5.2.5.3.2.3)	232
2.4.4.5.2.5.3.2.4	Verification of Fixed-Wing VSDA performance requirements (§2.2.4.5.2.5.3.2.4)	234
2.4.4.5.2.6	Verification of “HORIZONTAL VELOCITY” Subfields (§2.2.4.5.2.6)	235
2.4.4.5.2.6.1	Verification of Encoding as “North Velocity” Form (§2.2.4.5.2.6.1)	235
2.4.4.5.2.6.1.1	Verification of the “North/South Velocity” Sign Flag (§2.2.4.5.2.6.1.a)	235

2.4.4.5.2.6.1.2	Verification of the “North Velocity Magnitude” Subfield - Subsonic (§2.2.4.5.2.6.1.b)	236
2.4.4.5.2.6.1.3	Verification of the “North Velocity Magnitude” Subfield - Supersonic (§2.2.4.5.2.6.1.b)	239
2.4.4.5.2.6.2	Verification of Encoding as “Ground Speed” Form (§2.2.4.5.2.6.2)	242
2.4.4.5.2.6.2.1	Verification of “Reserved” Subfield (§2.2.4.5.2.6.2.a)	242
2.4.4.5.2.6.2.2	Verification of the Encoding of the Ground Speed Magnitude – Subsonic (§2.2.4.5.2.6.2.b)	242
2.4.4.5.2.6.3	Verification of Encoding as “East Velocity” Form (§2.2.4.5.2.6.3).....	244
2.4.4.5.2.6.3.1	Verification of the “East/West Velocity” Sign Flag (§2.2.4.5.2.6.3.a).....	244
2.4.4.5.2.6.3.2	Verification of the “East Velocity Magnitude” Subfield - Subsonic (§2.2.4.5.2.6.3.b) 246	
2.4.4.5.2.6.3.3	Verification of the “East Velocity Magnitude” Subfield - Supersonic (§2.2.4.5.2.6.3.b)	248
2.4.4.5.2.6.4	Verification of Encoding as “Track Angle/Heading” Form and "Track Angle/Heading Type" Subfield (§2.2.4.5.2.6.4)	251
2.4.4.5.2.7	Verification of “VERTICAL VELOCITY OR AIRCRAFT/VEHICLE SIZE” Field (§2.2.4.5.2.7)	253
2.4.4.5.2.7.1	Verification of Encoding as Vertical Velocity Form (§2.2.4.5.2.7.1).....	253
2.4.4.5.2.7.1.1	Verification of “Vertical Velocity Source” (VV Src) Subfield Encoding (§2.2.4.5.2.7.1.1)	253
2.4.4.5.2.7.1.2	Verification of “Vertical Rate Sign” (VV Sign) Subfield Encoding (§2.2.4.5.2.7.1.2) 254	
2.4.4.5.2.7.1.3	Verification of “Vertical Rate” Subfield Encoding (§2.2.4.5.2.7.1.3).....	255
2.4.4.5.2.7.2	Verification of Encoding as Aircraft/Vehicle Size Form (§2.2.4.5.2.7.2).....	257
2.4.4.5.2.8	Verification of “UTC” Field Encoding (§2.2.4.5.2.8)	258
2.4.4.5.2.9	Verification of Uplink Feedback Encoding (§2.2.4.5.2.9).....	259
2.4.4.5.2.10	Verification of Reserved Byte 18, Payload Type Zero (§2.2.4.5.2.10).....	260
2.4.4.5.3	Verification of STATE VECTOR Element (For TIS-B or ADS-R/ADS-SLR) (§2.2.4.5.3) 261	
2.4.4.5.3.1	Verification of “TIS-B SITE ID” Field Encoding (§2.2.4.5.3.1).....	261
2.4.4.5.3.2	Verification of Encoding for All Other Fields (§2.2.4.5.3.2)	261
2.4.4.5.4	Verification of MODE STATUS Element (§2.2.4.5.4)	261
2.4.4.5.4.1	Verification of “EMITTER CATEGORY” Field (§2.2.4.5.4.1)	261
2.4.4.5.4.2	Verification of “CALL SIGN/FLIGHT PLAN ID” Field (§2.2.4.5.4.2).....	262
2.4.4.5.4.3	Verification of Compressed Format Encoding for “EMITTER CATEGORY” and “CALL SIGN/FLIGHT PLAN ID” (§2.2.4.5.4.3)	262
2.4.4.5.4.3.1	Verification of Bytes #18 and #19 (§2.2.4.5.4.3.1).....	262
2.4.4.5.4.3.2	Verification of Bytes #20 and #21 (§2.2.4.5.4.3.2).....	263
2.4.4.5.4.3.3	Verification of Bytes #22 and 23 (§2.2.4.5.4.3.3).....	264
2.4.4.5.4.3.4	Verification of Unavailable “CALL SIGN/FLIGHT PLAN ID” Field (§2.2.4.5.4.2)	266
2.4.4.5.4.3.5	Verification of Call Sign Encoding (§2.2.4.5.4.2).....	267
2.4.4.5.4.3.6	Verification of “CALL SIGN” Field when using a Temporary Aircraft Address (§2.2.4.5.4.2)	268
2.4.4.5.4.4	Verification of “EMERGENCY/PRIORITY STATUS” Field Encoding (§2.2.4.5.4.4).....	268
2.4.4.5.4.5	Verification of “UAT MOPS VERSION” Field Encoding (§2.2.4.5.4.5).....	272
2.4.4.5.4.6	Verification of “SIL” Field Encoding (§2.2.4.5.4.6)	272
2.4.4.5.4.7	Verification of “TRANSMIT MSO” Field Encoding (§2.2.4.5.4.7)	273
2.4.4.5.4.8	Verification of System Design Assurance (SDA) Field Encoding (§2.2.4.5.4.8)	274
2.4.4.5.4.9	Verification of “Navigation Accuracy Category for Position” (NAC _P) Field Encoding (§2.2.4.5.4.9)	275

2.4.4.5.4.10	Verification of “Navigation Accuracy Category for Velocity” (NAC _V) Field Encoding (§2.2.4.5.4.10)	276
2.4.4.5.4.10.1	Verification of the “Navigation Accuracy Category for Velocity” Field when Supporting NAC _V = 0 – 4	276
2.4.4.5.4.10.2	Verification of “Navigation Accuracy Category for Velocity” Field when Supporting NAC _V = 0 – 3	276
2.4.4.5.4.10.3	Verification of “Navigation Accuracy Category for Velocity” Field when Supporting NAC _V = 0 – 2	277
2.4.4.5.4.10.4	Verification of “Navigation Accuracy Category for Velocity” Field when Supporting NAC _V = 0 – 1	277
2.4.4.5.4.11	“Reserved” Subfield (§2.2.4.5.4.11)	277
2.4.4.5.4.12	Verification of “CAPABILITY CODES” Field Encoding (§2.2.4.5.4.12)	278
2.4.4.5.4.12.1	Verification of “UAT IN Capability” Subfield (§2.2.4.5.4.12.1)	278
2.4.4.5.4.12.2	Verification of “1090ES IN Capability” Subfield Encoding (§2.2.4.5.4.12.2)	278
2.4.4.5.4.12.3	Verification of “CA Operational” Subfield (§2.2.4.5.4.12.3)	279
2.4.4.5.4.13	Verification of “OPERATIONAL MODES” Field Encoding (§2.2.4.5.4.13)	280
2.4.4.5.4.13.1	Verification of “CA Resolution Advisory Active” Flag (§2.2.4.5.4.13.1)	280
2.4.4.5.4.13.2	Verification of “IDENT Switch Active” Flag (§2.2.4.5.4.13.2)	281
2.4.4.5.4.13.3	Verification of “Reserved” Subfield (§2.2.4.5.4.13.3)	281
2.4.4.5.4.14	Verification of “Call Sign Identification” (CSID) Flag (§2.2.4.5.4.14)	282
2.4.4.5.4.15	Reserved	282
2.4.4.5.4.16	Verification of “SIL Supplement” (SIL _{SUPP}) Flag (§2.2.4.5.4.16)	283
2.4.4.5.4.17	Verification of “Geometric Vertical Accuracy” (GVA) Field (§2.2.4.5.4.17)	283
2.4.4.5.4.18	Verification of “Single Antenna” (SA) Subfield (§2.2.4.5.4.18)	284
2.4.4.5.4.19	Verification of “NIC Supplement” (NIC _{SUPP}) Flag (§2.2.4.5.4.19)	284
2.4.4.5.4.20	Verification of “Manned/Unmanned Operation” (M/U) Field Encoding (§2.2.4.5.4.20)	285
2.4.4.5.4.21	Verification of “Reserved” Subfield (§2.2.4.5.4.21)	285
2.4.4.5.5	Verification of AUXILIARY STATE VECTOR Element (§2.2.4.5.5)	285
2.4.4.5.5.1	Verification of “SECONDARY ALTITUDE” Field Encoding (§2.2.4.5.5.1)	286
2.4.4.5.5.2	Verification of “Reserved” Field (§2.2.4.5.5.2)	288
2.4.4.5.6	Verification of TARGET STATE Element (Payload Type Code “3”) (§2.2.4.5.6)	288
2.4.4.5.6.1	Verification of “SELECTED ALTITUDE TYPE” (SAT) Flag Encoding (§2.2.4.5.6.1)	289
2.4.4.5.6.2	Verification of “Selected Altitude” Field Encoding (§2.2.4.5.6.2)	289
2.4.4.5.6.3	Verification of “Barometric Pressure Setting” (Minus 800 millibars) Field Encoding (§2.2.4.5.6.3)	290
2.4.4.5.6.4	Verification of “Selected Heading” Field Encoding (§2.2.4.5.6.4)	291
2.4.4.5.6.5	Verification of “Status of MCP/FCU Mode Bits” (ST) Flag Encoding (§2.2.4.5.6.5)	292
2.4.4.5.6.6	Test procedures appropriate to verify §2.2.4.5.6.5 requirement are provided in §2.4.4.5.6.6 through §2.4.4.5.6.10. Verification of “Mode Indicators: Autopilot Engaged” (AP) Flag Encoding (§2.2.4.5.6.6)	292
2.4.4.5.6.7	Verification of “Mode Indicators: VNAV Mode Engaged” (VNAV) Flag Encoding (§2.2.4.5.6.7)	293
2.4.4.5.6.8	Verification of “Mode Indicators: Altitude Hold Mode” (ALT) Flag Encoding (§2.2.4.5.6.8)	294
2.4.4.5.6.9	Verification of “Mode Indicators: Approach Mode” (APP) Flag Encoding (§2.2.4.5.6.9)	294
2.4.4.5.6.10	Verification of “Mode Indicators: LNAV Mode Engaged” (LNAV) Flag Encoding (§2.2.4.5.6.10)	295
2.4.4.5.6.11	Verification of Reserved in Byte 34 (§2.2.4.5.6.11)	296
2.4.4.5.7	Verification of TARGET STATE Element (Payload Type Code “6”) (§2.2.4.5.7)	296

2.4.4.5.8	Reserved.....	296
2.4.4.5.9	Verification of EPISODIC Element (Payload Type Code “11”) (§2.2.4.5.9)	296
2.4.4.5.9.1	Verification of Payload Frames (§2.2.4.5.9.1).....	296
2.4.4.5.9.1.1	Verification of “Payload Frame Type Code” Field Encoding (§2.2.4.5.9.1.1)	296
2.4.4.5.9.1.2	Verification of “Payload Frame Type Length” Field Encoding (§2.2.4.5.9.1.2)	297
2.4.4.5.9.1.3	Verification of “Payload Frame Data” (§2.2.4.5.9.1.3).....	297
2.4.4.5.9.1.4	Verification of UAS/RPAS Contingency P-Frame (PFTC “0”) (§2.2.4.5.9.1.4).....	297
2.4.4.5.9.1.4.1	Verification of “Contingency Plan” Field (§2.2.4.5.9.1.4.1)	297
2.4.4.5.9.1.4.2	Verification of “UAS/RPAS TCP Altitude, Current” Field (§2.2.4.5.9.1.4.2)	298
2.4.4.5.9.1.4.3	Verification of “UAS/RPAS TCP Latitude, Current” Field (§2.2.4.5.9.1.4.3)	299
2.4.4.5.9.1.4.4	Verification of “UAS/RPAS TCP Longitude, Current” Field (§2.2.4.5.9.1.4.4).....	299
2.4.4.5.9.1.4.5	Verification of “UAS/RPAS TCP Altitude, Next” Field (§2.2.4.5.9.1.4.5).....	299
2.4.4.5.9.1.4.6	Verification of “UAS/RPAS TCP Latitude, Next” Field (§2.2.4.5.9.1.4.6)	299
2.4.4.5.9.1.4.7	Verification of “UAS/RPAS TCP Longitude, Next” Field (§2.2.4.5.9.1.4.7)	300
2.4.4.5.9.1.5	Verification of PIREP P-Frame (PFTC “1”) (§2.2.4.5.9.1.5).....	300
2.4.4.5.9.1.5.1	Verification of “PIREP Time” Field in PIREP P-Frame (§2.2.4.5.9.1.5.1).....	301
2.4.4.5.9.1.5.2	Verification of “Flight Visibility” Field in PIREP P-Frame (§2.2.4.5.9.1.5.2).....	301
2.4.4.5.9.1.5.3	Verification of “Flight Weather 1” Field in PIREP P-Frame (§2.2.4.5.9.1.5.3)	302
2.4.4.5.9.1.5.4	Verification of “Flight Weather 2” Field in PIREP P-Frame (§2.2.4.5.9.1.5.4)	303
2.4.4.5.9.1.5.5	Verification of “Flight Weather 3” Field in PIREP P-Frame (§2.2.4.5.9.1.5.5)	303
2.4.4.5.9.1.5.6	Verification of “Layer 'A' Height” Field in PIREP P-Frame (§2.2.4.5.9.1.5.6).....	303
2.4.4.5.9.1.5.7	Verification of “Layer 'A' Thickness” Field in PIREP P-Frame (§2.2.4.5.9.1.5.7)	304
2.4.4.5.9.1.5.8	Verification of “Layer 'A' Height Type” Field in PIREP P-Frame (§2.2.4.5.9.1.5.8)	305
2.4.4.5.9.1.5.9	Verification of “Layer 'A' Coverage” Field in PIREP P-Frame (§2.2.4.5.9.1.5.9)	305
2.4.4.5.9.1.5.10	Verification of “PIREP Air Temperature” Field in PIREP P-Frame (§2.2.4.5.9.1.5.10)	306
2.4.4.5.9.1.5.11	Verification of “PIREP Air Temperature Type” Field in PIREP P-Frame (§2.2.4.5.9.1.5.11)	306
2.4.4.5.9.1.5.12	Verification of “PIREP Wind Direction” Field in PIREP P-Frame (§2.2.4.5.9.1.5.12)	307
2.4.4.5.9.1.5.13	Verification of “PIREP Wind Speed” Field in PIREP P-Frame (§2.2.4.5.9.1.5.13).....	307
2.4.4.5.9.1.5.14	Verification of “Turbulence Duration” Field in PIREP P-Frame (§2.2.4.5.9.1.5.14)	308
2.4.4.5.9.1.5.15	Verification of “Turbulence Intensity” Field in PIREP P-Frame (§2.2.4.5.9.1.5.15)	309
2.4.4.5.9.1.5.16	Verification of “Turbulence Location” Field in PIREP P-Frame (§2.2.4.5.9.1.5.16)	309
2.4.4.5.9.1.5.17	Verification of “Layer 'B' Height” Field in PIREP P-Frame (§2.2.4.5.9.1.5.17).....	310
2.4.4.5.9.1.5.18	Verification of “Layer 'B' Thickness” Field in PIREP P-Frame (§2.2.4.5.9.1.5.18).....	310
2.4.4.5.9.1.5.19	Verification of “Layer 'B' Height Type” Field in PIREP P-Frame (§2.2.4.5.9.1.5.19)	311
2.4.4.5.9.1.5.20	Verification of “Layer 'B' Coverage” Field in PIREP P-Frame (§2.2.4.5.9.1.5.20)	312
2.4.4.5.9.1.5.21	Verification of “PIREP Icing” Field in PIREP P-Frame (§2.2.4.5.9.1.5.21)	312
2.4.4.5.9.1.5.22	Verification of “Airspeed Change” Field in PIREP P-Frame (§2.2.4.5.9.1.5.22).....	313
2.4.4.5.9.1.5.23	Verification of “Wind Shear Height” Field in PIREP P-Frame (§2.2.4.5.9.1.5.23)	313
2.4.4.5.9.1.5.24	Verification of “Braking Action” Field in PIREP P-Frame (§2.2.4.5.9.1.5.24)	314
2.4.4.5.9.1.5.25	Verification of “Runway Number” Field in PIREP P-Frame (§2.2.4.5.9.1.5.25).....	314
2.4.4.5.9.1.5.26	Verification of “Runway Position” Field in PIREP P-Frame (§2.2.4.5.9.1.5.26).....	315
2.4.4.5.9.1.5.27	Verification of “Layer 'C' Height” Field in PIREP P-Frame (§2.2.4.5.9.1.5.27).....	316
2.4.4.5.9.1.5.28	Verification of “Layer 'C' Thickness” Field in PIREP P-Frame (§2.2.4.5.9.1.5.28).....	316

2.4.4.5.9.1.5.29	Verification of “Layer 'C' Height Type” Field in PIREP P-Frame (§2.2.4.5.9.1.5.29)	317
2.4.4.5.9.1.5.30	Verification of “Layer 'C' Coverage” Field in PIREP P-Frame (§2.2.4.5.9.1.5.30)	317
2.4.4.5.9.1.5.31	Verification of "Flight Weather 1 Vicinity Direction" Field in PIREP P-Frame (§2.2.4.5.9.1.5.31)	318
2.4.4.5.9.1.5.32	Verification of "Flight Weather 2 Vicinity Direction" Field in PIREP P-Frame (§2.2.4.5.9.1.5.32)	319
2.4.4.5.9.1.5.33	Verification of "Turbulence Type" Field in PIREP P-Frame (§2.2.4.5.9.1.5.33)	319
2.4.4.5.9.2	Verification of EPISODIC Element Assembly (§2.2.4.5.9.2)	320
2.4.4.5.10	Verification of Payload Element Subtype Definitions (§2.2.4.5.10)	322
2.4.4.5.10.1	Verification of ADS-B Wx AIREP: Payload Element Subtypes “1” through “3” (§2.2.4.5.10.1)	322
2.4.4.5.10.1.1	Verification of AIREP Wind and Turbulence (Payload Element Subtype Number = 1) (§2.2.4.5.10.1.1)	322
2.4.4.5.10.1.1.1	Verification of “Subtype Number” Field in Payload Element Subtype 1 (AIREP Wind and Turbulence) (§2.2.4.5.10.1.1.1)	323
2.4.4.5.10.1.1.2	Verification of “Wind Quality Indicator” Field in Payload Element Subtype 1 (AIREP Wind and Turbulence) (§2.2.4.5.10.1.1.2)	323
2.4.4.5.10.1.1.3	Verification of “Wind Speed” Field in Payload Element Subtype 1 (AIREP Wind and Turbulence) (§2.2.4.5.10.1.1.3)	324
2.4.4.5.10.1.1.4	Verification of “Wind Direction” Field in Payload Element Subtype 1 (AIREP Wind and Turbulence) (§2.2.4.5.10.1.1.4)	325
2.4.4.5.10.1.1.5	Verification of “Mean EDR” Field in Payload Element Subtype 1 (AIREP Wind and Turbulence) (§2.2.4.5.10.1.1.5)	326
2.4.4.5.10.1.1.6	Verification of “Peak EDR” Field in Payload Element Subtype 1 (AIREP Wind and Turbulence) (§2.2.4.5.10.1.1.6)	327
2.4.4.5.10.1.1.7	Verification of “Peak EDR Offset” Field in Payload Element Subtype 1 (AIREP Wind and Turbulence) (§2.2.4.5.10.1.1.7)	328
2.4.4.5.10.1.1.8	Verification of “Roll Angle” Field in Payload Element Subtype 1 (AIREP Wind and Turbulence) (§2.2.4.5.10.1.1.8)	329
2.4.4.5.10.1.1.9	Verification of “Reserved” Field in Payload Element Subtype 1 (AIREP Wind and Turbulence) (§2.2.4.5.10.1.1.9)	331
2.4.4.5.10.1.2	Verification of AIREP Water, Temperature, and ARV (Payload Element Subtype Number = 2) (§2.2.4.5.10.1.2)	331
2.4.4.5.10.1.2.1	Verification of “Subtype Number” Field in Payload Element Subtype 2 (AIREP Water, Temperature, and ARV) (§2.2.4.5.10.1.2.1)	332
2.4.4.5.10.1.2.2	Verification of “Icing Status” Field in Payload Element Subtype 2 (AIREP Water, Temperature, and ARV) (§2.2.4.5.10.1.2.2)	332
2.4.4.5.10.1.2.3	Verification of “Air Temperature Type” Field in Payload Element Subtype 2 (AIREP Water, Temperature, and ARV) (§2.2.4.5.10.1.2.3)	333
2.4.4.5.10.1.2.4	Verification of “Air Temperature” Field in Payload Element Subtype 2 (AIREP Water, Temperature, and ARV) (§2.2.4.5.10.1.2.4)	335
2.4.4.5.10.1.2.5	Verification of “Airspeed Type” Field in Payload Element Subtype 2 (AIREP Water, Temperature, and ARV) (§2.2.4.5.10.1.2.5)	337
2.4.4.5.10.1.2.6	Verification of “Airspeed” Field in Payload Element Subtype 2 (AIREP Water, Temperature, and ARV) (§2.2.4.5.10.1.2.6)	339
2.4.4.5.10.1.2.7	Verification of “Water Vapor” Field in Field in Payload Element Subtype 2 (AIREP Water, Temperature, and ARV) (§2.2.4.5.10.1.2.7)	341
2.4.4.5.10.1.2.8	Verification of “Heading Type” Field in Payload Element Subtype 2 (AIREP Water, Temperature, and ARV) (§2.2.4.5.10.1.2.8)	342

2.4.4.5.10.1.2.9	Verification of “Heading” Field in Payload Element Subtype 2 (AIREP Water, Temperature, and ARV) (§2.2.4.5.10.1.2.9).....	344
2.4.4.5.10.1.3	Verification of AIREP Aircraft State (Payload Element Subtype Number = 3) (§2.2.4.5.10.1.3)	346
2.4.4.5.10.1.3.1	Verification of “Subtype Number” Field in Payload Element Subtype 3 (AIREP Aircraft State) (§2.2.4.5.10.1.3.1)	347
2.4.4.5.10.1.3.2	Verification of “Aircraft Configuration” Field in Payload Element Subtype 3 (AIREP Aircraft State) (§2.2.4.5.10.1.3.2)	347
2.4.4.5.10.1.3.3	Verification of “Aircraft Type” Field in ADS-B Wx Payload Element Subtype 3 (AIREP Aircraft State) (§2.2.4.5.10.1.3.3).....	349
2.4.4.5.10.1.3.4	Verification of “Gross Weight” Field in ADS-B Wx Payload Element Subtype 3 (AIREP Aircraft State) (§2.2.4.5.10.1.3.4).....	351
2.4.4.5.10.1.3.5	Verification of “Wingspan” Field in ADS-B Wx Payload Element Subtype 3 (AIREP Aircraft State) (§2.2.4.5.10.1.3.5)	353
2.4.4.5.10.1.3.6	Verification of “Reserved” Field in ADS-B Wx Payload Element Subtype 3 (AIREP Aircraft State) (§2.2.4.5.10.1.3.6)	355
2.4.4.5.11	Verification of HVA STATE VECTOR Element (§2.2.4.5.11).....	355
2.4.4.5.11.1	Verification of “LATITUDE” and “LONGITUDE” Field Encoding (§2.2.4.5.11.1).....	356
2.4.4.5.11.1.1	Verification of Latitude and Longitude for Normal Rate and $NAC_P < 10$ (§2.2.4.5.11.1 and §2.2.7.2.1).....	356
2.4.4.5.11.2	Verification of “HVA GEOMETRIC ALTITUDE (HAE)” Field Encoding (§2.2.4.5.11.2)	359
2.4.4.5.11.3	Verification of “Position Integrity Category” (PIC) Field Encoding (§2.2.4.5.11.3).....	360
2.4.4.5.11.4	Verification of “HVA HORIZONTAL VELOCITY” Field (§2.2.4.5.11.4).....	361
2.4.4.5.11.4.1	Verification of “HVA North Velocity” Subfield Encoding (§2.2.4.5.11.4.1).....	361
2.4.4.5.11.4.1.1	Verification of “North/South Velocity Sign” Flag (§2.2.4.5.11.4.1.a)	361
2.4.4.5.11.4.1.2	Verification of the “HVA North Velocity Magnitude” Subfield (§2.2.4.5.11.4.1.b) 362	362
2.4.4.5.11.4.2	Verification of “HVA East Velocity” Subfield Encoding (§2.2.4.5.11.4.2)	363
2.4.4.5.11.4.2.1	Verification of the “East/West Velocity Sign” Flag (§2.2.4.5.11.4.2.a).....	363
2.4.4.5.11.4.2.2	Verification of the “East/West Velocity Magnitude” Subfield (§2.2.4.5.11.4.2.b).....	364
2.4.4.5.11.5	Verification of “HVA VERTICAL VELOCITY” Field (§2.2.4.5.11.5).....	365
2.4.4.5.11.5.1.1	Verification of “Vertical Velocity Sign” (VV Sign) Flag Encoding (§2.2.4.5.11.5.a) 365	365
2.4.4.5.11.5.2	Verification of “Vertical Rate” Subfield Encoding (§2.2.4.5.11.5.1.b)	366
2.4.4.5.11.6	Verification of “HVA Rate” Subfield Encoding (§2.2.4.5.11.6).....	368
2.4.5	Verification of Procedures for Processing of Time Data (§2.2.5).....	369
2.4.5.1	Verification of UTC Coupled Condition (§2.2.5.a, §2.2.5.b, §2.2.5.c).....	369
2.4.5.2	Verification of Non-UTC Coupled Condition (§2.2.5.2)	370
2.4.6	Verification of Procedures for ADS-B Message Transmission (§2.2.6)	372
2.4.6.1	Verification of Scheduling of ADS-B Message Types (§2.2.6.1).....	372
2.4.6.1.1	Verification of Payload Selection Cycle (§2.2.6.1.1)	372
2.4.6.1.2	Verification of ADS-B Payload Type Allocation (§2.2.6.1.2)	373
2.4.6.1.2.1	Verification of Event-Driven ADS-B Payload Allocation (§2.2.6.1.2.1).....	373
2.4.6.1.2.2	Verification of Selection of SV and HVA SV (§2.2.6.1.2.2)	373
2.4.6.1.3	Verification of Message Transmission Cycle (§2.2.6.1.3)	374
2.4.6.1.3.1	Verification of Payload Element Subtype Transmission Cycle for AIREP Capable Equipment (§2.2.6.1.3.1).....	379
2.4.6.2	Verification of ADS-B Message Transmit Timing (§2.2.6.2).....	381
2.4.6.2.1	Verification of The Message Start Opportunity (MSO) (§2.2.6.2.1).....	382
2.4.6.2.1.1	Verification of MSO Selection for High Rate Transmissions (§2.2.6.2.1.1).....	385

2.4.6.2.2	Verification of Relationship of the MSO to the Modulated Data (§2.2.6.2.2)	389
2.4.6.3	Verification of Report Assembly on Transmission of Ownship ADS-B Message (§2.2.6.3)	391
2.4.7	Verification of UAT Transmitter Message Data Characteristics (§2.2.7)	391
2.4.7.1	Verification of UAT Transmitter Input Requirements (§2.2.7.1)	391
2.4.7.2	Verification of Time Registration and Latency (§2.2.7.2)	394
2.4.7.2.1	Verification of Requirements When in Non-Precision Condition and UTC Coupled (§2.2.7.2.1)	394
2.4.7.2.1.1	Verification of Latitude and Longitude Requirements When in Non-Precision Condition and UTC Coupled (§2.2.7.2.1.a, §2.2.4.5.2.1, §2.2.4.5.2.6)	394
2.4.7.2.1.2	Verification of Requirements for Other ADS-B Message Fields When in Non-Precision Condition and UTC Coupled (§2.2.7.2.1.b, §2.2.7.2.1.c)	397
2.4.7.2.2	Verification of Requirements When in Precision Condition and UTC Coupled (§2.2.7.2.2)	400
2.4.7.2.2.1	Verification of Latitude and Longitude Requirements When in Precision Condition and UTC Coupled (§2.2.7.2.2.a, §2.2.4.5.2.1, §2.2.4.5.2.6)	400
2.4.7.2.2.2	Verification of Requirements for Other ADS-B Message Fields When in Precision Condition and UTC Coupled (§2.2.7.2.2.b, §2.2.7.2.2.c)	402
2.4.7.2.3	Verification of Requirements When Non-UTC Coupled (§2.2.7.2.3)	405
2.4.7.2.4	Verification of Total Latency of Position Measurements (§2.2.7.2.4)	407
2.4.7.2.5	Verification of Data Timeout (§2.2.7.2.5)	408
2.4.7.2.6	Verification of Requirements When Transmitting at a High Rate (§2.2.7.2.6)	408
2.4.7.2.6.1	Verification of Latitude and Longitude Requirements When Transmitting 4 Messages per Second (§2.2.7.2.6.a, §2.2.4.5.11.1, §2.2.4.5.11.2)	408
2.4.7.2.6.2	Verification of Requirements for Other ADS-B Message Fields When Transmitting 4 Messages per Second (§2.2.7.2.6.b)	410
2.4.7.2.6.3	Verification of Latitude and Longitude Requirements When Transmitting 8 Messages per Second (§2.2.7.2.6.a, §2.2.4.5.11.1, §2.2.4.5.11.2)	411
2.4.7.2.6.4	Verification of Requirements for Other ADS-B Message Fields When Transmitting 8 Messages per Second (§2.2.7.2.6.b)	413
2.4.8	Verification of Receiver Characteristics (§2.2.8)	413
2.4.8.1	Verification of Receiving Diversity (§2.2.8.1)	414
2.4.8.1.1	Verification of Full Receiving Diversity (§2.2.8.1.a and §2.2.8.1.b)	414
2.4.8.1.2	Verification of Switching Receiving Diversity (§2.2.8.1.c)	415
2.4.8.2	Verification of Receiver Performance (§2.2.8.2)	417
2.4.8.2.1	Verification of Receiver Sensitivity (§2.2.8.2.1)	417
2.4.8.2.1.1	Verification of Long ADS-B Message As Desired Signal (§2.2.8.2.1.1)	417
2.4.8.2.1.2	Verification of Basic ADS-B Message As Desired Signal (§2.2.8.2.1.2)	419
2.4.8.2.1.3	Verification of Ground Uplink Message As Desired Signal (§2.2.8.2.1.3)	420
2.4.8.2.2	Verification of Receiver Desired Signal Dynamic Range (§2.2.8.2.2)	422
2.4.8.2.3	Verification of Receiver Selectivity (§2.2.8.2.3)	423
2.4.8.2.4	Verification of Receiver Tolerance to Pulsed Interference (§2.2.8.2.4)	427
2.4.8.2.5	Verification of Receiver Tolerance to Overlapping ADS-B Messages (Self Interference) (§2.2.8.2.5)	432
2.4.8.2.6	Verification of Rate of False “Trigger” (§2.2.8.2.6)	434
2.4.8.2.7	Verification of Trigger Processing Rate (§2.2.8.2.7)	435
2.4.8.3	Verification of Receiver Message Processing (§2.2.8.3)	436
2.4.8.3.1	Verification of Criteria for Successful Message Reception (§2.2.8.3.1)	436
2.4.8.3.1.1	Verification of ADS-B Messages (§2.2.8.3.1.1)	437
2.4.8.3.1.2	Verification of Ground Uplink Messages (§2.2.8.3.1.2)	448
2.4.8.3.2	Verification of Receiver Discrimination Between ADS-B and Ground Uplink Message Types (§2.2.8.3.2)	462

2.4.8.3.3	Verification of Receiver Processing of ADS-B Synchronization “Trigger” (§2.2.8.3.3)	462
2.4.8.3.4	Verification of Receiver Processing of Ground Uplink Synchronization “Trigger” (§2.2.8.3.4)	466
2.4.8.3.5	Verification of Receiver Time of Message Receipt (§2.2.8.3.5)	468
2.4.9	Verification of Report Assembly Requirements (§2.2.9)	469
2.4.9.1	Verification of Report Assembly on Receipt of ADS-B Message (§2.2.9.1)	469
2.4.9.2	Verification of Report Assembly on Receipt of Ground Uplink Message (§2.2.9.2)	470
2.4.10	Verification of Receiver Subsystem Capacity and Throughput Requirements (§2.2.10)	470
2.4.10.1	Verification of Fundamental Principals of Report Assembly (§2.2.10.1)	470
2.4.10.2	Verification of Capacity for Successful Message Reception (§2.2.10.2)	470
2.4.10.3	Verification of Applicable Messages (§2.2.10.3)	472
2.4.10.4	Verification of Message Reception-to-Report Completion Time (§2.2.10.4)	473
2.4.11	Verification of Special Requirements for Transceiver Implementations (§2.2.11)	473
2.4.11.1	Verification of Transmit-Receive Turnaround Time (§2.2.11.1)	473
2.4.11.2	Verification of Receive-Transmit Turnaround Time (§2.2.11.2)	474
2.4.12	Verification of Mutual Suppression Pulses (§2.2.12)	474
2.4.13	Verification of Self Test and Monitors (§2.2.13)	475
2.4.13.1	Verification of Self Test (§2.2.13.1)	475
2.4.13.2	Verification of Broadcast Monitoring (§2.2.13.2)	476
2.4.13.3	Verification of Address Verification (§2.2.13.3)	476
2.4.13.4	Verification of Receiver Self-Test Capability (§2.2.13.4)	476
2.4.13.5	Verification of Failure Annunciation (§2.2.13.5)	477
2.4.13.5.1	Verification of ADS-B Device Failure and ADS-B Function Fail Annunciation (§2.2.13.5.1)	477
2.4.13.5.2	Reserved	477
2.4.13.5.3	Verification of Co-Located UAT Transmitting and Receiving Device Failure Annunciation (§2.2.13.5.3)	477
2.4.14	Verification of Antenna System (§2.2.14)	478
2.4.14.1	Verification of Polarization (§2.2.14.1)	478
2.4.14.2	Verification of Antenna Voltage Standing Wave Ratio (VSWR) (§2.2.14.2)	478
2.4.14.3	Verification of Requirements for Optional Passive Diplexer (§2.2.14.3)	479
2.4.14.3.1	Verification of Diplexer RF Requirements (§2.2.14.3.1)	479
2.4.14.3.1.1	Verification of The UAT Channel (§2.2.14.3.1.1)	479
2.4.14.3.1.2	Verification of The Transponder Channel (§2.2.14.3.1.2)	480
2.4.14.3.1.3	Verification of Channel to Channel Isolation (§2.2.14.3.1.3)	482
2.4.15	Verification of Interfaces (§2.2.15)	483
2.4.15.1	Verification of ADS-B Transmitting Subsystem Interfaces (§2.2.15.1)	483
2.4.15.1.1	Verification of ADS-B Transmitting Subsystem Input Interfaces (§2.2.15.1.1)	483
2.4.15.1.1.1	Verification of Discrete Input Interfaces (§2.2.15.1.1.1)	483
2.4.15.1.1.2	Verification of Digital Communication Input Interfaces (§2.2.15.1.1.2)	484
2.4.15.1.1.3	Verification of Processing Efficiency (§2.2.15.1.1.3)	484
2.4.15.1.1.4	SSR Reply Reception Interface	484
2.4.15.1.2	Verification of ADS-B Transmitting Subsystem Output Interfaces (§2.2.15.1.2)	485
2.4.15.1.2.1	Verification of Discrete Output Interfaces (§2.2.15.1.2.1)	485
2.4.15.1.2.2	Verification of Digital Communication Output Interfaces (§2.2.15.1.2.2)	485
2.4.15.2	Verification of UAT Receiving Subsystem Interfaces (§2.2.15.2)	485
2.4.15.2.1	Verification of UAT Receiving Subsystem Input Interfaces (§2.2.15.2.1)	485
2.4.15.2.1.1	Verification of Discrete Input Interfaces (§2.2.15.2.1.1)	486
2.4.15.2.1.2	Verification of Digital Communication Input Interfaces (§2.2.15.2.1.2)	486
2.4.15.2.1.3	Verification of Processing Efficiency (§2.2.15.2.1.3)	486
2.4.15.2.2	Verification of UAT Receiving Subsystem Output Interfaces (§2.2.15.2.2)	487

2.4.15.2.2.1	Verification of Discrete Output Interfaces (§2.2.15.2.2.1)	487
2.4.15.2.2.2	Verification of Digital Communication Output Interfaces (§2.2.15.2.2.2)	487
2.4.16	Verification of Power Interruption (§2.2.16)	487
2.4.16.1	Verification of Power Interruption to UAT Transmitting Functions (§2.2.16)	487
2.4.16.2	Verification of Power Interruption to UAT Receiving Functions (§2.2.16)	488
2.4.17	Verification of Compatibility with Other Systems (§2.2.17)	489
2.4.17.1	Verification of EMI Compatibility (§2.2.17.1)	489
2.4.17.2	Verification of Compatibility with GNSS Receivers (§2.2.17.2)	489
2.4.17.3	Verification of Compatibility with Other Navigation Receivers and ATC Transponders (§2.2.17.3)	489
3	Equipment Performance Characteristics	492
3.1	Equipment Installation	492
3.1.1	Installed Equipment Considerations	492
3.1.1.1	Data Sources	492
3.1.1.2	ADS-B Transmitter	492
3.1.1.3	ADS-B Receiver	492
3.1.1.4	Report Assembly	493
3.1.1.5	Applications	493
3.1.2	Aircraft Environment	493
3.1.3	Aircraft Power Source	493
3.1.3.1	Power Fluctuation	493
3.1.4	Accessibility	493
3.1.5	Display Visibility	493
3.1.6	Indicators	494
3.1.7	Alerts	494
3.1.8	Failure Protection	494
3.1.9	Failure Indication	494
3.1.9.1	ADS-B Transmission or Receiver Device Failure Annunciation	494
3.1.9.2	ADS-B Function Fail Annunciation	494
3.1.10	Interference Effects	494
3.1.11	Mutual Suppression	495
3.2	Installed Equipment Performance Requirements	495
3.2.1	Antenna Installation	495
3.2.1.1	General Considerations	495
3.2.1.2	Transmission Lines	495
3.2.1.3	Antenna Polarization	495
3.2.1.4	Antenna Location	496
3.2.1.5	Minimum Distance from Other Antennas	496
3.2.1.6	Minimum Reception Range	496
3.2.1.7	Transmit Pattern Gain	497
3.2.1.8	Receive Pattern Gain	497
3.2.1.9	Dynamic Response	497
3.2.1.10	Antenna Diplexer	497
3.2.2	Mutual Suppression Bus	498
3.3	Conditions of Test	498
3.3.1	Safety Precautions	498
3.3.2	Power Input	498
3.3.3	Environment	498
3.3.4	Adjustment of Equipment	499
3.3.5	Warm-up Period	499

3.4	Test Procedures for Installed Equipment Performance	499
3.4.1	Verification of Antenna Installation (§3.2.1)	499
3.4.1.1	Verification of General Considerations (§3.2.1.1)	499
3.4.1.2	Verification of Transmission Lines (§3.2.1.2)	499
3.4.1.3	Verification of Antenna Polarization (§3.2.1.3)	500
3.4.1.4	Verification of Antenna Location (§3.2.1.4)	500
3.4.1.5	Verification of Minimum Distance from Other Antennas (§3.2.1.5)	500
3.4.1.6	Verification of Minimum Reception Range (§3.2.1.6)	500
3.4.1.7	Verification of Transmit Pattern Gain (§3.2.1.7)	500
3.4.1.7.1	Background Material on Gain Performance Verification	501
3.4.1.7.1.1	Full Scale Anechoic Antenna Range Measurements of Gain	501
3.4.1.7.1.2	Scaled Model Measurements of Gain	501
3.4.1.7.1.3	Model Tests.....	502
3.4.1.7.1.4	Theoretical Calculations of Antenna Gain.....	502
3.4.1.7.1.4.1	Validation of Theoretical Calculations.....	502
3.4.1.7.1.5	Distance Area Calculations.....	502
3.4.1.7.2	Success Criteria.....	503
3.4.1.7.3	Verification Procedure for Transmit Pattern Gain.....	503
3.4.1.8	Verification of Receive Pattern Gain (§3.2.1.8).....	509
3.4.1.9	Verification of Dynamic Response (§3.2.1.9).....	511
3.5	Flight Environment Data Sources	511
3.5.1	Navigation Integrity Category (NIC)	511
3.5.2	Navigation Accuracy Category – Position (NAC _P).....	511
3.5.3	Altitude	511
3.5.3.1	Altitude Reporting Source.....	511
3.5.4	Air/Ground Status.....	512
3.5.5	Reserved	512
3.5.6	IDENT Source	512
3.6	Aircraft / Vehicle Data	512
3.6.1	Static Data	512
3.6.2	Variable Data.....	512
3.6.3	On-Condition and Status Sensors.....	513
3.7	Flight Test Procedures.....	513
3.7.1	Displayed Data Reliability	513
3.7.2	Interference Effects	513
3.7.3	ADS-B Performance Testing.....	513
4	EQUIPMENT OPERATIONAL PERFORMANCE CHARACTERISTICS	516
4.1	Required Operational Performance Characteristics.....	516
4.1.1	Power Input and Control	516
4.1.1.1	Power On/Off (Optional).....	516
4.1.2	Equipment Operating Functions.....	516
4.1.2.1	Transmission Conditions.....	516
4.1.2.2	Receive Subsystem.....	517
4.1.2.2.1	Receive Function	517
4.1.2.2.2	Report Assembly Function	517
4.1.3	Reserved	517
4.1.4	Reserved	517
4.1.5	Reserved	517
4.1.6	Barometric Altitude.....	517
4.1.7	Broadcast Monitor.....	518

4.1.8	Address Monitor.....	518
4.1.9	Failure Indication.....	518
4.2	Reserved.....	518
5	Membership.....	520
Appendix A Acronyms & Definition of Terms.....		A-1
A.1	Acronyms.....	A-1
A.2	Definition of Terms.....	A-7
Appendix B MASPS Compliance Matrix.....		B-1
B.1	Introduction.....	B-1
Appendix C Example ADS-B Message Encoding.....		C-1
C.1	Reed Solomon Encoding of Message Payload.....	C-1
C.2	Reed Solomon Encoding of Basic Type 0 ADS-B Message Payload.....	C-2
C.3	Reed Solomon Encoding of Long Type 1 ADS-B Message Payload.....	C-4
C.4	Reed Solomon Encoding of Ground Uplink Message Payload.....	C-7
C.5	Appendix C References.....	C-7
Appendix D UAT Ground Infrastructure.....		D-1
D.1	General Description.....	D-1
Appendix E Aircraft Antenna Characteristics.....		E-1
E.1	Antenna Characteristics.....	E-1
E.2	General Characteristics.....	E-1
E.3	Radiation Patterns.....	E-1
E.4	Directional Gain Radiation Patterns.....	E-1
E.5	Typical VSWR Measurements of Existing Transponder / DME Antennas.....	E-3
E.6	Sensor Systems L Band Blade Antenna P/N S65-5366-7L.....	E-5
E.7	AeroAntenna P/N AT-130-1.....	E-5
E.8	¼ Wave Whip Antenna.....	E-5
E.9	Passive Antenna Diplexer Characteristics.....	E-6
E.10	Antenna Diplexer Testing.....	E-7
E.10.1	SSR Transponder Testing.....	E-7
E.10.2	UAT Diplexer Testing.....	E-11
E.10.3	Prototype Diplexer Performance.....	E-11
E.11	Typical Installation Diagram.....	E-15
Appendix F Transmitter and Receiver Power Requirements.....		F-1
Appendix G Standard Interference Environment.....		G-1
G.1	Background.....	G-1
G.2	Operational Environments.....	G-1
G.3	Co-Site Environment.....	G-4
G.4	Scenario Assessments.....	G-5
Appendix H UAT Synchronization Issues.....		H-1
H.1	Introduction.....	H-1
H.2	Synchronization Process Description.....	H-1
H.3	Synchronization Performance.....	H-3
H.4	False Alarm Rate (Noise).....	H-8

H.5	False Alarm Rate (Embedded Synchronization Sequence).....	H-10
H.6	Up Link Message Considerations.....	H-11
H.7	Required Memory Size.....	H-11
H.8	Summary	H-12
H.9	Reference.....	H-13
Appendix I UAT Timing Requirements.....		I-1
I.1	Background	I-1
I.2	Purpose	I-1
I.3	Installed End-End Timing Performance	I-1
I.4	MOPS Timing Requirements	I-3
I.5	Considerations for ADS-B Validation Applications	I-3
Appendix J Reference Upper-Layer External Interface Format.....		J-1
J.1	Background	J-1
J.2	Scope	J-1
J.3	Serial Data Format Description	J-1
Appendix K UAT System Performance Simulation Results.....		K-1
K.1	Introduction	K-1
K.2	Organization	K-1
K.3	Background	K-2
K.4	General Assumptions.....	K-2
K.5	UAT Detailed Simulation Description and Limitations	K-3
K.6	TLAT Antenna Model.....	K-5
K.7	Receiver Performance Model	K-7
K.8	Measured Data.....	K-7
K.9	Receiver Model Assumptions.....	K-11
K.10	Receiver Model Accuracy	K-14
K.11	Multi-Aircraft Simulation (MAUS) Results.....	K-18
K.12	Los Angeles Basin 2020 (LA2020).....	K-18
K.13	Core Europe Scenarios	K-35
K.13.1	Current Core Europe.....	K-36
K.13.2	Core Europe 2015.....	K-60
K.14	Low Density Scenario	K-74
K.15	Acquisition Performance.....	K-76
K.16	Surface Performance	K-79
K.17	An A0 on the Surface Receiving an Aircraft that is on Approach	K-88
K.18	Model Validation.....	K-90
K.19	UAT AIS Performance Analysis	K-92
K.20	2021 UAT Performance Model	K-95
K.21	Introduction and Overview.....	K-95
K.22	UAT Shared Channel Access Model.....	K-96
K.22.1	Link Access	K-96
K.23	Characteristics of UAT link.....	K-99
K.23.1	equipage classes, link budgets and co-channel interference signal levels.....	K-99
K.24	Operational Environment	K-101
K.24.1	Traffic Distribution.....	K-101
K.24.1.1	Horizontal distribution.....	K-101
K.24.1.2	Vertical distribution.....	K-102
K.24.1.3	Traffic in View.....	K-103

K.24.2	Co-channel interference.....	K-106
K.24.2.1	Air-to-Air.....	K-106
K.24.2.2	ADS-R uplink.....	K-107
K.24.2.3	Total UAT Interference Rate.....	K-111
K.25	Probability of Message Detection.....	K-114
K.25.1	Probability of Decode.....	K-114
K.25.2	Receiver Sensitivity.....	K-115
K.25.3	Probability of Message Detection.....	K-116
K.25.4	Performance Improvement with Number of Tries.....	K-117
K.26	UAT Update Interval for Assumed Scenario and Growth Examples.....	K-118
K.27	Glossary of Terms and Variables.....	K-121
Appendix L	Reserved.....	L-1
Appendix M	UAT Error Detection and Correction Performance.....	M-1
Appendix N	Setup Files for Test Procedures.....	N-1
Appendix O	DME Operation in the Presence of UAT Signals.....	O-1
Appendix P	UAT Message Overlap Statistics.....	P-1
P.1	Introduction.....	P-1
P.2	Statistical Model Results.....	P-2
P.3	Discussion.....	P-8
P.4	Effect of Uplink Message.....	P-10
P.5	MAUS Results.....	P-10
P.6	Summary.....	P-13
Appendix Q	Determining the Navigation Accuracy Category for Velocity (NAC_v).....	Q-1
Q.1	Purpose and Scope.....	Q-1
Q.2	Reference.....	Q-1
Appendix R	Proposed RTCA DO-282C Provisions for Backward Compatibility with RTCA DO-282A and RTCA DO-282B Message Formats.....	R-1
R.1	Background.....	R-1
R.2	VerSion 1 Message Processing.....	R-1
R.2.1	Version 1 and 2 Emitter Category Field Definition.....	R-1
R.2.2	Version 1 and 2 Emergency/Priority Status Field Definition.....	R-2
R.2.3	Version 1 SIL Field Definition.....	R-3
R.2.4	Version 1 and Version 2 Secondary Altitude Field Definition.....	R-4
R.3	Version 2 Message Processing.....	R-4
Appendix S	Reserved.....	S-1
Appendix T	Reserved.....	T-3
Appendix U	Sample Vertical Status Determination Algorithm.....	U-1
U.1	Introduction and Purpose.....	U-1
U.2	Algorithm Inputs.....	U-1
U.3	GNSS Sensor Data.....	U-1
U.4	Air Data.....	U-1
U.5	Persistent Data.....	U-2
U.6	Design Considerations.....	U-2
U.7	Airborne Bias.....	U-2

U.8	Slope Calculation.....	U-3
U.9	Level State.....	U-3
U.10	Landing Condition.....	U-4
U.11	Data Validity	U-4
U.12	Algorithm Description.....	U-5
U.13	Transitions to “AIRBORNE”	U-5
U.13.1	Ground Speed.....	U-5
U.13.2	Level State.....	U-5
U.14	Transitions to “ON-GROUND”	U-5
U.14.1	Ground Speed.....	U-5
U.14.2	Power-on	U-6
U.14.3	Ground Reference Point	U-6
U.14.4	Landing Condition.....	U-6
U.15	Vertical Status Not Determined.....	U-7
U.16	Transitions to “UNKNOWN”	U-7
U.17	Algorithm Flowchart	U-8
Appendix V Broadcast Message Format Algorithm (BMFA) Validation Test Vectors		V-1
V.1	Background	V-1
V.2	Configuration and Initialization	V-1
V.3	Format	V-1
V.4	Test Cases.....	V-2
V.5	Takeoff	V-2
V.6	Landing.....	V-3
V.7	Landing and Takeoff	V-3
V.8	En Route.....	V-4
V.9	Taxi.....	V-4

LIST OF FIGURES

Figure 1-1: UAT Frame	6
Figure 1-2: UAT ADS-B Message Structures	9
Figure 2-1: Time/Amplitude Profile of ADS-B Message Transmission Interval.....	24
Figure 2-2: UAT Transmit Spectrum.....	25
Figure 2-3: ADS-B Message Format	26
Figure 2-4: Ground Uplink Message Format.....	28
Figure 2-5: Ground Uplink Information Frame	29
Figure 2-6: Angular Weighted Binary Encoding of Latitude and Longitude.....	45
Figure 2-7: Payload Type Code “11” Message with EPISODIC Element	90
Figure 2-8: UTC Time Mark Pulse.....	143
Figure 2-9: Multiple Messages per Second Transmission Quadrants	146
Figure 2-10: Selection of Payload Type Code Containing HVA SV vs SV.....	148
Figure 2-11: Transmitter Antenna Use for Diversity Installations	148
Figure 2-12: Payload Element Subtype Transmission Cycle for AIREP Capable Equipment.....	149
Figure 2-13: Payload Element Subtype Transmission Cycle for AIREP Capable Equipment (HVA).....	149
Figure 2-14: ADS-B Receiving Architectures.....	158
Figure 2-15: ADS-B Message and Report General Data Flow.....	167
Figure 2-16: Digital Demodulation Mode – Trace A: Ch1 2FSK Meas Time	192
Figure 2-17: Digital Demodulation Mode – Trace C: “Eye Diagram”.....	194
Figure 2-18: MSO Timing Measurement Configuration.....	385
Figure 2-19: ADS-B Long Message Envelope & Spectrum – No Interference	426
Figure 2-20: ADS-B Long Message Envelope & Spectrum – With CW	427
Figure 2-21: ADS-B Long Message Envelope & Spectrum – With DME/TACAN.....	430
Figure 3-1: Antenna Test Configuration - 1	504
Figure 3-2: Antenna Test Configuration - 2	509
Figure A-1: Ideal eye diagram	A-10
Figure A-2: Distorted eye diagram	A-10
Figure E-1: L-Band Passive Gain Antenna.....	E-2
Figure E-2: Gain Array Antenna Azimuth Pattern	E-3
Figure E-3: Jet Transport Antenna.....	E-5
Figure E-4: Capstone Antenna.....	E-5
Figure E-5: ¼ Wave Whip Antenna	E-6
Figure E-6: Sensitivity Variation with Frequency, All 1’s Interrogation, Transponder MS-1... E-10	E-10
Figure G-1: Sample Scenario.....	G-3
Figure G-2: Normalized DME Pattern.....	G-3
Figure G-3: Normalized TACAN Pattern.....	G-4
Figure H-1: UAT Receiver Processing	H-2
Figure H-2: Baseband Transmit Filter. Truncated Raised-Cosine Nyquist Filter With Roll-Off Factor = 0.5	H-4
Figure H-3: ADS-B Synchronization Sequence	H-5
Figure H-4: A Portion of the ADS-B Synchronization Sequence	H-5
Figure H-5: Performance of the Three Sample per Bit Scheme	H-7
Figure H-6: Performance of the One Sample per Bit Scheme.....	H-8
Figure H-7: False Alarm Rate versus Threshold	H-10

Figure H-8: Memory Length Determination (Memory Size in bits)	H-12
Figure K-1 TLAT Antenna Model Elevation Gain.....	K-6
Figure K-2: TLAT Random Azimuth Gain	K-7
Figure K-3: Test Setup for measuring BER.....	K-8
Figure K-4: BER Due to DME interference	K-10
Figure K-5: BER Due to DME Interference	K-10
Figure K-6: Link 16 Interference.....	K-11
Figure K-7: Assumed Piecewise Linear IIBER Vs. SINR Curve (Typical)	K-12
Figure K-8: BER Vs. SINR Curve Corresponding to Figure K-7	K-12
Figure K-9: Gaussian Noise + Single UAT, 1.2 MHz Receiver.....	K-15
Figure K-10: Gaussian Noise + Two Equal UATs, 1.2 MHz Receiver.....	K-15
Figure K-11: Two Unequal UATs, INR \gg 0 dB, 0.8 MHz Receiver.....	K-16
Figure K-12: N Equal UATs, INR \gg 0, 0.8 MHz Receiver	K-16
Figure K-13: Model Errors for All Data, 1.2 MHz Receiver.....	K-17
Figure K-14: Model Errors for All Data, 0.8 MHz Receiver.....	K-17
Figure K-15: A3 Receiver in LA2020 at High Altitude Receiving A3 Transmissions	K-20
Figure K-16: A3 Receiver in LA2020 at High Altitude Receiving A2 Transmissions	K-21
Figure K-17: A3 Receiver in LA2020 at High Altitude Receiving A1H Transmissions	K-21
Figure K-18: A3 Receiver in LA2020 at FL 150 Receiving A3 Transmissions	K-22
Figure K-19: A3 Receiver in LA2020 at FL 150 Receiving A2 Transmissions	K-22
Figure K-20: A3 Receiver in LA2020 at FL 150 Receiving A1 and A0 Transmissions.....	K-23
Figure K-21: A2 Receiver in LA2020 at High Altitude Receiving A3 Transmissions	K-23
Figure K-22: A2 Receiver in LA2020 at High Altitude Receiving A2 Transmissions	K-24
Figure K-23: A2 Receiver in LA2020 at High Altitude Receiving A1H Transmissions	K-24
Figure K-24: A2 Receiver in LA2020 at FL 150 Receiving A3 Transmissions	K-25
Figure K-25: A2 Receiver in LA2020 at FL 150 Receiving A2 Transmissions	K-25
Figure K-26: A2 Receiver in LA2020 at FL 150 Receiving A1 and A0 Transmissions.....	K-26
Figure K-27: A1H Receiver in LA2020 at High Altitude Receiving A3 Transmissions	K-26
Figure K-28: A1H Receiver in LA2020 at High Altitude Receiving A2 Transmissions	K-27
Figure K-29: A1H Receiver in LA2020 at High Altitude Receiving A1H Transmissions	K-27
Figure K-30: A1 Receiver in LA2020 at FL 150 Receiving A3 Transmissions	K-28
Figure K-31: A1 Receiver in LA2020 at FL 150 Receiving A2 Transmissions	K-28
Figure K-32: A1 Receiver in LA2020 at FL 150 Receiving A1 and A0 Transmissions.....	K-29
Figure K-33: A0 Receiver in LA2020 at FL 150 Receiving A3 Transmissions	K-29
Figure K-34: A0 Receiver in LA2020 at FL 150 Receiving A2 Transmissions	K-30
Figure K-35: A0 Receiver in LA2020 at FL 150 Receiving A1 and A0 Transmissions.....	K-30
Figure K-36: Ground Receiver in LA2020 Receiving A3 Transmissions.....	K-31
Figure K-37: Ground Receiver in LA2020 Receiving A2 Transmissions.....	K-31
Figure K-38: Ground Receiver in LA2020 Receiving A1 and A0 Transmissions	K-32
Figure K-39: Ground Receiver in LA with Sectorized Antenna with a 10 kW TACAN at 980 MHz located 1000' away.....	K-32
Figure K-40: Standard Ground Receiver in LA with TACAN that delivers -90 dBm at 980 MHz to the UAT Ground Antenna.....	K-33
Figure K-41: State Vector Updates from Ground Vehicle Transmitters for all Types of Receivers at 2000 feet Altitude.....	K-33
Figure K-42: A3 Receiver at High Altitude in Current Europe Receiving A3 Transmissions...	K-37

Figure K-43: A3 Receiver at High Altitude in Current Europe Receiving A2 Transmissions...K-38

Figure K-44: A3 Receiver at High Altitude in Current Europe Receiving A1H TransmissionsK-38

Figure K-45: A3 Receiver at FL 150 in Current Europe Receiving A3 TransmissionsK-39

Figure K-46: A3 Receiver at FL 150 in Current Europe Receiving A2 TransmissionsK-39

Figure K-47: A3 Receiver at FL 150 in Current Europe Receiving A1 and A0 Transmissions K-40

Figure K-48: A2 Receiver at High Altitude in Current Europe Receiving A3 Transmissions...K-40

Figure K-49: A2 Receiver at High Altitude in Current Europe Receiving A2 Transmissions...K-41

Figure K-50: A2 Receiver at High Altitude in Current Europe Receiving A1H TransmissionsK-41

Figure K-51: A2 Receiver at FL 150 in Current Europe Receiving A3 TransmissionsK-42

Figure K-52: A2 Receiver at FL 150 in Current Europe Receiving A2 TransmissionsK-42

Figure K-53: A2 Receiver at FL 150 in Current Europe Receiving A1 and A0 Transmissions K-43

Figure K-54: A1H Receiver at High Altitude in Current Europe Receiving A3 TransmissionsK-43

Figure K-55: A1H Receiver at High Altitude in Current Europe Receiving A2 TransmissionsK-44
K-45

Figure K-56: A1H Receiver at High Altitude in Current Europe Receiving A1H Transmissions.K-45
K-45

Figure K-57: A1 Receiver at FL 150 in Current Europe Receiving A3 TransmissionsK-45

Figure K-58: A1 Receiver at FL 150 in Current Europe Receiving A2 TransmissionsK-46

Figure K-59: A1 Receiver at FL 150 in Current Europe Receiving A1 and A0 Transmissions K-46

Figure K-60: A0 Receiver at FL 150 in Current Europe Receiving A3 TransmissionsK-47

Figure K-61: A0 Receiver at FL 150 in Current Europe Receiving A2 TransmissionsK-47

Figure K-62: A0 Receiver at FL 150 in Current Europe Receiving A1 and A0 Transmissions K-48

Figure K-63: A3 Receivers in the Worst-Case Current DME Position (154 equipped aircraft) at High Altitude Receiving A3 TransmissionsK-49

Figure K-64: A3 Receivers in the Worst-Case Current DME Position (154 equipped aircraft) at High Altitude Receiving A2 TransmissionsK-50

Figure K-65: A3 Receivers in the Worst-Case Current DME Position (154 equipped aircraft) at High Altitude Receiving A1H TransmissionsK-50

Figure K-66: A3 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A3 TransmissionsK-51

Figure K-67: A3 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A2 TransmissionsK-51

Figure K-68: A3 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A1 and A0 Transmissions.....K-52

Figure K-69: A2 Receiver at High Altitude in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A3 Transmissions.....K-52

Figure K-70: A2 Receiver at High Altitude in the Current Worst-Case DME Position (154 equipped aircraft) Receiving A2 Transmissions.....K-53

Figure K-71: A2 Receiver at High Altitude in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A1H Transmissions.....K-53

Figure K-72: A2 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A3 TransmissionsK-54

Figure K-73: A2 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A2 TransmissionsK-54

Figure K-74: A2 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A1 and A0 Transmissions.....	K-55
Figure K-75: A1H Receiver at High Altitude in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A3 Transmissions.....	K-56
Figure K-76: A1H Receiver at High Altitude in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A2 Transmissions.....	K-56
Figure K-77: A1H Receiver at High Altitude in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A1H Transmissions.....	K-57
Figure K-78: A1 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A3 Transmissions	K-57
Figure K-79: A1 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A2 Transmissions	K-58
Figure K-80:A1 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A1 and A0 Transmissions.....	K-58
Figure K-81: A0 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A3 Transmissions	K-59
Figure K-82:A0 Receiver at FL 150 in the Worst-Case Current DME Position (154 equipped aircraft) Receiving A2 Transmissions	K-59
Figure K-83: A3 Receiver in CE2015 at High Altitude Receiving A3 Transmissions	K-61
Figure K-84: A3 Receiver in CE2015 at High Altitude Receiving A2 Transmissions	K-62
Figure K-85: A3 Receiver in CE2015 at High Altitude Receiving A1H Transmissions	K-62
Figure K-86: A3 Receiver in CE2015 at FL 150 Receiving A3 Transmissions.....	K-63
Figure K-87: A3 Receiver in CE2015 at FL 150 Receiving A2 Transmissions.....	K-63
Figure K-88: A3 Receiver in CE2015 at FL 150 Receiving A1 and A0 Transmissions.....	K-64
Figure K-89: A2 Receiver in CE2015 at High Altitude Receiving A3 Transmissions	K-64
Figure K-90: A2 Receiver in CE2015 at High Altitude Receiving A2 Transmissions	K-65
Figure K-91: A2 Receiver in CE2015 at High Altitude Receiving A1 and A0 Transmissions.....	K-65
Figure K-92: A2 Receiver in CE2015 at FL 150 Receiving A3 Transmissions.....	K-66
Figure K-93: A2 Receiver in CE2015 at FL 150 Receiving A2 Transmissions.....	K-66
Figure K-94: A2 Receiver in CE2015 at FL 150 Receiving A1 and A0 Transmissions	K-67
Figure K-95: A1H Receiver in CE2015 at High Altitude Receiving A3 Transmissions	K-67
Figure K-96: A1H Receiver in CE2015 at High Altitude Receiving A2 Transmissions	K-68
Figure K-97: A1H Receiver in CE2015 at High Altitude Receiving A1H Transmissions	K-68
Figure K-98: A1 Receiver in CE2015 at FL 150 Receiving A3 Transmissions.....	K-69
Figure K-99: A1 Receiver in CE2015 at FL 150 Receiving A2 Transmissions.....	K-69
Figure K-100: A1 Receiver in CE2015 at FL 150 Receiving A1 and A0 Transmissions.....	K-70
Figure K-101: A0 Receiver in CE2015 at FL 150 Receiving A3 Transmissions.....	K-70
Figure K-102: A0 Receiver in CE2015 at FL 150 Receiving A2 Transmissions.....	K-71
Figure K-103: A0 Receiver in CE2015 at FL 150 Receiving A1 and A0 Transmissions.....	K-71
Figure K-104: Ground Receiver in CE2015 with 3-Sector Antenna in Brussels Receiving all Equipage Transmissions	K-72
Figure K-105: Ground Receiver in CE2015 with 3-Sector Antenna in Brussels, co-located with a 979 MHz TACAN delivering –50 dBm power to antenna, Receiving All Equipage Transmissions	K-72

Figure K-106: Receptions of Ground Vehicle Transmissions by All Equipage Classes on Approach (at constant 2000 foot altitude) in CE2015 with 10 kW 979 MHz TACAN at Airport	K-73
Figure K-107: A3 Receiver in Low Density Scenario Receiving A3 Transmissions.....	K-75
Figure K-108: Receptions of A3 Transmissions by a Standard Ground Receiver in a Low Density Scenario co-located with a TACAN at 979 MHz with –30 dBm Power at the UAT Antenna	K-75
Figure K-109: A3 Receiver on the Surface in LA2020 Scenario Receiving A3 Transmissions	K-80
Figure K-110: A3 Receiver on the Surface in LA2020 Scenario Receiving A2 Transmissions	K-80
Figure K-111: A3 Receiver on the Surface in LA2020 Scenario Receiving A1 Transmissions...	K-81
Figure K-112: A3 Receiver on the Surface in LA2020 Scenario Receiving A0 Transmissions	K-81
Figure K-113: A2 Receiver on the Surface in LA2020 Scenario Receiving A3 Transmissions...	K-82
Figure K-114: A2 Receiver on the Surface in LA2020 Scenario Receiving A2 Transmissions...	K-82
Figure K-115: A2 Receiver on the Surface in LA2020 Scenario Receiving A1 Transmissions	K-83
Figure K-116: A2 Receiver on the Surface in LA2020 Scenario Receiving A0 Transmissions	K-83
Figure K-117: A1 Receiver on the Surface in LA2020 Scenario Receiving A3 Transmissions...	K-84
Figure K-118: A1 Receiver on the Surface in LA2020 Scenario Receiving A2 Transmissions...	K-84
Figure K-119: A1 Receiver on the Surface in LA2020 Scenario Receiving A1 Transmissions...	K-85
Figure K-120: A1 Receiver on the Surface in LA2020 Scenario Receiving A0 Transmissions..	K-85
Figure K-121: A0 Receiver on the Surface in LA2020 Scenario Receiving A3 Transmissions...	K-86
Figure K-122: A0 Receiver on the Surface in LA2020 Scenario Receiving A2 Transmissions...	K-86
Figure K-123: A0 Receiver on the Surface in LA2020 Scenario Receiving A1 Transmissions...	K-87
Figure K-124: A0 Receiver on the Surface in LA2020 Scenario Receiving A0 Transmissions	K-87
Figure K-125: A0 Receivers on the Ground in LA2020 Receiving All Aircraft on Approach at an Altitude of 2000 feet	K-89
Figure K-126: A0 Receivers on the Ground in CE2015 Receiving All Aircraft on Approach at an Altitude of 2000 ft to Brussels co-located with a 10 kW 979 MHz TACAN.....	K-89
Figure K-127: Comparison of Bench Test Measurements of MOPS-Compliant UAT Reception in LA2020 Self-Interference with Predictions by MAUS	K-90
Figure K-128: Bench Test Measurements of UAT Performance in Core Europe UAT Self-Interference, Combined with DME/TACAN and Link 16 Interference	K-91
Figure K-129: Bench Test Measurements of UAT Performance in the LA2020 UAT Self-Interference, Combined with DME/TACAN and Link 16 Interference	K-92
Figure K-130: Typical Result for Scenario 3 for Update Interval as a Function of Bank Angle ..	K-95

Figure K-131: Non-overlapped message propagation range vs number adjacent clear MSOs for several message lengths	K-97
Figure K-132: Comparison of random arrival UAT message decode model with probabilities of non-overlapped reception for several assumed maximum propagation ranges, i.e., clear slot gap width	K-98
Figure K-133: Horizontal traffic model and signal limited results	K-102
Figure K-134: Altitude Distribution of UAT Traffic.....	K-102
Figure K-135: Calculation of LOS limit on altitude distribution of traffic in view as a function of range.....	K-103
Figure K-136: Comparison of traffic in view of a ground based receive with total UAT traffic...K-104	
Figure K-137: LOS restriction on traffic in view for a receiver at 18 kft.....	K-105
Figure K-138: LOS and signal level limits on traffic contributing to co-channel interference	K-106
Figure K-139: Altitude distribution of 1090ES equipped traffic.....	K-107
Figure K-140: Radial distribution of GBT sites in the LAX	K-109
Figure K-141: Alternate assumed GBT distributions	K-109
Figure K-142: Uniform in range GBT distribution ADS-R interference rate	K-111
Figure K-143: Comparison of total interference rates and components vs range for two GBT distribution assumptions	K-112
Figure K-144: Weighted average conversion of component Interference rates to interference signal levels and results for both assumed GBT distributions.....	K-113
Figure K-145: Message overlap probabilities and correct message decode probability in co-channel interference vs separation of signal source.....	K-115
Figure K-146: UAT receiver sensitivity model result for Class 2 source with 98 NM MTL range	K-116
Figure K-147: Probability of UAT message detection vs range at confidence levels of 50% and 95%	K-116
Figure K-148: Improved probability of UAT message detection with h = 1,2 and 3 independent tries.....	K-117
Figure K-149: UAT State Vector message update time at CL = 95% compared with ADS-B MOPS required time for Class A2 source and indicated assumptions	K-118
Figure K-150: UAT State Vector message update time at CL = 95% for a broadcast rate, b = 2 messages/second/aircraft.....	K-119
Figure K-151: UAT State Vector message update time at CL = 95% for a broadcast rate, b = 1 messages/second/aircraft and Nt = 2000 aircraft within 200 NM	K-120
Figure M-1: Short ADS-B Message Performance	M-2
Figure M-2: Long ADS-B Message Performance	M-2
Figure M-3: Ground Up Link Message Performance.....	M-3
Figure M-4: Ground Up Link Message Undetected Message Error Rate	M-4
Figure M-5: Ground Up Link Message Total Message Error Rate	M-4
Figure M-6: Logical Flow of ADS-B Reception	M-5
Figure O-1: Bendix King KD-7000 Frequency Offset Test	O-2
	O-3
Figure O-2: Bendix King KD-7000 Reply Efficiency Test.....	O-3
Figure O-3: Bendix King KD-7000 CW testing: DME level -83 dBm	O-4
Figure O-4: Narco DME-890 Frequency Offset Test.....	O-5

Figure O-5: Narco DME-890 Reply Efficiency Test.....	O-6
Figure O-6: Narco DME-890 CW testing: DME level -75 dBm.....	O-6
Figure O-7: Honeywell KDM-706A Frequency Offset Test.....	O-7
Figure O-8: Honeywell KDM-706A Reply Efficiency Test.....	O-8
Figure O-9: Honeywell KDM-706A CW testing: DME level –83 dBm.....	O-9
Figure O-10: Rockwell-Collins DME-900 Frequency Offset Test.....	O-9
Figure O-11: Rockwell-Collins DME-900 Reply Efficiency Test.....	O-10
Figure O-12: Rockwell-Collins DME-900 CW testing: DME level –83 dBm.....	O-10
Figure O-13: Comparison of all DME Frequency Offset Tests.....	O-11
Figure O-14: Comparison of all DME Reply Efficiency Tests.....	O-11
Figure O-15: Comparison of all DME CW Interference Tests.....	O-13
Figure O-16: JTIDS and UAT Combined Interference Analysis.....	O-15
Figure P-1: Possible UAT Receiver Architecture.....	P-1
Figure P-2: UAT Received Power Distribution (for 2200 users).....	P-3
Figure P-3: Message Overlap Possibilities.....	P-3
Figure P-4: Simulation Results for 200 Aircraft.....	P-5
Figure P-5: Simulation Results for 600 Aircraft.....	P-5
Figure P-6: Simulation Results for 1000 Aircraft.....	P-6
Figure P-7: Simulation Results for 1400 Aircraft.....	P-6
Figure P-8: Simulation Results for 1800 Aircraft.....	P-7
Figure P-9: Simulation Results for 2200 Aircraft.....	P-7
Figure P-10: Simulation Results for 2600 Aircraft.....	P-8
Figure P-11: Simulation Results for 3000 Aircraft.....	P-8
Figure P-12: Overall Synchronization Performance.....	P-9
Figure P-13: Fraction of Rejected Messages (Parameter is the Number of Registers).....	P-10
Figure P-14a: Percentage of Successful Overlapping Synch Sequences for Messages Received > - 94 dBm for an A2 at 40,000 ft. in CE 2015 for the Bottom Antenna.....	P-12
Figure P-14b: Percentage of Successful Overlapping Synch Sequences for Messages Received > - 94 dBm for an A2 at 40,000 ft. in CE 2015 for the Top Antenna.....	P-13
Figure U-1: VSD Algorithm Flow Chart.....	U-9

LIST OF TABLES

Table 1-1: ADS-B Optional Features	13
Table 2-1: UAT Installed Equipment Classes	19
Table 2-2: Transmitter Power Requirements	20
Table 2-3: UAT Transmit Spectrum	25
Table 2-4: Format of the Ground Uplink Message Payload	28
Table 2-5: Encoding of TIS-B SITE ID	31
Table 2-6: The Information Frame	32
Table 2-7: Frame Types	32
Table 2-8: Traffic Uplink Management Message Content	33
Table 2-9: “Service Status Bits” Field Encoding	34
Table 2-10: “Service Status” Flag Encoding	34
Table 2-11: Ground Uplink Interleaver Matrix	36
Table 2-12: ADS-B Payload Elements	37
Table 2-13: “Payload Element Subtype Number” Field	37
Table 2-14: Composition of ADS-B Payload	38
Table 2-15: Encoding of HEADER Element into ADS-B Payload	39
Table 2-16: Address Selection and Mode A Code Relationship to Address Qualifier	40
Table 2-17: “ADDRESS QUALIFIER” Field Encoding	40
Table 2-18: Format of STATE VECTOR Element	43
Table 2-19: Angular Weighted Binary Encoding of Latitude and Longitude	44
Table 2-20: “ALTITUDE TYPE” (ALT TYPE) Flag Encoding	46
Table 2-21: “ALTITUDE” Encoding	46
Table 2-22: “Navigation Integrity Category” (NIC) Field Encoding	48
Table 2-23: “Air/Ground Velocity State” (A/GV STATE) Field Encoding	50
Table 2-24: “North Velocity” Form	54
Table 2-25: “North/South Sign” Flag Encoding	55
Table 2-26: “North Velocity Magnitude” Subfield Encoding	55
Table 2-27: Ground Speed Form	56
Table 2-28: “Ground Speed” Subfield Encoding	56
Table 2-29: East Velocity Form	57
Table 2-30: “East/West Sign” Flag Encoding	57
Table 2-31: “East Velocity Magnitude” Subfield Encoding	57
Table 2-32: Track Angle/Heading Form	58
Table 2-33: “Track Angle/Heading Type” Subfield Encoding	58
Table 2-34: “Track Angle/Heading” Subfield Encoding	59
Table 2-35: Vertical Velocity Form	60
Table 2-36: “Vertical Velocity Source” (VV Src) Subfield Encoding	60
Table 2-37: “Vertical Velocity Sign” (VV Sign) Flag Encoding	60
Table 2-38: “Vertical Rate” Subfield Encoding	61
Table 2-39: Aircraft/Vehicle Size Form	62
Table 2-40: “Aircraft Length and Width” Subfield Encoding	62
Table 2-41: Lateral Axis GPS Antenna Offset Encoding	63
Table 2-42: Longitudinal Axis GPS Antenna Offset Encoding	64
Table 2-43: “UTC” Flag Encoding	64
Table 2-44: “Uplink Feedback” Field Encoding	65

Table 2-45: Format of STATE VECTOR Element (For TIS-B or ADS-R/ADS-SLR).....	66
Table 2-46: Format of MODE STATUS Element.....	67
Table 2-47: “EMITTER CATEGORY” Field Encoding.....	68
Table 2-48: “Call Sign” Character Encoding.....	69
Table 2-49: “Emergency/Priority Status” Field Encoding.....	71
Table 2-50: “Emergency/Priority Status” – Priority Order.....	73
Table 2-51: UAT MOPS Version Number.....	74
Table 2-52: “Source Integrity Level” (SIL) Encoding.....	75
Table 2-53: “System Design Assurance” (SDA) Field Encoding.....	76
Table 2-54: “Navigation Accuracy Category for Position” (NAC _P) Field Encoding.....	77
Table 2-55: “Navigation Accuracy Category for Velocity” (NAC _V) Field Encoding.....	78
Table 2-56: “CAPABILITY CODES” Encoding.....	79
Table 2-57: “OPERATIONAL MODES” Field Encoding.....	81
Table 2-58: “SIL Supplement” (SIL _{SUPP}) Flag Encoding.....	82
Table 2-59: “Geometric Vertical Accuracy” (GVA) Field Encoding.....	83
Table 2-60: “Manned/Unmanned Operation” (M/U) Field.....	84
Table 2-61: Format of AUXILIARY STATE VECTOR Element.....	84
Table 2-62: Format of TARGET STATE Element (Payload Type Codes “3” and “4”).....	85
Table 2-63: “Selected Altitude Type” (SAT) Flag.....	85
Table 2-64: “Selected Altitude” Field.....	86
Table 2-65: “Barometric Pressure Setting” (Minus 800 millibars) Field Encoding.....	87
Table 2-66: “Selected Heading” Magnitude Subfield Encoding.....	87
Table 2-67: Format of TARGET STATE Element.....	90
Table 2-68: The Payload Frame.....	91
Table 2-69: “Payload Frame Type Code” Field Encoding.....	91
Table 2-70: Possible PFTLC Values Encodings.....	91
Table 2-71: Format of UAS/RPAS Contingency P-Frame.....	93
Table 2-72: “Contingency Plan” Subfield Encoding.....	93
Table 2-73: “UAS/RPAS TCP Altitude” Subfields Encoding.....	94
Table 2-74: PIREP P-Frame Definition.....	96
Table 2-75: “PIREP Time” Encoding.....	96
Table 2-76: “Flight Visibility” Encoding.....	97
Table 2-77: “Flight Weather” Encoding.....	97
Table 2-78: “Layer Height” Encoding.....	101
Table 2-79: “Layer Thickness” Encoding.....	102
Table 2-80: “Layer Height Type” Encoding.....	102
Table 2-81: “Layer Coverage” Encoding.....	103
Table 2-82: “PIREP Air Temperature” Encoding.....	104
Table 2-83: “PIREP Wind Direction” Encoding.....	105
Table 2-84: “Turbulence Duration” Encoding.....	105
Table 2-85: “Turbulence Intensity” Encoding.....	106
Table 2-86: “Turbulence Location” Encoding.....	106
Table 2-87: “PIREP Icing” Encoding.....	108
Table 2-88: “Airspeed Change” Encoding.....	109
Table 2-89: “Wind Shear Height” Encoding.....	109
Table 2-90: “Braking Action” Encoding.....	110

Table 2-91: “Runway Number” Encoding.....	111
Table 2-92: “Runway Position” Encoding.....	111
Table 2-93: “Flight Weather Vicinity Direction” Encoding.....	113
Table 2-94: “Turbulence Type” Encoding.....	113
Table 2-95: EPISODIC Priorities and Transmission Rates	114
Table 2-96: AIREP Wind and Turbulence (Payload Element Subtype Number = 1)	116
Table 2-97: AIREP Water, Temperature, and ARV (Payload Element Subtype Number = 2)....	116
Table 2-98: AIREP Aircraft State (Payload Element Subtype Number = 3)	117
Table 2-99: “Wind Quality Indicator” Field Encoding.....	118
Table 2-100: “Wind Speed” Field Encoding	119
Table 2-101: “Wind Direction” Field Encoding.....	119
Table 2-102: “Mean EDR” Field Encoding.....	120
Table 2-103: “Peak EDR” Field Encoding	121
Table 2-104: “Peak EDR Offset” Field Encoding	121
Table 2-105: “Roll Angle” Field Encoding	122
Table 2-106: “Icing Status” Field Encoding.....	124
Table 2-107: “Air Temperature Type” Field Encoding.....	125
Table 2-108: “Air Temperature” Field Encoding	126
Table 2-109: “Airspeed Type” Field Encoding	126
Table 2-110: “Airspeed” (TAS or IAS) Field Encoding	127
Table 2-111: “Water Vapor” Field Encoding	127
Table 2-112: “Heading Type” Field Encoding	128
Table 2-113: “Heading” Field Encoding	128
Table 2-114: “Aircraft Configuration” Field Encoding.....	129
Table 2-115: “Gross Weight” Ranges and Resolutions.....	131
Table 2-116: Format of HVA STATE VECTOR Element.....	133
Table 2-117: “HVA GEOMETRIC ALTITUDE (HAE)” Encoding	135
Table 2-118: “Position Integrity Category” (PIC) Field Encoding	136
Table 2-119: HVA North Velocity Format.....	137
Table 2-120: “HVA North Velocity Magnitude” Subfield Encoding	138
Table 2-121: HVA East Velocity Format	138
Table 2-122: “HVA East Velocity Magnitude” Subfield Encoding.....	139
Table 2-123: “HVA VERTICAL VELOCITY” Field Format	140
Table 2-124: “HVA Vertical Rate” Subfield Encoding.....	140
Table 2-125: “HVA Rate” Subfield Encoding.....	141
Table 2-126: Payload Type Code Allocation.....	145
Table 2-127: HVA Payload Type Code Allocation.....	145
Table 2-128: UAT ADS-B Transmitter Input Requirements	152
Table 2-129: Selectivity Rejection Ratios	160
Table 2-130: Message-to-Completed Report Assembly Throughput Requirements.....	168
Table 2-131: Range Criteria for ADS-B Messages	169
Table 2-132: Range Criteria for Ground Uplink Messages	169
Table 2-133: Environmental Test Group Applicability	179
Table 2-134: Performance Test Requirements During Environmental Testing	181
Table 2-135: Digital Demodulation Mode Configuration	190
Table 2-136: FEC Parity Encoding for Basic ADS-B Messages.....	202

Table 2-137: FEC Parity Encoding for Long ADS-B Messages	203
Table 2-73: FEC Parity Encoding for Long ADS-B Messages (Continued).....	204
Table 2-138: ICAO Aircraft Address Encoding	210
Table 2-139: Temporary Aircraft Addresses with ICAO Aircraft Address	211
Table 2-140: Temporary Aircraft Addresses without ICAO Aircraft Address	211
Table 2-141: Latitude Encoding Values	216
Table 2-142: Longitude Encoding Values	218
Table 2-143: Latitude and Longitude Encoding Values for Data Unavailable and Data Equals ZERO Cases.....	219
Table 2-144: Altitude Field Encoding	221
Table 2-145: ON-GROUND Override Verification	230
Table 2-146: Discrete Values for Subsonic North/South Velocity.....	237
Table 2-147: Discrete Values for Supersonic North/South Velocity.....	240
Table 2-148: Discrete Values for Subsonic Ground Speed	243
Table 2-149: Discrete Values for Subsonic East/West Velocity	247
Table 2-150: Discrete Values for Supersonic East/West Velocity	250
Table 2-151: Vertical Rate Discrete Values	256
Table 2-152: “EMITTER CATEGORY” Field Encoding Test Data	262
Table 2-153: EMITTER CATEGORY And Bytes 18 & 19 Encoding Test Data.....	263
Table 2-154: Bytes 20 & 21 Encoding Test Data.....	264
Table 2-155: Bytes 22 & 23 Encoding Test Data.....	266
Table 2-156: Call Sign Encoding.....	268
Table 2-157: Geometric Vertical Accuracy Validation Values.....	284
Table 2-158: “SECONDARY ALTITUDE” Field Encoding.....	287
Table 2-159: “Selected Altitude” Field Encoding Values	290
Table 2-160: Barometric Pressure Setting Encoding Values.....	291
Table 2-161: Selected Heading Encoding Values	292
Table 2-162: Payload Type Code “11” EPISODIC Element P-Frames	321
Table 2-163: “Wind Speed” Field Encoding Test Values	324
Table 2-164: “Wind Direction” Field Encoding.....	325
Table 2-165: “Mean EDR” Field Encoding Test Values.....	326
Table 2-166: “Peak EDR” Field Encoding Test Values	327
Table 2-167: “Roll Angle” Field Encoding Test Values	330
Table 2-168: “Air Temperature” Field Encoding Test Values	336
Table 2-169: “Airspeed” (TAS or IAS) Encoding Test Values.....	340
Table 2-170: “Water Vapor” Encoding Test Values	341
Table 2-171: “Heading” Field Encoding Test Values	345
Table 2-172: “Aircraft Configuration” Field Encoding Test Values.....	348
Table 2-173: “Aircraft Type” Field Encoding Test Values	350
Table 2-174: “Gross Weight” Field Encoding Test Values.....	352
Table 2-175: “Wingspan” Field Encoding Test Values.....	354
Table 2-176: HAV “GEOMETRIC ALTITUDE” Field Encoding	360
Table 2-177: Discrete Values for HVA North/South Velocity.....	363
Table 2-178: Discrete Values for HVA East/West Velocity Magnitude.....	365
Table 2-179: Vertical Rate Discrete Values	367
Table 2-180: Payload Type and Tx Antenna Selection versus Equipment Class.....	375

Table 2-181: Payload Type and Tx Antenna Selection for HVA.....	378
Table 2-182: Payload Type with Payload Element Subtype for AIREP Capable Equipment.....	381
Table 2-183: Payload Type with Payload Element Subtype for AIREP Capable Equipment (HVA).....	381
Table 2-184: MSO Sequence Validation	384
Table 2-185: High Rate Initial MSO Sequence Validation	387
Table 2-186: 4 Transmissions per Second Subsequent MSO Sequence Validation.....	388
Table 2-187: 8 Transmissions per Second Subsequent MSO Sequence Validation.....	389
Table 2-188: UAT ADS-B Transmitter Input Requirements	392
Table 2-189: Mode A Code Input Pattern #1.....	399
Table 2-190: Mode A Code Input Pattern #2.....	404
Table 2-191: Mode A Code Input Pattern #3.....	407
Table 2-192: Vector Mode Configuration	424
Table 2-193: Signal Generator Configuration	425
Table 2-194: Selectivity Rejection Ratios	427
Table 2-195: Tx Schedule and Power Level for A3, A2 and A1H Message Sources	436
Table 2-196: Tx Schedule and Power Level for A1S, A1L and A0 Message Sources	436
Table 2-197: ADS-B Message Reception – Set 1.....	439
Table 2-198: ADS-B Message Reception – Set 2.....	443
Table 2-199: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 1.....	450
Table 2-200: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 2.....	451
Table 2-201: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 3.....	452
Table 2-202: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 4.....	453
Table 2-203: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 5.....	455
Table 2-204: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 6.....	456
Table 2-205: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 7.....	458
Table 2-206: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 8.....	459
Table 2-207: Six consecutive De-Interleaved RS Block Values of a Ground Uplink Message – Set 9.....	461
Table 3-1: Minimum Ranges for Receiving Capability.....	496
Table C-1: Transmitted Basic ADS-B Message Data Byte #.....	C-2
Table C-1: Example of Basic ADS-B Message Payloads	C-3
Table C-2: Example of Long Type 1 ADS-B Message Payloads.....	C-5
Table C-3: Transmitted Long Type 1 ADS-B Message Data Bytes #.....	C-6
Table E-1: Typical Antennas	E-4
Table E-2: Diplexer Testing with ATC Transponders.....	E-8
Table F-1: Air-To-Air Link Budgets	F-1
Table G-1: Signal Level Analysis of the Sample Scenario.....	G-4

Table G-2: Interference Scenarios and Implementation Assumptions	G-1
Table G-3: Received Power Levels (dBm) for Current European DME/TACAN Environment	G-2
Table G-4: Received Power Levels (dBm) for 2015 European DME/TACAN Environment	G-2
Table G-5: Co-site Environment.....	G-2
Table G-6: Overview of Scenario Assessments.....	G-1
Table I-1: Transmitter to Receiver Time Offset Worst Case.....	I-2
Table J-1: Report Format.....	J-1
Table J-2: Report Packet Types	J-2
Table K-1: Ranges of ADS-B MASPS Compliance for UAT Transmit-Receive Combinations in the LA2020 Scenario	K-34
Table K-2: Ranges of ADS-B MASPS Compliance for UAT Transmit-Receive Combinations in CE 2015 Scenario	K-73
Table K-3: Acquisition Requirements	K-76
Table K-4: 99 th Percentile Range for Information Acquisition for Various Combinations of Transmit-Receive Pairs (NM).....	K-77
Table K-5: 99 th Percentile Air-Ground Acquisition Ranges for Both Scenarios.....	K-78
Table K-6: 99 th Percentile Air-Air Acquisition Ranges for LA2020 Scenario.....	K-78
Table K-7: 99 th Percentile Air-Air Acquisition Ranges for CE2015 Scenario.....	K-78
Table K-8: 99 th Percentile Air-Air Acquisition Ranges for CE2015 Scenario.....	K-79
Table K-9: 95% Update Interval for Scenario 1 as a Function of Range and Transmit Power..	K-93
Table K-10: 95% Update Interval for Scenario 2a as a Function of Multipath Effect and Ground Transmissions	K-94
Table K-11: 95% Update Interval for Scenario 2b as a Function of Multipath Effect and Ground Transmissions	K-94
Table M-1: Maximum Undetected RS Word Error Rates	M-1
Table M-2: Upper Bounds on Undetected Message Error Probabilities	M-7
Table N-1: Files Associated with Test Procedures.....	N-1
Table R-1: Version 2 versus Version 1 Message Fields.....	R-1
Table R-2: Version 1 and 2 “Emitter Category” Decoding.....	R-2
Table R-3: Version 1 and 2 “Emergency/Priority Status” Decoding	R-3
Table R-4: Version 1 “SIL” Decoding.....	R-4
Table R-5: Version 3 versus Version 2 Message Fields.....	R-5
Table U-1: GNSS Sensor Data	U-1
Table U-2: Air Data	U-1
Table U-3: Persistent Data.....	U-2
Table V-1: Aircraft Characteristics.....	V-1
Table V-2: Takeoff Test Vectors	V-3
Table V-3: Landing Test Vectors	V-3
Table V-4: Landing and Takeoff Test Vectors.....	V-4
Table V-5: En Route Test Vectors.....	V-4
Table V-6: Taxi Test Vectors	V-4

1 PURPOSE AND SCOPE

1.1 Introduction

This document contains Minimum Operational Performance Standards for airborne equipment to support Automatic Dependent Surveillance - Broadcast (ADS-B) utilizing the Universal Access Transceiver (UAT). ADS-B is a system by which aircraft and certain equipped surface vehicles can share position, velocity, in-situ weather, and other information with one another (and also with ground-based facilities/fixed locations such as air traffic services) via radio broadcast techniques. UAT is a multi-purpose aeronautical data link intended to support not only ADS-B, but also Flight Information Service - Broadcast (FIS-B), Traffic Information Service - Broadcast (TIS-B), ADS-B Rebroadcast (ADS-R), ADS-B Same Link Rebroadcast (ADS-SLR) and, potential future capabilities. While UAT has been expressly designed as a multi-purpose data link for surveillance-related applications, the focus of this document is on its support of ADS-B and basic ground uplink capabilities.

The standards contained in this document specify desired system characteristics that should prove useful to designers, manufacturers, installers and users of UAT equipment. Compliance with these standards is recommended as one means of ensuring that the equipment will satisfactorily perform its intended functions under conditions normally encountered in routine aeronautical operations. Some or all of these standards could be referenced by appropriate government agencies for certification and operational approval. Such regulatory application of any part of this document is solely the responsibility of appropriate government agencies. Version C of these MOPS (RTCA DO-282C) reflects additional operational experience with UAT, lessons learned in certification of UAT equipment, and further inputs from the International aviation community during the development of International Civil Aviation Organization (ICAO) Standards and Recommended Practices (SARPs) for UAT.

Note: The use of “shall” in the body of this document indicates a requirement. The use of “should” indicates a characteristic that is highly recommended but is not required.

Since the basic equipment implementation includes computer processing, RTCA DO-178(), Software Considerations in Airborne Systems and Equipment Certification, should be considered. Application of the software requirements of RTCA DO-178() should take into account the level of criticality of supported functions, consequences of equipment failure, and the presence and effectiveness of back-up and fault-monitoring features.

Section 1 of this document provides information and assumptions needed to understand the rationale for the equipment characteristics and requirements in this document. A high-level technical description of ADS-B and the UAT data link is provided, including the ability of UAT to support FIS-B, TIS-B, ADS-R/ADS-SLR, and independent ranging. This section forms the basis for the standards stated in Sections 2 through 4.