

RTCA, Inc.  
1150 18th Street, NW, Suite 910  
Washington, DC 20036-4001  
USA

**Feasibility Study**  
**Airborne LIDAR for Clear Air Turbulence**  
**Detection**

RTCA FS-2  
June 11, 2020

Prepared by: SC-230  
© 2020 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: [www.rtca.org](http://www.rtca.org)

Please visit the RTCA Online Store for document pricing and ordering information.

## **FOREWORD**

This feasibility study was prepared by Special Committee 230 (SC-230) and approved by the RTCA Program Management Committee (PMC) on June 11, 2020.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organization's recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders and several advisory circulars.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

## **DISCLAIMER**

This publication is based on material submitted by various participants during the SC approval process. Neither the SC nor RTCA has made any determination whether these materials could be subject to valid claims of patent, copyright or other proprietary rights by third parties, and no representation or warranty, expressed or implied is made in this regard. Any use of or reliance on this document shall constitute an acceptance thereof "as is" and be subject to this disclaimer.

This Page Intentionally Left Blank

## EXECUTIVE SUMMARY

RTCA Special Committee 230 was tasked with assessing and documenting the maturity and the feasibility of using an airborne Light Detection and Ranging (LIDAR) system for detection of clear air turbulence (CAT).

This feasibility study document details the context of the study and a description of the intended function (situational display of regions ahead of the aircraft that present potential hazards to the aircraft due to clear air turbulence). Its goals are:

- To determine realistic goals for an airborne LIDAR system when used for clear air turbulence detection.
- To determine aircraft manufacturer needs for an airborne LIDAR clear air detection function.
- To determine the feasibility that LIDAR systems can meet aircraft manufacturer needs.

Aircraft manufacturers have expressed the following operational goals for a LIDAR-based CAT detection function:

- A minimum detection range of 12 NM, in order to provide at least 90 seconds to secure the majority of passengers and crew.
- An angular display extent of +/- 25 degrees from the aircraft's longitudinal axis or track.
- Consistency with WXR-based ATA or Turbulence functions for:
  - Display thresholds
  - Precision/refresh rates
  - Must and must-not detection requirements

### CAT Detection

SNR analysis was performed on two types of LIDAR systems, with the following results:

- **Coherent LIDAR:** Existing coherent LIDAR systems are not able to meet the OEM's requirements for long range CAT detection at high altitude (around 32,000 ft), although it may be possible to meet these requirements at lower altitudes. Although many experimental demonstrations of CAT detection have been shown in the past, further research is needed in the area of LIDAR transmitters if coherent LIDAR systems are to be used for airborne CAT detection.
- **Direct Detection LIDAR:** Direct detection LIDAR systems with state-of-the-art laser power, telescope sizes, and detection equipment may be able to detect moderate to severe clear air turbulence for all altitudes up to 39,000 ft. Numerical simulations suggest that the direct detection LIDAR can meet OEM requirements. Further research and flight tests are needed to substantiate the simulations.

## Gust Load Alleviation

Using the same SNR analysis, LIDAR manufacturers concluded that it may be feasible to meet OEM requirements for gust load alleviation. Analysis indicates that when enough aerosols are present in the atmosphere, coherent LIDAR systems with lower output power have comparable performance to much higher-powered direct detection LIDAR systems. However, areas that are low in aerosol content will be challenging for coherent LIDAR systems.

## AUTHORS

Venkata Sishtla (Working Group Co-Chair)	Collins Aerospace
Shumpei Kameyama (Working Group Co-Chair)	Mitsubishi Electric
Jeff Finley (SC-230 Co-Chair)	Collins Aerospace
Dawn Gidner (SC-230 Co-Chair)	Honeywell International, Inc.
Lee Nguyen (Government Authorized Representative)	Federal Aviation Administration (FAA)
Karan Hofmann (Program Director)	RTCA, Inc.
Jean Baptiste Berthier	Airbus
Thibault Lefez	Airbus
Xiao Zhu Fan	Honeywell International, Inc.
Grady Koch	NASA
Ivan Clark	NASA
Shigeru Machida	Japan Aerospace Exploration Agency (JAXA)
Yukun (Kenny) Ren	The Boeing Company
Luke Tschacher	The Boeing Company
Patrick Vrancken	DLR

This Page Intentionally Left Blank

## **GUIDELINES**

This document uses a structure similar to a Minimal Operational Performance Standard (MOPS). It will assess and document the maturity and the feasibility of using airborne LIDAR for clear air turbulence (CAT) detection. The content has not been written as requirements (no “shall” statements). It considers existing functions and their criticality.

This Page Intentionally Left Blank

## TABLE OF CONTENTS

<b>1.INTRODUCTION/CONTEXT.....</b>	<b>1</b>
1.1 Background .....	1
1.2 Impacts of Turbulence on Aviation.....	2
1.2.1 Safety Impacts.....	2
1.2.2 Economic Impacts.....	4
1.3 CAT Pilot Reports .....	5
1.4 CAT Projects and Flight Test Campaigns .....	5
1.4.1 The First Airborne LIDAR for Clear Air Turbulence Detection .....	5
1.4.2 Projects & Campaigns in The United States .....	6
1.4.3 Projects & Campaigns in Europe .....	7
1.4.4 Projects & Campaigns in Japan.....	7
1.5 LIDAR Technology for CAT Detection.....	8
1.5.1 Wind Sensing Coherent Doppler LIDAR .....	8
1.5.2 Wind sensing direct-detection Doppler LIDAR.....	9
1.5.3 Air Density Fluctuation Sensing Direct-Detection LIDAR .....	10
<b>2. REFERENCES &amp; DEFINITIONS.....</b>	<b>13</b>
2.1 References .....	13
2.2 Acronyms, Initialisms, and Definitions.....	19
<b>3. DEFINITION OF INTENDED FUNCTION.....</b>	<b>23</b>
3.1 Functional Hazard Analysis (FHA) recommendations .....	23
<b>4. OPERATIONAL AND PERFORMANCE GOALS .....</b>	<b>25</b>
4.1 Operational Needs .....	25
4.1.1 Conceptual Operational Goals .....	25
4.1.2 Altitude, Temperature, and Flight Phase.....	25
4.1.3 Geographic Localization .....	25
4.1.4 Range .....	25
4.1.5 Non-interference .....	26
4.1.6 Definition of Thresholds for CAT.....	26
4.1.7 Nuisance/Missed Annunciation Rate .....	26
4.1.8 CAT Detection Envelope .....	26
4.1.9 Retrofit .....	26
4.2 Other LIDAR applications .....	27
4.2.1 Gust Load alleviation .....	27
4.2.2 Wake Turbulence .....	27
4.2.3 Particle (Volcanic Ash) Detection.....	27
4.2.4 Weather Hazard / Windshear Detection.....	27
4.2.5 Air Data.....	28
4.2.6 Meteorological Observations .....	28

<b>5.</b>	<b>LIDAR COMPLIANCE WITH OPERATIONAL AND PERFORMANCE GOALS.....</b>	<b>30</b>
5.1	Past Accomplishments.....	30
5.1.1	Wind Sensing Coherent Doppler LIDAR for CAT detection .....	30
5.1.2	Wind Sensing Direct-Detection Doppler LIDAR .....	41
5.1.3	Air Density fluctuation sensing Direct-Detection LIDAR.....	42
5.1.4	Summary of Past Accomplishments .....	44
5.2	Preliminary Simulation Study on Coherent and Direct-Detection LIDAR to Meet the Aircraft OEM’s Needs for High-Altitude Application.....	46
5.2.1	Atmospheric Parameters .....	46
5.2.2	Parameter Study on Coherent LIDAR .....	47
5.2.3	Direct-Detection LIDAR for CAT Detection Sensitivity.....	55
5.2.4	Gust Load Alleviation with Direct-Detection Doppler Wind LIDAR.....	65
5.2.5	Discussion on Direct Detection LIDAR.....	70
5.3	Compliance Matrix.....	74
<b>6.</b>	<b>VALIDATION AND VERIFICATION STRATEGY.....</b>	<b>77</b>
6.1	Validation .....	77
6.2	Verification.....	77
<b>7.</b>	<b>DISPLAY SYMBOLOGY CONCEPTS.....</b>	<b>79</b>
7.1	Current Standards for Display of Meteorological Information .....	79
7.2	Display Constraints .....	79
7.2.1	Color Availability.....	79
7.2.2	Display Protocols .....	80
7.2.3	Existing WXR Display Symbology .....	80
7.3	Other Constraints.....	85
7.4	CAT Display Symbology Recommendations.....	86
7.4.1	Concepts Considered.....	86
7.4.2	CAT Display Symbology Layering.....	87
7.5	Recommended Display Symbology .....	87
7.6	Human Factors Perspective .....	88
<b>8.</b>	<b>WAY FORWARD AND RECOMMENDATIONS.....</b>	<b>89</b>
8.1	Conclusions .....	89
8.1.1	CAT Detection .....	89
8.1.2	Gust Load Alleviation.....	89
8.2	Recommendations .....	89
8.2.1	CAT Detection .....	89
8.2.2	Gust Load Alleviation.....	90
	<b>APPENDIX A: VOICES FROM JAPANESE AIRLINES.....</b>	<b>A-1</b>

## TABLE OF TABLES

Table 1-1: Flight Operations for Each Type of Atmospheric Hazard (1987-2011) [8] .....	3
Table 4-1: Relation Between the Aircraft Class, Wing Loading, and Minimum Performance Level .....	26
Table 5-1: Representative Atmospheric Parameters Used in the LIDAR Feasibility Study [2] .....	47
Table 5-2: Example of LIDAR Parameters.....	50
Table 5-3: Required Pulse energy for the Laser Transmitter for Various Altitudes and Detection Probabilities .....	51
Table 5-4: Example of LIDAR Parameters.....	53
Table 5-5: Parameters Used for the Derivation of Direct-Detection SNR.....	64
Table 5-6: Settings for the Calculation of DWL <i>P.A.P.</i> .....	69
Table 5-7: Lidar Compliance with Operational and Performance Goals.....	74
Table 7-1: Existing Display Symbology – Company One Weather Radar.....	80
Table 7-2: Existing Display Symbology on Company Two Radar.....	82
Table 7-3: Display Symbology Considered.....	86

## TABLE OF FIGURES

Figure 1-1: Illustration of Polar and Subtropical Jet Streams and Their Relative Location Around the Globe [5].....	1
Figure 1-2: Kelvin-Helmholtz Instability .....	2
Figure 1-3: Turbulence Types in Part 121 Accidents: 2008-2016.....	3
Figure 1-4: Phase of Flight for Part 121 Turbulence Accidents: 2008-2016 [14] .....	3
Figure 1-5: Injuries Due to Turbulence [19].....	5
Figure 1-6: Example of System Configuration of Wind Sensing Coherent Doppler LIDAR [37].....	9
Figure 1-7: Optical Spectrum of Mie and Rayleigh Scattering Regions [43].....	10
Figure 1-8: Example of System Configuration of Wind Sensing Direct Detection Doppler LIDAR [43] .	10
Figure 1-9: Turbulence Indication Within Received Signal [45].....	11
Figure 5-1: National Integrated Windshear Program: NASA Research Aircraft and LIDAR Sensor Head [1].....	30
Figure 5-2: National Integrated Windshear Program: Example of Wind Sensing Results (altitude: 500 m) [25].....	31
Figure 5-3: Overview of ACLAIM LIDAR and its Installation [29].....	31
Figure 5-4: Time Chart of Measurable Distance in ACLAIM Project (altitude: 13500 ft) [29].....	32
Figure 5-5: Demonstration of Moderate CAT detection [29] .....	32
Figure 5-6: Example of Wake Vortex Detection in DLR’s Project (altitude: unknown) [40].....	33
Figure 5-7: ONERA:LIDAR-based Detection [41] .....	33
Figure 5-8: ONERA: Example of Wake Vortex Sensing [41].....	34
Figure 5-9: JAXA’s Flight Test Campaign with Compact LIDAR [47].....	34
Figure 5-10: JAXA: Example of Wind Shear Detection (altitude: 600 m) [47] .....	35
Figure 5-11: JAXA: Example of Turbulence Detection Using Fh-factor (altitude: 1200 m) [47] .....	35
Figure 5-12: JAXA: Overview of Flight Test Campaign Using Improved LIDAR [49].....	36
Figure 5-13: JAXA: Turbulence Detection at a Long Distance (altitude: 2,000 ft) [49].....	36
Figure 5-14: JAXA: Long Range Wind Sensing (altitude: 5,000 ft) [49].....	36
Figure 5-15: JAXA: Wind Sensing at High Altitude (altitude: 28,700 ft) [49] .....	36
Figure 5-16: JAXA: Turbulence Detection at Middle Altitude (altitude: 10,500 ft) [50].....	37
Figure 5-17: JAXA: Weak Turbulence Detection at High Altitude (altitude: 40,000 ft) [50].....	37
Figure 5-18: JAXA: LIDAR Developed by SA Project (weight: 83.7 kg) [51] .....	38
Figure 5-19: JAXA: Detection Distance in the SA Project Flight Test Campaign [51] .....	38
Figure 5-20: JAXA: Example of Wind Shear Detection in SA Project (altitude: below 3,000 ft) [52].....	38
Figure 5-21: JAXA: Example of Turbulence Detection in SA Project (altitude: below 3,000 ft) [52] .....	39
Figure 5-22: JAXA SA Project Display Concepts [52] .....	39
Figure 5-23: JAXA SA Project Display System Installation [52] .....	40
Figure 5-24: JAXA’s Full Flight Simulator [52] .....	40
Figure 5-25: JAXA SA Project: Verified Usefulness of the Developed Display [52].....	40
Figure 5-26: AWIATOR LIDAR Installation in the Aircraft [42].....	41
Figure 5-27: Airbus A340 Aircraft with AWIATOR LIDAR [43].....	41
Figure 5-28: AWIATOR: Wind Sensing Demonstration at High Altitude [43] .....	42
Figure 5-29: Photo of the First Airborne CAT Sensing LIDAR [22] .....	42
Figure 5-30: First Evidence of the CAT (aircraft wake) Detection Using Airborne LIDAR (altitude: below 10,000 ft) [22] .....	43
Figure 5-31: DELICAT LIDAR [44].....	43
Figure 5-32: Map Showing Flights Made During DELICAT Flight Test Campaign [45] .....	44
Figure 5-33: DELICAT LIDAR: Distance Dependence of Signal to Noise Ratio [44].....	44
Figure 5-34: Schematic of Steps for the Feasibility Study .....	46
Figure 5-35: Schematic of Detectability .....	49

Figure 5-36: Example of Distance Dependence of Detectability.....	50
Figure 5-37: Predicted Performance of JAXA SafeAvio LIDAR .....	51
Figure 5-38: Example of Distance Dependence of Detectability.....	52
Figure 5-39: Radar-Measured and LIDAR-Measured Spectrum.....	54
Figure 5-40: Calculation Process for CAT Detection Probability .....	55
Figure 5-41: Procedure for Direct-Detection LIDAR Analysis .....	55
Figure 5-42: ICAO Turbulence Levels and Resulting Air Density Fluctuations by Equations (8) and (10) .....	57
Figure 5-43: Backscatter Ratio for 355 nm LIDAR for Relevant Altitudes .....	58
Figure 5-44: Setup for Density-Technique Turbulence LIDAR .....	58
Figure 5-45: Fabry-Perot and Michelson Response Functions [75]. .....	59
Figure 5-46: Calculated Power-Aperture-Product for Given Requirements.....	61
Figure 5-47: Trading Laser Power Against Receiver Telescope Diameter .....	63
Figure 5-48: Scanning Geometry Parameters Comparison.....	65
Figure 5-49: Scanning Geometry Parameters .....	66
Figure 5-50: P.A.P. Required for Single-vector Direct-Detection DWL for Gust Load Alleviation .....	67
Figure 5-51: Range Dependency of the Determined P.A.P. for Two Values of CAT Severity (EDR) .....	71
Figure 5-52: Scanning Geometry Derived from Radar Setups .....	72
Figure 5-53: Altitude-Dependent “Atmospheric Gain Factor” in Eq. (19) and (20) .....	73
Figure 7-1: Display Example from Company One WXR (MultiScan V2).....	82
Figure 7-2: Display Example from Company Two WXR .....	85
Figure 7-3: Display Example from Company Two Navigation Display on Synthetic MAP.....	86
Figure 7-4: Examples of WXR Based Turbulence Symbology .....	88

This Page Intentionally Left Blank

## 1. INTRODUCTION/CONTEXT

### 1.1 Background

One of the most significant forms of threat to an aircraft comes in the form of turbulence. Clear air turbulence (CAT), which is usually encountered in cloud-free regions at high-altitudes (~20,000 ft – 50,000 ft) outside of convective regions, can be sudden and severe. CAT is a recognized problem which impacts all aircraft operations. This phenomenon is especially troublesome because it is often encountered unexpectedly, and frequently does not provide visual clues to warn the pilots of the hazard.


Per the FAA Advisory Circular on Clear Air Turbulence Avoidance, AC 00-30C [5]:

CAT is defined as “sudden severe turbulence occurring in cloudless regions that causes violent buffeting of aircraft.” This term is commonly applied to higher altitude turbulence associated with wind shear. The most comprehensive definition is high-altitude turbulence encountered outside of convective clouds. This includes turbulence in cirrus clouds, within and in the vicinity of standing lenticular clouds and, in some cases, in clear air in the vicinity of thunderstorms. Generally, though, CAT definitions exclude turbulence caused by thunderstorms, low-altitude temperature inversions, thermals, strong surface winds, or local terrain features.

Historically, Light Detection and Ranging (LIDAR) sensors have been shown to detect various atmospheric phenomenon including but not limited to: mountain wave induced turbulence, low altitude rotors, volcanic ash, high altitude ice crystals, low level Windshear, etc.

The scope of this report includes the detection of moderate or greater turbulence. It also addresses detection of turbulence due to terrain features such as mountain waves, low altitude rotors, and convectively induced turbulence in cloud-free regions.

One of the principal areas where CAT is found is in the vicinity of jet streams. Jet streams are relatively narrow bands of strong wind in the upper levels of the atmosphere. In jet streams, winds blow from west to east, but the flow meanders southward and northward in waves. Jet streams follow the boundaries between hot and cold air. Because these hot and cold air boundaries are most pronounced in winter, jet streams are strongest in winter in both the northern and southern hemispheres. One noteworthy generator of CAT is the confluence of two jet streams. The wind shear effect between two jet streams in the region of confluence and immediately downstream is often highly turbulent.



**Figure 1-1: Illustration of Polar and Subtropical Jet Streams and Their Relative Location Around the Globe [5]**

Another phenomenon that can cause CAT is Kelvin-Helmholtz instability. This instability can occur when there is a velocity shear in a single contiguous fluid, or when there is a vertical velocity difference across