

RTCA, Inc.
1150 18th Street NW, Suite 910
Washington, DC 20036
USA

**Minimum Operational Performance Standards for
Airborne Collision Avoidance System X (ACAS X)
(ACAS Xa and ACAS Xo)**

Volume I and II

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

FOREWORD

This document was prepared jointly by Special Committee 147 (SC-147) and EUROCAE Working Group 75(WG-75). It was approved by the RTCA Program Management Committee (PMC) on September 20, 2018 and by the EUROCAE Council on October 2, 2018.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organization's recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders and several advisory circulars.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

DISCLAIMER

This publication is based on material submitted by various participants during the SC approval process. Neither the SC nor RTCA has made any determination whether these materials could be subject to valid claims of patent, copyright or other proprietary rights by third parties, and no representation or warranty, expressed or implied is made in this regard. Any use of or reliance on this document shall constitute an acceptance thereof "as is" and be subject to this disclaimer.

This Page Intentionally Left Blank

TABLE OF CONTENTS

1	PURPOSE AND SCOPE	1
1.1	Introduction.....	1
1.1.1	Document Structure.....	1
1.1.2	Operational Goals.....	2
1.1.2.1	Operation of ACAS X on the Airport Surface.....	2
1.1.3	Equipment	3
1.1.3.1	ACAS X Equipment Classes and Article Designations.....	3
1.1.3.2	Aircraft Equipment Information Vulnerabilities.....	5
1.2	Background.....	6
1.2.1	Collision Avoidance Systems.....	6
1.2.1.1	TCAS II.....	6
1.2.1.2	ACAS X.....	7
1.2.1.2.1	ACAS Xa/Xo.....	7
1.2.1.2.2	ACAS Xu	8
1.3	System Overview	8
1.3.1	Surveillance and Tracking.....	8
1.3.2	Threat Resolution	9
1.3.3	Coordinating RAs Against ACAS-Equipped Threats	9
1.3.3.1	Future Coordination Schemes.....	10
1.3.3.2	Multiple Threats, Sense and Intent, and Reversals	11
1.3.4	Control of Interference Caused by Active Surveillance	11
1.3.5	Provision of RA Information to Ground Systems	12
1.3.6	Hybrid Surveillance and Extended Hybrid Surveillance.....	12
1.3.6.1	Overview.....	12
1.3.6.2	Description.....	12
1.3.6.2.1	Use When Airborne.....	14
1.3.6.2.2	Use When On The Ground.....	15
1.3.7	ACAS Xo functionality	16
1.4	Assumptions and Limitations	16
1.4.1	Operational	16
1.4.1.1	Airworthiness.....	16
1.4.1.2	Improvements or Alternative Techniques.....	16
1.4.2	Environment	16
1.4.2.1	Transponders.....	17
1.4.2.2	ADS-B Systems	17
1.4.2.3	Integration with ASA Systems.....	17
1.4.2.4	Interoperability with Onboard Aircraft Systems.....	17
1.4.2.5	Ownship Capability	17
1.4.2.5.1	Barometric Altimetry System.....	17
1.4.2.5.2	Mode S Transponder	18
1.4.2.5.3	Ownship Position Source	18
1.4.2.5.4	Aircraft Discretes	18
1.4.2.5.5	Radio Altimeter	18
1.4.2.5.6	Heading	18
1.4.3	Human.....	19
1.4.3.1	Pilot Actions	19
1.4.3.1.1	Existing TCAS Pilot Responsibilities	19

1.4.3.2	Interaction With ATC	20
1.4.3.3	Use of ACAS X With Other Onboard Traffic Alerting Systems	20
1.5	Test Procedures	20
1.5.1	Environmental Tests	20
1.5.2	Bench Tests	21
1.5.3	Installed System Tests	21
1.5.4	Computer Performance Verification Test	21
1.5.5	Interoperability	21
1.6	Configuration Control, Security and Distribution of the ACAS X Electronic Products.....	22
1.6.1	Configuration Control, Security and Distribution of ACAS X Parameter Data Item Files	22
1.6.1.1	Purpose.....	22
1.6.1.2	Overview and Guidelines.....	22
1.6.1.3	PDIF Details	23
1.6.2	Additional Electronic Products	23
1.7	Glossary of Terms.....	23
1.8	Abbreviations.....	31
1.9	References.....	34
2	ACAS X EQUIPMENT REQUIREMENTS AND TEST PROCEDURES.....	37
2.1	General Requirements.....	37
2.1.1	Airworthiness	37
2.1.2	General Performance.....	37
2.1.3	Federal Communications Commission Rules	37
2.1.4	Self-Test	37
2.1.5	Performance Monitoring	37
2.1.6	Interrogation Test Modes	37
2.1.7	Controls	38
2.1.7.1	Operation of Controls	38
2.1.7.2	Minimum Flight Crew Control Functions	38
2.1.8	Display Functions.....	39
2.1.8.1	Minimum Display Functions	39
2.1.9	Equipment Configuration.....	39
2.1.10	Mode S Transponder Capabilities	39
2.1.10.1	Performance Compatibility with Ownship ACAS X.....	39
2.1.11	ACAS X Combined with Other Aircraft Systems.....	40
2.1.12	Aural Annunciation	40
2.1.13	Shared Use of 1090 MHz Receiver with an ADS-B Receiving Subsystem.....	40
2.2	Minimum Performance Standards	40
2.2.1	Definition Of Standard Conditions.....	41
2.2.1.1	Measurement Conventions.....	41
2.2.1.2	Operational Environment.....	41
2.2.1.2.1	Aircraft Density.....	41
2.2.1.2.2	Aircraft Equipage	42
2.2.1.2.3	Interrogator Environment.....	42
2.2.1.2.3.1	Maximum ATCRBS Fruit Rate	43
2.2.1.2.3.2	Maximum Mode S FRUIT Rate	43
2.2.1.2.3.3	Maximum Co-Site Transmitter Rate.....	43
2.2.1.2.3.4	Intruder Transponder Availability	43

2.2.1.2.3.5	Mode S Transponder Compatibility.....	44
2.2.1.2.4	Maximum Level Of ATCRBS Synchronous Garble Interference.....	44
2.2.1.2.5	Maximum Level Of Multipath Interference.....	44
2.2.1.2.5.1	Transponder Reply.....	44
2.2.1.2.5.2	ACAS X Interrogation.....	45
2.2.1.3	Target-Of-Interest.....	45
2.2.1.3.1	Maximum Closing Speed.....	45
2.2.1.3.2	Closing Speed As A Function Of Azimuth.....	45
2.2.1.3.3	Elevation Angle Relative To ACAS X.....	46
2.2.1.3.4	Altitude Relative To ACAS X.....	46
2.2.1.3.5	Minimum AGL Altitude.....	46
2.2.2	System Performance.....	46
2.2.2.1	Surveillance Range.....	46
2.2.2.1.1	For Generation Of RAs.....	46
2.2.2.1.2	For Generation Of TAs.....	47
2.2.2.2	Surveillance Performance Objectives.....	47
2.2.2.2.1	General Surveillance Performance.....	47
2.2.2.2.1.1	Probability Of Track.....	47
2.2.2.2.1.2	False Track Rate.....	47
2.2.2.2.2	Flight Test Surveillance Performance.....	48
2.2.2.2.3	Range Accuracy.....	48
2.2.2.2.4	Bearing Accuracy.....	48
2.2.3	Compatibility With Other Systems.....	48
2.2.3.1	Radiated Output Power.....	49
2.2.3.2	Unwanted Output Power.....	49
2.2.3.3	Interrogation Spectrum.....	49
2.2.3.4	Interrogation Jitter.....	50
2.2.3.5	Transmit Frequency And Tolerance.....	50
2.2.3.6	Interference Limiting.....	50
2.2.3.6.1	Interference Limiting Formulas.....	50
2.2.3.6.2	Interference Limiting Procedures.....	53
2.2.3.6.3	Interrogations From ACAS X On The Ground.....	54
2.2.3.6.4	Interrogations From ACAS X Above 18,000 Ft Barometric Altitude.....	55
2.2.3.7	Transmit Pulse Characteristics.....	56
2.2.3.7.1	Mode C Transmissions.....	56
2.2.3.7.2	Mode S Transmissions.....	57
2.2.3.8	Mode S Message Field Formats.....	58
2.2.3.8.1	Data Blocks.....	58
2.2.3.8.2	Format Structure.....	59
2.2.3.8.2.1	Bit Numbering and Sequence.....	59
2.2.3.8.2.2	Fields.....	59
2.2.3.8.2.2.1	Essential Fields.....	59
2.2.3.8.2.2.2	Mission Fields.....	61
2.2.3.8.2.2.3	Subfields.....	62
2.2.3.8.3	Field Descriptions.....	62
2.2.3.8.3.1	Fields and Subfields Defined by Reference B.....	65
2.2.3.8.3.1.1	AA Address, Announced.....	65
2.2.3.8.3.1.2	AC Altitude Code.....	65
2.2.3.8.3.1.3	AQ Acquisition, Special.....	66
2.2.3.8.3.1.4	BDS: Comm-B Data Selector.....	66
2.2.3.8.3.1.5	CA Capability.....	67
2.2.3.8.3.1.6	CC Crosslink Capability.....	67
2.2.3.8.3.1.7	DR Downlink Request.....	67
2.2.3.8.3.1.8	FS Flight Status.....	68

2.2.3.8.3.1.9	MA Message, Comm-A	68
2.2.3.8.3.1.10	MB Message, Comm-B	68
2.2.3.8.3.1.11	ME Message, Extended Squitter	68
2.2.3.8.3.1.12	MU Message, Comm-U	69
2.2.3.8.3.1.13	MV Message, Comm-V	69
2.2.3.8.3.1.14	RI Air-to-Air Reply Information	69
2.2.3.8.3.1.15	RL Reply Length	70
2.2.3.8.3.1.16	RR Reply Request	70
2.2.3.8.3.1.17	SD Special Designator	70
2.2.3.8.3.1.18	VS Vertical Status	70
2.2.3.8.3.2	ACAS X Fields and Subfields	71
2.2.3.8.3.2.1	Subparagraph Not Used	71
2.2.3.8.3.2.2	MA Fields Used by ACAS X	71
2.2.3.8.3.2.3	MB Fields Used by ACAS X	71
2.2.3.8.3.2.3.1	Subfields in MB for RA Report	71
2.2.3.8.3.2.3.2	Subfields in MB for Data Link Capability Report	77
2.2.3.8.3.2.3.2.1	Coding of Data Link Capability Report	77
2.2.3.8.3.2.4	MU Fields Used by ACAS X	78
2.2.3.8.3.2.4.1	Subfields in MU for a TCAS Resolution Message	78
2.2.3.8.3.2.4.2	Subfields in MU for a TCAS Broadcast Interrogation Message	82
2.2.3.8.3.2.4.3	Subfields in MU for an RA Broadcast Interrogation Message	82
2.2.3.8.3.2.5	MV Fields Used by ACAS X	83
2.2.3.8.3.2.5.1	Subfields in MV for a Coordination Reply Message	83
2.2.3.8.3.2.6	SL TCAS II Sensitivity Level Report	84
2.2.3.8.3.2.7	Unassigned Coding Space	85
2.2.3.8.3.2.8	ME Fields Used by ACAS X for Passive Surveillance	85
2.2.3.8.3.2.8.1	TYPE Subfield of the ME Field	86
2.2.3.8.3.2.8.2	Altitude from Airborne Position Message	86
2.2.3.8.3.2.8.3	CPR Format from Airborne Position Message	87
2.2.3.8.3.2.8.4	Encoded Latitude from Airborne Position Message	87
2.2.3.8.3.2.8.5	Encoded Longitude from Airborne Position Message	87
2.2.3.8.3.2.8.6	ADS-B Version Number from Aircraft Operational Status Message	87
2.2.3.8.3.2.8.7	Navigational Integrity Category (NIC) from Airborne Position Message	87
2.2.3.8.3.2.8.8	Navigation Accuracy Category for Position (NACp)	88
2.2.3.8.3.2.8.8.1	NACp from Aircraft Operational Status Message	88
2.2.3.8.3.2.8.8.2	NACp from Target State and Status Message	88
2.2.3.8.3.2.8.9	Source Integrity Level (SIL)	88
2.2.3.8.3.2.8.9.1	SIL from Aircraft Operational Status Message	88
2.2.3.8.3.2.8.9.2	SIL from Target State and Status Message	88
2.2.3.8.3.2.8.10	System Design Assurance (SDA)	88
2.2.3.8.3.2.8.11	CPR Format from Surface Position Message	88
2.2.3.8.3.2.8.12	Encoded Latitude from Surface Position Message	89
2.2.3.8.3.2.8.13	Encoded Longitude from Surface Position Message	89
2.2.3.8.3.2.9	ME Fields Used by ACAS X for Air-to-Air Coordination	89
2.2.3.8.3.2.9.1	Subfields in ME for Operational Coordination Message	89
2.2.3.8.3.2.9.2	Subfields in ME for Aircraft Operational Status Message	91
2.2.3.8.3.2.10	ME Fields Used by ACAS X for Communication of RA Information	93
2.2.3.8.3.2.10.1	ADS-B TCAS RA Broadcast	93
2.2.3.9	ACAS X Signal Protocol	94
2.2.3.9.1	Mode C Surveillance Signals	94
2.2.3.9.1.1	ATCRBS-Only All-Call Interrogation	94
2.2.3.9.2	Mode S Surveillance Signals	94
2.2.3.9.2.1	Detection	94
2.2.3.9.2.2	Surveillance Interrogations	95

2.2.3.9.2.2.1	Acquisition.....	95
2.2.3.9.2.2.2	Tracking.....	95
2.2.3.9.2.3	Surveillance Replies.....	95
2.2.3.9.2.3.1	Acquisition.....	95
2.2.3.9.2.3.2	Tracking.....	95
2.2.3.9.2.4	TCAS Broadcast Interrogations.....	96
2.2.3.9.3	Coordination with Other Aircraft.....	96
2.2.3.9.3.1	Determining Own Coordination Protocol.....	96
2.2.3.9.3.2	Transmission of Coordination Interrogations to Other Active CAS Aircraft.....	97
2.2.3.9.3.3	Capacity and Handling Requirements for Incoming Coordination Interrogations	98
2.2.3.9.3.4	Coordination Delivery Delay Requirements.....	99
2.2.3.9.3.5	Additional Coordination Topics.....	100
2.2.3.9.3.5.1	Slave Geometric Reversals.....	100
2.2.3.9.3.5.2	Coordination Delay When Transitioning from TA-Only Mode to TA/RA Mode.....	100
2.2.3.9.3.6	Use of Extended Squitter ME Field Information in Air-to-Air Coordination ...	101
2.2.3.9.3.6.1	Coordination Information Received by ACAS X in Incoming ADS-B Messages.....	101
2.2.3.9.3.6.1.1	Operational Coordination Message.....	101
2.2.3.9.3.6.1.2	Aircraft Operational Status Message.....	101
2.2.3.9.3.6.2	Coordination Information Composed by ACAS X for Inclusion in Outgoing ADS-B Messages.....	101
2.2.3.9.3.6.2.1	Operational Coordination Message.....	101
2.2.3.9.4	Communication of RA Information.....	102
2.2.3.9.5	Communication With Mode S Ground Sensors.....	103
2.2.3.9.5.1	RA Report.....	103
2.2.3.9.5.2	Data Link Capability Report.....	104
2.2.3.9.5.3	ACAS X Unit Part Number and ACAS X Software Part Number.....	104
2.2.3.9.5.4	TCAS Sensitivity Level Control.....	104
2.2.3.9.6	Communication With Other Ground Equipment.....	105
2.2.3.9.6.1	RA Broadcast Interrogations.....	105
2.2.3.9.7	Mode S Crosslink Capability.....	105
2.2.3.9.8	Extended Squitter With Aircraft Identification Message.....	105
2.2.3.10	Compatibility With Own Mode S Transponder.....	105
2.2.3.11	Aircraft Suppression Bus.....	106
2.2.3.12	Interfaces With Other Systems.....	107
2.2.3.12.1	Mode S Transponder Related Interfaces.....	107
2.2.3.12.2	ACAS X Interface with Mode S Transponder.....	107
2.2.3.12.2.1	General Requirements of the Interface to the Mode S Transponder.....	107
2.2.3.12.2.1.1	ACAS X/Transponder System Capability Determination.....	107
2.2.3.12.2.1.2	Determination of ACAS X-to-Transponder Write Compatibility.....	108
2.2.3.12.2.1.3	Determination of Transponder OCM Transmit Capability and Setting of CCCB Value.....	108
2.2.3.12.2.1.4	Data Reception.....	109
2.2.3.12.2.1.5	Data Integrity.....	109
2.2.3.12.2.2	Data Provided by the ACAS X Equipment to the Mode S Transponder.....	110
2.2.3.12.2.2.1	Data Provided to Own Transponder for Use in Special Surveillance Replies (DF=0, 16).....	110
2.2.3.12.2.2.2	Data Provided to Own Transponder for Use in Altitude and Identity Surveillance and Comm-B Replies (DF=4, 5, 20, 21).....	110
2.2.3.12.2.2.3	Data Provided to Own Transponder for Use in Long Special Surveillance Replies (DF=16).....	110

2.2.3.12.2.2.4	Data Provided to Own Transponder for Use in Altitude and Identity Comm-B Replies (DF=20, 21)	110
2.2.3.12.2.2.5	Data Provided to Own Transponder for Use in 1090ES Transmissions	111
2.2.3.12.2.2.5.1	Operational Coordination Message Priority	112
2.2.3.12.2.3	Data Received by the ACAS X Equipment from the Mode S Transponder	113
2.2.3.12.2.3.1	Data Received in Long Special Surveillance Interrogations (UF=16) from Other TCAS Aircraft via Own Mode S Transponder	113
2.2.3.12.2.3.2	Data Received in Altitude and Identity Comm-A Interrogations (UF=20, 21) from Mode S Ground Stations via Own Mode S Transponder	113
2.2.3.12.3	ACAS X Operating Mode Control	113
2.2.3.12.4	Radio Altimeter Interface	114
2.2.3.12.5	Flight Test Recording	114
2.2.3.12.6	Position Source Interface	114
2.2.3.12.7	Heading Interface	114
2.2.3.12.8	Air/Ground Interface	114
2.2.3.12.9	ASA System Interface	114
2.2.3.12.9.1	Receive Self-Test Status	115
2.2.3.12.9.2	Send Temporal Test Pattern	115
2.2.3.12.9.3	Send Self-Test Results	115
2.2.3.12.9.4	ASA System Interface for ACAS Xo	115
2.2.4	Surveillance Requirements	115
2.2.4.1	Surveillance Update Rate	116
2.2.4.2	System Delay	116
2.2.4.3	Differential Channel Delay	116
2.2.4.4	Signal Reception	116
2.2.4.4.1	Receiver Sensitivity And Bandwidth	116
2.2.4.4.1.1	In-Band Acceptance	116
2.2.4.4.1.2	Out-of-Band Rejection	117
2.2.4.4.2	Reply Detection and Decoding	117
2.2.4.4.2.1	Mode C Reply Reception	117
2.2.4.4.2.2	Mode S Squitter and Reply Reception	119
2.2.4.5	Interference Rejection and Control	122
2.2.4.5.1	Multipath Rejection	122
2.2.4.5.1.1	Interrogation Link Interference	122
2.2.4.5.1.2	Reply Link Interference	122
2.2.4.5.1.2.1	Narrow Pulse Discrimination	122
2.2.4.5.1.2.2	TACAN and DME Discrimination	123
2.2.4.5.2	Narrow Pulse Rejection	123
2.2.4.5.3	TACAN and DME Signal Rejection	123
2.2.4.5.4	Control of ATCRBS Synchronous Garble	123
2.2.4.5.4.1	Control of Synchronous Garble by Whisper-Shout	123
2.2.4.5.4.1.1	Minimum Basic Whisper-Shout Sequence	124
2.2.4.5.4.1.2	Higher Capability Whisper-Shout Sequences for Improved Degarbling Performance	124
2.2.4.5.4.1.3	Determination of Whisper-Shout Based on Synchronous Garble	130
2.2.4.5.4.1.4	Criteria for Selection of a Specific Whisper-Shout Sequence	131
2.2.4.5.4.1.5	Surveillance in Areas of No ATCRBS Intruder Aircraft	132
2.2.4.5.4.2	Control of Synchronous Garble by Directional Interrogation	133
2.2.4.5.4.2.1	Directional Interrogation Beamwidth Control	133
2.2.4.5.4.2.2	Directional Interrogation Radiated Power	133
2.2.4.5.4.2.3	Degarbling Performance as a Function of Azimuth Resolution	134
2.2.4.5.5	ATCRBS and Mode S Fruit Rejection	134
2.2.4.6	Surveillance Tracking Requirements	134
2.2.4.6.1	Surveillance Target Track Capacity	135

2.2.4.6.1.1	Surveillance Overload.....	135
2.2.4.6.2	Intruder Air/Ground Status Determination.....	135
2.2.4.6.2.1	Estimate of Ground Level.....	136
2.2.4.6.2.2	Determination of Intruder Air-Ground Status.....	136
2.2.4.6.2.2.1	Determination for Newly Initiated Tracks	136
2.2.4.6.2.2.2	Determination for Intruders Equipped with Mode S Transponders.....	136
2.2.4.6.2.2.3	Determination for Intruders Equipped with Mode C (ATCRBS) Transponders	137
2.2.4.6.2.2.3.1	Determination for Intruders Equipped with Mode C (ATCRBS) Transponders and Reporting Pressure Altitude.....	137
2.2.4.6.2.2.3.2	Determination for Intruders Equipped with Mode C (ATCRBS) Transponders and NOT Reporting Pressure Altitude	137
2.2.4.6.2.2.4	Summary of Rules for Determining Air-Ground Status	137
2.2.4.6.3	Determination of Ownship Air-Ground Status.....	138
2.2.4.6.4	Range and Altitude Estimation.....	139
2.2.4.6.4.1	Mode C Targets	139
2.2.4.6.4.1.1	Reply Merging	139
2.2.4.6.4.1.2	Track Initiation	139
2.2.4.6.4.1.3	Maintenance of Established Tracks	140
2.2.4.6.4.1.4	Multipath False Tracks	140
2.2.4.6.4.2	Mode S Targets.....	140
2.2.4.6.4.2.1	Squitter Processing.....	140
2.2.4.6.4.2.2	Acquisition.....	141
2.2.4.6.4.2.2.1	Acquisition Using Passive Position Reports	142
2.2.4.6.4.2.2.1.1	Extended Hybrid Surveillance Quality Requirements.....	143
2.2.4.6.4.2.2.1.2	Establishing an Extended Hybrid Surveillance Track	143
2.2.4.6.4.2.2.1.3	Extended Hybrid Surveillance MTL	143
2.2.4.6.4.2.2.1.4	Determination of Estimated Signal Strength.....	144
2.2.4.6.4.2.2.2	Acquisition Using Interrogations	144
2.2.4.6.4.2.3	Maintenance of Established Tracks	145
2.2.4.6.4.2.3.1	Maintenance of Tracks Using Passive Surveillance	146
2.2.4.6.4.2.3.1.1	Conditions for Extended Hybrid Surveillance.....	146
2.2.4.6.4.2.3.1.2	Persistence of Extended Hybrid Surveillance	147
2.2.4.6.4.2.3.1.3	Transitions to Extended Hybrid Surveillance.....	147
2.2.4.6.4.2.3.1.4	Conditions for Hybrid Surveillance.....	147
2.2.4.6.4.2.3.1.5	Persistence of Hybrid Surveillance.....	147
2.2.4.6.4.2.3.1.6	Hybrid Surveillance Region	148
2.2.4.6.4.2.3.1.7	Transitions to Hybrid Surveillance.....	148
2.2.4.6.4.2.3.1.8	Track Updates Using Airborne Position Messages	149
2.2.4.6.4.2.3.1.9	Tracking in the Absence of Airborne Position Messages.....	150
2.2.4.6.4.2.3.1.10	Revalidation.....	151
2.2.4.6.4.2.3.1.11	Error Budget Allocated to ACAS X for Slant Range Validation	153
2.2.4.6.4.2.3.2	Maintenance of Tracks Using Active Surveillance.....	154
2.2.4.6.4.2.3.2.1	Conditions for Active Surveillance of a Track	154
2.2.4.6.4.2.3.2.2	Persistence of Active Surveillance	154
2.2.4.6.4.2.3.2.3	Active Surveillance Region	154
2.2.4.6.4.2.3.2.4	Passive to Active Surveillance Transition	155
2.2.4.6.4.2.3.2.5	Track Updates Using Active Surveillance.....	155
2.2.4.6.4.2.3.2.6	Power Programming	157
2.2.4.6.4.2.3.2.7	Validation of Airborne Position Message Data	158
2.2.4.6.4.2.4	NTA3/NTA6 Range Determination for Active CAS On-Ground Intruders	159
2.2.4.6.5	Non-Altitude-Reporting Aircraft.....	159
2.2.4.6.6	Bearing Estimation.....	159
2.2.4.6.6.1	General Requirements.....	159

2.2.4.6.6.2	Active Surveillance Bearing Accuracy With Standard Ground Plane.....	160
2.2.4.6.6.2.1	Accuracy, -10 Deg. To +10 Deg. Elevation.....	160
2.2.4.6.6.2.2	Accuracy, greater than 10 Deg. To +20 Deg. Elevation	160
2.2.4.6.6.3	Bearing Accuracy in the Presence of Interference.....	160
2.2.4.6.6.3.1	Mode C Interleaved Replies.....	161
2.2.4.6.6.3.2	Mode C Overlapped Replies.....	161
2.2.4.6.6.3.3	Mode S Overlapped Replies	161
2.2.4.6.6.4	Bearing Filter Performance.....	161
2.2.4.6.6.4.1	Bearing Filter	161
2.2.4.6.6.5	Dynamic Range and Reply Frequency	162
2.2.4.7	Antenna System	162
2.2.4.7.1	Polarization.....	162
2.2.4.7.2	Radiation Pattern.....	162
2.2.4.7.2.1	Transmit Radiation Pattern	162
2.2.4.7.2.2	Receive Radiation Pattern.....	163
2.2.4.7.3	Use of a Directional Antenna for Mode S Interrogations.....	163
2.2.4.7.4	Antenna Selection	164
2.2.4.7.4.1	Squitter Listening.....	164
2.2.4.7.4.2	Interrogations and Replies	164
2.2.4.8	Relationship Between Front-End Surveillance and the STM	164
2.2.5	Surveillance and Tracking Module / Threat Resolution Module	165
2.2.5.1	STM – Surveillance and Tracking Module Overview	165
2.2.5.1.1	STM Tracking	165
2.2.5.1.2	STM Track Source Selection	165
2.2.5.1.3	STM Belief State Outputs for the TRM	167
2.2.5.2	TRM - Threat Resolution Module Overview.....	167
2.2.5.2.1	State Estimation.....	169
2.2.5.2.2	Cost Estimation and Update of Intruder Coordination Data	170
2.2.5.2.2.1	Offline Cost Estimation	171
2.2.5.2.2.2	Online Cost Estimation.....	171
2.2.5.2.2.3	Individual Cost Estimation	172
2.2.5.2.3	Action Selection	172
2.2.5.2.4	Coordination Selection	172
2.2.5.2.5	Track Threat Assessment	172
2.2.5.2.6	Display Logic Determination	172
2.2.5.2.7	Generate TRM Output.....	173
2.2.5.2.8	ACAS X TRM Processing Modes.....	173
2.2.5.3	General Integration Requirements	177
2.2.5.3.1	GenerateSTMReport	177
2.2.5.3.2	VerticalTRMUpdate.....	177
2.2.5.4	STM / Surveillance Correlation Requirements.....	177
2.2.5.5	Combined STM/TRM Input Interfaces.....	179
2.2.5.5.1	ReceiveBaroAltObservation.....	180
§2.2.7.2.5.1)	181
2.2.5.5.2	ReceiveRadAltObservation	181
2.2.5.5.3	ReceiveHeadingObservation	182
2.2.5.5.4	ReceiveWgs84Observation	182
2.2.5.5.5	ReceiveDiscretas	183
2.2.5.5.6	ReceiveDF0.....	185
2.2.5.5.7	ReceiveModeCReply.....	186
2.2.5.5.8	ReceiveModeCReplies	187
2.2.5.5.9	ReceiveStateVectorPosition	188

2.2.5.5.10	ReceiveStateVectorVelocity	190
2.2.5.5.11	ReceiveModeStatus	191
2.2.5.5.12	ReceiveTargetDesignation	192
2.2.5.5.13	ReceiveUF16UDS30	193
2.2.5.5.14	ReceiveCapabilityReport.....	194
2.2.5.6	Combined STM/TRM Output Interfaces	195
2.2.5.6.1	Crew Outputs.....	196
2.2.5.6.1.1	Traffic Display Outputs	196
2.2.5.6.1.1.1	STMReport.display	196
2.2.5.6.1.1.2	TRMReport.display.intruder	197
2.2.5.6.1.2	RA Output (TRMReport.display)	198
2.2.5.6.1.3	ACAS Xo Traffic Designation Information (TRMReport.designation)	199
2.2.5.6.1.3.1	TRMReport.Designation.Intruder	199
2.2.5.6.2	RA Information Transmitted by ACAS X.....	201
2.2.5.6.2.1	Data for TCAS Resolution Message (TRMReport.coordination)	201
2.2.5.6.2.2	Data for the RA Broadcast Interrogation Message (TRMReport.broadcast)....	203
2.2.5.6.3	Data To Be Provided to Own Transponder	204
2.2.5.6.3.1	SL/RI and DLCR (STMReport.transponder).....	204
2.2.5.6.3.2	Coordination Data Provided to the Transponder (TRMReport.coordination) ...	205
2.2.5.6.3.3	Data for the RA Report (TRMReport.ground_msg).....	205
2.2.5.6.4	STMReport.trm_input	205
2.2.6	Displays and Controls	205
2.2.6.1	Traffic Displays	206
2.2.6.1.1	Functions	206
2.2.6.1.2	Characteristics	206
2.2.6.1.2.1	General Characteristics	206
2.2.6.1.2.1.1	Ownship Symbol.....	206
2.2.6.1.2.1.2	Range Rings	206
2.2.6.1.2.1.3	Traffic Symbology	206
2.2.6.1.2.1.4	Off-Scale Symbology.....	207
2.2.6.1.2.1.5	Altitude Data Tag.....	207
2.2.6.1.2.1.6	Intruder Vertical Speed Arrow.....	208
2.2.6.1.2.1.7	Non-Altitude Reporting Intruders.....	208
2.2.6.1.2.1.8	Intruder Bearing	208
2.2.6.1.2.1.9	Display of Traffic.....	209
2.2.6.1.2.1.10	Altitude Band for the Display	209
2.2.6.1.2.1.11	ACAS X Operating Mode and Selected Display Range Annunciation	210
2.2.6.1.2.1.12	RA Annunciations.....	210
2.2.6.1.2.1.13	Lighting Control	210
2.2.6.1.2.1.14	Status and Failure Annunciations	210
2.2.6.1.2.2	Fixed Range Displays	211
2.2.6.1.2.2.1	Display Range	211
2.2.6.1.2.2.2	Range Ring	211
2.2.6.1.2.3	Variable Range Displays	211
2.2.6.1.2.3.1	Display Range	211
2.2.6.1.2.3.2	Range Selection	211
2.2.6.1.2.3.3	Range Rings	211
2.2.6.1.2.4	Part Time (Pop-up) Displays	211
2.2.6.1.2.4.1	Activation.....	211
2.2.6.1.2.4.2	Information Displayed	211
2.2.6.1.2.4.3	Display Format	212
2.2.6.1.2.4.4	Pilot Selection	212
2.2.6.1.2.5	Full Time Displays.....	212
2.2.6.1.2.5.1	Display Format	212

2.2.6.1.2.6	Dedicated Displays	212
2.2.6.1.2.6.1	Display Format	212
2.2.6.1.2.6.2	Ownship Symbol and Location.....	212
2.2.6.1.2.7	Shared Displays	212
2.2.6.1.2.7.1	Shared Weather (WX) Radar Displays	212
2.2.6.1.2.7.1.1	Display Modes	212
2.2.6.1.2.7.1.2	Ownship Symbol and Location.....	213
2.2.6.1.2.7.2	Shared Navigation Displays (ND) or Electronic Horizontal Situation Indicator (EHSI).....	214
2.2.6.1.2.7.2.1	Display Characteristic	214
2.2.6.1.2.7.2.2	Failure Annunciations	214
2.2.6.1.2.7.2.3	Traffic Display	214
2.2.6.1.2.7.2.4	ACAS X and Weather Information.....	214
2.2.6.1.2.7.2.5	ACAS X and Navigation Information.....	214
2.2.6.1.2.7.2.6	HSI Display Mode	215
2.2.6.1.2.7.2.6.1	Display Characteristics.....	215
2.2.6.1.2.7.2.6.2	Ownship Symbol and Location	216
2.2.6.1.2.7.2.7	EXPANDED Mode.....	216
2.2.6.1.2.7.2.7.1	Display Characteristics.....	216
2.2.6.1.2.7.2.7.2	Display Range and Range Ring.....	216
2.2.6.1.2.7.2.7.3	Ownship Symbol and Location	217
2.2.6.1.2.7.2.8	MAP Display Mode	217
2.2.6.1.2.7.2.8.1	Display Characteristics.....	217
2.2.6.1.2.7.2.8.2	Display Range and Range Rings	217
2.2.6.1.2.7.2.8.3	Display Orientation	217
2.2.6.1.2.7.2.8.4	Ownship Symbol and Location	217
2.2.6.1.2.7.2.9	North-up Mode.....	217
2.2.6.1.2.7.2.9.1	Display Characteristics.....	217
2.2.6.1.2.7.2.9.2	Display Range and Range Rings	217
2.2.6.1.2.7.2.9.3	Ownship Symbol	217
2.2.6.1.2.7.2.9.4	Display Orientation	218
2.2.6.1.2.7.2.9.5	TA or RA Annunciation	218
2.2.6.1.2.7.2.9.6	Selection of Heading Up Display	218
2.2.6.1.2.7.3	Shared EICAS/SYSTEMS Displays.....	218
2.2.6.1.2.7.3.1	Display Characteristics	218
2.2.6.1.2.7.3.2	Ownship Symbol and Location.....	218
2.2.6.1.2.7.3.3	Traffic Display Inhibit	218
2.2.6.1.2.7.3.4	Restrictions	218
2.2.6.1.2.7.4	TA/RA/VSI Displays.....	219
2.2.6.1.2.7.4.1	General Requirements.....	219
2.2.6.1.2.7.4.1.1	Format	219
2.2.6.1.2.7.4.1.2	VSI Requirements	219
2.2.6.1.2.7.4.2	Traffic Display Function.....	219
2.2.6.1.2.7.4.2.1	Display Characteristics.....	219
2.2.6.1.2.7.4.2.2	Ownship Symbol and Location	219
2.2.6.1.2.7.4.2.3	Interference with Vertical Speed Scale	219
2.2.6.2	RA Displays.....	219
2.2.6.2.1	General	219
2.2.6.2.2	RA/VSI (Round dial VSI)	219
2.2.6.2.2.1	RA Display Characteristics.....	220
2.2.6.2.2.1.1	Red Arcs	220
2.2.6.2.2.1.2	Green Arcs	220
2.2.6.2.2.1.3	Black Arcs.....	220
2.2.6.2.2.1.4	Multi-aircraft Encounters.....	220

2.2.6.2.2.2	VSI Characteristics	221
2.2.6.2.2.3	Lighting Control	221
2.2.6.2.3	RA/VSI (Integrated Tape VSI on a Primary Flight Display [PFD])	221
2.2.6.2.3.1	RA Display Characteristics.....	221
2.2.6.2.3.1.1	Red Zone.....	221
2.2.6.2.3.1.2	Green Zone	221
2.2.6.2.3.1.3	Black Zones	222
2.2.6.2.3.1.4	Multi-aircraft Encounters.....	222
2.2.6.2.3.2	VSI Characteristics	222
2.2.6.2.3.3	VSI Scale	222
2.2.6.2.3.4	Lighting Control	222
2.2.6.2.4	Pitch Cues on the PFD.....	222
2.2.6.2.4.1	No-Fly Pitch Angles	223
2.2.6.2.4.2	Mode Annunciation	224
2.2.6.2.4.3	Multi-aircraft Encounters.....	224
2.2.6.2.5	Flight Director Guidance.....	224
2.2.6.2.6	Heads-up Display	224
2.2.6.2.6.1	No-Fly Zone.....	225
2.2.6.2.6.2	Mode Annunciation	225
2.2.6.2.6.3	Flight Path Target	225
2.2.6.2.6.4	Multi-aircraft Encounters.....	225
2.2.6.2.6.5	Display Decluttering.....	225
2.2.6.2.6.6	RA Guidance Availability	226
2.2.6.3	Aural Annunciations	226
2.2.6.3.1	General	226
2.2.6.3.1.1	Announcement Methodology	226
2.2.6.3.1.2	Aural Annunciation Generation.....	226
2.2.6.3.1.3	Aural Annunciation Description and Interruption	226
2.2.6.3.2	Quality.....	226
2.2.6.3.3	Aural Annunciation Inhibit	226
2.2.6.3.4	TAs.....	226
2.2.6.3.5	RAs.....	227
2.2.6.4	Visual Alerts	227
2.2.6.4.1	TAs.....	227
2.2.6.4.2	RAs.....	238
2.2.6.4.3	Message on PFD.....	238
2.2.6.4.4	Visual Alert Inhibit.....	238
2.2.6.5	Controls.....	238
2.2.6.5.1	ACAS X/Mode S Controls.....	238
2.2.6.5.2	Traffic Display Controls.....	239
2.2.6.5.3	Traffic Display Controls on Shared Weather Radar.....	239
2.2.6.5.3.1	WX/ACAS X Mode.....	239
2.2.6.5.3.2	WX-and-Traffic Mode	239
2.2.6.5.3.3	Optional Mode Selection	239
2.2.6.5.4	ACAS Xo Controls.....	240
2.2.6.6	Status and Failure Annunciations	240
2.2.6.6.1	General	240
2.2.6.6.2	Traffic Display Annunciations	240
2.2.6.6.3	RA Display	240
2.2.6.7	Display and Control Interfaces	241
2.2.6.7.1	Display and Control Outputs.....	241
2.2.6.7.2	Display and Control Inputs.....	241
2.2.7	Monitor Requirements.....	252
2.2.7.1	General Requirements.....	252

2.2.7.1.1	Failure Response	252
2.2.7.1.2	Noninterference with Normal Operation.....	252
2.2.7.1.3	Self-Test	252
2.2.7.2	Monitoring of ACAS X Components	252
2.2.7.2.1	Computer Monitoring.....	252
2.2.7.2.2	Coordination Monitoring.....	253
2.2.7.2.3	ACAS X/Transponder Interface Monitoring.....	253
2.2.7.2.4	Display Monitoring	253
2.2.7.2.5	Altitude Input Monitoring	256
2.2.7.2.5.1	Barometric Altitude Monitoring	256
2.2.7.2.5.2	Radio Altitude Monitoring - General.....	256
2.2.7.2.5.2.1	Radio Altimeter Input to the Monitor	256
2.2.7.2.5.2.2	Monitor Inputs to the STM and STM Inputs to the TRM.....	256
2.2.7.2.5.2.3	Monitor Verification of Radio Altitude Source Prior to Issuance of TAs or RAs	256
2.2.7.2.5.2.4	Radio Altitude Credibility.....	257
2.2.7.2.5.2.4.1	Radio Altitude Credibility Determination Test #1	257
2.2.7.2.5.2.4.2	Radio Altitude Credibility Determination Test #2	258
2.2.7.2.5.2.4.2.1	Radio Altitude Track Initiation.....	258
2.2.7.2.5.2.4.2.2	Operation Subsequent to Radio Altitude Track Initiation	258
2.2.7.2.5.2.5	Radio Altitude Source Failure	258
2.2.7.2.6	ICAO 24-Bit Aircraft Address	259
2.2.7.2.7	Monitoring of Transponder Status	259
2.2.7.2.8	Higher Priority Warning Systems	259
2.2.7.2.9	Monitoring of Ownship Position Source , Ground Speed and Heading Input	260
2.2.7.2.10	Monitoring of ACAS X Transmitter	260
2.2.7.3	Monitor Interfaces.....	260
2.2.7.3.1	Data Provided by the Monitor to Surveillance	260
2.2.7.3.2	Data Provided by the Monitor to the STM.....	260
2.2.7.3.3	Data Received by the Monitor from the STM.....	261
2.2.7.3.4	Data Received by the Monitor from the Control Panel via the Mode S Transponder	261
2.2.7.3.5	Data Received by the Monitor from Aircraft Discretes	261
2.2.7.3.6	Data Provided by the Monitor to Displays and Controls	262
2.2.7.3.8	Data Received by the Monitor from Ownship Position Source	264
2.2.7.3.9	Data Received by the Monitor from Ownship Heading Source	264
2.2.8	ACAS Xo	264
2.2.8.1	ACAS Xo Overview	264
2.2.8.1.1	Xo Parameters	265
2.2.8.2	Xo Controls and Displays	266
2.2.8.2.1	Xo Traffic Designation/Undesignation	267
2.2.8.2.2	Xo Display.....	268
2.2.8.2.3	ACAS Xo Mode Availability.....	269
2.2.8.2.3.1	DNA.....	269
2.2.8.2.3.2	CSPO-3000	270
2.2.8.3	Traffic Xo Mode Validity	270
2.2.8.3.1	Traffic Valid for DNA.....	271
2.2.8.3.2	Traffic Valid for CSPO-3000.....	272
2.2.8.3.3	Traffic Validity Reported to the ASA System	272
2.2.8.4	CAS Logic in Use for Designated/Undesignated Traffic	272
2.2.8.4.1	Switching Logic Modes.....	273
2.2.8.4.2	Multi-threat Encounters with DNA Traffic	274
2.2.8.5	Automatic Undesignation	274
2.2.8.5.1	Dropped Traffic.....	275

2.2.8.6	Logic Requirements.....	275
2.2.8.6.1	DNA	275
2.2.8.6.1.1	DNA Coordination.....	275
2.2.8.6.2	CSPO-3000.....	276
2.2.8.7	State Tables.....	276
2.2.8.8	Xo / ASA System Interface.....	283
2.2.8.8.1	Xo Mode Availability.....	283
2.2.8.8.2	Send Traffic Xo Mode Validity.....	283
2.2.8.8.3	Send Traffic Designation Information.....	283
2.2.8.8.4	Receive Xo Traffic Designation/Undesignation Request.....	284
2.3	Equipment Performance - Environmental Conditions	284
2.3.1	Environmental Test Conditions.....	285
2.4	Equipment Test Procedures	289
2.4.1	Definitions of Terms and Conditions of Test.....	289
2.4.1.1	Standard Test Signals.....	291
2.4.1.2	Test Equipment Capabilities	292
2.4.1.3	Alternative Mode S Transponder Procedures	299
2.4.1.4	Bench Test Coverage of the TCAS Software	299
2.4.2	Detailed Test Procedures.....	299
2.4.2.1	Surveillance	299
2.4.2.1.1	Transmitter Characteristics.....	299
2.4.2.1.1.1	Transmit Frequency (§2.2.3.5).....	299
2.4.2.1.1.2	Radiated Output Power (§2.2.3.1)	302
2.4.2.1.1.3	Control of Synchronous Interference by Transmitter Power (§2.2.4.5.4.1)	304
2.4.2.1.1.3.1	Control of Synchronous Garble by Whisper-Shout (§2.2.4.5.4, §2.2.4.5.4.1)	304
2.4.2.1.1.3.2	Determination of Whisper-Shout Sequence (§2.2.4.5.4, §2.2.4.5.4.1.3, §2.2.4.5.4.1.5)	306
2.4.2.1.1.4	ACAS X Transmit Pulse Characteristics (§2.2.3.7, §2.2.4.5.4.2.1).....	308
2.4.2.1.1.5	Interrogation Spectrum (§2.2.3.3).....	313
2.4.2.1.1.6	Unwanted Output Power (§2.2.3.2).....	315
2.4.2.1.1.7	Aircraft Suppression Bus (§2.2.3.11)	317
2.4.2.1.1.7.1	Suppression Pulse Supplied by ACAS X.....	317
2.4.2.1.1.7.2	Suppression Pulse Supplied by Other Avionics.....	317
2.4.2.1.1.8	Interrogation Repetition Interval (§2.2.4.1) and Jitter (§2.2.3.4).....	317
2.4.2.1.2	Receiver Characteristics (§2.2.4.4.1)	317
2.4.2.1.2.1	In-Band Acceptance.....	320
2.4.2.1.2.1.1	Ability to Operate Over the Frequency Band 1087 to 1093 MHz for ATCRBS and 1089 to 1091 MHz for Mode S Signals (§2.2.4.4.1.1).....	320
2.4.2.1.2.1.2	Sensitivity and Dynamic Range at 1090 MHz (§2.2.4.4.1.1)	322
2.4.2.1.2.2	Out-of-Band Rejection (§2.2.4.4.1.2)	323
2.4.2.1.3	Reply Link Interference (§2.2.4.5.1.2)	325
2.4.2.1.3.1	Mode C Reply Reception (§2.2.4.4.2, §2.2.4.4.2.1). Narrow Pulse Discrimination (§2.2.4.5.1.2.1) and TACAN and DME Discrimination (§2.2.4.5.1.2.2).....	326
2.4.2.1.3.2	Mode S Squitter and Reply Reception (§2.2.4.4.2.2), Narrow Pulse Discrimination (§2.2.4.5.1.2.1) and TACAN and DME Discrimination (§2.2.4.5.1.2.2).....	328
2.4.2.1.4	Mode C Reply Reception (§2.2.4.4.2.1).....	330
2.4.2.1.4.1	Bracket Detection and Reply Decoding (§2.2.4.4.2, §2.2.4.4.2.1)	330
2.4.2.1.4.2	Wide Pulse Detection and Pulse Position Discrimination (§2.2.4.4.2, §2.2.4.4.2.1(c)).....	332
2.4.2.1.4.3	Narrow Pulse Rejection (§2.2.4.4.2.1(b), §2.2.4.5.2)	333

2.4.2.1.4.4	Detection of Garbled Replies (§2.2.4.4.2.1(c)).....	334
2.4.2.1.4.5	Detection of Interleaved Replies (§2.2.4.4.2.1(c)).....	336
2.4.2.1.4.6	Phantom Rejection (§2.2.4.4.2.1(d)).....	337
2.4.2.1.4.7	TACAN and DME Pulse Rejection (§2.2.4.5.3)	338
2.4.2.1.5	Mode S Squitter and Reply Reception (§2.2.4.4.2.2).....	338
2.4.2.1.5.1	Mode S Preamble Reception (§2.2.4.4.2.2(b))	339
2.4.2.1.5.2	Mode S Squitter and Fruit Reply Reception (§2.2.4.4.2.2(c))	341
2.4.2.1.5.3	Mode S Extended Squitter Reception (§2.2.3.9.8, §2.2.3.9.2.1, §2.2.4.6.4.2, §2.2.4.4.2.2(c)).....	342
2.4.2.1.5.4	Mode S Error Correction (§2.2.4.4.2.2(d))	344
2.4.2.1.6	Mode C Target Surveillance Performance (§2.2.4.6.4).....	344
2.4.2.1.6.1	Mode C Surveillance Initiation (§2.2.4.6.4.1.2, §2.2.4.5, §2.2.4.6)	345
2.4.2.1.6.2	Mode C Surveillance Extension (§2.2.4.6.4.1.3, §2.2.4.6.4.1.4)	346
2.4.2.1.6.2.1	Elimination of Multipath False Tracks	346
2.4.2.1.6.2.2	Range Correlation	349
2.4.2.1.6.2.3	Altitude Correlation	352
2.4.2.1.6.2.4	Altitude Code Processing.....	354
2.4.2.1.6.3	Missing Mode C Replies (§2.2.4.6.4.1.3)	355
2.4.2.1.6.4	Surveillance Target Capacity (Mode C) (§2.2.4.6.1).....	356
2.4.2.1.6.5	Surveillance Overload (§2.2.4.6.1.1)	360
2.4.2.1.7	Mode S Target Surveillance Performance (§2.2.4.6.4.2, §2.2.4.4.2.2)	361
2.4.2.1.7.1	Mode S Surveillance Initiation (§2.2.4.6.2.2.2, §2.2.4.6.4.2.1).....	362
2.4.2.1.7.2	Mode S Range Acquisition (§2.2.4.6.2.2.2, §2.2.4.6.4.2.2.1, §2.2.4.2, §2.2.4.7, §2.2.4.7.4.1)	366
2.4.2.1.7.3	Maintenance of Established Mode S Tracks (§2.2.4.6.4.2.3.2.5, §2.2.4.7, §2.2.5.5.6).....	369
2.4.2.1.7.4	Interference Limiting (§2.2.3.6).....	371
2.4.2.1.7.4.1	Interrogation Control of Airborne ACAS X (§2.2.3.6.1, §2.2.3.6.2, §2.2.3.6.4)	371
2.4.2.1.7.4.2	Interrogation Control of ACAS X On The Ground (§2.2.3.6.3).....	375
2.4.2.1.7.4.3	Correct Content of Transmitted TCAS Broadcast Interrogation Messages (§2.2.3.8.3.2.4.2, §2.2.3.9.2.4).....	376
2.4.2.1.7.4.4	Surveillance Special Functionality Test (§2.2.3.6.2)	376
2.4.2.1.7.4.5	Interference Limiting and Required Interrogations	378
2.4.2.1.7.5	Surveillance Target Capacity and Overload (Mode S) (§2.2.4.6.1, §2.2.4.6.1.1)	378
2.4.2.1.7.6	Mode S Power Programming (§2.2.4.6.4.2.3.2.6)	383
2.4.2.1.8	Combined Mode S and Mode C Surveillance	383
2.4.2.1.8.1	Surveillance Target Capacity (§2.2.4.6.1)	383
2.4.2.1.8.2	Altitude and Range Tracking of Mode C and Mode S Targets for TRM (§2.2.4.6)	385
2.4.2.1.8.2.1	Range Tracking Accuracy.....	385
2.4.2.1.8.2.2	Altitude Tracking Accuracy	386
2.4.2.1.9	Bearing Estimation	387
2.4.2.1.9.1	Bearing Accuracy with Standard Ground Plane (§2.2.4.6.6.1, §2.2.4.6.6.2).....	387
2.4.2.1.9.2	Reply Processing (§2.2.4.6.6.3)	389
2.4.2.1.9.2.1	Mode C Interleaved Replies (§2.2.4.6.6.3.1).....	389
2.4.2.1.9.2.2	Mode C Overlapped Replies (§2.2.4.6.6.3.2)	390
2.4.2.1.9.2.3	Mode S Overlapped Replies (§2.2.4.6.6.3.3).....	390
2.4.2.1.9.3	Bearing Filter Performance (§2.2.4.6.6.4)	391
2.4.2.1.9.3.1	Bearing Track and Coast (§2.2.4.6.6.4.1)	391
2.4.2.1.9.3.2	Filter Lag (§2.2.4.6.6.4.1)	392
2.4.2.1.9.4	Radiation Pattern (§2.2.4.7.2, §2.2.4.7.2.1).....	392
2.4.2.1.9.5	Mode C Azimuth Filtering (§2.2.4.6.4.1.2)	393

2.4.2.1.10	ACAS X Antenna System	394
2.4.2.1.10.1	Use of Directional Interrogations for Mode C Surveillance (2.2.4.5.4.2.1, §2.2.4.7.2.1) and Bearing Receive Radiation Pattern (§2.2.4.5.4.2.2, §2.2.4.7.2.2) 394	
2.4.2.1.10.2	Use of Directional Antenna for TCAS Broadcast Interrogations (§2.2.4.7.3, §2.2.3.9.2.4)	395
2.4.2.1.10.2.1	Total Radiated Power	395
2.4.2.1.10.2.2	Interrogation Repetition Interval and Jitter	396
2.4.2.2.1	Encounter Input Files	398
2.4.2.2.1.1	Rounding	400
2.4.2.2.1.2	Timing	400
2.4.2.2.2	Encounter Output Files	401
2.4.2.2.2.1	STM Report	401
2.4.2.2.2.2	TRM Report	403
2.4.2.2.2.3	CostFile	405
2.4.2.2.3	Pass / Fail Criteria	407
2.4.2.2.3.1	STM Report	407
2.4.2.2.3.2	TRM Report	408
2.4.2.2.3.3	CostFile	409
2.4.2.2.4	Prescriptive/Mandatory Vs. Suggestive/Optional Algorithms	409
2.4.2.2.7	Detailed Test Suite Encounter List	413
2.4.2.3	External Parameter Selection	413
2.4.2.3.1	Ground Control of Sensitivity Level	415
2.4.2.3.2	TA-Only Mode Selection	416
2.4.2.4	Coordination	418
2.4.2.4.1	Transmission of RA Report to Mode S Sensor	418
2.4.2.4.2	Transmission of RA Broadcast Interrogation	424
2.4.2.4.3	Coordination with Active CAS	426
2.4.2.4.3.1	Sense Selection and Communication (§2.2.3.9.3.1, §2.2.3.9.3.2)	426
2.4.2.4.3.2	Validity Check for ACAS X Communications Link with Another Active CAS	440
2.4.2.4.3.3	ACAS X in Multi-Aircraft Conflict (§2.2.3.8.3.2.3.1, §2.2.3.9.3.2)	441
2.4.2.4.3.4	Coordination Monitor (§2.2.3.8.3.2.4.1, §2.2.7.2.2)	444
2.4.2.4.3.5	Transponder to ACAS X Interface and Transponder/ACAS X Throughput (§2.2.3.12.2.1.4, §2.2.3.9.3.3)	446
2.4.2.4.3.6	Coordination Timing (§2.2.3.9.3.4)	451
2.4.2.4.3.7	Use of Received Collision Avoidance Coordination Capability Bits (CCCB) (§2.2.3.9.3.1, §2.2.3.9.3.6.1.2, §2.2.3.9.3.6.2.1)	452
2.4.2.4.3.8	Transmission of Own Collision Avoidance Coordination Capability Bits (CCCB) (§2.2.3.12.2.1.3)	463
2.4.2.5	ACAS X Capability and Part Number Reporting (§2.2.3.9.5.3, §2.2.3.12.2.2.4, §2.2.3.12.2.2.1, §2.2.5.5.5)	465
2.4.2.6	Transmission of Low-level Descend Inhibit (LDI) Information in RF Messages (§2.2.3.8.3.2.3.1)	471
2.4.2.7	System Integration Tests	473
2.4.2.8	Display and Controls Stand Alone Tests	475
2.4.2.8.1	Traffic Displays	476
2.4.2.8.1.1	General Characteristics	476
2.4.2.8.1.1.1	Ownship Symbol (§2.2.6.1.2.1, §2.2.6.1.2.6.2, §2.2.6.1.2.7.1.2, §2.2.6.1.2.7.2.6.2, §2.2.6.1.2.7.2.7.3, §2.2.6.1.2.7.2.8.4, §2.2.6.1.2.7.2.9.3, §2.2.6.1.2.7.3.2, §2.2.6.1.2.7.4.2.2)	476

2.4.2.8.1.1.2	Range Rings (§2.2.6.1.2.1.2, §2.2.6.1.2.2.2, §2.2.6.1.2.3.3, §2.2.6.1.2.7.2.7.2, §2.2.6.1.2.7.2.8.2, §2.2.6.1.2.7.2.9.2)	477
2.4.2.8.1.1.3	Threat Symbology (§2.2.6.1.2.1.3, §2.2.6.1.2.1.12)	478
2.4.2.8.1.1.4	Off-Scale Symbology (§2.2.6.1.2.1.4, §2.2.6.1.2.1.11, §2.2.6.1.2.1.12)	478
2.4.2.8.1.1.5	Altitude Data Tag (§2.2.6.1.2.1.5, §2.2.6.1.2.1.7)	479
2.4.2.8.1.1.5.1	Display of Intruder's Relative Altitude	479
2.4.2.8.1.1.5.2	Display of Intruder's Reported Altitude	479
2.4.2.8.1.1.6	Intruder Vertical Speed Arrow (§2.2.4.6.5, §2.2.6.1.2.1.6)	481
2.4.2.8.1.1.7	No-Bearing Advisories (§2.2.4.6.6.1, §2.2.6.1.2.1.8, §2.2.6.1.2.1.12)	482
2.4.2.8.1.1.8	Display of Traffic (§2.2.6.1.2.1.9)	483
2.4.2.8.1.1.9	Altitude Band for the Display (§2.2.6.1.2.1.10, §2.2.6.5.2)	483
2.4.2.8.1.1.10	Display of ACAS X Operating Mode (§2.2.6.1.2.1.11, §2.2.6.6.2, §2.2.6.1.2.1.14)	485
2.4.2.8.1.2	Fixed Range Displays	485
2.4.2.8.1.3	Variable Range Displays	486
2.4.2.8.1.3.1	Display Range (§2.2.6.1.2.3.1)	486
2.4.2.8.1.3.2	Range Selection (§2.2.6.1.2.3.2)	486
2.4.2.8.1.4	Part Time Displays	487
2.4.2.8.1.4.1	Activation and Information Displayed (§2.2.6.1.2.4.1, §2.2.6.1.2.4.2)	487
2.4.2.8.1.5	Full Time Displays	488
2.4.2.8.1.6	Dedicated Displays	488
2.4.2.8.1.7	Shared Displays	488
2.4.2.8.1.7.1	Shared Weather Radar Displays	488
2.4.2.8.1.7.1.1	Available Display Modes (§2.2.6.1.2.7.1.1)	488
2.4.2.8.1.7.1.2	Display Mode Characteristics (§2.2.6.1.2.7.1.1)	489
2.4.2.8.1.7.1.2.1	WX/ACAS X Mode	489
2.4.2.8.1.7.1.2.2	WX-and-Traffic Mode	490
2.4.2.8.1.7.1.2.3	WX-Only Mode	492
2.4.2.8.1.7.1.2.4	Traffic-Only Mode	493
2.4.2.8.1.7.2	Navigation Displays or Electronic Horizontal Situation Indicators	493
2.4.2.8.1.7.2.1	Failure Annunciations (§2.2.6.1.2.7.2.2)	493
2.4.2.8.1.7.2.2	Display of Traffic (§2.2.6.1.2.7.2.3)	494
2.4.2.8.1.7.2.3	ACAS X and Weather Information (§2.2.6.1.2.7.2.4)	494
2.4.2.8.1.7.2.4	ACAS X and Navigation Information (§2.2.6.1.2.7.2.5)	495
2.4.2.8.1.7.2.5	HSI Display Mode (§2.2.6.1.2.7.2.6.1)	495
2.4.2.8.1.7.2.6	EXPANDED Mode (§2.2.6.1.2.7.2.7.1)	496
2.4.2.8.1.7.2.7	MAP Mode	497
2.4.2.8.1.7.2.7.1	Display Characteristics (§2.2.6.1.2.7.2.8.1)	497
2.4.2.8.1.7.2.7.2	Display Range and Orientation (§2.2.6.1.2.7.2.8.2; §2.2.6.1.2.7.2.8.3)	498
2.4.2.8.1.7.2.8	North-up Displays	499
2.4.2.8.1.7.2.8.1	Display Characteristics (§2.2.6.1.2.7.2.9.1, §2.2.6.1.2.7.2.9.3, §2.2.6.1.2.7.2.9.4, §2.2.6.1.2.7.2.9.5)	499
2.4.2.8.1.7.2.8.2	Display Orientation (§2.2.6.1.2.7.2.9.6)	500
2.4.2.8.1.7.3	EICAS or Systems Displays (§2.2.6.1.2.7.3.3)	501
2.4.2.8.1.7.4	TA/RA/VSI	502
2.4.2.8.1.7.4.1	VSI Requirements (§2.2.6.1.2.7.4.1.2)	502
2.4.2.8.1.7.4.2	Interference with Vertical Speed Scale (§2.2.6.1.2.7.4.2.3)	503
2.4.2.8.2	RA Displays	503
2.4.2.8.2.1	Round Dial VSI (§2.2.6.2.2, §2.2.6.2.2.1.1, §2.2.6.2.2.1.2, §2.2.6.2.2.1.3, §2.2.6.2.2.1.4)	503
2.4.2.8.2.2	Vertical Speed Tape (§2.2.6.2.3, §2.2.6.2.3.1.1, §2.2.6.2.3.1.2, §2.2.6.2.3.1.3, §2.2.6.2.3.1.4)	507
2.4.2.8.2.2.1	Vertical Speed Tape Range (§2.2.6.2.3)	511

2.4.2.8.2.3	Pitch Cues on the PFD (§2.2.6.2.4.1, §2.2.6.2.4.2, §2.2.6.2.4.3).....	511
2.4.2.8.2.4	Flight Director Guidance (§3.2.13.2).....	516
2.4.2.8.2.5	HUD (§2.2.6.2.6.1; §2.2.6.2.6.2; §2.2.6.2.6.3; §2.2.6.2.6.4; §2.2.6.2.6.5; §2.2.6.2.6.6).....	518
2.4.2.8.3	Controls.....	523
2.4.2.8.3.1	ACAS X/Mode S Controls (§2.2.6.5.1).....	523
2.4.2.8.3.2	Traffic Display Controls (§2.2.6.5.2).....	524
2.4.2.8.3.3	Shared Weather Radar/Traffic Display Controls (§2.2.6.5.3, §2.2.6.5.3.1, §2.2.6.5.3.2, §2.2.6.5.3.3).....	525
2.4.2.8.4	Status and Failure Annunciations (§2.2.6.6).....	525
2.4.2.8.4.1	Traffic Display Annunciations (§2.2.6.6.1).....	525
2.4.2.8.4.2	RA Display Annunciations (§2.2.6.6.2).....	525
2.4.2.9	Automatic Performance Monitoring and Self Test (§2.2.7).....	526
2.4.2.9.1	Automatic Performance Monitoring (§2.2.7.1.1).....	526
2.4.2.9.2	Self-Test (§2.2.7.1.3).....	527
2.4.2.9.3	Own Transponder ICAO 24-Bit Aircraft Address (§2.2.7.2.6).....	527
2.4.2.10	Performance Compatibility with Ownship's Mode S Transponder.....	527
2.4.2.10.1	ACAS X to Mode S Transponder Interference (§2.1.10.1).....	527
2.4.2.10.2	Mode S Transponder to ACAS X Interference (§2.2.3.10).....	527
2.4.2.11	Tests Related to Passive Surveillance.....	528
2.4.2.11.1	General Scenario Description.....	528
2.4.2.11.1.1	ACAS X (Own) Aircraft.....	528
2.4.2.11.1.2	Intruder Aircraft.....	528
2.4.2.11.1.3	Test Success Criteria.....	531
2.4.2.11.2	Verification of Shared Use of 1090 MHz Receiver with an ADS-B Receiving Subsystem (§2.1.13).....	532
2.4.2.11.3	Verification of Acquisition and Maintenance of Established Tracks Using Active Surveillance (§2.2.4.6.4.2.3.2).....	532
2.4.2.11.4	Verification of Maintenance of Established Tracks Using Passive Surveillance (§2.2.4.6.4.2.3.1).....	537
2.4.2.11.5	Verification of Requirements Related to Transitions Between Passive and Active Surveillance.....	558
2.4.2.11.6	Verification of Error Budget in Computing Slant Range from Passive Data (§2.2.4.6.4.2.3.1.11).....	574
2.4.2.11.7	Surveillance Overload and Capacity Tests (§2.2.4.6.4.2.3.2.5).....	574
2.4.2.11.8	Verification of DF17 Decoding (§2.2.3.8.3.2.8.1, §2.2.3.8.3.2.8.3, §2.2.3.8.3.2.8.4, §2.2.3.8.3.2.8.5).....	575
2.4.2.11.9	Verification of Monitoring Requirements (§2.2.7.2).....	579
2.4.2.11.10	Verification of On-Ground ACAS X Range Determination Using ADS-B (§2.2.4.6.4.2.4).....	580
2.4.2.11.11	Verification of DF=18 ADS-B and ADS-R Only Passive Surveillance (§2.2.3.8.3.2.8, §2.2.5.5.4, §2.2.5.5.9, §2.2.5.5.10).....	582
2.4.2.11.12	Verification of Intruder ADS-B Reports to STM.....	587
2.4.2.12	ACAS Xo.....	590
2.4.3	Computer Performance Verification.....	590
2.4.3.1	RAM Pattern Tests.....	590
2.4.3.2	CPU Instruction Tests.....	590
2.4.3.3	Program Memory Tests.....	591
2.4.3.4	CPU Input/Output Tests.....	591
2.4.3.5	CPU Timing Tests.....	591
2.4.4	Cross-Reference of Requirements and Associated Tests.....	591

3	INSTALLED EQUIPMENT PERFORMANCE.....	621
3.1	Test Conditions	621
3.1.1	Power Input	621
3.1.2	Associated Equipment.....	621
3.1.3	Environment	621
3.1.4	Adjustment of Equipment	621
3.2	Equipment Installation.....	621
3.2.1	Equipment Accessibility.....	621
3.2.2	Display Visibility	621
3.2.3	Interference.....	621
3.2.4	Physical Installation	621
3.2.5	Aircraft Power Source.....	622
3.2.6	Transmission Lines.....	622
3.2.7	Antenna Location	622
3.2.7.1	Minimum Distance from Other Antennas.....	622
3.2.8	Altimetry System.....	622
3.2.8.1	Barometric Altimetry Performance Required for ACAS X Operation.....	623
3.2.8.2	Altimetry System Error Assessment.....	624
3.2.8.3	Definitions	625
3.2.9	Number of Intruders Displayed (§2.2.6.1.2.1.9)	626
3.2.10	Display of Traffic on EICAS/SYSTEMS Displays (§2.2.6.1.2.7.3.3).....	626
3.2.11	Use of Flight Director Cues for RA Guidance (§3.2.13.2).....	626
3.2.12	Red Visual Alert (§2.2.6.4.2)	626
3.2.13	Integration with Aircraft Flight Controls	626
3.2.13.1	Pitch Cues on PFD and HUD.....	626
3.2.13.2	Flight Director.....	626
3.2.13.3	Autopilot TCAS Mode to Perform RA Maneuvers	627
3.3	Minimum Installed Equipment Performance Requirements.....	627
3.4	Test Procedures for Installed Equipment Performance.....	627
3.4.1	Conformity Inspection.....	627
3.4.2	General Test Procedures.....	628
3.4.2.1	Equipment Function.....	628
3.4.2.2	Interference Effects (Ground Test)	628
3.4.2.2.1	Suppression Bus	628
3.4.2.3	Accessibility.....	628
3.4.2.4	Integration with Aircraft Flight Controls	628
3.4.2.4.1	Pitch Cues (§3.2.13.1)	628
3.4.2.4.2	Flight Director (§3.2.13.2)	629
3.4.2.4.3	Auto Pilot (§3.2.13.3).....	629
3.4.3	Antenna Gain Performance	629
3.4.3.1	Success Criteria.....	629
3.4.3.2	Full-Scale Anechoic Antenna Range Measurements of Gain.....	629
3.4.3.3	Scaled Model Measurements of Gain	630
3.4.3.3.1	Aircraft Model.....	630
3.4.3.3.2	Model Tests	630
3.4.3.4	Theoretical Calculations of Antenna Gain.....	631
3.4.3.4.1	Validation of Theoretical Calculations.....	631
3.4.3.5	Antenna Location Using Distance-Area Calculations	631
3.4.4	Certification Flight Test Procedures.....	631
3.4.4.1	Mode C Surveillance Flight Tests.....	632

3.4.4.2	Mode S Surveillance Flight Tests	634
3.4.4.3	Coordination Flight Tests	636
3.4.4.4	Passive Surveillance Flight Tests.....	636
3.4.5	Bearing Estimation Tests.....	638
3.4.5.1	Success Criteria for Bearing Estimation Measurements.....	638
3.4.5.2	Antenna Range Measurements of Bearing Accuracy	638
3.4.5.3	Airborne Measurements of Bearing Accuracy.....	640
3.4.5.4	Scaled Model Measurements of Bearing Accuracy	640
3.4.5.4.1	Aircraft Model.....	640
3.4.5.4.2	Antenna Model.....	640
3.4.5.4.3	Model Tests	640
3.4.5.5	Theoretical Calculations of Bearing Accuracy	641
3.4.5.5.1	Validation of Theoretical Calculations of Bearing Accuracy	641
4	MEMBERSHIP	643
APPENDIX A	SURVEILLANCE PROCEDURES	A-1
A.1	Interference Limiting Procedure	A-1
A.2	Rejection of Reply Link Interference	A-3
A.3	Mode S Error Correction	A-4
A.4	Determination of Synchronous Garble Potential.....	A-10
A.5	Mode C Track Initiation	A-17
A.6	Mode C Track Maintenance	A-18
A.7	Multipath False Targets.....	A-20
A.8	Mode S Squitter Processing.....	A-21
A.9	Non-Altitude Reporting Aircraft.....	A-21
A.10	Bearing Estimation.....	A-24
A.11	Mode S Tracker Using a Five-Second Update Rate	A-25
A.12	Transition from On-The-Ground to Airborne Interference Limiting.....	A-26
APPENDIX B	ACAS X RF COMMUNICATION PATHS	B-1
B.1	Introduction	B-1
B.2	Air-to-Air Communication.....	B-1
B.2.1	Coordination	B-1

B.2.2	TCAS Broadcast Interrogation Messages	B-1
B.2.3	RA Broadcast Interrogation Messages.....	B-3
B.2.4	Surveillance	B-3
B.3	Air-to-Ground, Ground-to-Air Communication.....	B-3
B.3.1	Sensitivity Level Command Messages (Ground-to-Air)	B-3
B.3.2	RA Report (Air-to-Ground)	B-3
B.3.3	Data Link Capability Report (Air-to-Ground)	B-4
B.3.4	Surveillance	B-4
APPENDIX C DEGRADEDD SURVEILLANCE.....		C-1
C.1	Introduction	C-1
C.2	Analysis Overview	C-1
C.3	Analysis of Degraded Surveillance Inputs	C-1
C.3.1	ADS-B	C-2
C.3.1.1	Update Rate	C-2
C.3.1.1.1	Gating	C-2
C.3.1.1.2	Environment	C-2
C.3.1.2	Quality.....	C-3
C.3.1.2.1	NACp	C-3
C.3.1.2.2	NACv	C-4
C.3.2	Active.....	C-5
C.3.2.1	Bearingless	C-5
C.3.2.2	Sensitivity to Stressing Bearing Error Models	C-5
C.3.2.3	Active Update Delay	C-6
C.3.2.4	Quantization Deception.....	C-6
C.3.3	Ownship.....	C-7
C.3.3.1	Ownship Heading.....	C-7
C.3.3.1.1	Headingless	C-7

C.3.3.1.2	Track Angle.....	C-8
C.3.3.2	Ownship Altitude Quantization.....	C-9
C.3.4	TA Alerting Region	C-10
C.4	Summary	C-10
APPENDIX D CONVERSION OF REPORTED POSITION TO SLANT RANGE.....		D-1
D.1	Overview	D-1
D.2	Exact Conversion Equations.....	D-1
D.3	Height Above Ellipsoid vs. Barometric Altitude.....	D-2
D.4	Spherical Earth Approximation.....	D-3
D.5	Approximation Assuming N is the Same for All Aircraft.....	D-4
D.6	Ellipsoidal Differential Approximation.....	D-6
D.7	Spherical Differential Approximation.....	D-9
APPENDIX E ANALYSIS OF VALIDATION/REVALIDATION RANGE TOLERANCE		
ERROR BUDGET.....		E-1
E.1	Introduction	E-1
E.2	ACAS X Active Surveillance Range Error	E-2
E.3	Own and Intruder Position Sensor Error	E-2
E.4	Intruder Message LSB.....	E-2
E.5	Uncompensated Latency in Intruder Position When Received by ACAS X.....	E-2
E.6	Uncompensated Latency in Ownship Passive Position When Received by ACAS X.....	E-3
E.7	Error Budget Allocated For Hybrid Surveillance Data Processing	E-3
E.8	Sample Allocation of Hybrid Data Processing Errors.....	E-3
APPENDIX F TEST SUITE ENCOUNTER LIST.....		F-1
APPENDIX G VARIABLE VALIDATION INTERVALS.....		G-1
G.1	Derivation of the Revalidation Time Interval	G-1

APPENDIX H 1090 MHz SPECTRUM REDUCTION ANALYSIS	H-1
H.2 Simulation and Input Data Set.....	H-1
H.3 Evaluate Algorithm Changes.....	H-2
H.3.1 Algorithm Changes to RTCA/DO-185B.....	H-2
H.3.1.1 Reduced Surveillance Volume when Operating on Airport Surface.....	H-2
H.3.1.2 Eliminating Range Monitoring Interrogations to On-Ground TCAS Aircraft when Own TCAS is on the Ground	H-2
H.3.2 Algorithm Changes to RTCA/DO-300	H-3
H.3.2.1 Passively Monitor TCAS Aircraft when Below 2000 ft AGL	H-3
H.3.2.2 Two Validation Attempts	H-3
H.3.2.3 Variable Validation Rate	H-3
H.3.2.4 Use of Short Replies for Validation	H-4
H.3.2.5 Extended Hybrid Surveillance.....	H-4
H.3.2.6 Passive Only Surveillance on the Ground	H-5
H.4 Results	H-5

APPENDIX I ACAS X EQUIPMENT CLASS REQUIREMENTS COMPLIANCE MATRIX... I-1

I.1 ACAS X Equipment Compliance Matrix.....	I-1
---	-----

APPENDIX J PDIF LIFE CYCLE PROCESS FLOW AND THE ROLES AND RESPONSIBILITIES OF THE STAKEHOLDERS.....J-1

J.1 PDIF Life Cycle Process Flow and the Roles and Responsibilities of the Stakeholders	J-1
---	-----

TABLE OF FIGURES

Figure 1-1: Transition from Passive to Active Surveillance as a Function of Collision Potential.....	13
Figure 1-2: Extended Hybrid Surveillance State Transition Diagram (Ownship Taking Off / Airborne)..	14
Figure 1-3: Extended Hybrid Surveillance State Transition Diagram (Ownship Operating on Surface)...	15
Figure 2-1: Mode C-Only All-Call Interrogation Pulse Sequence for ACAS X	56
Figure 2-2: Mode S Interrogation Pulse Sequence For ACAS X	58
Figure 2-3: Mode S Interrogation or Uplink Formats Used by ACAS X	60
Figure 2-4: Mode S Reply or Downlink Formats Used by ACAS X.....	61
Figure 2-5: RF Transmissions Containing RA Information	103
Figure 2-6: Mode C Reply	118
Figure 2-7: Mode S Reply.....	120
Figure 2-8: Minimum Basic Whisper-Shout Sequence	126
Figure 2-9: Timing For Six Power Steps In The Minimum Basic Whisper-Shout Sequence For Top Antenna Forward Beam.....	127
Figure 2-10: High Resolution Whisper-Shout Sequence	129
Figure 2-11: Surveillance Region State Transition Diagram.....	146
Figure 2-12: Example Coast Timeline	157
Figure 2-13: The Main Blocks of TRM.....	167
Figure 2-14: State Estimation	168
Figure 2-15: Transformation of Inputs.....	169
Figure 2-16: Estimation of Tau Distribution – Horizontal Entry Table.....	170
Figure 2-18: Offline Cost Estimation – Cost Table Look-up	171
Figure 2-19: Sample Navigation Display Modes.....	216
Figure 2-20: RA Pitch Cues on a PFD.....	223
Figure 2-21: ASA / ACAS X System Interface	267
Figure 2-22: Example CDTI display with designated traffic symbology and associated data block indicating ACAS Xo mode	269
Figure 2-23: Example state chart for one ACAS Xo mode showing CAS logic and validity for a traffic	271
Figure 2-24: Permitted/Prohibited Xo Mode Changes during RA.....	273
Figure 2-25: Signal Relationship Between ACAS X, Mode S & Test Equipment.....	293
Figure 2-26: Definition Of Variables Associated With The Linear Movement Of Targets In The Range Dimension.....	297
Figure 2-27: Frequency Test Setup.....	301
Figure 2-28: Peak Power Test Setup.....	303
Figure 2-29: Whisper-Shout And Interrogation Rate Jitter Test Setup.....	305
Figure 2-30: Mode S Transmission Test Setup.....	311
Figure 2-31: DPSK Phase Reversal Tolerance Test Setup	312
Figure 2-32: Mode S RF Spectrum Test Setup	314
Figure 2-33: Unwanted Output Power Test Setup	316
Figure 2-34: Geometrical Illustration Of Multipath.....	347
Figure 2-35: Real Multipath.....	347
Figure 2-36: Simulated Multipath.....	348
Figure 2-37: Reply Sequence For Range Correlation Test Scenario A (Above 10 Kft).....	350
Figure 2-38: Reply Sequence For Range Correlation Test Scenario B (Below 10 Kft)	351
Figure 2-39: Reply Sequence For Altitude Correlation Test	353
Figure 2-40: Range Vs. Time Plot For Intruders 1, 2, 23, And 24	360
Figure 3-1: Altimetry System Elements and Error Components	623
Figure 3-2: Ramp Test Geometry Considerations	639
Figure A-1: Interference Limiting Flow Diagram.	A-2
Figure A-2: Initial Conditions For Error Detection.	A-6
Figure A-3: Final Conditions Of Error Detection For 56 And 112 Bit Replies.....	A-7
Figure A-4: Initialization Of Error Pattern Location Logic For 56 And 112 Bit Replies.....	A-9
Figure A-5: Generation Of Correction Enable Bit.....	A-11

Figure A-6: Correction Of Decision Sequence.....	A-12
Figure A-7: Final State Of Error Correction Function.....	A-13
Figure A-8: Low Confidence Bit Measurement - Flow Diagram.....	A-14
Figure A-9: Intruder Range Track Comparison - Flow Diagram.....	A-16
Figure B-1: ACAS X Communications.....	B-2
Figure C-1: Gating.....	C-2
Figure C-2: Reduced Update Interval For ADS-B Report.....	C-3
Figure C-3: NACp.....	C-4
Figure C-5: NACv.....	C-4
Figure C-6: Bearingless.....	C-5
Figure C-7: Active update delay.....	C-6
Figure C-8: Reported and Actual Quantization Mismatch.....	C-7
Figure C-9: No Heading Source Available.....	C-8
Figure C-10: Track Angle Supplied as Ownship Heading.....	C-9
Figure C-11: – Ownship Coarse Altitude Quantization.....	C-10
Figure C-12 – Non-Nominal Surveillance Region Compared to TA Alerting Region.....	C-10

TABLE OF TABLES

Table 1-1: Equipment Classes and Designations.....	4
Table 2-1: Assumptions About Aircraft Density.....	42
Table 2-2: Maximum ATRBS Fruit Rate.....	43
Table 2-3: Maximum Mode S FRUIT Rates.....	43
Table 2-4: Aircraft Co-Site Transmissions.....	43
Table 2-5: Interrogation Spectrum.....	49
Table 2-6: Mode C Pulse Shapes.....	56
Table 2-7: Mode S Pulse Shapes.....	57
Table 2-8: Field Index.....	62
Table 2-9: Flight Status Codes.....	68
Table 2-10: Horizontal Sense Bits (HSB field).....	79
Table 2-11: Vertical Sense Bits (VSB field).....	81
Table 2-12: Capability Class (CC) Subfield in Aircraft Operational Status Messages, Airborne Format, in Version 2 Transmitting Subsystems.....	92
Table 2-13: Operational Mode (OM) Subfield in Aircraft Operational Status Messages, Airborne Format	93
Table 2-14: Coordination Timing Requirements.....	100
Table 2-15: Out-of-Band Rejection.....	117
Table 2-16: Illegal Altitude Codes.....	121
Table 2-17: Improvement Factors For Higher Resolution Whisper-Shout Sequences.....	125
Table 2-18: Summary of Rules for Determining Air-Ground Status.....	138
Table 2-19: Interval Between Revalidations.....	152
Table 2-20: Summary of STM Outputs for Intruder Surveillance Inputs.....	166
Table 2-21: ACAS X TRM Processing Modes.....	175
Table 2-22: Barometric Altitude Observation - [ADD Table 2-10].....	180
Table 2-23: Radio Altitude Observation – [ADD Table 2-11].....	181
Table 2-24: Heading Observation – [ADD Table 2-12].....	182
Table 2-25: WGS84 Observation - [ADD Table 2-13].....	183
Table 2-26: Ownship Discretes - [ADD Table 2-8].....	184
Table 2-27: DF0 Message - [ADD Table 2-2].....	185
Table 2-28: Receive Mode C Reply Message - [ADD ModeCReply type].....	186
Table 2-29: State Vector Position Report - [ADD Table 2-5].....	189
Table 2-30: State Vector Velocity Report - [ADD Table 2-6].....	190
Table 2-31: Mode Status Report - [ADD Table 2-7].....	192

Table 2-32: Target Designation – [ADD Table 2-9].....	193
Table 2-33: Designation Field Values	193
Table 2-34: UF16UDS30 Message - [ADD Table 2-14]	194
Table 2-35: Coordination Capability Report	194
Table 2-36: STM /TRM Output Data	195
Table 2-37: StmDisplayStruct.....	197
Table 2-38: TrmIntruderDisplayData	198
Table 2-39: TrmDisplayData	198
Table 2-40: TRMDesignationData.....	199
Table 2-41: TRMIntruderDesignationData.....	200
Table 2-42: TRMCoordinationInterrogationData	202
Table 2-43: Coordination Protocol	203
Table 2-44: TRMRABroadcastData	203
Table 2-45: TRMRACoordinationData	204
Table 2-46: TransponderData	204
Table 2-47: TRMGroundMsgData.....	205
Table 2-48: Recommended Location of No-Bearing Advisories	209
Table 2-49: Mapping Between RA, Aural Annunciation, and ARINC Word 270 Contents	228
Table 2-50: ACAS X Display and Controls Output (Control Panel).....	242
Table 2-51: ACAS X Display and Controls Output (Displays).....	243
Table 2-52: ACAS X Display and Controls Outputs (Aural Annunciations).....	243
Table 2-53: ACAS X Display and Controls Inputs (RA Displays).....	244
Table 2-54: ACAS X Display and Controls Inputs (Aural Annunciations).....	248
Table 2-55: ACAS X Display and Controls Inputs (Traffic Display).....	249
Table 2-56: Recommended Display Actions and Monitor Response to “Not Operational” Status Received from ACAS X Displays	255
Table 2-57: ACAS X Display and Controls Inputs (RA Displays).....	262
Table 2-58: ACAS X Display and Controls Inputs (Aural Annunciations).....	262
Table 2-59: ACAS X Display and Controls Inputs (Traffic Display).....	263
Table 2-60: ACAS X Display and Controls Output (Control Panel).....	263
Table 2-61: ACAS X Display and Controls Output (Displays)	264
Table 2-62: ASA System Traffic state information (for each traffic) for display for ACAS Xo	277
Table 2-63: Nominal ASA System DNA States (for each traffic)	278
Table 2-64: Nominal ASA System CSPO-3000 States (for each traffic)	279
Table 2-65: Nominal ACAS Xo System DNA States (for each traffic)	280
Table 2-66: Nominal ACAS Xo System CSPO-3000 States (for each traffic).....	282
Table 2-67: Designation Status	283
Table 2-68: Environmental Test Groupings.....	286
Table 2-69: Applicable Test Groups per Environmental Condition	288
Table 2-70: Standard Test Signal Pulse Shapes.....	291
Table 2-71: Standard Test Signal Total Jitter	292
Table 2-72: Confidence Factor Required For A 90% Confidence Level.....	319
Table 2-73: Minimum Number Of Trials Vs. Number Of Failures For The Required Probability Of Success Values Specified In §2.4.2.1.2	320
Table 2-74: Squitter And Reply Probability Vs. Range And Altitude.....	381
Table 2-75: Functional Areas Covered by Test Suite	397
Table 2-76: Input File Details	398
Table 2-77: STM Report Details.....	401
Table 2-78: TRM Report Details	403
Table 2-79: CostFile Details	405
Table 2-80: STM Report Test Values and Tolerances	407
Table 2-81: TRM Report Test Values and Tolerances	408
Table 2-82: Cost Value Tolerances.....	409
Table 2-83: Branches of Prescriptive Algorithms Not Covered By Prescriptive Test Encounters.....	410

Table 2-84: Unreachable Branches (Defensive Code) in Prescriptive Algorithms.....	411
Table 2-85: Unreachable Branches (Defensive Code) in Suggestive Algorithms	412
Table 2-86: Round Dial VSI RA Tests	504
Table 2-87: Vertical Speed Tape RA Tests	508
Table 2-88: RA Tests for Implementations Using Pitch Cues on a PFD.....	513
Table 2-89: RA Depiction Using Flight Director Guidance	517
Table 2-90: Tests for Implementations Displaying RAs on a HUD	520
Table 2-91: Airborne Position Decoding Values With Range and Bearing	576
Table 2-92: Cross-Reference of Requirements to Associated Tests	592
Table 2-93: Cross-Reference of Associated Tests to Requirements	606
Table 3-1: Specification Of Total Altimetry System Performance.....	623
Table A-1: Code Pulse Agreement	A-18
Table C-1: ADS-B Degradations	C-11
Table C-2: Degraded Inputs Affecting Active Tracks	C-11
Table D-1: Comparison of R and N for a Spherical Earth Radius as a Function of Latitude	D-2
Table D-2: Example of Errors in Spherical Earth Approximation	D-4
Table D-3: Example of Errors Using the Same N for Both Aircraft.....	D-5
Table D-4: Example of Errors in Ellipsoidal Differential Approximation with No Longitude Difference	D-7
Table D-5: Example of Errors in Ellipsoidal Differential Approximation with No Latitude Difference .	D-8
Table D-6: Example of Errors in Ellipsoidal Differential Approximation with Combined Latitude, Longitude and Height Differences.....	D-9
Table D-7: Example of Errors in Spherical Differential Approximation with No Longitude Difference.....	D-10
Table D-8: Example of Errors in Spherical Differential Approximation with No Latitude Difference .	D-11
Table D-9: Example of Errors in Spherical Differential Approximation with Combined Latitude, Longitude and Height Differences.....	D-12
Table E-1 Error Sources in the Hybrid Slant Range Calculation and Validation with ACAS X Range ..	E-2
Table E-2: Sample Allocation of Hybrid Data Processing Errors	E-4
Table F-1: Test Group 10F	F-1
Table F-2: Test Group 20.....	F-12
Table F-3: Test Group 30.....	F-17
Table F-4: Test Group 40.....	F-30
Table F-5: Test Group 50.....	F-32
Table F-6: Test Group 60.....	F-36
Table F-7: Test Group 70.....	F-64
Table H-1: Simulated Reduction in 1090 MHz Receiver Occupancy	H-7

1 PURPOSE AND SCOPE

1.1 Introduction

This document sets forth minimum operational performance standards for the Airborne Collision Avoidance System X (ACAS X) equipment, including both Active surveillance (Xa) and special Operations (Xo) functions. Unless otherwise noted, ACAS X references in this document refer to ACAS Xa/Xo.

ACAS X is intended to improve air safety by acting as a last-resort method of preventing mid-air collisions or near mid-air collisions (NMAC) between aircraft. By utilizing surveillance information from Secondary Surveillance Radar (SSR) and ADS-B technology, ACAS X equipment operates independently of ground-based aids and air traffic control (ATC). Aircraft equipped with ACAS X have the ability to interrogate airborne transponders and receive ADS-B Messages to determine the location of other aircraft in the vicinity and assess the risk of collision. ACAS Xa/Xo equipment is not required to detect non-cooperative aircraft.

ACAS X provides Traffic Advisories (TAs) and Resolution Advisories (RAs) in the vertical plane. RAs are indications given to the flight crew recommending maneuvers intended to avoid collisions with all threats, or restrict maneuvers to maintain existing separation. (In this document the term *separation* means physical separation, i.e., absence of NMAC, and should not be confused with the provision of ATC minimum separation.) ICAO standards give ACAS RAs priority over ATC clearances and instructions, i.e., flight crews are instructed to follow RAs even when it conflicts with ATC guidance (Ref. ICAO Doc. 8168 – PANS-OPS, §3.2.c.2). Controllers typically have no knowledge of RAs unless notified by the flight crew via the radio. RA information is provided by ACAS X to Mode S SSRs and ADS-B ground radios, but typically is not presented to controllers. Some alerts (e.g. wind shear warnings, stall warnings, and Ground Proximity Warning System warnings) have higher priority than ACAS RAs. Results of United States and European safety studies show that there is a significant safety benefit to be gained from the widespread carriage and operation of ACAS, specifically, the risk of mid-air collision is reduced by at least a factor of three (Ref. ACASA/WP1.8/210D/V1.1 27-12-01). Globally, operational experience has shown that ACAS systems have significantly improved the safety of flight.

Incorporated within these standards are system characteristics that should be of value to users, designers, manufacturers, and installers. These characteristics are intended to accommodate the requirements of various users.

1.1.1 Document Structure

This document is published in two volumes.

Section 1 of Volume I is intended to provide information needed to understand the rationale for equipment characteristics and requirements stated in the remaining sections. It describes typical equipment applications and operational goals and is the basis for the standards stated in the document. Definitions essential to proper understanding of this document are also provided in Section 1.

Section 2 of Volume I contains the minimum performance standards for the equipment. These standards define the required performance under standard operating conditions and stressed physical environmental conditions. It also details bench test procedures that demonstrate compliance, including specific bench tests for the collision avoidance logic performance.