

RTCA, Inc.
1828 L Street, NW, Suite 805
Washington, DC 20036-5133 USA

**Minimum Operational Performance Standards
for Global Positioning System / Wide Area
Augmentation System Airborne Equipment**

RTCA DO-229D
December 13, 2006

Prepared by: SC-159
© 2006 RTCA, Inc.

Copies of this document may be obtained from

RTCA, Inc.

Telephone: 202-833-9339

Facsimile: 202-833-9434

Internet: www.rtca.org

Please visit the RTCA Online Store for document pricing and ordering information.

Foreward

This report was prepared by Special Committee 159 (SC-159) and approved by the RTCA Program Management Committee (PMC) on December 13, 2006.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal Advisory Committee and develops consensus based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- Coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- Analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity, and efficiency;
- Developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- Assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organizations' recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

This Page Intentionally Left Blank

TABLE OF CONTENTS

1.0	<i>PURPOSE AND SCOPE</i>	1
1.1	Introduction	1
1.2	System Overview	3
1.2.1	Wide Area Augmentation System	3
1.2.2	GNSS Satellite Signal Characteristics	4
1.2.2.1	GPS Signal Characteristics	4
1.2.2.2	WAAS Signal Characteristics	5
1.3	Operational Goals	6
1.3.1	Intended Operational Applications	6
1.3.2	Operational Environment	6
1.3.3	International Compatibility	7
1.4	Equipment Classes	8
1.4.1	Functional Classes	8
1.4.2	Operational Classes	9
1.4.3	Relation of Classes to Document Organization	10
1.5	Aiding and Barometric Vertical Navigation	11
1.5.1	SBAS and Barometric Vertical Navigation	11
1.5.2	Aiding of Fault Detection and Exclusion	12
1.6	Test Considerations	12
1.6.1	Environmental Tests	12
1.6.2	Bench Tests	12
1.7	Definition of Key Terms	13
1.7.1	General Terms	13
1.7.2	Alert Limits and Protection Levels	14
1.7.3	Fault Detection and Exclusion (FDE) Terms	15
1.8	Assumptions and Approach to Selected Issues	20
1.8.1	General	20
1.8.1.1	GPS Constellation and WAAS/SBAS Ground/Space Segments	20
1.8.1.2	GPS/SBAS Performance	20
1.8.1.3	Applicability	21
1.8.1.4	Interoperability	21
1.8.1.5	Integrity Monitoring	21
1.8.1.6	Navigational Waypoints	21
1.8.1.7	RF Interference	22
1.8.1.8	Time of Applicability of Information in the SBAS Signal-in-Space	22
1.8.1.9	Change of Broadcast Ephemeris	22
1.8.1.10	SBAS Regional Message Type (Message Type 27 and 28)	22
1.8.2	Approach Applications	22
1.8.2.1	SBAS Performance for Approaches	22
1.8.2.2	Approach Path-in-Space	23
1.8.2.3	LNAV/VNAV, LP, LPV Approach Position Integrity	23
1.8.2.4	Vector-to-Final (VTF) Approach	24
2.0	<i>EQUIPMENT PERFORMANCE AND TEST PROCEDURES</i>	25
2.1	General Requirements	25
2.1.1	Requirements Applicable to Beta, Gamma, and Delta Equipment	25
2.1.1.1	General Requirements for All Navigation Modes	25
2.1.1.1.1	Airworthiness	25
2.1.1.1.2	General Performance	25

2.1.1.1.3	Fire Resistance	25
2.1.1.1.4	Equipment Interfaces	25
2.1.1.1.5	Effects of Test	25
2.1.1.2	GPS Signal Processing Requirements	25
2.1.1.3	SBAS Signal Processing Requirements	26
2.1.1.3.1	Acquisition and Track	26
2.1.1.3.2	Demodulation and Forward Error Correction (FEC) Decoding	27
2.1.1.3.3	SBAS Satellite Pseudorange Determination	27
2.1.1.4	SBAS Message Processing	27
2.1.1.4.1	Message Type 0 - Don't Use for Safety Applications	27
2.1.1.4.2	Message Type 1 - PRN Mask Assignments	28
2.1.1.4.3	Message Types 2-5 and 24 - Fast Corrections	28
2.1.1.4.4	Message Type 6 - Integrity Information	28
2.1.1.4.5	Message Type 7 - Fast Correction Degradation	29
2.1.1.4.6	Message Type 9 - SBAS Satellite Navigation Message	29
2.1.1.4.7	Message Type 17 - SBAS Satellite Almanac	29
2.1.1.4.8	Message Type 27 - SBAS Service Message	29
2.1.1.4.9	Message Timeout Periods	29
2.1.1.4.10	Combining Data from Separate Broadcasts	31
2.1.1.4.11	Message Type 24 and 25 Long-Term Corrections	31
2.1.1.4.12	Application of Differential Corrections	32
2.1.1.4.13	Message Type 28 - Clock-Ephemeris Covariance Matrix Message	33
2.1.1.5	Satellite Integrity Status	33
2.1.1.5.1	Step Detector	33
2.1.1.5.2	SBAS UNHEALTHY Designation	34
2.1.1.5.3	SBAS UNMONITORED Designation	34
2.1.1.5.4	SBAS HEALTHY Designation	34
2.1.1.5.5	GPS UNHEALTHY Designation	35
2.1.1.5.6	GPS HEALTHY Designation	35
2.1.1.6	Satellite Selection	35
2.1.1.7	Initial Acquisition Time	36
2.1.1.8	Satellite Acquisition Time	37
2.1.1.8.1	GPS Satellite Acquisition Time	37
2.1.1.8.2	SBAS Satellite Acquisition Time	37
2.1.1.9	Satellite Reacquisition Time	37
2.1.1.10	Sensitivity and Dynamic Range	37
2.1.1.11	Equipment Burnout Protection	39
2.1.1.12	Integrity in the Presence of Interference	39
2.1.1.13	Alerts/Outputs	40
2.1.1.13.1	Protection Level	40
2.1.1.13.2	Navigation Alert	40
2.1.2	Requirements for En Route and Terminal Mode	41
2.1.2.1	Accuracy	41
2.1.2.2	Integrity Requirements	41
2.1.2.2.1	Development Assurance	41
2.1.2.2.1.1	Hardware Compliance	42
2.1.2.2.1.2	Software Compliance	42
2.1.2.2.2	Integrity Monitoring	42
2.1.2.2.2.1	SBAS-Provided Integrity Monitoring	42
2.1.2.2.2.2	FDE-Provided Integrity Monitoring	42
2.1.2.2.2.2.1	Time-to-Alert	44
2.1.2.2.2.2.2	Missed Alert Probability	44
2.1.2.2.2.2.3	False Alert Probability	44
2.1.2.2.2.2.4	Failed Exclusion Probability	44
2.1.2.2.2.2.5	Availability	45
2.1.2.3	Equipment Reliability	45
2.1.2.4	Satellite Tracking Capability	45

2.1.2.5	Dynamic Tracking	45
2.1.2.6	Position Output	46
2.1.2.6.1	Position Output Data Update Rate	46
2.1.2.6.2	Position Output Data Latency	46
2.1.3	Requirements for LNAV	46
2.1.3.1	Accuracy	46
2.1.3.2	Integrity Requirements	46
2.1.3.2.1	Development Assurance	46
2.1.3.2.1.1	Hardware Compliance	46
2.1.3.2.1.2	Software Compliance	46
2.1.3.2.2	Integrity Monitoring	46
2.1.3.2.2.1	SBAS-Provided Integrity Monitoring	47
2.1.3.2.2.2	FDE-Provided Integrity Monitoring	47
2.1.3.2.2.2.1	Time-to-Alert	47
2.1.3.2.2.2.2	Missed Alert Probability	47
2.1.3.2.2.2.3	False Alert Probability	47
2.1.3.2.2.2.4	Failed Exclusion Probability	47
2.1.3.2.2.2.5	Availability	47
2.1.3.2.2.3	FD Prediction	47
2.1.3.3	Equipment Reliability	48
2.1.3.4	Satellite Tracking Capability	48
2.1.3.5	Dynamic Tracking	48
2.1.3.6	Position Output	48
2.1.3.6.1	Position Output Update Rate	49
2.1.3.6.2	Position Output Latency	49
2.1.3.7	SBAS Message Processing	49
2.1.3.8	Application of Differential Correction Terms	49
2.1.3.9	Satellite Selection	49
2.1.4	Requirements for LNAV/VNAV Operations	49
2.1.4.1	Accuracy	49
2.1.4.1.1	Smoothing	49
2.1.4.1.2	Measurement Quality Monitoring	50
2.1.4.1.3	Accuracy	50
2.1.4.1.4	GPS Satellites	51
2.1.4.1.5	SBAS Satellites	51
2.1.4.1.6	Position Solution	52
2.1.4.2	Integrity Requirements	52
2.1.4.2.1	Development Assurance	52
2.1.4.2.1.1	Hardware Compliance	52
2.1.4.2.1.2	Software Compliance	52
2.1.4.2.2	Integrity Monitoring	52
2.1.4.2.2.1	SBAS-Provided Integrity Monitoring	52
2.1.4.2.2.2	Fault Detection-Provided Integrity Monitoring	52
2.1.4.2.2.2.1	Frequency of Fault Detection	53
2.1.4.2.2.2.2	Missed Alert	53
2.1.4.2.2.2.3	False Alert	53
2.1.4.2.2.2.4	Availability	53
2.1.4.3	Equipment Reliability	53
2.1.4.4	Satellite Tracking Capability	53
2.1.4.5	Tracking Constraints	53
2.1.4.5.1	GPS Tracking Constraints	54
2.1.4.5.2	SBAS Tracking Constraints	56
2.1.4.6	Correlation Peak Validation	56
2.1.4.7	Dynamic Tracking	57
2.1.4.8	Position Output	57
2.1.4.8.1	Position Output Update Rate	57
2.1.4.8.2	Position Output Latency	57

2.1.4.9	SBAS Message Processing	57
2.1.4.9.1	Message Type 2-5, 6 and 24 Fast Corrections	57
2.1.4.9.2	Message Types 24 and 25 Long-Term Corrections	58
2.1.4.9.3	Message Type 18 - Ionospheric Grid Point Masks	58
2.1.4.9.4	Message Type 26 - Ionospheric Grid Point Delays	58
2.1.4.9.5	Message Types 7 and 10 - Degradation Parameters	58
2.1.4.10	Application of Differential Correction Terms	58
2.1.4.10.1	Application of Clock and Ephemeris Corrections	58
2.1.4.10.2	Application of Ionospheric Corrections	58
2.1.4.10.3	Application of Tropospheric Corrections	59
2.1.4.11	Satellite Selection	59
2.1.4.12	Alerts/Outputs/Inputs	59
2.1.4.12.1	Protection Level	59
2.1.4.12.2	Navigation Alert	60
2.1.5	Requirements for LPV and LP Approach Operations	60
2.1.5.1	Accuracy	60
2.1.5.2	Integrity Requirements	60
2.1.5.2.1	Development Assurance	60
2.1.5.2.1.1	Hardware Compliance	61
2.1.5.2.1.2	Software Compliance	61
2.1.5.2.2	Integrity Monitoring	61
2.1.5.2.2.1	SBAS-Provided Integrity Monitoring	61
2.1.5.2.2.2	Fault Detection-Provided Integrity Monitoring	61
2.1.5.2.2.2.1	Frequency of Fault Detection	62
2.1.5.2.2.2.2	Missed Alert	62
2.1.5.2.2.2.3	False Alert	62
2.1.5.2.2.2.4	Availability	62
2.1.5.3	Equipment Reliability	62
2.1.5.4	Satellite Tracking Capability	62
2.1.5.5	Tracking Constraints	62
2.1.5.5.1	GPS Tracking Constraints	62
2.1.5.5.2	SBAS Tracking Constraints	62
2.1.5.6	Correlation Peak Validation	62
2.1.5.7	Dynamic Tracking	62
2.1.5.8	Position Output	62
2.1.5.8.1	Position Output Update Rate	62
2.1.5.8.2	Position Output Latency	63
2.1.5.9	SBAS Message Processing	63
2.1.5.9.1	Message Type 2-5, 6 and 24 Fast Corrections	63
2.1.5.9.2	Message Types 24 and 25 Long-Term Corrections	63
2.1.5.9.3	Message Type 18 - Ionospheric Grid Point Masks	63
2.1.5.9.4	Message Type 26 - Ionospheric Grid Point Delays	63
2.1.5.9.5	Message Types 7 and 10 - Degradation Parameters	63
2.1.5.10	Application of Differential Correction Terms	63
2.1.5.11	Satellite Selection	63
2.1.5.12	Alerts/Outputs/Inputs	64
2.1.5.12.1	Protection Level	64
2.1.5.12.2	Navigation Alert	64
2.1.5.13	HPL and VPL Prediction	64
2.2	Class Gamma Requirements	66
2.2.1	Class Gamma General Requirements	66
2.2.1.1	General Human Factors Requirements and Applicable Documents	66
2.2.1.1.1	Controls	67
2.2.1.1.1.1	Operation	67
2.2.1.1.1.2	Control Labels	67
2.2.1.1.2	Equipment Operating Procedures	67

2.2.1.1.3	Minimum Workload Functions	67
2.2.1.1.4	Displays	69
2.2.1.1.4.1	Discernability	69
2.2.1.1.4.2	Brightness, Contrast, and Color	70
2.2.1.1.4.3	Angle of Regard	70
2.2.1.1.4.4	Symbology	70
2.2.1.1.4.5	Alphanumerics	70
2.2.1.1.4.6	Moving Map	71
2.2.1.1.4.7	Primary Navigation Display	71
2.2.1.1.4.8	Bearing Labels	71
2.2.1.1.5	Annunciations	71
2.2.1.1.5.1	Annunciators	72
2.2.1.1.5.2	Messages	72
2.2.1.1.6	Set of Standard Function Labels	72
2.2.1.1.7	Set of Standard Abbreviations and Acronyms	73
2.2.1.2	Path Selection	76
2.2.1.2.1	Flight Plan Selection	76
2.2.1.2.2	Flight Plan Review	76
2.2.1.2.3	Flight Plan Activation	77
2.2.1.2.4	Waypoint Sequencing	77
2.2.1.2.5	Manually-Selected Active Waypoint	77
2.2.1.2.5.1	Direct To	77
2.2.1.2.5.2	TO/FROM Course Selection	77
2.2.1.2.5.3	Manually-Selected Waypoint and Waypoint Sequencing	78
2.2.1.2.6	User-Defined Waypoints	78
2.2.1.2.7	Emergency Procedures	78
2.2.1.3	Path Definition	78
2.2.1.3.1	Initial Fix (IF)	79
2.2.1.3.2	Fixed Waypoint to a Fixed Waypoint (TF)	79
2.2.1.3.3	DME Arcs (AF) and Constant Radius to a Fix (RF)	79
2.2.1.3.4	Direct To (DF)	80
2.2.1.3.5	Course to a Fix Waypoint (CF)	81
2.2.1.3.6	FROM Leg	81
2.2.1.3.7	Fly-By Turns	81
2.2.1.3.7.1	Fly-By Turn Indications	82
2.2.1.3.7.2	Fly-By Theoretical Transition Area	82
2.2.1.3.7.3	Acceptable Means of Defining Fly-By Turns	83
2.2.1.3.8	Fly Over Turns	83
2.2.1.3.9	Fixed Radius Turns	84
2.2.1.3.10	Waypoint Sequencing	84
2.2.1.3.11	Holding Patterns / Procedure Turns	85
2.2.1.3.12	Magnetic Course	86
2.2.1.3.13	Dead Reckoning	86
2.2.1.3.14	Fuel Management and Alerting	86
2.2.1.3.15	Geodesic Path Computation Accuracy	87
2.2.1.3.16	Parallel Offsets	87
2.2.1.4	Navigation Displays	88
2.2.1.4.1	Primary Navigation Display	88
2.2.1.4.2	Non-Numeric Display/Output Characteristics	88
2.2.1.4.2.1	Electrical Output	88
2.2.1.4.2.2	Display	89
2.2.1.4.3	Active Waypoint Distance Display	89
2.2.1.4.4	Active Waypoint Bearing Display	89
2.2.1.4.5	Track Displays	90
2.2.1.4.5.1	Desired Track	90
2.2.1.4.5.2	Track Angle	90
2.2.1.4.5.3	Track Angle Error	90

2.2.1.4.6	Display of TO or FROM Operation	90
2.2.1.4.7	Waypoint Bearing/Distance Display	90
2.2.1.4.8	Estimate of Position Uncertainty	90
2.2.1.4.9	Magnetic Course	90
2.2.1.4.10	Ground Speed	90
2.2.1.4.11	Aircraft Present Position	91
2.2.1.5	Database Requirements	91
2.2.1.5.1	Access	91
2.2.1.5.2	Content	91
2.2.1.5.3	Database Standard	92
2.2.1.5.4	Reference Coordinate System	92
2.2.1.5.4.1	Incorporation of Conversion Algorithms	92
2.2.1.5.4.2	Operational Approval	92
2.2.1.6	Alerts/Outputs	93
2.2.1.6.1	Caution Associated with Loss of Integrity Monitoring	93
2.2.1.6.2	Caution Associated with Loss of Navigation	93
2.2.1.7	Mode Switching Requirements	93
2.2.2	Class Gamma Requirements for En Route / Terminal Operation	97
2.2.2.1	General Human Factors Requirements	97
2.2.2.2	Path Selection	97
2.2.2.3	Path Definition	97
2.2.2.4	Navigation Displays	97
2.2.2.4.1	Primary Navigation Displays	97
2.2.2.4.2	Non-Numeric Cross-Track Deviation	98
2.2.2.4.3	Numeric Cross-Track Deviation	98
2.2.2.4.4	Displayed Data Update Rate	98
2.2.2.4.5	Display Update Latency	98
2.2.2.5	Database Requirements	98
2.2.2.6	Alerts	98
2.2.2.6.1	Alert Limits	98
2.2.2.6.2	Caution Associated with Loss of Integrity Monitoring	98
2.2.2.6.3	Caution Associated with Loss of Navigation	99
2.2.2.7	En Route / Terminal Mode Switching Requirements	99
2.2.2.7.1	En Route Mode Switching Requirements	99
2.2.2.7.1.1	Entry Criteria	99
2.2.2.7.1.2	Exit Criteria	100
2.2.2.7.1.3	Display Transition Requirements	100
2.2.2.7.2	Terminal Mode Switching Requirements	100
2.2.2.7.2.1	Entry Criteria	100
2.2.2.7.2.2	Exit Criteria	100
2.2.2.7.2.3	Display Transition Requirements	100
2.2.3	Class Gamma Requirements for LNAV Approach Operation	100
2.2.3.1	General Human Factors Requirements	100
2.2.3.2	Path Selection	100
2.2.3.2.1	Approach Selection	101
2.2.3.2.2	Missed Approach Sequencing	101
2.2.3.3	Path Definition	101
2.2.3.3.1	Approach Path Definition	101
2.2.3.3.2	Missed Approach Path Definition	103
2.2.3.3.3	Departure Path Definition	104
2.2.3.3.4	Vertical Path for LNAV Procedures	104
2.2.3.4	Navigation Displays	105
2.2.3.4.1	Primary Navigation Displays	105
2.2.3.4.2	Non-Numeric Cross-Track Deviation	105
2.2.3.4.3	Numeric Cross-Track Deviation	105
2.2.3.4.4	Missed Approach Waypoint Distance Display	106
2.2.3.4.5	Missed Approach Waypoint Bearing Display	106

2.2.3.4.6	Displayed Data Update Rate	106
2.2.3.4.7	Display Update Latency	106
2.2.3.5	Database Requirements	106
2.2.3.6	Alerts	107
2.2.3.6.1	Alert Limits	107
2.2.3.6.2	Caution Associated with Loss of Integrity Monitoring	107
2.2.3.6.3	Caution Associated with Loss of Navigation	107
2.2.3.7	Mode Switching Requirements	108
2.2.3.7.1	LNAV Approach Mode Switching Requirements	108
2.2.3.7.1.1	Entry Criteria	108
2.2.3.7.1.2	Exit Criteria	108
2.2.3.7.1.3	Display Transition Requirements	108
2.2.3.7.2	Departure Requirements	109
2.2.3.7.2.1	Entry Criteria	109
2.2.3.7.2.2	Exit Criteria	109
2.2.3.7.2.3	Display Transition Requirements	109
2.2.4	Class Gamma Requirements for LNAV/VNAV Operations	109
2.2.4.1	General Human Factors Requirements	109
2.2.4.2	Path Selection	109
2.2.4.2.1	5-Digit Channel Selection	109
2.2.4.2.2	Approach Selection	110
2.2.4.2.3	Missed Approach Sequencing	110
2.2.4.2.4	Deselection of Vertical Guidance	110
2.2.4.3	Path Definition	110
2.2.4.3.1	Approach Path Definition	110
2.2.4.3.2	Missed Approach Path Definition	111
2.2.4.3.3	Navigation Center Offset	111
2.2.4.4	Navigation Displays	111
2.2.4.4.1	Primary Navigation Displays	111
2.2.4.4.2	Non-Numeric Lateral Cross-Track Deviation	112
2.2.4.4.2.1	Definition of Final Approach Segment Lateral deviations	112
2.2.4.4.2.2	Non-VTF Deviation with FAS Data Block	112
2.2.4.4.2.3	VTF Deviation with FAS Data Block	113
2.2.4.4.2.4	Deviation without FAS Data Block	113
2.2.4.4.2.5	Missed Approach Deviation	113
2.2.4.4.3	Numeric Lateral Cross-Track Deviation	114
2.2.4.4.4	Non-Numeric Vertical Deviation	114
2.2.4.4.5	Missed Approach Waypoint/LTP/FTP Distance Display	116
2.2.4.4.6	Missed Approach Waypoint/LTP/FTP Bearing Display	116
2.2.4.4.7	Displayed Data Update Rate	116
2.2.4.4.8	Display Update Latency	117
2.2.4.4.9	Display of Vertical Accuracy	117
2.2.4.5	Database Requirements	117
2.2.4.5.1	Content	117
2.2.4.5.2	Data Integrity	118
2.2.4.6	Alerts	118
2.2.4.6.1	Alert Limits	118
2.2.4.6.2	Caution Associated with Loss of Integrity Monitoring	118
2.2.4.6.3	Caution Associated with Loss of Navigation	119
2.2.4.6.4	Low Altitude Alert	120
2.2.4.6.5	Alerting Scheme	120
2.2.4.7	LNAV/VNAV Approach Mode Switching Requirements	120
2.2.4.7.1	Entry Criteria	120
2.2.4.7.2	Exit Criteria	121
2.2.4.7.3	Display Transition	121
2.2.4.7.4	Advisory of LNAV/VNAV Availability	121
2.2.5	Class Gamma Requirements for LP and LPV Approach Operations	121

2.2.5.1	General Human Factors Requirements	121
2.2.5.2	Path Selection	122
2.2.5.2.1	5-Digit Channel Selection	122
2.2.5.2.2	Approach Name Selection	122
2.2.5.2.3	Missed Approach Sequencing	122
2.2.5.2.4	Selection of the Approach Type	122
2.2.5.3	Path Definition	122
2.2.5.3.1	Approach Path Definition	122
2.2.5.3.2	Missed Approach Path Definition	122
2.2.5.3.3	Navigation Center Offset	122
2.2.5.4	Navigation Displays	123
2.2.5.4.1	Primary Navigation Displays	123
2.2.5.4.2	Non-Numeric Lateral Cross-Track Deviation	123
2.2.5.4.2.1	Definition of Final Approach Segment Lateral Deviations	123
2.2.5.4.2.2	Non-VTF Deviation	123
2.2.5.4.2.3	VTF Deviation	123
2.2.5.4.2.4	Missed Approach Deviation	123
2.2.5.4.3	Numeric Lateral Cross-Track Deviation	123
2.2.5.4.4	Non-Numeric Vertical Deviation	123
2.2.5.4.5	Missed Approach Waypoint/LTP/FTP Distance Display	123
2.2.5.4.6	Missed Approach Waypoint/LTP/FTP Bearing Display	123
2.2.5.4.7	Displayed Data Update Rate	123
2.2.5.4.8	Display Update Latency	123
2.2.5.4.9	Display of Vertical Accuracy	124
2.2.5.5	Database Requirements	124
2.2.5.5.1	Content	124
2.2.5.5.2	Data Integrity	124
2.2.5.6	Alerts	125
2.2.5.6.1	Alert Limits	125
2.2.5.6.2	Caution Associated with Loss of Integrity Monitoring	125
2.2.5.6.3	Caution Associated with Loss of Navigation	125
2.2.5.6.4	Low Altitude Alert	126
2.2.5.6.5	Alerting Scheme	126
2.2.5.7	LP/LPV Approach Mode Switching Requirements	127
2.2.5.7.1	Entry Criteria	127
2.2.5.7.2	Exit Criteria	127
2.2.5.7.3	Display Transition	127
2.2.5.7.4	Advisory of LPV, LP Availability	127
2.3	Class Delta-4 Requirements for Approach Operations	128
2.3.1	General Human Factors Requirements	128
2.3.2	Approach Selection	128
2.3.2.1	Confirmation of Selected Approach	128
2.3.3	Path Definition	128
2.3.3.1	Navigation Center Offset	129
2.3.4	Navigation Displays	129
2.3.4.1	Non-Numeric Lateral Cross-Track Deviation	129
2.3.4.2	Non-Numeric Vertical Deviation	129
2.3.4.3	Landing Threshold Point/Fictitious Threshold Point Distance Display	129
2.3.4.4	Data Update Rate	129
2.3.4.5	Data Update Latency	129
2.3.5	Database Requirements	129
2.3.5.1	Content	130
2.3.5.2	Access	130
2.3.6	Alerts	130
2.3.6.1	Alert Limits	130
2.3.6.2	Caution Associated with Loss of Navigation	130

2.4	Airborne Equipment Performance - Environmental Conditions	131
2.4.1	Environmental Tests	132
2.4.1.1	Required Performance	132
2.4.1.1.1	Accuracy	132
2.4.1.1.2	Loss of Navigation Indication	133
2.4.1.1.3	Loss of Integrity Indication	133
2.4.1.1.4	Initial Acquisition Test	133
2.4.1.1.5	Sensitivity and Dynamic Range	133
2.4.1.1.6	Navigation Display	133
2.4.1.1.7	Database	133
2.4.1.1.8	Mode Annunciation	133
2.4.1.1.9	TO-TO and TO-FROM Capability	133
2.4.1.1.10	System Operating	134
2.4.1.2	Clarification of Environmental Tests	134
2.4.1.2.1	Power Input Tests	134
2.4.1.2.2	Icing Tests	134
2.4.1.2.3	RF and Induced Signal Susceptibility Tests	134
2.4.1.2.4	Lightning Induced Transient Susceptibility Tests	135
2.4.1.2.5	Lightning Direct Effects Tests	135
2.4.1.2.6	Crash Safety Shock	135
2.5	Test Methods and Procedures	143
2.5.1	Test Cross Reference Matrix	145
2.5.2	SBAS Message Loss Rate Test	223
2.5.2.1	Evaluation of Message Loss Rate During the Measurement Accuracy Test	223
2.5.2.2	Test Procedure	223
2.5.2.3	Pass/Fail Determination	223
2.5.2.4	Evaluation of Message Loss Rate During the 24-Hour System Accuracy Test	223
2.5.2.4.1	Test Procedure	223
2.5.2.4.2	Pass/Fail Criteria	223
2.5.3	Step Detector Test	223
2.5.3.1	Verification of Step Detector Operation Without Exclusion Capability	224
2.5.3.2	Verification of No Interference with Fault Detection Algorithm	224
2.5.3.3	Verification of Step Detector Operation with Exclusion Capability	224
2.5.3.4	Verification of No Interference with Exclusion of the FDE Algorithm	225
2.5.4	Initial Acquisition Test Procedures	225
2.5.4.1	Simulator and Interference Conditions	225
2.5.4.2	Test Procedures (Initial Acquisition)	226
2.5.4.3	Pass/Fail Determination	226
2.5.4.4	Test Procedures (Initial Acquisition After Abnormal Interference)	228
2.5.5	Reserved	228
2.5.6	Satellite Reacquisition Time Test	228
2.5.6.1	Simulator and Interference Conditions	228
2.5.6.2	Test Procedures	229
2.5.6.3	Pass/Fail Determination	230
2.5.7	Interference Rejection Test	230
2.5.7.1	Simulator and Interference Conditions	230
2.5.7.2	Test Procedures	231
2.5.7.3	Pass/Fail Determination	231
2.5.8	Accuracy Tests	231
2.5.8.1	Measurement Accuracy Test	231
2.5.8.2	Simulator and Interference Conditions	232
2.5.8.2.1	Test Procedures	234
2.5.8.3	24-Hour Actual Satellite Accuracy Test	236
2.5.8.3.1	Test Procedure	236
2.5.8.3.2	Pass/Fail Criteria	236
2.5.8.4	SBAS Tracking Bias	236

2.5.9	Integrity Monitoring Test Procedures	237
2.5.9.1	General Test Conditions	237
2.5.9.1.1	Test Philosophy	237
2.5.9.1.2	GPS Constellation	237
2.5.9.1.3	Applicability of RTCA/DO-178B	237
2.5.9.1.4	Test Repetition	238
2.5.9.1.5	Protection Level/Alert Limit	238
2.5.9.1.6	Time-to-Alert	238
2.5.9.2	Availability Tests	238
2.5.9.3	Off-Line FDE Tests	241
2.5.9.3.1	Off-Line Test Setup	241
2.5.9.3.2	Selection of Geometries	241
2.5.9.3.3	Test Procedure	242
2.5.9.3.3.1	Class Gamma Equipment	242
2.5.9.3.3.2	Class Beta Equipment	243
2.5.9.3.4	Pass/Fail Criteria	243
2.5.9.4	False Alert Rate Test	244
2.5.9.4.1	False Alert Rate Simulations for Snapshot Algorithms	244
2.5.9.4.2	False Alert Rate Simulations for Non-Snapshot Algorithms	245
2.5.9.5	On-Line Verification Test	245
2.5.9.5.1	On-Target Computational Test	245
2.5.9.5.2	On-Line Behavioral Test	246
2.5.10	LNAV/VNAV, LP, LPV Approach Fault Detection	246
2.5.10.1	General Test Conditions	246
2.5.10.1.1	Test Philosophy	246
2.5.10.1.2	GPS Constellation	246
2.5.10.1.3	Applicability of RTCA/DO-178B	247
2.5.10.1.4	Test Repetition	247
2.5.10.1.5	Protection Level/Alert Limit	247
2.5.10.1.6	Time-to-Alert	247
2.5.10.2	Availability Tests	247
2.5.10.3	Off-Line Missed Alert Tests	247
2.5.10.3.1	Off-Line Test Setup	247
2.5.10.3.2	Selection of Geometries	249
2.5.10.3.3	Test Procedures and Pass/Fail Criteria	249
2.5.10.4	False Alert Rate Test	250
2.5.10.5	On-Line Verification Test	250
2.5.10.5.1	On-Target Computational Test	250
2.5.10.5.2	On-Line Behavioral Test	251
2.5.11	Test Procedures for Class Gamma Equipment	251
2.5.11.1	General Gamma Bench Test Procedures	251
2.5.11.1.1	Simulated Flight Bench Test Procedures	252
2.5.11.1.1.1	Simulated Flight Plan Test 1	252
2.5.11.1.1.2	Simulated Flight Plan Test 2	253
2.5.11.1.2	Waypoint Distance Display	267
2.5.11.1.3	Equipment Response Time Test	268
2.5.11.1.4	Loss of Power and Navigation Cautions and Annunciations	269
2.5.11.1.5	Cross-Track Deviation Display Bench Test for En Route and Terminal	269
2.5.11.1.6	Cross-Track Deviation Display Test for LNAV Approaches	273
2.5.11.2	Reserved	278
2.5.11.3	Human Factors Bench Tests	278
2.5.11.3.1	Equipment Usability	278
2.5.11.3.2	Display Brightness and Readability Test	278
2.5.11.3.3	Audible Alerts Test	281
2.5.11.3.4	Equipment Controls Test	282

3.0 INSTALLED EQUIPMENT PERFORMANCE 285

4.0	OPERATIONAL CHARACTERISTICS	287
5.0	MEMBERSHIP	289
APPENDIX A SPACE-BASED AUGMENTATION SYSTEM SIGNAL SPECIFICATION		
A.1	Introduction	A-1
A.2	Signal Characteristics	A-1
A.2.1	Carrier Frequency	A-1
A.2.2	Spurious Transmissions	A-1
A.2.3	Modulation	A-1
A.2.4	Carrier Phase Noise	A-1
A.2.5	Signal Spectrum	A-1
A.2.6	Signal Characteristics Modified Relative To GPS	A-2
A.2.6.1	Doppler Shift	A-2
A.2.6.2	Carrier Frequency Stability	A-2
A.2.6.3	Polarization	A-2
A.2.6.4	Code/Carrier Frequency Coherence	A-2
A.2.6.5	User Received Signal Levels	A-2
A.2.6.6	Correlation Loss	A-2
A.2.6.7	Maximum Code Phase Deviation	A-3
A.3	SBAS C/A Codes	A-3
A.3.1	Requirements	A-3
A.3.2	Identification of SBAS Codes	A-3
A.3.3	SBAS Codes	A-3
A.3.4	Recommended SBAS/GPS Coder Implementation	A-3
A.4	SBAS Signal Data Contents and Formats	A-5
A.4.1	Introduction	A-5
A.4.2	Principles and Assumptions	A-6
A.4.2.1	Data Rate	A-6
A.4.2.2	Timing	A-6
A.4.2.3	Error Corrections	A-7
A.4.2.4	Tropospheric Model	A-7
A.4.2.5	Residual Tropospheric Error	A-9
A.4.2.6	PRN Masks	A-9
A.4.2.7	Number of Satellites	A-9
A.4.2.8	Issue of Data	A-9
A.4.2.9	Acquisition Information	A-10
A.4.3	Format Summary	A-10
A.4.3.1	Block Format	A-10
A.4.3.2	Block Length and Content	A-10
A.4.3.3	Parity	A-10
A.4.3.4	Preamble	A-12
A.4.4	Messages and Relationships Between Message Types	A-12
A.4.4.1	Do Not Use for Safety Applications Message Type 0	A-14
A.4.4.2	PRN Mask Assignments Message Type 1	A-14
A.4.4.2.1	PRN Mask Transition	A-15
A.4.4.3	Fast Corrections Message Types 2 - 5	A-15
A.4.4.4	Integrity Information Message Type 6	A-17
A.4.4.5	Fast Correction Degradation Factor Message Type 7	A-18
A.4.4.6	Degradation Factors Message Type 10	A-20
A.4.4.7	Long Term Satellite Error Corrections Message Type 25	A-20
A.4.4.8	Mixed Fast Corrections/Long Term Satellite Error Corrections Messages Type 24	A-24
A.4.4.9	Ionospheric Grid Point Masks Message Type 18	A-25
A.4.4.10	Ionospheric Delay Corrections Messages Type 26	A-31
A.4.4.10.1	Pierce Point Location Determination	A-33

A.4.4.10.2	Selection of Ionospheric Grid Points	A-34
A.4.4.10.3	Ionospheric Pierce Point Vertical Delay and Model Variance Interpolation	A-36
A.4.4.10.4	Computing Slant Ionospheric Delay and Ionospheric Model Variance	A-39
A.4.4.11	GEO Navigation Message Type 9	A-40
A.4.4.12	GEO Almanacs Message Type 17	A-41
A.4.4.13	SBAS Service Message Type 27	A-43
A.4.4.13.1	Definition of Regions	A-43
A.4.4.14	Null Message Type 63 and Internal Test Message 62	A-45
A.4.4.15	SBAS Network Time/UTC/GLONASS Time Offset Parameters Message Type 12	A-45
A.4.4.16	Clock-Ephemeris Covariance Matrix Message Type 28	A-46
A.4.5	Modeling the Degradation of Data	A-49
A.4.5.1	Fast and Long-Term Correction Degradation	A-50
A.4.5.1.1	Fast Correction Degradation	A-50
A.4.5.1.2	Range-Rate Correction Degradation	A-51
A.4.5.1.2.1	Range-Rate Correction Degradation - IODF \neq 3	A-51
A.4.5.1.2.2	Range-Rate Correction Degradation - Either IODF = 3	A-51
A.4.5.1.3	Long Term Correction Degradation	A-52
A.4.5.1.3.1	Long Term Correction Degradation - Velocity Code = 1	A-52
A.4.5.1.3.2	Long Term Correction Degradation - Velocity Code = 0	A-53
A.4.5.1.3.3	GEO Navigation Message Degradation	A-53
A.4.5.1.4	Degradation for En Route Through LNAV	A-53
A.4.5.2	Degradation of Ionospheric Corrections	A-54
A.4.6	Principles and Rules for the Generation and Use of Data	A-55
A.4.7	Timing	A-55
A.5	References:	A-56

APPENDIX B STANDARD GPS/WAAS ASSUMPTIONS

B.1	GPS Constellation	B-1
B.2	WAAS Constellation	B-1
B.3	Selective Availability	B-2
B.4	GPS Satellite Failure	B-2
B.5	GPS Constellation for Availability Analysis	B-2
B.6	Signal Quality Monitoring	B-3
B.6.1	Dead Zones	B-3
B.6.2	False Peaks	B-3
B.6.3	Distortions	B-4
B.6.4	Threat Models	B-4
B.6.4.1	Threat Model A	B-4
B.6.4.2	Threat Model B	B-4
B.6.4.3	Threat Model C	B-4

APPENDIX C STANDARD RECEIVED SIGNAL AND INTERFERENCE ENVIRONMENT

C.1	Introduction	C-1
C.2	Operating Interference Environment	C-1
C.2.1	Out-of-Band Interference	C-1
C.2.1.1	Out-of-Band Pulse Interference	C-2
C.2.2	In-Band and Near-Band Interference	C-2
C.2.2.1	In-Band and Near-Band Pulsed Interference	C-3
C.2.3	GNSS Noise	C-4
C.3	Minimum Standard Antenna Frequency Selectivity	C-4

APPENDIX D DATA FORMAT FOR HIGH INTEGRITY INFORMATION TO SUPPORT STRAIGHT AND ADVANCED LANDING APPROACH OPERATIONS

D.1	Introduction	D-1
D.2	Format	D-1
D.2.1	Overall Structure	D-1
D.2.2	Data Block Description	D-1
D.2.3	Data Block Structure	D-2
D.3	Final Approach Segment Data Block	D-2
D.3.1	Final Approach Segment Parameter Definition	D-3
D.3.2	Final Approach Segment Data Table	D-5
D.4	Advanced Procedures Data Blocks	D-6
D.5	CRC Definition	D-6
D.6	Informative Section	D-6
D.6.1	Integrity Protection of Data Blocks	D-6
D.6.2	Approach Path Selection	D-7
D.6.3	Data Block Generation	D-7
D.6.4	Database Formatting and Distribution	D-8
D.6.5	CRC Generation and decoding	D-8
D.6.6	CRC selection	D-9
D.6.7	Reference Coordinate System	D-10
D.7	References:	D-10

APPENDIX E BASELINE WEIGHTED NAVIGATION SOLUTION AND NAVIGATION SYSTEM ERROR ALGORITHMS FOR SBAS VERTICALLY GUIDED APPROACHES

E.1	Introduction	E-1
E.2	Baseline Navigation Solution	E-1
E.3	References	E-2

APPENDIX F VELOCITY DATA IN SUPPORT OF ADS-B

F.1	Introduction	F-1
F.2	Velocity Solution with Figure of Merit	F-1
F.3	References	F-4

APPENDIX G REQUIREMENTS FOR BAROMETREIC ALTIMETER AIDING

G.1	General	G-1
G.2	Altimeter Aiding with GNSS Calibration	G-1
G.2.1	Requirements for Calibration	G-1
G.2.2	Calculation of σ_{baro}	G-2
G.2.3	Actual Use of the Altitude Measurement to Augment GNSS	G-3
G.3	Barometric Altimeter Aiding Using Baro-corrected Pressure Altitude	G-4
G.3.1	Requirements for calibration	G-4
G.3.2	Calculation of σ_{baro}	G-4
G.3.3	Actual Use of the Barometric Altitude Measurement to Augment GNSS	G-5
G.3.4	Requirements for Pilot Interaction	G-5
G.4	Test Procedures	G-5
G.5	References	G-6

APPENDIX H STANDARD OUTPUT FORMAT

H.1	Introduction	H-1
H.2	GPS Minimum Output and Output Timing	H-1
H.2.1	Minimum GPS/SBAS Output	H-1
H.2.2	Timing	H-3
H.3	Other Desirable GPS Outputs	H-5
H.4	Summary	H-5
H.5	References:	H-5

APPENDIX I MODE SWITCHING FLOWCHART FOR GAMMA EQUIPMENT

I.1	Introduction	I-1
------------	---------------------	------------

APPENDIX J SBAS-BASED PROTECTION LEVELS FOR EN ROUTE THROUGH LPV APPROACH

J.1	SBAS Protection Level Equations - General Least Squares Solutions	J-1
J.2	HPL_{SBAS} Parameters	J-2
J.2.1	K	J-2
J.2.2	Variance of Fast and Long Term Correction Residuals	J-3
J.2.3	Variance of Ionospheric Delay	J-3
J.2.4	Variance of Airborne Receiver Errors	J-3
J.2.5	Variance of Tropospheric Errors	J-5
J.3	Rationale for HPL and VPL Parameters	J-5
J.3.1	Selection of K Values	J-5
J.3.2	Rationale for Fast and Long-Term Residuals	J-5
J.3.3	Rationale for Ionospheric Delay Residuals	J-6
J.3.4	Rationale for Receiver Residuals	J-6
J.3.5	Rationale for Tropospheric Residuals	J-6

APPENDIX K FAULT DETECTION AND EXCLUSION REFERENCES**APPENDIX L THE DIRECT AND INDIRECT GEODETIC PROBLEMS FOR GREAT CIRCLE NAVIGATION**

L.1	General	L-1
L.2	Definitions of Terms	L-2
L.3	Nomenclature	L-2
L.4	WGS-84 Parameters (from [5])	L-3
L.5	The Indirect Problem	L-3
L.6	The Direct Problem	L-5
L.7	Validation	L-6
L.8	References	L-9

APPENDIX M TEST CONSIDERATIONS

M.1	Introduction	M-1
M.2	(Initial) Acquisition and Reacquisition Testing Statistical Justification	M-1
M.3	Accuracy Statistical Justification	M-2
M.4	General Simulator Scenario Conditions	M-4

M.5	Example Test Set-up and Compensation of Signals, Noise and Interference	M-5
M.5.1	Description of the Test Set-up	M-5
M.5.2	Use of the Test Set-up for the Accuracy Test (See 2.5.8)	M-6

APPENDIX N REFERENCE MATERIAL FOR DETERMINING THE MEAN SEA LEVEL HEIGHT FROM WGS-84 COORDINATES

N.1	Introduction	N-1
N.1.1	General Altimetry	N-1
N.1.2	Mean Sea Level (MSL) Altitude	N-1
N.1.3	Barometric Altitude	N-2
N.1.4	Radar Altitude	N-2
N.1.5	GPS Altitude	N-2
N.1.6	SBAS-Derived Altitude	N-2

APPENDIX O GLOSSARY AND ACRONYMS

APPENDIX P IONOSPHERIC GRID POINT (IGP) SELECTION FLOWCHARTS

P.1	Introduction	P-1
------------	---------------------	------------

APPENDIX Q SBAS CONSIDERATIONS FOR HELICOPTERS

Q.1	General	Q-1
Q.1.1	Helicopter/Heliport Deceleration	Q-1
Q.1.2	PinS Description	Q-1
Q.2	PinS Approach Operations	Q-1
Q.2.1	Fictitious Helipoint Equivalence to Fictitious Threshold Point	Q-1
Q.2.2	FAS Data Block Application to PinS Procedures	Q-1
Q.2.3	PinS Lateral Display Scaling	Q-3
Q.2.4	Vertical Display Scaling	Q-3
Q.3	Deceleration Point Annunciation	Q-3
Q.4	Selective CDI and HAL Values to Support Tighter Route Area Semi-widths	Q-4
Q.5	Autopilot Considerations	Q-4
Q.6	Heliport Approach Database Considerations	Q-4

APPENDIX R REQUIREMENTS AND TEST PROCEDURES FOR TIGHTLY INTEGRATED GPS/INERTIAL SYSTEMS

R.1	Introduction	R-1
R.2	Requirements	R-1
R.2.1	General FDE Requirements	R-1
R.2.1.1	Fault Free Performance	R-2
R.2.2	Unique Additional Requirements	R-3
R.2.2.1	Assumed Failure Mechanisms	R-3
R.2.2.2	Detection limit	R-4
R.2.2.3	SatZap	R-4
R.2.2.4	Receiver Clock Aiding	R-5
R.2.2.5	Altitude Aiding	R-5
R.2.2.6	Discriminator Averaging	R-5
R.2.2.7	Inertial Coasting Performance Evaluation	R-6
R.2.2.7.1	Accuracy Coasting	R-6
R.2.2.7.2	Integrity Coasting	R-7
R.2.2.8	Gravity Compensation	R-8
R.3	Tightly Integrated GPS/Inertial Design Concepts	R-9

R.3.1	Integration Methods	R-9
R.3.1.1	Pre-residual (Innovation) Screening	R-9
R.3.1.2	Post-Residual Monitoring	R-10
R.3.1.3	Additional Measurement Bias States	R-10
R.3.1.4	Multiple Kalman Filters	R-10
R.3.1.5	Extrapolation Method	R-10
R.3.1.6	Solution Separation Method	R-10
R.3.2	Detection and Exclusion Mechanisms	R-11
R.3.2.1	Transient Detection/Exclusion for 2 nmi/hour Grade Systems	R-11
R.3.2.2	Satellite Redundancy	R-11
R.3.2.3	Integrity Coasting	R-11
R.3.2.4	Gravity/Schuler Coupling	R-11
R.3.2.5	Other Schuler Coupling Related Effects	R-12
R.4	Assumptions	R-12
R.4.1	Signal Error Model	R-12
R.4.2	Satellite Clock Drift Characteristics	R-13
R.5	Validation	R-13
R.5.1	Categorization of Detection and Exclusion Mechanisms	R-13
R.5.1.1	Examples	R-14
R.5.2	Covariance Simulation	R-14
R.5.2.1	Covariance Simulation Methods for Availability Evaluation	R-14
R.5.3	False Alert Probability	R-15
R.5.4	Fault Free Accuracy Performance	R-15
R.5.5	Off-Line Rare Normal Verification	R-16
R.5.6	Off-Line Detection/Exclusion Verification	R-16
R.5.6.1	Detection and Exclusion Mechanism Equivalent to RAIM	R-16
R.5.6.2	Claimed Additional Detection and Exclusion Mechanisms	R-16
R.5.6.2.1	Examples	R-17
R.5.6.2.1.1	RAIM with Transient Detection/Exclusion	R-17
R.5.6.2.1.2	Solution Separation Detection and Exclusion	R-17
R.5.6.2.2	Reference RAIM Models	R-18
R.5.6.3	Integrity Coasting	R-18
R.5.7	On-Line Validation	R-19
R.5.8	Gravity Compensation Validation	R-19
R.5.9	Ionospheric Error Models	R-20
R.5.9.1	Ionospheric Daily Variation	R-20
R.5.9.2	Ionospheric Storms	R-20
R.6	References	R-21
APPENDIX S PROCESSING FLOW DIAGRAMS		
S.1	Introduction	S-1
APPENDIX T GEO BIAS ANALYSIS TOOL		
T.1	GEO Bias Algorithm Rationale	T-1
T.2	GEO Bias Algorithm Procedure (Overview)	T-1
T.3	Analysis	T-2
T.3.1	GEO Filter Models	T-3
T.3.1.1	Future GEOs	T-5
T.3.2	Range Normalization	T-5
T.4	Bias Model Tool: Instructions and examples	T-6
APPENDIX U GUIDANCE MATERIAL FOR INTERFACING WITH ADS-B		

U.1	Purpose and Scope	U-1
U.2	Position Output and Validity	U-1
U.3	Horizontal Figure of Merit (HFOM)	U-1
U.4	Horizontal Protection Limit (HPL)	U-1
U.5	Velocity	U-2
U.6	Vertical Figure of Merit and Vertical Protection Limit (VPL)	U-2

FIGURES

FIGURE 1-1	WAAS ARCHITECTURE	5
FIGURE 1-2	FUNCTIONAL CLASSES	10
FIGURE 1-3	DIAGRAM OF FDE CONDITIONS	16
FIGURE 1-4	MARKOV CHAIN FOR FDE	17
FIGURE 1-5	EXAMPLE FDE EVENTS	18
FIGURE 2-1	SENSITIVITY AND DYNAMIC RANGE CONFIGURATION	39
FIGURE 2-2A	RECEIVER BANDWIDTH AND AVERAGE CORRELATOR SPACING FOR E-L DISCRIMINATOR TRACKING OF GPS SATELLITES	55
FIGURE 2-2B	RECEIVER BANDWIDTH AND AVERAGE CORRELATOR SPACING FOR DD DISCRIMINATOR TRACKING OF GPS SATELLITES	56
FIGURE 2-3	TF LEG	79
FIGURE 2-4	RF LEG	80
FIGURE 2-5	DIRECT-TO PATH DEFINITION	81
FIGURE 2-6	CF LEG	81
FIGURE 2-7	FLY-BY THEORETICAL TRANSITION AREA	83
FIGURE 2-8	FLY-OVER THEORETICAL TRANSITION AREA	84
FIGURE 2-9	WAYPOINT SEQUENCING	85
FIGURE 2-10	DEFAULT NAVIGATION MODES	95
FIGURE 2-11	FULL-SCALE DEFLECTION AND DEFINED PATH FOR NORMAL LNAV APPROACH (not VTF approach)	102
FIGURE 2-12	FULL SCALE DEFLECTION AND DEFINED PATH FOR LNAV VTF APPROACH	103
FIGURE 2-13	MISSED APPROACH SCENARIOS	104
FIGURE 2-14	FINAL APPROACH SEGMENT DEFINITION	111
FIGURE 2-15	VTF FINAL APPROACH SEGMENT LATERAL DEVIATIONS WITH FAS DATA BLOCK	113
FIGURE 2-16	FINAL APPROACH SEGMENT VERTICAL DEVIATIONS	116
FIGURE 2-17	FLIGHT PROFILE FOR FLIGHT PLAN 1	266
FIGURE 2-18	FLIGHT PROFILE FOR FLIGHT PLAN 2	267
FIGURE 2-19	CROSS-TRACK DEVIATION FOR EN ROUTE AND TERMINAL	271
FIGURE 2-20	CROSS TRACK DEVIATION FOR VTF LNAV APPROACH	275
FIGURE 2-21	CROSS-TRACK DEVIATION FOR LNAV APPROACH	277
FIGURE A-1	SBAS/GPS CODER IMPLEMENTED WITH SINGLE G2 OUTPUT PLUS PROGRAMMABLE G2 DELAY	A-5
FIGURE A-2	SBAS/GPS CODER IMPLEMENTED WITH A PROGRAMMABLE INITIAL G2 STATE	A-5
FIGURE A-3	CONVOLUTIONAL ENCODING	A-6
FIGURE A-4	DATA BLOCK FORMAT	A-10
FIGURE A-5	INTERRELATIONSHIPS OF MESSAGES	A-13
FIGURE A-6	EXAMPLE PRN MASK	A-15

FIGURE A-7 TYPES 2 - 5 FAST CORRECTIONS MESSAGES FORMAT.....	A-16
FIGURE A-8 TYPE 6 INTEGRITY MESSAGE FORMAT.....	A-17
FIGURE A-9 TYPE 7 FAST CORRECTION DEGRADATION FACTOR MESSAGE FORMAT ...	A-19
FIGURE A-10 TYPE 25 LONG TERM SATELLITE ERROR CORRECTIONS Velocity Code = 0	A-21
FIGURE A-11 TYPE 25 LONG TERM SATELLITE ERROR CORRECTIONS Velocity Code = 1	A-23
FIGURE A-12 TYPE 24 MIXED FAST CORRECTION/LONG TERM SATELLITE ERROR CORRECTIONS MESSAGE FORMAT.....	A-25
FIGURE A-13 EXAMPLE OF AN IONOSPHERIC GRID MASK.....	A-27
FIGURE A-14 PREDEFINED GLOBAL IGP GRID (BANDS 9 AND 10 ARE NOT SHOWN).....	A-30
FIGURE A-15 TYPE 18 IGP MASK MESSAGE FORMAT.....	A-31
FIGURE A-16 TYPE 26 IONOSPHERIC DELAY CORRECTIONS MESSAGE FORMAT.....	A-32
FIGURE A-17 IONOSPHERIC PIERCE POINT GEOMETRY.....	A-34
FIGURE A-18 IONOSPHERIC GRID POINT INTERPOLATION.....	A-36
FIGURE A-19 FOUR-POINT INTERPOLATION ALGORITHM DEFINITIONS.....	A-38
FIGURE A-20 THREE-POINT INTERPOLATION ALGORITHM DEFINITIONS.....	A-39
FIGURE A-21 TYPE 9 GEO NAVIGATION MESSAGE FORMAT.....	A-40
FIGURE A-22 TYPE 17 GEO ALMANACS MESSAGE FORMAT.....	A-42
FIGURE A-23 SERVICE MESSAGE TYPE 27.....	A-44
FIGURE A-24 TYPE 28 CLOCK-EPHEMERIS COVARIANCE MATRIX MESSAGE FORMAT	A-48
FIGURE C-1 INTERFERENCE LEVELS AT THE ANTENNA PORT.....	C-1
FIGURE C-2 IN-BAND AND NEAR-BAND INTERFERENCE ENVIRONMENTS.....	C-2
FIGURE C-3 FREQUENCY SELECTIVITY.....	C-5
FIGURE D-1 FINAL APPROACH SEGMENT DIAGRAM.....	D-2
FIGURE D-2 PROBABILITY OF UNDETECTED ERROR.....	D-9
FIGURE D-3 PROBABILITIES OF CORRECT DECODING AND DETECTED ERRORS.....	D-10
FIGURE H-1 GPS TIMING RELATIONSHIPS.....	H-4
FIGURE M-1 (RE)ACQUISITION TEST PROBABILITY STATISTICS.....	M-2
FIGURE M-2 PSEUDORANGE ACCURACY TEST PASS CRITERIA.....	M-3
FIGURE M-3 PSEUDORANGE ACCURACY TEST PASS PROBABILITY.....	M-4
FIGURE P-1 GRID POINT SELECTION CRITERIA.....	P-2
FIGURE P-2 ABS IPP LATTITUDE BELOW 60 DEG (5X5).....	P-3
FIGURE P-3 ABS IPP LATITUDE BELOW 85 DEG.....	P-4
FIGURE P-4 ABS IPPLATITUDE BETWEEN 60 & 75 DEG BANDS 9-10.....	P-5
FIGURE P-6 ABS IPP LATITUDE ABOVE 85 DEG.....	P-6
FIGURE P-7 ABS IPP LATITUDE BELOW 60 DEG (10X10 SQUARES).....	P-7
FIGURE P-8 ABS IPP LATITUDE BELOW 60 DEG (10X10 TRIANGLES).....	P-8
FIGURE P-9 ABS IPP LATITUDE BETWEEN 60 & 75 DEG BANDS 9-10.....	P-9
FIGURE Q-1 LATERAL DISPLAY SCALING FOR PinS APPROACH OPERATIONS.....	Q-3
FIGURE R-1 FLIGHT PROFILE ASSUMED FOR THE COASTING TIMES.....	R-8
FIGURE S-1 APPLICATION OF SBAS CORRECTION PARAMETERS.....	S-2
FIGURE S-2 SATELLITE CORRECTIONS (WHEN SBAS-BASED SIGMA VALUES ARE APPLIED).....	S-3
FIGURE S-3 IONOSPHERIC CORRECTIONS.....	S-4
FIGURE S-4 GEOMETRIC RANGE (WHEN SBAS-BASED SIGMA VALUES ARE APPLIED)....	S-5
FIGURE S-5 POSITION SOLUTION (WHEN SBAS-BASED SIGMA VALUES ARE APPLIED)...	S-6
FIGURE S-6 CLOCK/EPHEMERIS CONTRIBUTION TO WEIGHT USED FOR HPLFD FOR EN ROUTE THROUGH APPROACH (LNAV).....	S-7
FIGURE T-1 COMPARISON OF CORRELATION PEAKS FOR A NARROWBAND GEO AND A GPS CORRELATION PEAK.....	T-1
FIGURE T-2 OVERVIEW OF GEO BIAS CALCULATION ALGORITHM FOR A SINGLE RECEIVER.....	T-2

FIGURES T-3 AND T-4 MAGNITUDE AND GROUP DELAY RESPONSES OF THE WAAS GEO SIGNAL GENERATOR IN COMBINATION WITH THE NARROWBAND GEO (AOR-W)....	T-4
FIGURES T-5 AND T-6 MAGNITUDE AND GROUP DELAY RESPONSES OF THE GCCS GEO SIGNAL GENERATOR IN COMBINATION WITH THE WIDEBAND (PANAMSAT/ORBITAL) GEO	T-4
FIGURES T-7 AND T-8 MAGNITUDE AND PHASE RESPONSES OF A SAMPLE RECEIVER (FINAL IF, PRECORRELATION) FILTER.....	T-4
FIGURES T-9 AND T-10 ALL EARLY-MINUS-LATE AND DOUBLE-DELTA TRACKING ERRORS OF GPS AND INMARSAT NARROWBAND GEO SIGNALS AS OUTPUT BY TOOL GIVEN THE SAMPLE INPUT PARAMETERS ABOVE (EXAMPLE 1)	T-8
FIGURES T-11 AND T-12 ALL EARLY-MINUS-LATE AND DOUBLE-DELTA TRACKING ERRORS OF GPS AND MTSAT NARROWBAND GEO SIGNALS AS OUTPUT BY TOOL GIVEN THE SAMPLE INPUT PARAMETERS ABOVE (EXAMPLE 1)	T-8
FIGURES T-13 AND T-14 ALL EARLY-MINUS-LATE AND DOUBLE-DELTA TRACKING ERRORS OF GPS AND WIDEBAND GEO SIGNALS AS OUTPUT BY TOOL GIVEN THE SAMPLE INPUT PARAMETERS ABOVE (EXAMPLE 1).....	T-9
FIGURES T-15 AND T-16 SUMMARY OF GEO BIAS ERRORS FOR ALL (32+19) GPS AND SBAS PRNS AS OUTPUT BY TOOL GIVEN THE SAMPLE INPUT PARAMETERS ABOVE (EXAMPLE 1). RECEIVER DESIGN PASSES IF ALL BIASES ARE BELOW LIMITS INDICATED ON PLOTS.....	T-9
FIGURES T-17 AND T-18 ALL EARLY-MINUS-LATE AND DOUBLE-DELTA TRACKING ERRORS OF GPS AND INMARSAT NARROWBAND GEO SIGNALS AS OUTPUT BY TOOL GIVEN THE SAMPLE INPUT PARAMETERS ABOVE (EXAMPLE 2)	T-11
FIGURES T-19 AND T-20 ALL EARLY-MINUS-LATE AND DOUBLE-DELTA TRACKING ERRORS OF GPS AND MTSAT NARROWBAND GEO SIGNALS AS OUTPUT BY TOOL GIVEN THE SAMPLE INPUT PARAMETERS ABOVE (EXAMPLE 2)	T-11
FIGURES T-21 AND T-22 ALL EARLY-MINUS-LATE AND DOUBLE-DELTA TRACKING ERRORS OF GPS AND WIDEBAND GEO SIGNALS AS OUTPUT BY TOOL GIVEN THE SAMPLE INPUT PARAMETERS ABOVE (EXAMPLE 2).....	T-12
FIGURES T-23 AND T-24 SUMMARY OF GEO BIAS ERRORS FOR ALL (32+19) GPS AND SBAS PRNS AS OUTPUT BY TOOL GIVEN THE SAMPLE INPUT PARAMETERS ABOVE (EXAMPLE 2). RECEIVER DESIGN PASSES IF ALL BIASES ARE BELOW LIMITS INDICATED ON PLOTS.....	T-12

TABLES

TABLE 1-1 EQUIPMENT CLASSES AND REQUIREMENTS ORGANIZATION.....	11
TABLE 2-1 TIMEOUT INTERVALS	30
TABLE 2-2 FAST CORRECTION USER TIME-OUT INTERVAL EVALUATION.....	31
TABLE 2-3 URA VALUES	43
TABLE 2-4A GPS TRACKING CONSTRAINTS FOR E-L DLL DISCRIMINATORS.....	54
TABLE 2-4B GPS TRACKING CONSTRAINTS FOR DD DLL DISCRIMINATORS	54
TABLE 2-4C SBAS RANGING FUNCTION TRACKING CONSTRAINTS	56
TABLE 2-5 SAFETY-CRITICAL FUNCTIONS	68
TABLE 2-6 LABELS AND MESSAGES.....	73
TABLE 2-7 FLY-BY THEORETICAL TRANSITION AREA 'R' AND Y VALUES	82
TABLE 2-8 NON-NUMERIC ELECTRICAL OUTPUT REQUIREMENTS	89
TABLE 2-9 NON-NUMERIC DISPLAY REQUIREMENTS	89
TABLE 2-10 NON-NUMERIC DISPLAY REQUIREMENTS	94
TABLE 2-11 DEFINITION OF DEFAULT NAVIGATION MODES	96
TABLE 2-12 SUMMARY OF TYPICAL MODE SWITCHING TRANSITIONS.....	96

TABLE 2-13 SUMMARY OF CHANGES IN CROSS-TRACK FULL SCALE DEFLECTION FOR MODE SWITCHING	97
TABLE 2-14 CLASS BETA-1 ENVIRONMENTAL TEST REQUIREMENTS	136
TABLE 2-15 CLASS GAMMA-1 ENVIRONMENTAL TEST REQUIREMENTS	137
TABLE 2-16 CLASS BETA-2 ENVIRONMENTAL TEST REQUIREMENTS	138
TABLE 2-17 CLASS GAMMA-2 ENVIRONMENTAL TEST REQUIREMENTS	139
TABLE 2-18 CLASS BETA-3 ENVIRONMENTAL TEST REQUIREMENTS	140
TABLE 2-19 CLASS GAMMA-3 ENVIRONMENTAL TEST REQUIREMENTS	141
TABLE 2-20 CLASS DELTA-4 ENVIRONMENTAL TEST REQUIREMENTS	142
TABLE 2-21 TEST CROSS REFERENCE MATRIX	147
TABLE 2-22 GRADUATED SAMPLING PASS/FAIL CRITERIA	227
TABLE 2-23 STEADY STATE ACCURACY TEST CWI VALUES	233
TABLE 2-24 SATELLITE EQUIVALENT POWER SPECTRAL DENSITY	234
TABLE 2-25 PASS THRESHOLD TABLE	236
TABLE 2-26 MAXIMUM NUMBER OF OUTCOMES TO OFF-LINE FDE TEST	244
TABLE 2-27 WAYPOINT INFORMATION FOR FIRST FLIGHT PLAN FOR SIMULATED FLIGHT PLAN TEST 1	252
TABLE 2-28 WAYPOINT INFORMATION FOR SIMULATED FLIGHT PLAN TEST 2	254
TABLE 2-29 SIMULATED FLIGHT PLAN TEST NUMBER 1	255
TABLE 2-30 SIMULATED FLIGHT PLAN TEST NUMBER 2	261
TABLE 2-31 WAYPOINTS FOR CROSS TRACK DEVIATION BENCH TEST FOR EN ROUTE AND TERMINAL	272
TABLE 2-32 TEST SEQUENCE FOR EN ROUTE AND TERMINAL CROSS-TRACK DEVIATION	273
TABLE 2-33 TEST SEQUENCE FOR VTF LNAV APPROACH CROSS TRACK DEVIATION	274
TABLE 2-34 TEST SEQUENCE FOR LNAV APPROACH CROSS-TRACK DEVIATION	276
TABLE 2-35 HUMAN FACTORS TEST: CHECKLIST 1. EQUIPMENT USABILITY	279
TABLE 2-36 HUMAN FACTORS TEST: CHECKLIST 2. DISPLAY BRIGHTNESS	280
TABLE 2-37 HUMAN FACTORS TEST: CHECKLIST 3. AUDIBLE ALERTS	282
TABLE 2-38 HUMAN FACTORS TEST: CHECKLIST 4. EQUIPMENT CONTROLS	283
TABLE A-1 SBAS RANGING C/A CODES	A-4
TABLE A-2 METEOROLOGICAL PARAMETERS FOR TROPOSPHERIC DELAY	A-8
TABLE A-3 MESSAGE TYPES	A-13
TABLE A-4 PRN MASK ASSIGNMENTS	A-14
TABLE A-5 TYPE 6 INTEGRITY MESSAGE CONTENT	A-18
TABLE A-6 EVALUATION OF UDREII	A-18
TABLE A-7 TYPE 7 FAST CORRECTION DEGRADATION FACTOR MESSAGE CONTENTS	A-19
TABLE A-8 FAST CORRECTIONS DEGRADATION FACTOR AND USER TIME-OUT INTERVAL EVALUATION	A-19
TABLE A-9 TYPE 10 DEGRADATION FACTORS	A-20
TABLE A-10 TYPE 25 LONG TERM SATELLITE ERROR CORRECTIONS HALF MESSAGE PARAMETERS WITH VELOCITY CODE OF 0	A-22
TABLE A-11 TYPE 25 LONG TERM SATELLITE ERROR CORRECTIONS HALF MESSAGE PARAMETERS WITH VELOCITY CODE OF 1	A-23
TABLE A-12 PREDEFINED WORLD-WIDE IGP SPACING – BANDS 0 - 8	A-25
TABLE A-13 PREDEFINED WORLD-WIDE IGP SPACING - BANDS 9 - 10	A-25
TABLE A-14 IONOSPHERIC MASK BANDS	A-28
TABLE A-14 IONOSPHERIC MASK BANDS (CONTINUED)	A-29
TABLE A-15 TYPE 18 IGP MASK MESSAGE CONTENTS	A-31
TABLE A-16 IONOSPHERIC DELAY MODEL PARAMETERS FOR MESSAGE TYPE 26	A-32
TABLE A-17 EVALUATION OF GIVEII	A-33

TABLE A-18	TYPE 9 GEO NAVIGATION MESSAGE PARAMETERS	A-41
TABLE A-19	TYPE 17 GEO ALMANACS MESSAGE PARAMETERS	A-42
TABLE A-20	TYPE 27 SERVICE MESSAGE PARAMETERS	A-44
TABLE A-21	SDRE INDICATOR EVALUATION	A-45
TABLE A-22	SBAS NETWORK TIME/UTC PARAMETERS	A-46
TABLE A-23	UTC STANDARD IDENTIFIER	A-46
TABLE A-24	TYPE 28 CLOCK-EPHEMERIS COVARIANCE MATRIX MESSAGE PARAMETERS	A-49
TABLE A-25	MESSAGE CONTENT BROADCAST INTERVALS	A-56
TABLE B-1	OPTIMIZED 24 GPS CONSTELLATION	B-1
TABLE B-2	GPS CONSTELLATION ON DECEMBER 1, 1995 AT 00:00 UTC	B-3
TABLE C-1	OUT-OF-BAND PULSE INTERFERENCE	C-2
TABLE C-2	IN-BAND AND NEAR-BAND INTERFERENCE BANDWIDTH DEFINITIONS	C-3
TABLE C-3	IN-BAND AND NEAR-BAND PULSE INTERFERENCE	C-4
TABLE C-4	EFFECTIVE NOISE DENSITY FOR ALL GNSS SOURCES	C-4
TABLE C-5	FREQUENCY SELECTIVITY	C-5
TABLE D-1	FINAL APPROACH SEGMENT (FAS)	D-5
TABLE G-1	PRESSURE GRADIENT ERRORS (KNOWN GL)	G-3
TABLE G-2	PRESSURE GRADIENT ERRORS (UNKNOWN GL)	G-3
TABLE H-1	MINIMUM GPS OUTPUT	H-1
TABLE L-1	TEST CASE INPUT	L-7
TABLE L-2	TEST CASE OUTPUT	L-8
TABLE L-3	NUMBER OF ITERATIONS	L-8
TABLE M-1	GRADUATED SAMPLING PASS/FAIL CRITERIA	M-2
TABLE R-1	SUMMARY OF FDE REQUIREMENTS	R-1
TABLE R-2	SUMMARY OF FAILURE TYPE PROBABILITIES	R-4
TABLE R-3	ACCURACY COASTING PERFORMANCE EXAMPLE	R-7
TABLE R-4	INTEGRITY COASTING PERFORMANCE EXAMPLE	R-8
TABLE R-5	EQUIVALENT ALTITUDE ACCURACY	R-11
TABLE R-6	REQUIRED NUMBER OF TRIALS FOR EACH FAILURE MODE	R-17

THIS PAGE INTENTIONALLY LEFT BLANK

1.0 PURPOSE AND SCOPE

1.1 Introduction

This document contains minimum operational performance standards (MOPS) for airborne navigation equipment (2D and 3D) using the Global Positioning System (GPS) augmented by Satellite-Based Augmentation Systems (SBAS); which, in the U.S. is the Wide Area Augmentation System (WAAS). DO-229 only provides standards for single frequency airborne navigation equipment. A separate document will be created in the future to address standards for dual frequency equipment. These standards are intended to be applicable to other SBAS providers, such as European Geostationary Navigation Overlay Service (EGNOS) and Japan's Multi-functional Transport Satellite (MTSAT) Satellite-based Augmentation System (MSAS).

In this document, the term "shall" is used to indicate requirements. An approved design should comply with every requirement, which can be assured by inspection, test, analysis, or demonstration. The term "must" is used to identify items that are important but are either duplicated somewhere else in the document as a "shall", or are considered to be outside the scope of this document. The term "should" is used to denote a recommendation that would improve the SBAS equipment, but does not constitute a requirement.

The standards define minimum performance, functions and features for SBAS-based sensors that provide position information to a multi-sensor system or separate navigation system. They also address SBAS-based Area Navigation (RNAV) equipment to be used for the en route, terminal, and Lateral Navigation (LNAV) phases of flight. These standards are based upon a nominal allocation of the aircraft-level requirements in RTCA/DO-236B, *Minimum Aviation System Performance Standards: Required Navigation Performance for Area Navigation*, accounting for the unique issues associated with SBAS and GNSS navigation service and minimizing the need for pilot training. These standards also define performance, functions and features for equipment that satisfies the requirements for Lateral Navigation/Vertical Navigation (LNAV/VNAV), Localizer Performance without vertical guidance (LP), and Localizer Performance with Vertical guidance (LPV) instrument procedures. The standards cover SBAS-based equipment that is designed to serve combinations of the above phases of flight.

Compliance with these standards by manufacturers, installers and users is recommended as one means of assuring that the equipment will satisfactorily perform its intended functions under conditions encountered in routine aeronautical operations, and will ensure a basic compatibility with the requirements defined in RTCA/DO-236B. Manufacturers and operators who elect to comply directly with the requirements of RTCA/DO-236B as part of an aircraft certification (type certificate or supplemental type certificate) may bypass these RNAV standards, but are not expected to be eligible for a Class Gamma TSO authorization.

The regulatory application of these standards is the responsibility of appropriate government agencies. In the United States, the Federal Aviation Administration (FAA) has published a Technical Standard Order (TSO) for GPS/WAAS equipment to reference the requirements and bench test procedures in Section 2.

The word "equipment", as used in this document, includes all components or units necessary (as determined by the equipment manufacturer or installer) to properly perform its intended function. For example, the airborne "equipment" may include: sensor(s), a computer unit, an input-output unit that interfaces with existing aircraft displays/systems, a control unit, a display, shock mount(s), etc. In the case of this example, all of the