

RTCA, Inc.
1828 L Street, NW, Suite 805
Washington D.C. 20036

**SIGNAL-IN-SPACE MINIMUM AVIATION SYSTEM PERFORMANCE
STANDARDS (MASPS) FOR ADVANCED VHF DIGITAL DATA
COMMUNICATIONS INCLUDING COMPATIBILITY WITH
DIGITAL VOICE TECHNIQUES**

RTCA DO-224B
August 3, 2005

Prepared by SC-172
©RTCA, Inc. 2005

Copies of this document may be obtained from

RTCA, Incorporated
1828 L Street, Northwest, Suite 805
Washington, D.C. 20036-5133

Telephone: 202-833-9339
Facsimile: 202-833-9434
Internet: www.rtca.org

Please contact RTCA for price and ordering information.

FOREWORD

This document was prepared by Special Committee 172 (SC-172) and approved by the RTCA Program Management Committee (PMC) on August 3, 2005.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Federal Advisory Committee and develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- Coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- Analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- Developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- Assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organization's recommendations are often used as a basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency have statutory jurisdiction over any matters to which the recommendations relate.

This Page Intentionally Left Blank

Executive Summary

The purpose of this document is to define Minimum Aviation System Performance Standards (MASPS) for the signal-in-space characteristics for an advanced Very High Frequency (VHF) digital data communications radio, including compatibility with digital voice techniques. The MASPS is divided into three sections; an introduction, aviation user requirements, and technical characteristics.

The introductory section provides VHF communications system characteristics including aeronautical VHF communications frequencies utilized and spectrum congestion. Service rules as defined by the Federal Communications Commission (FCC) and the Federal Aviation Administration (FAA) are also provided. Principles of operation of the current VHF voice and data systems and the proposed future system are presented. General applications are divided into three categories; they are Air Traffic Services, Aeronautical Operational Control, and Aeronautical Administrative Communications. Current system interconnection, routing, integration considerations and deficiencies are highlighted.

The aviation user requirements section identifies the users of the systems and specific aircraft characteristics. The expected availability and integrity of the avionics are described. System interoperability and compatibility requirements are emphasized to assure coexistence with the present analog voice system.

The technical characteristics section describes the new system. Two modes of operation are defined: VDL Mode 2 and VDL Mode 3. VDL Mode 2 refers to the operation of the Carrier Sense Multiple Access (CSMA) scheme, to support data link compatibility. VDL Mode 3 refers to the functionally simultaneous voice and data link capability of the Time Division Multiple Access (TDMA) architecture.

The signal-in-space may be used for either or both modes of operation provided implementation is in accordance with the VDL Mode 2 and VDL Mode 3 characteristics described herein and with industry standards. The definition, description, and specification of both modes are expected to continue to evolve as the industry, the service providers, and the users further develop future system concepts and capabilities.

This Page Intentionally Left Blank

TABLE OF CONTENTS

1.0	INTRODUCTION.....	1
1.1	VHF Communications System Characteristics.....	1
1.1.1	Introduction.....	1
1.1.2	Definitions of Terms.....	3
1.1.3	Aeronautical VHF Communications Frequencies.....	16
1.1.4	Spectrum Congestion.....	16
1.1.5	Service Rules.....	17
1.1.5.1	Federal Communications Commission (FCC).....	17
1.1.5.2	Federal Aviation Administration (FAA).....	17
1.2	VHF Voice and Data System Elements and Principles of Operation.....	18
1.2.1	Principles of Operation for VHF Packet Data System Elements.....	18
1.2.2	New VHF Integrated Voice and Data System Elements.....	19
1.2.3	Principles of Operation for New VHF Integrated Voice and Data System Elements.....	19
1.3	General Applications.....	20
1.3.1	Introduction.....	20
1.3.2	Data Services.....	20
1.3.2.1	Air Traffic Services.....	20
1.3.2.2	Aeronautical Operational Control (AOC).....	21
1.3.2.3	Aeronautical Administrative Communications (AAC).....	22
1.3.3	Digital Voice.....	22
1.3.4	VDL Mode 3 Configuration Descriptions.....	22
1.4	System Interconnection and Routing.....	25
1.4.1	Data.....	25
1.4.2	Voice.....	25
1.5	System Integration Considerations.....	25
1.6	Present VHF System.....	26
1.6.1	Technical Description.....	29
1.6.2	Deficiencies.....	30
2.0	AVIATION USER REQUIREMENTS.....	33
2.1	System Users.....	33
2.2	Aircraft Characteristics.....	33
2.3	User Applications.....	34
2.4	Availability and Integrity.....	34
2.4.1	Availability.....	34
2.4.2	Integrity.....	35
2.4.3	Continuity of Function.....	36
2.5	System Interoperability and Compatibility Requirements.....	36
2.5.1	Provision of Digital Voice and Data Link.....	37

TABLE OF CONTENTS

2.5.2	Coexistence with Analog Voice	37
2.6	Delay	37
2.6.1	VDL Mode 2	37
2.6.2	VDL Mode 3	38
2.6.2.1	Data	38
2.6.2.2	Voice	38
3.0	Technical Characteristics	39
3.1	Modes of Operation	39
3.2	VDL Mode 2	39
3.2.1	Physical Layer Protocols and Services	39
3.2.1.1	Functions	40
3.2.1.1.1	Transceiver Frequency Control	40
3.2.1.1.2	Data Reception by the Transceiver or Receiver	40
3.2.1.1.3	Data Transmission by the Transceiver or Transmitter	40
3.2.1.1.4	Notification Services	40
3.2.1.2	Modulation Scheme	41
3.2.1.2.1	Data Encoding	41
3.2.1.2.2	Transmitted Signal Form	42
3.2.1.2.3	Modulation Rate	42
3.2.1.2.4	Emission Designator	43
3.2.1.2.5	Pulse Shaping Filters	43
3.2.1.3	Training Sequence	44
3.2.1.3.1	Transmitter Ramp-up and Power Stabilization	44
3.2.1.3.2	Transmitter Power Ramp-Down	45
3.2.1.3.3	Synchronization and Ambiguity Resolution	45
3.2.1.3.4	Reserved Symbol	46
3.2.1.3.5	Transmission Length	46
3.2.1.3.6	Header FEC	46
3.2.1.3.7	Bit Transmission Order	47
3.2.1.4	Error Correction Encoding Techniques	47
3.2.1.4.1	Error Correction Encoding of Data	47
3.2.1.4.2	Error Detection Encoding of Data	47
3.2.1.4.3	Forward Error Correction	47
3.2.1.4.3.1	FEC Calculation	47
3.2.1.4.3.2	Block Lengths	48
3.2.1.4.3.2.1	No Error Correction	48
3.2.1.4.3.2.2	Single-Byte Error Correction	48
3.2.1.4.3.2.3	Two-Byte Error Correction	48
3.2.1.4.3.2.4	Three-Byte Error Correction	49
3.2.1.5	Interleaving	49
3.2.1.6	Bit Scrambling	49
3.2.1.7	Channel Sensing	51
3.2.1.7.1	Channel Busy to Idle Detection	51
3.2.1.7.2	Channel Idle to Busy Detection	51
3.2.1.8	Physical Layer System Parameter	52
3.2.1.9	Receiver/Transmitter Interactions	52
3.2.1.9.1	Receive to Transmit Turnaround Time	52

TABLE OF CONTENTS

3.2.1.9.2	Transmit to Receive Turnaround Time	52
3.2.1.10	Transmission Characteristics	53
3.2.1.10.1	Carrier Frequencies	53
3.2.1.10.2	Spurious Emissions	54
3.2.1.10.3	Adjacent Channel Emissions	54
3.2.2	Link Layer Protocols and Services	55
3.2.2.1	Structure	55
3.2.2.2	Service	55
3.2.2.2.1	Connection-Oriented	55
3.2.2.2.2	Connection-Less	55
3.2.2.3	MAC Sublayer	55
3.2.2.3.1	MAC Services	56
3.2.2.3.1.1	Multiple Access	56
3.2.2.3.1.2	Channel Occupancy	56
3.2.2.3.1.3	Channel Congestion	56
3.2.2.3.2	MAC Service System Parameters	56
3.2.2.3.2.1	Timer TM1 (Inter-access Delay Timer)	57
3.2.2.3.2.2	Timer TM2 (Channel Busy Timer)	57
3.2.2.3.2.3	Parameter p (Persistence)	57
3.2.2.3.2.4	Counter M1 (Maximum Number of Access Attempts)	57
3.2.2.3.3	Description of Procedures	57
3.2.2.3.3.1	Channel Sensing	57
3.2.2.3.3.2	Access Attempt	57
3.2.2.4	Data Link Service Sublayer	58
3.2.2.4.1	Services	58
3.2.2.4.1.1	Frame Sequencing	58
3.2.2.4.1.2	Error Detection	58
3.2.2.4.1.3	Station Identification	59
3.2.2.4.1.4	Broadcast Addressing	59
3.2.2.4.1.5	Data Transfer	59
3.2.2.4.2	AVLC Data Link Service Protocol Specification	59
3.2.2.4.2.1	Frame Format	59
3.2.2.4.2.2	Address Structure	59
3.2.2.4.2.3	Address Fields	60
3.2.2.4.2.3.1	Air/Ground Status Bit	61
3.2.2.4.2.3.2	Command/Response Status Bit	61
3.2.2.4.2.3.3	Data Link Service Addresses	61
3.2.2.4.2.3.4	Address Type	61
3.2.2.4.2.3.5	Aircraft Specific Addresses	62
3.2.2.4.2.3.6	ICAO-Administered Ground Station Specific Addresses	62
3.2.2.4.2.3.7	ICAO-Delegated Ground Station Specific Addresses	62
3.2.2.4.2.4	Broadcast Address	62
3.2.2.4.2.4.1	Encoding	62
3.2.2.4.2.5	Link Control Field	63
3.2.2.4.2.6	Information Field	63
3.2.2.4.3	Data Link Service System Parameters	64
3.2.2.4.3.1	Timer T1 (Delay Before Retransmission)	64
3.2.2.4.3.2	Parameter T2 (Delay Before Acknowledgment)	66
3.2.2.4.3.3	Timer T3 (Link Initialization Time)	66
3.2.2.4.3.4	Timer T4 (Maximum Delay Between Transmissions)	67
3.2.2.4.3.5	Parameter N1 (Maximum Number of Bits of any Frame)	67

TABLE OF CONTENTS

3.2.2.4.3.6	Counter N2 (Maximum Number of Transmissions)	68
3.2.2.4.3.7	Parameter k (Window Size)	68
3.2.2.4.4	Description of Procedures.....	68
3.2.2.4.5	Modes of Operation	69
3.2.2.4.5.1	Operational Mode.....	69
3.2.2.4.5.2	Non-operational Mode	69
3.2.2.4.5.2.1	DISC Frame	69
3.2.2.4.5.2.2	DM Frame	69
3.2.2.4.5.2.3	Frame Reject Mode.....	70
3.2.2.4.5.2.4	Sent Selective Reject Mode	70
3.2.2.4.6	Use of the P/F Bit.....	70
3.2.2.4.6.1	General	70
3.2.2.4.6.2	INFO Frames.....	70
3.2.2.4.6.3	Unnumbered Frames	71
3.2.2.4.7	Unnumbered Command Frame Collisions.....	71
3.2.2.4.7.1	DLE Procedures	71
3.2.2.4.7.2	LME Procedures.....	71
3.2.2.4.8	XID Frame	71
3.2.2.4.9	Broadcast	72
3.2.2.4.10	Information Transfer	72
3.2.2.4.10.1	Transmission Queue Management	72
3.2.2.4.10.1.1	Eliminate Redundant Frames	72
3.2.2.4.10.1.2	Procedures for Transmission.....	73
3.2.2.4.10.2	SREJ Frame.....	73
3.2.2.4.10.3	FRMR Frame	74
3.2.2.4.10.4	UA Frame.....	74
3.2.2.4.10.5	UI Frame	74
3.2.2.4.10.6	TEST Frame.....	74
3.2.2.5	VDL Management Entity	74
3.2.2.5.1	Services.....	74
3.2.2.5.1.1	Link Provision.....	75
3.2.2.5.1.2	Link Change Notifications	75
3.2.2.5.2	Exchange Identity (XID) Parameter Formats	75
3.2.2.5.2.1	Encoding	76
3.2.2.5.2.2	Public Parameters.....	76
3.2.2.5.2.2.1	HDLC Public Parameter Set Identifier.....	76
3.2.2.5.2.2.2	Timer T1	77
3.2.2.5.2.3	VDL Private Parameters	77
3.2.2.5.2.4	General Purpose Information Private Parameters	77
3.2.2.5.2.4.1	VDL Private Parameter Set Identifier	79
3.2.2.5.2.4.2	Connection Management Parameter	79
3.2.2.5.2.4.3	Signal Quality Parameter (SQP)	80
3.2.2.5.2.4.4	XID Sequencing Parameter.....	81
3.2.2.5.2.4.5	AVLC Specific Options Parameter.....	81
3.2.2.5.2.4.6	Expedited Subnetwork Connection Parameter.....	83
3.2.2.5.2.4.7	LCR Cause Parameter	83
3.2.2.5.2.5	Aircraft-Initiated Information Private Parameters	86
3.2.2.5.2.5.1	Modulation Support Parameter	86
3.2.2.5.2.5.2	Acceptable Alternate Ground Station Parameter	87
3.2.2.5.2.5.3	Destination Airport Parameter	87
3.2.2.5.2.5.4	Aircraft Location Parameter.....	87

TABLE OF CONTENTS

3.2.2.5.2.6	Ground-Initiated Modification Private Parameters	88
3.2.2.5.2.6.1	Autotune Frequency Parameter	88
3.2.2.5.2.6.2	Replacement Ground Station List	89
3.2.2.5.2.6.3	Timer T4 Parameter	90
3.2.2.5.2.6.4	MAC Persistence Parameter	90
3.2.2.5.2.6.5	Counter M1 Parameter	90
3.2.2.5.2.6.6	Timer TM2 Parameter	91
3.2.2.5.2.6.7	Timer TG5 Parameter	91
3.2.2.5.2.6.8	T3min Parameter	92
3.2.2.5.2.6.9	Ground Station Address Filter Parameter	92
3.2.2.5.2.6.10	Broadcast Connection Parameter	93
3.2.2.5.2.7	Ground-Initiated Information Private Parameters	94
3.2.2.5.2.7.1	Frequency Support List	94
3.2.2.5.2.7.2	Airport Coverage Indication Parameter	95
3.2.2.5.2.7.3	Nearest Airport Parameter	95
3.2.2.5.2.7.4	ATN Router NETs Parameter	96
3.2.2.5.2.7.5	Station Operator Mask Parameter	96
3.2.2.5.2.7.6	Timer TG3 Parameter	97
3.2.2.5.2.7.7	Timer TG4 Parameter	97
3.2.2.5.2.7.8	Ground Station Location Parameter	98
3.2.2.5.3	VME Service System Parameters	98
3.2.2.5.3.1	Timer TG1 (Frequency Dwell Time)	99
3.2.2.5.3.2	Timer TG2 (Maximum Idle Activity Time)	100
3.2.2.5.3.3	Timer TG3 (Maximum Time Between Transmissions)	100
3.2.2.5.3.4	Timer TG4 (Minimum Time Between GSIFs)	101
3.2.2.5.3.5	Timer TG5 (Maximum Link Overlap Time)	101
3.2.2.5.4	Description of LME Procedures	101
3.2.2.5.4.1	Frequency Management Procedures	101
3.2.2.5.4.1.1	Frequency Search	102
3.2.2.5.4.1.2	Frequency Recovery	102
3.2.2.5.4.2	Link Connectivity Procedures	102
3.2.2.5.4.3	Ground Station Identification	102
3.2.2.5.4.4	Link Establishment	108
3.2.2.5.4.4.1	Aircraft Initiation	108
3.2.2.5.4.4.2	General Ground Response	108
3.2.2.5.4.4.3	Exceptional Cases	109
3.2.2.5.4.5	Link Parameter Modification (LPM)	109
3.2.2.5.4.5.1	Ground Initiation	109
3.2.2.5.4.5.2	General Aircraft Response	109
3.2.2.5.4.6	Aircraft-Initiated Handoff	110
3.2.2.5.4.6.1	Aircraft Handoff	110
3.2.2.5.4.6.2	Site Selection Preference	110
3.2.2.5.4.6.3	Interaction of LMEs	110
3.2.2.5.4.6.4	General Ground Response	111
3.2.2.5.4.6.5	Disconnecting Old Link	111
3.2.2.5.4.6.6	Exceptional Cases	111
3.2.2.5.4.7	Aircraft-Requested Ground-Initiated Handoff	112
3.2.2.5.4.7.1	Aircraft Action	112
3.2.2.5.4.7.2	General Ground Response	112
3.2.2.5.4.7.3	Exceptional Cases	112
3.2.2.5.4.8	Ground-Initiated Handoff	113
3.2.2.5.4.8.1	Ground Action	113
3.2.2.5.4.8.2	General Aircraft Response	113
3.2.2.5.4.8.3	Disconnecting Old Link	113

TABLE OF CONTENTS

3.2.2.5.4.8.4	Exceptional Cases	114
3.2.2.5.4.9	Ground-Requested Aircraft-Initiated Handoff	114
3.2.2.5.4.9.1	Ground Action	114
3.2.2.5.4.9.2	General Aircraft Response	114
3.2.2.5.4.9.3	Exceptional Cases	115
3.2.2.5.4.10	Ground-Requested Broadcast Handoff	115
3.2.2.5.4.10.1	Ground Action	115
3.2.2.5.4.10.2	Aircraft Response	116
3.2.2.5.4.10.3	Exceptional Cases	116
3.2.2.5.4.11	Ground-Commanded Autotune	117
3.2.2.5.4.11.1	Ground Action	117
3.2.2.5.4.11.2	General Aircraft Response	117
3.2.2.5.4.11.3	Exceptional Cases	117
3.2.2.5.4.12	Expedited Subnetwork Connection Management	117
3.2.2.5.4.12.1	Initiating Station of Subnetwork Connection Management	118
3.2.2.5.4.12.2	General Responder Action	118
3.2.2.5.4.12.3	Exceptional Cases	118
3.2.3	Subnetwork Layer Protocols and Services	119
3.2.3.1	Architecture	119
3.2.3.1.1	Access Points	119
3.2.3.1.2	ACARS Over AVLC (AOA)	119
3.2.3.1.3	Flight Information Services-Broadcast (FIS-B)	121
3.2.3.2	Services	122
3.2.3.2.1	Subnetwork Connection Management	123
3.2.3.2.2	Packet Fragmentation and Reassembly	123
3.2.3.2.3	Error Recovery	123
3.2.3.2.4	Connection Flow Control	123
3.2.3.3	Packet Format	124
3.2.3.3.1	General Format Identifier	124
3.2.3.3.2	Calling and Called DTE Addresses	124
3.2.3.3.2.1	Encoding	124
3.2.3.3.2.2	Address Field	125
3.2.3.3.2.2.1	Aircraft DTE Address	125
3.2.3.3.2.2.2	Ground VDL Specific DTE Addressing (VSDA)	125
3.2.3.3.2.2.2.1	Ground DTE Address	125
3.2.3.3.2.2.2.2	Ground Network DTE Addresses	126
3.2.3.3.3	Call User Data Field	126
3.2.3.3.4	Packet Types	126
3.2.3.4	Subnetwork Layer Service System Parameters	126
3.2.3.4.1	Packet Size	127
3.2.3.4.2	Parameter W (Transmit Window Size)	127
3.2.3.4.3	Parameter A (Acknowledgment Window Size)	128
3.2.3.5	Effects of Layers 1 and 2 on the Subnetwork Layer	128
3.2.3.6	Description of Procedures	128
3.2.3.6.1	Supported Facilities	128
3.2.3.6.2	Unsupported Facilities	129
3.2.3.6.3	Subnetwork Establishment and Connection Management	129
3.2.3.6.3.1	Subnetwork Entity Initialization	131
3.2.3.6.3.2	Subnetwork Connection Establishment	131
3.2.3.6.3.2.1	Explicit Subnetwork Connection Establishment	131
3.2.3.6.3.2.2	Expedited Network Connection Establishment	131

TABLE OF CONTENTS

3.2.3.6.3.3	Subnetwork Connection Maintenance	132
3.2.3.6.3.3.1	Explicit Subnetwork Connection Maintenance	132
3.2.3.6.3.3.2	Expedited Subnetwork Connection Maintenance	133
3.2.3.6.3.3.3	Broadcast Subnetwork Connection Maintenance.....	133
3.2.3.6.4	Error Handling	134
3.2.3.6.5	Acknowledgments	134
3.2.4	VDL MOBILE SNDCF	134
3.2.4.1	Introduction	134
3.2.4.2	(reserved).....	134
3.2.4.3	Call User Data Encoding.....	134
3.2.4.3.1	ISH PDU	134
3.2.4.3.2	Maintained/Initialized Status Bit	134
3.2.4.3.3	CALL REQUEST	135
3.2.4.3.4	CALL CONFIRMATION	135
3.3	VDL Mode 3	135
3.3.1	Physical Layer	135
3.3.1.1	Functions	135
3.3.1.1.1	Transceiver Frequency Control.....	135
3.3.1.1.2	Data Reception by the Transceiver or Receiver.....	135
3.3.1.1.3	Data Transmission by the Transceiver or Transmitter	135
3.3.1.1.4	Notification Services.....	136
3.3.1.2	Modulation Scheme.....	136
3.3.1.2.1	Data Encoding.....	136
3.3.1.2.2	Transmitted Signal Form	136
3.3.1.2.3	Modulation Rate	136
3.3.1.2.4	Emission Designator	136
3.3.1.2.5	Pulse Shaping Filters.....	136
3.3.1.3	Time Division Multiple Access (TDMA) Time Slot Bursts	137
3.3.1.3.1	Management (M) Burst and Handoff Check Message (H) Uplink	137
3.3.1.3.1.1	Training Sequence.....	137
3.3.1.3.1.1.1	Transmitter Ramp-Up and Power Stabilization	137
3.3.1.3.1.1.2	Synchronization and Ambiguity Resolution	137
3.3.1.3.1.2	System Data and Handoff Check Message	138
3.3.1.3.1.3	Transmitter Ramp-Down	139
3.3.1.3.2	Management (M) Burst Downlink.....	139
3.3.1.3.2.1	Training Sequence.....	139
3.3.1.3.2.1.1	Transmitter Ramp-Up and Power Stabilization	139
3.3.1.3.2.1.2	Synchronization and Ambiguity Resolution	139
3.3.1.3.2.2	System Data	140
3.3.1.3.2.3	Transmitter Ramp-Down	140
3.3.1.3.3	Voice or Data (V/D) Burst.....	140
3.3.1.3.3.1	Training Sequence.....	140
3.3.1.3.3.1.1	Transmitter Ramp-Up and Power Stabilization	140
3.3.1.3.3.1.2	Synchronization and Ambiguity Resolution	141
3.3.1.3.3.2	Header	141
3.3.1.3.3.3	User Information	141
3.3.1.3.3.4	Transmitter Ramp-Down	142
3.3.1.4	Interleaving.....	142
3.3.1.5	Bit Scrambling.....	142
3.3.1.6	Transmit/Receive Turnaround Times.....	142
3.3.1.6.1	Receive to Transmit Turnaround Time.....	142

TABLE OF CONTENTS

3.3.1.6.2	Transmit to Receive Turnaround Time	143
3.3.1.7	Transmission Characteristics	143
3.3.1.7.1	Carrier Frequencies	143
3.3.1.7.2	Spurious Emissions	143
3.3.1.7.3	Adjacent Channel Emissions	143
3.3.1.8	Fringe Coverage	143
3.3.1.8.1	Recommendation	144
3.3.2	Data Link Layer	144
3.3.2.1	MAC Sublayer (VDL Mode 3)	144
3.3.2.1.1	MAC Services	144
3.3.2.1.1.1	Multiple Access	144
3.3.2.1.1.1.1	Recommendation	145
3.3.2.1.1.2	Channel Occupancy	145
3.3.2.1.2	MAC Protocol Framework	145
3.3.2.1.2.1	Timing Structure	145
3.3.2.1.2.1.1	TDMA Frame	145
3.3.2.1.2.1.2	Time Slot	146
3.3.2.1.2.1.2.1	Timing Accuracy (Timing State 1)	146
3.3.2.1.2.1.2.2	Timing Accuracy (Timing State 2 or 3)	146
3.3.2.1.2.1.3	Bursts	146
3.3.2.1.2.1.4	Epoch	149
3.3.2.1.2.1.5	External Time Reference Interface	149
3.3.2.1.2.2	System Data and Header Field Formats	151
3.3.2.1.2.3	User Groups	151
3.3.2.1.2.4	System Configurations	151
3.3.2.1.2.5	Media Access Control Cycle	153
3.3.2.1.2.5.1	Logical Burst Access Channels (LBACs)	153
3.3.2.1.2.5.2	Burst Access Timing	155
3.3.2.1.2.5.3	Access Rules for M Downlink	156
3.3.2.1.3	Aircraft MAC Service System Parameters	156
3.3.2.1.3.1	Parameter t (Truncation)	160
3.3.2.1.3.1.1	Validity Window	165
3.3.2.1.3.1.2	Receipt of Beacon Information	166
3.3.2.1.3.2	Parameter f (Free Running)	166
3.3.2.1.3.3	Parameter NM1 (Maximum Retry)	166
3.3.2.1.3.4	Parameter RR (Reservation Request Randomizer)	166
3.3.2.1.3.5	Parameter RE (Net Entry Request Randomizer)	166
3.3.2.1.3.6	Parameter RL (Leaving Net Randomizer)	167
3.3.2.1.3.7	Parameter WR (Reservation Request Retransmission Delay)	167
3.3.2.1.4	Description of Procedures	167
3.3.2.1.4.1	Timing Acquisition and Maintenance	167
3.3.2.1.4.1.1	Primary Timing Reference	167
3.3.2.1.4.1.2	Alternate Timing Reference	168
3.3.2.1.4.1.3	Coast Timing Counters	169
3.3.2.1.4.1.4	Timing States	169
3.3.2.1.4.1.4.1	Recommendation	171
3.3.2.1.4.1.5	Timing State Transitions	171
3.3.2.1.4.1.5.1	Tuning to Invalid Channel – TS1	172
3.3.2.1.4.1.5.2	Tuning to Invalid Channel – TS2/TS3	172
3.3.2.1.4.1.6	Dummy Poll Responses	172
3.3.2.1.4.2	Voice Operation Support	173

TABLE OF CONTENTS

3.3.2.1.4.2.1	Voice Access Channel Contention.....	175
3.3.2.1.4.2.3	Free Running Voice Operation.....	176
3.3.2.1.4.3	Link Management Support.....	176
3.3.2.1.4.3.1	Polling.....	176
3.3.2.1.4.3.2	Net Entry Request Message.....	177
3.3.2.1.4.3.3	Next Net Message.....	178
3.3.2.1.4.3.4	Leaving Net Message.....	178
3.3.2.1.4.3.4.1	Tuning to Next Net.....	179
3.3.2.1.4.3.4.2	Maximum Leaving Net Delay.....	179
3.3.2.1.4.3.5	Terminate Net Message.....	179
3.3.2.1.4.3.6	Supported Options Message.....	179
3.3.2.1.4.3.7	RESERVED.....	180
3.3.2.1.4.4	Data Operation Support.....	180
3.3.2.1.4.4.1	Segmentation Function.....	180
3.3.2.1.4.4.2	Uplink Data Transfer.....	180
3.3.2.1.4.4.2.1	Acknowledgement Protocol.....	181
3.3.2.1.4.4.3	Downlink Data Transfer.....	182
3.3.2.1.4.4.3.1	Data Transfer.....	182
3.3.2.1.4.4.3.2	Assemble Message for MAC Data Transfer.....	182
3.3.2.1.4.4.3.3	Request a Reservation.....	182
3.3.2.1.4.4.3.4	Reservation Request Retransmission.....	185
3.3.2.1.4.4.3.5	Reservation Confirmation Indication.....	185
3.3.2.1.4.4.3.6	Acknowledgment Protocol.....	185
3.3.2.1.4.5	MAC Data Frame Transmission/Retransmission.....	185
3.3.2.1.4.6	Automated Handoff for 3T Configuration.....	187
3.3.2.2	Data Link Services (DLS) (VDL Mode 3).....	188
3.3.2.2.1	Services.....	188
3.3.2.2.1.1	Error Detection.....	188
3.3.2.2.1.2	Address Identification.....	188
3.3.2.2.1.2.1	Address Uniqueness.....	189
3.3.2.2.1.2.2	Broadcast Addressing.....	189
3.3.2.2.1.3	Data Transfer.....	189
3.3.2.2.2	VDL Mode 3 Data Link Service Protocol Specification.....	189
3.3.2.2.2.1	Frame Format.....	189
3.3.2.2.2.2	FCS/Aircraft Address Field.....	190
3.3.2.2.2.2.1	FCS/Aircraft Station Address.....	190
3.3.2.2.2.2.2	Address Type.....	190
3.3.2.2.2.3	Link Control Field.....	191
3.3.2.2.2.3.1	Frame Type.....	192
3.3.2.2.2.3.2	Priority.....	192
3.3.2.2.2.3.3	More Frame.....	193
3.3.2.2.2.4	Data Control Field.....	194
3.3.2.2.2.4.1	Ground Subnetwork Address Subfield.....	194
3.3.2.2.2.4.2	Data Length Subfield.....	195
3.3.2.2.2.5	Information Field.....	195
3.3.2.2.3	Data Link Service System Parameters.....	195
3.3.2.2.3.1	Timer T3 (Link Initialization Time).....	195
3.3.2.2.3.2	Parameter N1 (Maximum Frame Group Size).....	195
3.3.2.2.4	Description of Procedures.....	196
3.3.2.2.4.1	Modes of Operation.....	196
3.3.2.2.4.1.1	Operational Mode.....	196
3.3.2.2.4.2	Broadcast.....	196

TABLE OF CONTENTS

3.3.2.2.4.3	Information Transfer	196
3.3.2.2.4.3.1	Transmission Queue Management	196
3.3.2.2.4.3.1.1	Priority Processing	196
3.3.2.2.4.3.1.2	Recommendation for Frame Grouping	197
3.3.2.2.4.3.2	Reception Acknowledgement	197
3.3.2.2.4.3.2.1	Acknowledged Frames	198
3.3.2.2.4.3.2.2	Unacknowledged Frames	198
3.3.2.2.4.3.3	Transmission Acknowledgement/Retransmission	198
3.3.2.2.4.4	Control Frame	198
3.3.2.2.4.4.1	Control Command Frame	199
3.3.2.2.4.4.2	Control Response Frame	199
3.3.2.2.5	MAC-DLS Processing Delays	199
3.3.2.2.5.1	Aircraft DLS-MAC Processing Delay	199
3.3.2.2.5.2	Downlink ACK Transmission Delay	199
3.3.2.2.5.3	Uplink ACK Transmission Delay	199
3.3.2.2.5.4	Downlink Data Transmission Delay	201
3.3.2.3	Link Management Entity (LME) Sublayer (VDL Mode 3)	201
3.3.2.3.1	Services	201
3.3.2.3.2	Operation Procedures	201
3.3.2.3.2.1	Link Establishment	201
3.3.2.3.2.1.1	Net Initialization	202
3.3.2.3.2.1.2	Net Entry	203
3.3.2.3.2.1.2.1	Supported Options	206
3.3.2.3.2.1.3	Initial Link Negotiation	206
3.3.2.3.2.1.3.1	Air Initiation	207
3.3.2.3.2.1.3.2	General Ground Response	207
3.3.2.3.2.1.3.3	Air Response	207
3.3.2.3.2.1.3.4	Exceptional Cases	207
3.3.2.3.2.1.3.5	Parameter Longevity	208
3.3.2.3.2.2	Slot Selection (Configurations 3S and 2S1X)	208
3.3.2.3.2.3	Link Modification	212
3.3.2.3.2.3.1	Description of LME Procedures	212
3.3.2.3.2.3.2	Link Maintenance Procedures	212
3.3.2.3.2.3.2.1	Addressed Link Parameter Modification	212
3.3.2.3.2.3.2.2	Broadcast Link Parameter Modification	213
3.3.2.3.2.3.2.3	Parameter Longevity	214
3.3.2.3.2.4	Link Maintenance	214
3.3.2.3.2.5	Recovery	214
3.3.2.3.2.5.1	Polling System Configurations	217
3.3.2.3.2.5.2	Data-Capable System Configurations	218
3.3.2.3.2.5.3	Missed Poll	219
3.3.2.3.2.5.4	Retransmission	219
3.3.2.3.2.5.5	Verification	219
3.3.2.3.2.6	Link Release	219
3.3.2.3.2.6.1	Explicit Link Release	220
3.3.2.3.2.6.2	Implicit Link Release	220
3.3.2.3.2.7	Handoff	221
3.3.2.3.2.7.1	Air-initiated Link Handoff	221
3.3.2.3.2.7.2	Ground-initiated Link Handoff	221
3.3.2.3.2.7.3	Same GNI	221
3.3.2.3.2.7.4	Different GNI	221

TABLE OF CONTENTS

3.3.2.3.2.8	Authentication	221
3.3.2.3.2.8.1	Signature Verification	221
3.3.2.3.2.8.2	Unknown Authentication Type	222
3.3.2.3.2.8.3	Authentication Type Mismatch	222
3.3.2.3.2.8.4	Invalid Signature	222
3.3.2.3.3	Link Management Frames	222
3.3.2.3.3.1	M Burst Message Format	222
3.3.2.3.3.2	LME Service System Parameters	223
3.3.2.3.3.2.1	RESERVED	224
3.3.2.3.3.2.2	Counter NL2 (Polling Reply Counter)	224
3.3.2.3.3.2.3	Timer TL3 (Disconnect Delay Timer)	224
3.3.2.3.3.2.4	Timer TL4 (Polling Interval)	224
3.3.2.3.3.2.5	Parameter WE (Net Entry Retransmission Delay)	225
3.3.2.3.3.2.6	Parameter NL5 (Multiple Radio Local Identifier Buffer)	225
3.3.2.3.3.2.7	Parameter NL6 (Free Address Recovery)	225
3.3.2.3.3.3	Exchange Identity (XID) Parameter Format	225
3.3.2.3.3.3.1	Public Parameters	226
3.3.2.3.3.3.1.1	General Public Parameters	226
3.3.2.3.3.3.1.2	VDL Mode 3 Public Parameters	226
3.3.2.3.3.3.2	Private Parameters	228
3.3.2.3.3.3.3	General Private Parameters	228
3.3.2.3.3.3.3.1	General Purpose Information Private Parameters	228
3.3.2.3.3.3.3.2	Aircraft-Initiated Information Private Parameters	228
3.3.2.3.3.3.4	VDL Mode 3 Private Parameters	228
3.3.2.3.3.3.4.1	General Purpose Information Private Parameters	229
3.3.2.3.3.3.4.1.8	Assigned Altitude Parameter	234
3.3.2.3.3.3.4.2	Air-initiated Information Private Parameters	234
3.3.2.3.3.3.4.3	Ground-initiated Modification Private Parameters	236
3.3.2.3.3.3.4.3.11	Operative_GNIP Parameter	239
3.3.2.3.3.3.4.3.12	Aircraft_TMbB Parameter	239
3.3.2.3.3.3.4.3.13	MbB_Operations_Permitted	239
3.3.2.3.3.3.4.4	Ground-initiated Information Private Parameters	240
3.3.2.3.3.3.4.4.1	Counter NL2 (Polling Reply) Parameter	240
3.3.2.3.3.3.4.4.2	NL5 (Multiple Radio Local Identifier Buffer) Parameter	240
3.3.2.3.3.3.4.4.3	NL6 (Free Address Recovery) Parameter	240
3.3.3	Subnetwork Layer Protocols and Services (VDL Mode 3)	241
3.3.3.1	Payload Identification	241
3.3.3.2	Compression Signaling	241
3.3.3.2.1	ISO 8208 Compression	242
3.3.3.2.2	CLNP Compression	242
3.3.3.2.3	Raw Payload Type	242
3.3.3.2.4	ATN Frame Mode Payload Type	242
3.3.3.3	Make-before-Break (MbB) Operation	242
3.3.3.3.1	General Requirements	243
3.3.3.3.1.1	GNIP-Group Addressing	243
3.3.3.3.1.2	GNIP-Group Parameter Set	243
3.3.3.3.2	MbB Avionics Requirements	243
3.3.3.3.2.1	Initialization	244
3.3.3.3.2.2	Determining MbB Applicability in the Aircraft	244
3.3.3.3.2.3	Aircraft MbB-Operation	245
3.3.3.3.3	GNIP Requirements	246
3.3.3.3.3.1	Determining MbB Applicability on the Ground	246

TABLE OF CONTENTS

3.3.3.3.2	Compatibility with Aircraft not Requesting MbB Capability	247
3.3.3.3.3	Operative_GNIP Requirements	247
3.3.3.3.4	Former_GNIP Requirements	249
3.3.3.4	Recommended MbB Parameter Values	250
3.3.3.4	Router Interface Recommendation	251
3.3.3.5	Subnetwork Interface Support	251
3.3.3.5.1	Aircraft Subnetwork Interface Support	251
3.3.3.5.2	Ground Station Subnetwork Interface Support	251
3.3.3.6	Raw Subnetwork Interface Operation	251
3.3.3.6.1	Protocol Identifier	251
3.3.3.6.2	Supported Protocols	252
3.3.3.6.2.1	ACARS over VDL3	252
3.3.3.6.2.2	Flight Information Service - Broadcast	252
3.3.3.6.2.3	Reserved for Testing	252
3.3.4	VDL Mode 3 SNDCF Introduction	252
3.3.4.1	The ISO 8208 SNDCF Interface	253
3.3.4.2	The Frame-Based SNDCF Interface	253
3.3.4.2.1	Frame-Based SNDCF Support for Broadcast & Unicast Network Packets	253
3.3.4.2.2	ATN Router Support	253
3.3.4.2.2.1	Join/Leave Events	253
3.3.4.2.2.2	Payload Identification	254
3.3.4.2.2.3	Disposition of CLNP and ISH Packets	254
3.3.4.2.2.4	ISH Packets	254
3.3.4.2.2.5	CLNP Compression	254
3.3.4.3	The ATN Frame Mode SNDCF	254
3.3.5	Voice Unit	254
3.3.5.1	Services	254
3.3.5.1.1	Priority Access	255
3.3.5.1.2	Message Source Identification	255
3.3.5.1.3	Coded Squelch	255
3.3.5.1.4	Urgent Downlink Request (UDR) Signaling	255
3.3.5.2	Speech Encoding	255
3.3.5.2.1	Speech Encoding Algorithm	255
3.3.5.2.2	Voice Burst Framing	256
3.3.5.2.3	Vocoder Frame Bit Ordering	256
3.3.5.3	Parameters	257
3.3.5.3.1	Group ID	257
3.3.5.3.2	Squelch Window	257
3.3.5.3.3	Algorithm Version Number	257
3.3.5.4	Description of Procedures	258
3.3.5.4.1	Link Establishment	258
3.3.5.4.1.1	Link Initialization	258
3.3.5.4.1.2	Net Entry	258
3.3.5.4.2	Timing	258
3.3.5.4.2.1	Transmit Delay	258
3.3.5.4.2.2	Receive Delay	259
3.3.5.4.3	Voice Transmit Function	259
3.3.5.4.3.1	Demand-Assigned Circuits	259
3.3.5.4.3.2	Vocoder Processing	260
3.3.5.4.3.2.1	Truncated Mode Encoding	260

TABLE OF CONTENTS

3.3.5.4.3.2.2	Truncated Mode Decoding.....	260
3.3.5.4.3.2.3	Truncated Mode Formatting	261
3.3.5.4.3.3	Access Pre-emption.....	261
3.3.5.4.3.4	Urgent Downlink Request (UDR)	261
3.3.5.4.3.4.1	Urgent Downlink Request Not Supported	262
3.3.5.4.3.5	Anti-blocking	262
3.3.5.4.4	Voice Receive Function.....	262
3.3.5.4.4.1	Pre-processing.....	262
3.3.5.4.4.1.1	Source Filtering.....	263
3.3.5.4.4.1.2	Vocoder Processing.....	264
3.3.5.4.4.1.3	Source Identification	264
3.3.5.4.4.2	Voice Synthesis.....	264
3.3.5.4.5	Handoff Recommendation	265
3.4	Ground Transmitter.....	265
3.4.1	Ground Transmitter Power.....	265
3.4.2	Transmitter Duty Cycle.....	265
3.5	Uplink	265
3.5.1	Uplink Channel Characteristics.....	265
3.5.1.1	Doppler Characteristics	266
3.5.1.1.1	Doppler Shift.....	266
3.5.1.1.2	Doppler Rate	266
3.5.1.1.3	Delay and Doppler Spread	267
3.5.1.2	Signal Fading.....	267
3.5.1.2.1	Fast Fading with Rotary Wing Aircraft	268
3.5.1.3	Aircraft Noise Environment	268
3.5.1.4	Cochannel Interference.....	268
3.5.1.4.1	VDL Mode 2.....	268
3.5.1.4.2	VDL Mode 3	268
3.5.2	Typical Uplink Power Budget.....	268
3.6	Aircraft Receiver.....	272
3.6.1	Minimum Detectable Signal (Uplink).....	272
3.7	Combined Aircraft Receive/Transmit Characteristics	274
3.7.1	Frequency Stability	274
3.7.2	Tuning Time.....	274
3.7.3	Aircraft Antenna Characteristics	274
3.7.4	Link Availability	275
3.8	Aircraft Transmitter	276
3.8.1	Transmitter Power	276
3.9	Downlink.....	277
3.9.1	Downlink Channel Characteristics	277
3.9.1.1	Ground Noise Environment.....	277
3.9.2	Typical Downlink Power Budget.....	277
3.10	Ground Receiver	280
3.10.1	Minimum Detectable Signal (Downlink).....	280
3.11	Combined Ground Receive/Transmit Characteristics.....	281
3.11.1	Frequency Stability	282
3.11.2	Ground Antenna Characteristics	282

TABLE OF CONTENTS

APPENDICES

- Appendix A Membership
- Appendix B Tutorial on Aspects of VHF Communications System Design
- Appendix C Acronyms
- Appendix D System Link Margin Comparison of D8PSK and DSB-AM
- Appendix E VDL Mode 2 Generator Polynomial $G(X)$
- Appendix F Sample VDL Packet and Circuit Mode Transmission Examples
- Appendix G Format and Usage of the System Data and Header Segments for VDL Mode 3 Operation

- Appendix H Random Number Generation Algorithm
- Appendix I Random Access Downlink M Burst Selection Algorithms for Aircraft Radios

- Appendix J ISO 8208 Compression Definition
- Appendix K CLNP Compression Definition
- Appendix L Preparation of Link Budgets for VHF Data Link
- Appendix M VHF Channel Labels
- Appendix N MASPs to SARPs Matrix

TABLE OF CONTENTS

TABLE OF FIGURES

Figure 1-1: End-to-End ATN Compatible Data System Structure.....	27
Figure 1-2: VDL Mode 3 End-to-End Voice Services System Structure.....	28
Figure 1-3: Establishing Reuse Distance in the ATC Environment.....	31
Figure 3-1: Transmitter Power Stabilization	45
Figure 3-2: PN Generator for BIT Scrambling Sequence	50
Figure 3-3: Turnaround Time.....	53
Figure 3-4: Link Layer Frame Format.....	60
Figure 3-5a: Management (M) and V/D Bursts and Slot Components	147
Figure 3-5b: Four Management (M) Bursts and Slot Components (Downlink Slot A of 3T) ...	148
Figure 3-5c: Bursts and Slot Components for Management (M) and Handoff Check Message (H) Bursts (Uplink Slot A of 3T).....	148
Figure 3-6a: Frame Structure for Normal Range Non-3T Configurations (Section 3.3.2.1.2.3)	149
Figure 3-6b: Frame structure for Normal Range 3T Configurations (Section 3.3.2.1.2.3).....	150
Figure 3-6c: Frame Structure for Long Range Configurations (Section 3.3.2.1.2.3).....	150
Figure 3-7: M Burst ACK Timing.....	181
Figure 3-8: DLS Sublayer Frame Format.....	190
Figure 3-9: VDL Mode 3 Link Control Field.....	192
Figure 3-10: Payload octet.....	241
Figure F-1: FEC Computation.....	7
Figure F-2: Absolute Phase Encoding (Gray code).....	10
Figure F.2-1. Power Stabilization Sequence	14
Figure F.2-2. Synchronization Sequence.....	14
Figure F.2-3. Golay Coded Header Sequence	15
Figure F.2-4. Reed-Solomon Coded Data Sequence	20
Figure F.2-5. Bit Scrambler Sequence	21
Figure F.2-6. Payload Sequence.....	22
Figure F.2-7. Scrambled Payload	22
Figure F.2-8. Phase Change Sequence	25
Figure F.2-9. Final Phase Sequence	26
Figure G-1. Non-3T Configuration Generic M Uplink System Data Segment	2
Figure G-2. M Uplink (Normal Message).....	7
Figure G-3. M Uplink (Net Entry Response Message)	9
Figure G-4. M Uplink (Next Net Command Message).....	11
Figure G-5. M Uplink (Recovery Message).....	11
Figure G-6. M Uplink (Handoff Check Message).....	12
Figure G-7. 3T Configuration Generic M Uplink System Data Segment	15
Figure G-8. M Downlink (Net Entry Request Message).....	16
Figure G-9. Poll Response and M Downlink (Reservation Request Message).....	17
Figure G-10. M Downlink (Acknowledgement Message).....	18
Figure G-11. M Downlink (Leaving Net Message)	19
Figure G-12. M Downlink (Next Net ACK Message)	19
Figure G-12a: M Uplink (Terminate Net Message)	20
Figure G-12b: M Uplink (Supported Options Message).....	21
Figure G-13. V/D (Voice) Burst Header Segment	22
Figure G-14. V/D (Data) Burst Header Segment	23
Figure J.1-1: ISO 8208 Compressor Architecture	2
Figure K-1: ATN CLNP Packet	2

Figure K-2: Compressed CLNP Header Format	3
Figure K-3: Compression Field (Type-Specific Information Field) Definition for ISO8473 (Payload Field Value of 0001 Binary)	4
Figure K-4: Bit Field Definitions	5
Figure K-5: CLNP Compression System Parameters.....	11

TABLE OF TABLES

Table 3-1: Data Encoding.....	41
Table 3-2: Scrambler Functions	50
Table 3-3: MAC Service System Parameters	56
Table 3-4: Address Type Field Encoding.....	61
Table 3-5: Broadcast Address Encoding	62
Table 3-6: AVLC Commands and Responses.....	63
Table 3-7: Data Link Service System Parameters	65
Table 3-8: HDLC Public Parameter Set Identifier	77
Table 3-9: Timer T1 Parameter	78
Table 3-10: VDL Private Parameter Identification	78
Table 3-11: Private Parameter Set Identification	79
Table 3-12: Connection Management Parameter	79
Table 3-13: Connection Management Parameter Values	79
Table 3-14: Abbreviated XID Names.....	80
Table 3-15: Signal Quality Parameter	80
Table 3-16: XID Sequence Parameter.....	81
Table 3-17: AVLC Specific Options Parameter Format	82
Table 3-18: AVLC Specific Options Parameter Values.....	82
Table 3-19: Expedited Subnetwork Connection.....	83
Table 3-20: LCR Cause Parameter.....	84
Table 3-21: Cause Code Table	84
Table 3-22: Modulation Support	86
Table 3-23: Modulation Scheme and Bit Rate	86
Table 3-24: Acceptable Alternative Ground Station Parameter	87
Table 3-25: Destination Airport	87
Table 3-26: Aircraft Location.....	88
Table 3-27: Aircraft Location Subfield Description.....	88
Table 3-28: Autotune Frequency Parameter.....	89
Table 3-29: Replacement Ground Station List.....	89
Table 3-30: Timer T4 Parameter	90
Table 3-31: MAC Persistence Parameter	90
Table 3-32: Counter M1 Parameter	91
Table 3-33: Timer TM2 Parameter.....	91
Table 3-34: Timer TG5 Parameter	91
Table 3-35: T3min Parameter.....	92
Table 3-36: Ground Station Address Filter Parameter	92
Table 3-37: Broadcast Connection (Link Only) Parameter.....	93
Table 3-38: Broadcast Connection (Link and Subnetwork) Parameter	94
Table 3-39: Frequency Support List.....	95
Table 3-40: Airport Coverage Indication Parameter	95

TABLE OF CONTENTS

Table 3-41: Nearest Airport Parameter	96
Table 3-42: ATN Router NETs Parameter	96
Table 3-43: Station Operator Mask Parameter	97
Table 3-44: Timer TG3 Parameter	97
Table 3-45: Timer TG4 Parameter	98
Table 3-46: Ground Station Location Parameter.....	98
Table 3-47: VDL Management Entity System Parameters	99
Table 3-48a: XID Parameters	103
Table 3-48b: XID Parameters.....	104
Table 3-48c: XID Parameters	106
Table 3-49a: AOA Message Format within the AVLC frame	120
Table 3-49b: FIS-B Message Format	122
Table 3-49: Subnetwork Layer Service System Parameter	127
Table 3-50: Facilities Supported By VDL Mode2	129
Table 3-51: Facilities Not Supported	130
Table 3-52: System Configurations and Addressing Schemes.....	152
Table 3-53: Logical Burst Access Channel (LBAC) Descriptions for Configurations 4V, 2V2D, 3V, 3V1D and 2V1D.....	154
Table 3-54: LBAC Timing Offset Values for Configurations	155
2V2D, 3V, 3V1D and 2V1D	155
Table 3-55: LBAC Description and Timing for 3T Configuration	157
Table 3-56a: LBAC Description and Timing for 3S Configuration.....	158
Table 3-56b: LBAC Description and Timing for 2S1X Portion of Configuration.....	158
Table 3-56c: LBAC Description and Timing for 1V3D Configuration	159
Table 3-56d: LBAC Description and Timing for 1V2D Configuration.....	159
Table 3-56e: Relative Timing Relationship for TRPs of Different User Groups for All System Configurations.....	160
Table 3-57: Access Rules for M Downlink.....	161
Table 3-58a: Aircraft MAC Service System Parameters.....	164
Table 3-58b: Aircraft MAC Service System Parameters	165
Table 3-59: Rules for CTCs' Maintenance	169
Table 3-60: Timing States for Non-3T Configurations	170
Table 3-60a: Timing States for 3T Configuration.....	170
Table 3-61: Conditions for Voice Media Access (AircraftRadio).....	175
Table 3-62: MAC Data Frame Transmission System Parameters.....	186
Table 3-63: VDL Mode 3/ATN Priority Mapping.....	193
Table 3-64: DLS System Parameters	195
Table 3-65a: XID Parameters	210
Table 3-65b: XID Parameters.....	215
Table 3-66a: LME System Parameters.....	223
Table 3-66b: WE and TL4 Parameter Default Values	223
Table 3-67: VDL Mode 3 Public Parameter Set Identifier.....	227
Table 3-68: Timer T1 Parameter	227
Table 3-69: Timer T_ack Parameter.....	228
Table 3-70: Parameter Set Identification.....	229
Table 3-71a: Algorithm Version Number Parameter	229
Table 3-71b: Vocoder Algorithm Version Encoding	230
Table 3-72a: Network Initialization	230
Table 3-72b Network Type Values	231
Table 3-73a: Connection Check Parameter	232
Table 3-73b: Version Parameter.....	232

Table 3-73c: Version Values	232
Table 3-73d: Authentication Parameter.....	233
Table 3-73e: Authentication Type.....	233
Table 3-73f: Subnetwork User Data Parameter.....	234
Table 3-73g: Assigned Altitude Parameter	234
Table 3-74: Expedited Recovery Parameter.....	235
Table 3-75: t Parameter	235
Table 3-76a: f Parameter	235
Table 3-76b: Former_GNI _p Parameter	236
Table 3-77: NM1 Parameter.....	236
Table 3-78: RR Parameter	236
Table 3-79: WR Parameter.....	237
Table 3-80: RE Parameter	237
Table 3-81: RL Parameter	237
Table 3-82: Timer T3 Parameter	237
Table 3-84: Timer TL3 Parameter.....	238
Table 3-85: Timer TL4 Parameter.....	238
Table 3-86: WE Parameter	238
Table 3-88: Operative_GNI _p Parameter	239
Table 3-89: Aircraft_TMbB Parameter	239
Table 3-90a: MbB_Operations_Permitted Parameter	239
Table 3-90b: Counter NL2 Parameter	240
Table 3-90c: NL5 Parameter	240
Table 3-91a: NL6 Parameter	240
Table 3-91b: Recommended MbB Parameter Values	250
Table 3-91c: IPI and EIPi Protocol Identifiers.....	252
Table 3-92: Source Filtering Squelch Window Matrix for 4-Slot Configurations.....	263
Table 3-93: Source Filtering Squelch Window Matrix for 3-Slot Configurations.....	263
Table 3-94: Uplink Power Budget for VHF Digital Radio	270
Table 3-95: Excess Path Loss 95% Prob 1 Hr. Avg 137 MHz(dB)	272
Table 3-96: Link Margin (Uplink) in Decibels	272
Table 3-97: Minimum Detectable (Uplink) Signal Calculations.....	273
Table 3-98: Downlink Power Budget for VHF Digital Radio.....	279
Table 3-99: Link Margin (Downlink) (dB)	280
Table 3-100: Minimum Detectable (Downlink) Signal Calculations.....	281
Table B-1: Signal Fading On VHF Air/Ground Path.....	2
Table B-2: Terminal Domain Application Message Traffic Model.....	11
Table B-3: VDL Mode 3 Data Link Message Delay Performance for Frame-based SNDCF	12
Table D-1: Margin Comparison for D8PSK (Voice) and DSB-AM (Voice).....	2
Table F.2-1. Data Encoding.....	24
Table G-1: M Burst Messages.....	3
Table G-2: System Configuration Codes	4
Table G-3. Voice Signal Codes.....	5
Table G-4: Aircraft ID Codes.....	5
Table G-5. Beacon ID Codes.....	5
Table G-6: Reserved Slot Subfield Encoding.....	8
Table G-7. Next Net Subfield Encoding when Net Type field set to 0 (AM).....	10
Table G-8. Voice Request Field	18
Table G-9: Options field.....	21
Table G-10: Radio Identifier Field.....	21
Table J.4-1: DCE Substate Hierarchy	4

TABLE OF CONTENTS

Table J.5-1: VDL Mode 3 Call Request Packet	8
Table J.5-2: VDL Mode 3 Call REQUEST Packet	11
Table J.5-3: VDL Mode 3 Call ACCEPT Packet	13
Table J.5-4: VDL Mode 3 CALL ACCEPT Packet	15
Table J.5-5: VDL Mode 3 CLEAR REQUEST Packet	17
Table J.5-6: VDL Mode 3 CLEAR REQUEST Packet	19
Table J.5-7: VDL Mode 3 DATA Packet	20
Table J.5-10: VDL Mode 3 RESET REQUEST Packet	22
Table J.5-11: VDL Mode 3 RECEIVE READY Packet	24
Table J.5-12: VDL Mode 3 RECEIVE NOT READY Packet	25
Table J.5-13: VDL Mode 3 CLEAR CONFIRMATION Packet	26
Table J.5-14: VDL Mode 3 RESET CONFIRMATION Packet	27
Table J.5-15: VDL Mode 3 REJECT Packet	28
Table J.6-1: DCE Actions at State Transition	30
Table J.7-1: Multiplexing Header Packet Structure	41
Table J.9-1: VDL Mode 3 Subnetwork Timers	43
Table J.10-1a: 8208 Compression System Parameters	43
Table J.10-1b: ADSA Parameter	44
Table J.10-2: GDTE Parameter	44
Table J.10-3: VER Parameter	45
Table J.10-4: M-BIT Parameter	45
Table J.11-1: DCE Special Cases	47
Table J.11-2: DTE Effect on DCE Restart States	48
Table J.11-3: DTE Effect on DCE Call Setup and Clearing States	50
Table J.11-4: DTE Effect on DCE Reset States	53
Table J.11-5: RESERVED	55
Table J.11-6: DTE Effect on DCE Flow Control Transfer States	55
Table J.11-7: XDCE Effect on DCE Restart States	56
Table J.11-8: XDCE Effect on DCE Call Setup and Clearing States	57
Table J.11-9: XDCE Effect on DCE Reset States	58
Table J.11-10: RESERVED	58
Table J.11-11: GNI (ANI) Effect on ADCE (GDCE) Packet Layer Ready States	58
Table J.11-12: GNI (ANI) Effect on ADCE (GDCE) Call Setup and Clearing States	59
Table J.11-13: GNI (ANI) Effect on ADCE (GDCE) Reset States	62
Table J.11-14: RESERVED	63
Table J.11-15: GNI (ANI) Effect on ADCE (GDCE) Flow Control Transfer States	63
Table J.11-16: DCE Effect on ADCE (GDCE) Call Setup and Clearing States	65
Table J.11-17: DCE Effect on ADCE (GDCE) Reset States	67
Table J.11-18: RESERVED	68
Table K-6: CT1 Parameter	12
Table K-7: CT2 Timer	12
Table K-8: CT3 Timer	12
Table L-1: Free Space and Ground Reflection Loss vs. Range, Aircraft Flight Level and Ground Antenna Height, (Median refractive conditions or effective Earth radius factor $\kappa = 4/3$)	5
Table L-2: Free Space and Ground Reflection Loss vs. Range, Aircraft Flight Level and Ground Antenna Height (Worst case sub-refractive conditions or effective Earth radius factor $\kappa = 1$)	6
Table L-3: Parameters for Sample Link Budgets	10
Table L-4: Sample Ground-to-Air Long-Range Link Budgets Using Ray-Tracing and Effective Earth Radius Factor $\kappa = \frac{4}{3}$ (Median)	12

Table L-5: Sample Ground-to-Air Long-Range Link Budgets Using Ray-Tracing and Effective Earth Radius Factor $\kappa = 1$ (Worst Case)	13
Table L-6: Sample Ground-to-Air Long-Range Link Budgets Using Johnson-Gierhart Propagation Model (95 th Percentile)	14
Table L-7: Sample Air-to-Ground Long-Range Link Budgets Using Ray-Tracing and Effective Earth Radius Factor $\kappa = \frac{4}{3}$ (Median)	16
Table L-8: Sample Air-to-Ground Long-Range Link Budgets Using Ray-Tracing and Effective Earth Radius Factor $\kappa = 1$ (Worst Case)	17
Table L-9: Sample Air-to-Ground Long-Range Link Budgets Using Johnson-Gierhart Propagation Model (95 th Percentile)	18
Table M-1: VHF Channel Labels	2
Table N-1 Correlation Matrix: DO-224B to Core SARPs	1
Table N-2 Correlation Matrix: DO-224B to Tech Manual for VDL-2	8
Table N-3 Correlation Matrix: DO-224B to Tech Manual for VDL-3	18

1.0 INTRODUCTION

The purpose of this document is to provide RTCA Minimum Aviation System Performance Standards (MASPS) that define the signal-in-space characteristics for an advanced Very High Frequency (VHF) digital data communications radio, including compatibility with digital voice techniques. This document examines the VHF communications system characteristics and principles of operation for both VHF voice and data system elements. Aviation user requirements and system requirements are considered and technical characteristics are developed for aircraft transceivers and ground transmitters/receivers. Finally, considerations are examined with regard to accommodating existing systems while making a transition to a new improved VHF data link.

1.1 VHF Communications System Characteristics

1.1.1 Introduction

The characteristics of the present air/ground VHF communications system are contained in the Federal Communications Commission (FCC) Rules (47 CFR Part 87), the International Civil Aviation Organization (ICAO) Standards and Recommended Practices (SARPs) (Annex 10, Volume I, Chapter 4 Paras. 4.5 - 4.7), and RTCA/DO-186 (Minimum Operational Performance Standards (MOPS) For Airborne Radio Communications Equipment Operating Within the Radio Frequency Range 117.975 – 136.000 MHz. These documents set forth the minimum mandatory and desired operational performance standards for VHF air/ground communications systems. The following list summarizes pertinent industry standards and their specific versions.

Reference Document Name	Doc. #
ARINC Specification – Air-Ground Character-Oriented Protocol Specification	618
ARINC Specification – ACARS Protocols for Avionic End Systems	619
ARINC Specification – Data Link Ground System Standard and Interface Specification (DGSS/IS)	620
ARINC Specification – ATS Data Link Applications Over ACARS Air-Ground Network	622
ARINC Specification – Character-Oriented Air Traffic Services (ATS)	623