

PD ISO/TS 12901-2:2014



BSI Standards Publication

Nanotechnologies — Occupational risk management applied to engineered nanomaterials

Part 2: Use of the control banding approach

bsi.

...making excellence a habit.™

National foreword

This Published Document is the UK implementation of ISO/TS 12901-2:2014.

The UK participation in its preparation was entrusted to Technical Committee NTI/1, Nanotechnologies.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2014. Published by BSI Standards Limited 2014

ISBN 978 0 580 68368 8

ICS 07.030; 13.100

Compliance with a British Standard cannot confer immunity from legal obligations.

This Published Document was published under the authority of the Standards Policy and Strategy Committee on 28 February 2014.

Amendments issued since publication

Date	Text affected
------	---------------

**TECHNICAL
SPECIFICATION**

**ISO/TS
12901-2**

First edition
2014-01-15

**Nanotechnologies — Occupational risk
management applied to engineered
nanomaterials —**

**Part 2:
Use of the control banding approach**

*Nanotechnologies — Gestion du risque professionnel appliquée aux
nanomatériaux manufacturés —*

Partie 2: Utilisation de l'approche par bandes de dangers



Reference number
ISO/TS 12901-2:2014(E)

© ISO 2014



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	4
5 General framework for control banding applied to NOAA	4
5.1 General.....	4
5.2 Information gathering and data recording.....	5
5.3 Hazard banding.....	6
5.4 Exposure banding.....	6
5.5 Control banding.....	6
5.6 Review and data recording.....	7
6 Information gathering	7
6.1 NOAA characterization.....	7
6.2 Exposure characterization.....	8
6.3 Characterization of control measures.....	9
7 Control banding implementation	10
7.1 Preliminary remarks.....	10
7.2 Hazard band setting.....	10
7.3 Exposure band setting.....	16
7.4 Control band setting and control strategies.....	20
7.5 Evaluation of controls.....	21
7.6 Retroactive approach — Risk banding.....	22
8 Performance, review and continual improvement	24
8.1 General.....	24
8.2 Objectives and performance.....	24
8.3 Data recording.....	24
8.4 Management review.....	25
Annex A (informative) Exposure algorithm in the Stoffenmanager risk banding approach	26
Annex B (informative) Health hazard class according to GHS	29
Bibliography	30

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 229, *Nanotechnologies*.

ISO/TS 12901 consists of the following parts, under the general title *Nanotechnologies — Occupational risk management applied to engineered nanomaterials*:

- *Part 1: Principles and approaches*
- *Part 2: Use of the control banding approach*

Introduction

According to the current state of knowledge, nano-objects, and their aggregates and agglomerates greater than 100 nm (NOAA) can exhibit properties, including toxicological properties, which are different from those of non-nanoscale (bulk) material. Therefore, current occupational exposure limits (OELs), which are mostly established for bulk materials might not be appropriate for NOAA. In the absence of relevant regulatory specifications for NOAA, the control banding approach can be used as a first approach to controlling workplace exposure to NOAA.

NOTE 1 Aggregates and agglomerates smaller than 100 nm are to be considered as nano-objects.

Control banding is a pragmatic approach which can be used for the control of workplace exposure to possibly hazardous agents with unknown or uncertain toxicological properties and for which quantitative exposure estimations are lacking. It may complement the traditional quantitative methods based on air sampling and analysis with reference to OELs when they exist. It can provide an alternative risk assessment and risk management process, by grouping occupational settings in categories presenting similarities of hazards and/or exposure, while incorporating professional judgment and monitoring. This process applies a range of control techniques (such as general ventilation or containment) to a specific chemical, considering its range (or band) of hazard and the range (or band) of exposure.

In general, control banding is based on the idea that while workers can be exposed to a diversity of chemicals, implying a diversity in risks, the number of common approaches to risk control is limited. These approaches are grouped into levels based on how much protection the approach offers (with “stringent” controls being the most protective). The greater the potential for harm, the greater the levels of protection needed for exposure control.

Control banding was originally developed by the pharmaceutical industry as a way to safely work with new chemicals that had little or no toxicity information. These new chemicals were classified into “bands” based on the toxicity of analogous and better known chemicals and were linked to anticipated safe work practices, taking into consideration exposure assessments. Each band was then aligned with a control scheme.^[1] Following this concept, the Health and Safety Executive (HSE) in the UK has developed a user-friendly scheme called COSHH Essentials,^{[2][3][4]} primarily for the benefit of small- and medium-sized enterprises that might not benefit from the expertise of a resident occupational hygienist. Similar schemes are used in the practical guidance given by the German Federal Institute for Occupational Safety and Health.^[5] The Stoffenmanager Tool^[6] represents a further development, combining a hazard banding scheme similar to that of COSHH Essentials and an exposure banding scheme based on an exposure process model, which was customized in order to allow non-expert users to understand and use the model.

Control banding can be particularly useful for the risk assessment and management of nanomaterials, given the level of uncertainty in work-related potential health risks from NOAA. It may be used for risk management in a proactive manner and in a retroactive manner. In the proactive manner existing control measures, if any, are not used as input variables in the potential exposure banding while in a retroactive manner existing control measures are used as input variables. Both approaches are described in this part of ISO/TS 12901. While control banding appears, in theory, to be appropriate for nanoscale materials exposure control, very few comprehensive tools are currently available for ongoing nanotechnology operations. A conceptual control banding model was presented by Maynard^[7] offering the same four control approaches as COSHH. A slightly different approach, called “Control Banding Nanotool”, was presented by Paik et al.^{[8][9]} This approach takes into account existing knowledge of NOAA toxicology and uses the control banding framework proposed in earlier publications. However, the ranges of values used in the “Control Banding Nanotool” correspond to those ranges that one would expect in small-scale research type operations (less than one gram) and might not seem appropriate for larger scale uses. In the meantime several other specific control banding tools have been published to control inhalation exposure to engineered nanomaterials for larger scale uses.^{[10][11][12][13][14]} All these tools define hazard bands and exposure bands for inhalatory exposure and combine these in a two-dimensional matrix, resulting in a score for risk control (proactive approach).

Schneider et al.^[15] have developed a conceptual model for assessment of inhalation exposure to engineered nanomaterials, suggesting a general framework for future exposure models. This framework follows

the same structure as the conceptual model for inhalation exposure used in the Stoffenmanager Tool and the Advanced REACH Tool (ART).^{[6][16][17]} Based on this conceptual framework, a control banding tool called “Stoffenmanager Nano” has been developed,^[18] encompassing both proactive approach and retroactive (risk banding) approach.

In addition, the French agency for food, environmental and occupational health and safety (ANSES) have developed a control banding tool specifically for nanomaterials which is described in the report “Development of a specific control banding tool for nanomaterials” ^[31].

The biggest challenge in developing any control banding approach for NOAA is to decide which parameters are to be considered and what criteria are relevant to assign a nano-object to a control band, and what operational control strategies ought to be implemented at different operational levels.

This part of ISO/TS 12901 proposes guidelines for controlling and managing occupational risk based on a control banding approach specifically designed for NOAA. It is the responsibility of manufacturers and importers to determine whether a material of concern contains NOAA, and to provide relevant information in safety data sheets (SDS) and labels, in compliance with any national or international existing regulation. Employers can use this information to identify hazards and implement appropriate controls. This part of ISO/TS 12901 does not intend to give recommendations on this decision-making process. It cannot replace regulation and employers are expected to comply with the existing regulations.

It is emphasized that the control banding method applied to manufactured NOAA requires assumptions to be formulated on information that is desirable but unavailable. Thus the user of the control banding tool needs to have proven skills in chemical risk prevention and more specifically in risk issues known to be related to that type of material. The successful implementation of this approach requires a solid expertise combined with a capacity for critical evaluation of potential occupational exposures and training to use control banding tools to ensure appropriate control measures and an adequately conservative approach.

In parallel to the approach described in this part of ISO/TS 12901, a full hazard assessment is advisable to consider all substance-related hazards, including explosive risk (see NOTE 2), and environmental hazards.

NOTE 2 Explosive dust clouds can be generated from most organic materials, many metals and even some non-metallic inorganic materials. The primary factor influencing the ignition sensitivity and explosive violence of a dust cloud is the particle size or specific surface area (i.e. the total surface area per unit volume or unit mass of the dust) and the particle composition. As the particle size decreases the specific surface area increases. The general trend is for the violence of the dust explosion and the ease of ignition to increase as the particle size decreases, though for many dusts this trend begins to level out at particle sizes of the order of tens of micrometres (μm). However, no lower particle size limit has been established below which dust explosions cannot occur and it has to be considered that many nanoparticle types have the potential to cause explosions.

Nanotechnologies — Occupational risk management applied to engineered nanomaterials —

Part 2: Use of the control banding approach

1 Scope

The purpose of this part of ISO/TS 12901 is to describe the use of a control banding approach for controlling the risks associated with occupational exposures to nano-objects, and their aggregates and agglomerates greater than 100 nm (NOAA), even if knowledge regarding their toxicity and quantitative exposure estimations is limited or lacking.

The ultimate purpose of control banding is to control exposure in order to prevent any possible adverse effects on workers' health. The control banding tool described here is specifically designed for inhalation control. Some guidance for skin and eye protection is given in ISO/TS 12901-1.^[19]

This part of ISO/TS 12901 is focused on intentionally produced NOAA that consist of nano-objects such as nanoparticles, nanopowders, nanofibres, nanotubes, nanowires, as well as of aggregates and agglomerates of the same. As used in this part of ISO/TS 12901, the term "NOAA" applies to such components, whether in their original form or incorporated in materials or preparations from which they could be released during their lifecycle. However, as for many other industrial processes, nanotechnological processes can generate by-products in the form of unintentionally produced NOAA which might be linked to health and safety issues that need to be addressed as well.

This part of ISO/TS 12901 is intended to help businesses and others, including research organizations engaged in the manufacturing, processing or handling of NOAA, by providing an easy-to-understand, pragmatic approach for the control of occupational exposures.

Control banding applies to issues related to occupational health in the development, manufacturing and use of NOAA under normal or reasonably predictable conditions, including maintenance and cleaning operations but excluding incidental or accidental situations.

Control banding is not intended to apply to the fields of safety management, environment or transportation; it is considered as only one part of a comprehensive risk management process.

Materials of biological origin are outside the scope of this part of ISO/TS 12901.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/TS 27687, *Nanotechnologies — Terminology and definitions for nano-objects — Nanoparticle, nanofibre and nanoplate*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/TS 27687 and the following apply.